NACOmatic

Effective: 22-October-2009 Expires: 17-December-2009

Your Ad Here ~60,000 Page views/month

Contact:

Doug Ranz 248-318-0011 NACOmatic@hotmail.com

Warranty

I make absolutely no warranty nor guarantee whatsoever about the accuracy, availability, applicability and/or correctness of any of the information in this document.

The official, original NACO documents are available for your downloading pleasure from: http://naco.faa.gov/index.asp?xml=naco/onlineproducts

Copyright

This compilation is protected by US copyright laws and international copyright treaties.

Limitations

The sale, hosting and/or distribution of this document in any and all forms, is prohibited.

Release from Liability

All users of this compilation must agree to be legally bound hereby, that Douglas R. Ranz ("Released Party") SHALL NOT BE LIABLE FOR MY DEATH OR INJURY TO MY PERSON, OR FOR ANY LOSS FOR DAMAGE TO MY PROPERTY OR REPUTATION caused in any manner whatsoever, whether attributable to the negligence of the Released Party, or for any other reason, occurring during the time that I am operating an aircraft.

I do hereby waive any right of action against the Released Party from any and all causes or claims that I may have against them from the beginning of time. I further agree not to sue on any such cause or claim. This agreement shall not release liability for gross negligence or willful misconduct of the Released Party. I agree to indemnify and hold the Released Party harmless for any losses, judgments, damages or fees he may incur, including but not limited to attorneys fees, arising out any lawsuit related to the planning, flight and/or enforcement of or legal challenge to this agreement. It is my intention that this agreement be interpreted and enforced to the maximum extent allowed by Michigan law.

Kindle-DX		Index;	by	AptID	Use	"Menu",	then	"Goto	Page"
0770	_	4.0							
0U8	=>	48							
1U9	=>	54							
24K	=>	48							
50s	=>	53							
52U	=>	28							
55H	=>	27							
65S	=>	30							
66S	=>	35							
67S	=>	52							
75C	=>	53							
78U	=>	46							
85U	=>	59							
AOC	=>	27							
BOI	=>	30							
BYI	=>	31							
COE	=>	34							
DIJ	=>	37							
EUL	=>	32							
GNG	=>	40							
IDA	=>	43							
JER	=>	44							
LLJ	=>	33							
LWS	=>	46							
MLD	=>	48							
MUO	=>	50							
MYL	=>	49							
PIH	=>	54							
RXE	=>	56							
SMN	=>	58							
SUN	=>	41							
SZT	=>	58							
TWF	=>	61							
U03	=>	31							
U53	=>	45							
υ97	=>	42							

GENERAL INFORMATION

This Airport/Facility Directory is a Civil Flight Information Publication published and distributed every eight weeks by the National Aeronautical Charting Office, FAA, Department of Transportation, Silver Spring, Maryland 20910. It is designed for use with Aeronautical Charts covering the conterminous United States, Puerto Rico and the Virgin Islands.

This directory contains all open to the public airports, seaplane bases and heliports, military facilities, and selected private use facilities specifically requested by the Department of Defense (DoD) for which a DoD Instrument Approach Procedure has been published in the U.S. Terminal Procedures Publication. Additionally, this directory contains communications data, navigational facilities and certain special notices and procedures.

Military data contained within this publication is provided by the National Geospatial-Intelligence Agency and is intended to provide reference data for military and/or joint civil/military airports. Not all military data contained in this publication is applicable to civil users.

CORRECTIONS, COMMENTS, AND/OR PROCUREMENT

CRITICAL information such as equipment malfunction, abnormal field conditions, hazards to flight, etc., should be reported as soon as possible to the nearest FAA facility, either in person or by reverse charge telephone call.

FOR AIRPORT SUPPLEMENT REVISIONS FORM VISIT WEB SITE: http://nfdc.faa.gov/portal/airportchanges.do

FAA, Aeronautical Information Services, ATO-R, Rm. 626

800 Independence Ave., SW

Washington, DC 20591

Telephone 1-866-295-8236 Fax 202-267-5322

Email 9-ATOR-HO-AIS-AIRPORTCHANGES@FAA.GOV

NOTICE: Changes must be received by the Aeronautical Information Services as soon as possible but not later than the "cut-off" dates listed below to assure publication on the desired effective date.

	Airport Information	Airspace Information*
Effective Date	Cut-off date	Cut-off date
22 Oct 09	9 Sep 09	20 Aug 09
17 Dec 09	4 Nov 09	15 Oct 09
11 Feb 10	30 Dec 09	10 Dec 09
8 Apr 10	24 Feb 10	4 Feb 10
3 Jun 10	21 Apr 10	1 Apr 10
29 Jul 10	16 Jun 10	27 May 10

^{*}Including changes to preferred routes and graphic depictions on charts.

FOR CHARTING ERRORS CONTACT:

ı

FAA, National Aeronautical Charting Office, ATO-W

SSMC-4 Sta. #2335

1305 East West Highway

Silver Spring, MD 20910-3281

Telephone 1-800-626-3677

Email 9-AMC-Aerochart@faa.gov

Frequently asked questions (FAQs) are answered on our web site at www.naco.faa.gov. See the FAQs prior to contact via toll free number.

FOR PROCUREMENT CONTACT:

FAA, National Aeronautical Charting Office

Distribution Division, ATO-W

10201 Good Luck Road

Glenn Dale, MD 20769-9700

Online at www.naco.faa.gov

Email 9-AMC-Chartsales@faa.gov

Telephone 1-800-638-8972

Fax 301-436-6829

or any authorized FAA Chart Agent

New or Changed Information—To alert users of new information or changes to information from the previous issue, a vertical line will be portrayed in the outside margin and extending the full length of the new and/or revised data. This will not apply to the front cover or the airport/facility directory listing.

This Airport/Facility Directory comprises part of the following sections of the United States Aeronautical Information Publication (AIP): GEN, ENR and AD.

TABLE OF CONTENTS

General Information	Inside Front Cover
Abbreviations	2
Directory Legend	4
Airport/Facility Directory	•
Idaho	22
Montana	59
Oregon	104
Washington	141
Wyoming	195
City/Military Airport Cross Reference	216
Seaplane Landing Areas	217
Special Notices	217
·	
Regulatory Notices	226
FAA and National Weather Service	
Telephone Numbers	227
Key to Aviation Weather Reports	228
Air Traffic Facilities Telephone Numbers	230
Air Route Traffic Control Centers	232
Flight Service Station Communication Frequencies	233
Flight Standards District Offices	236
Routes/Waypoints	
Low Altitude Directional Routes	237
High Altitude Preferred Routes	238
Q-Routes	239
RNAV Routing Pitch and Catch Points	242
VFR Waypoints	253
VOR Receiver Check	261
Parachute Jumping Areas	264
Aeronautical Chart Bulletins	266
Supplemental Communication Reference	275
Airport Diagrams	281
National Weather Service (NWS) Upper Air Observing Stations	328
Enroute Flight Advisory Service (FFAS)	Inside Back Cover

ABBREVIATIONS

The following abbreviations/acronyms are those commonly used within this Directory. Other abbreviations/acronyms may be found in the Legend and are not duplicated below. The abbreviations presented are intended to represent grammatical variations of the basic form. (Example—''req'' may mean ''request", ''requesting'', ''requested'', or ''requests'').

AAF	Army Air Field	byd	beyond
AB	Airbase	c	Commercial Circuit (Telephone)
abv	above	CGAF	Coast Guard Air Facility
ACC	Air Combat Command; Area Control	CGAS	Coast Guard Air Station
	Center	CIV	Civil
acft	aircraft	clsd	closed
ADCC	Air Defense Control Center	comd	command
AER	approach end rwy	CONUS	Continental United States
AFB	Air Force Base	CSTMS	Customs
AFHP	Air Force Heliport	ctc	contact
afld	airfield	ctl	control
AFOD	US Army Flight Operations Detachment	dalgt	daylight
AFRC	Armed Forces Reserve Center/Air Force	Dec	December
	Reserve Command	DIAP	DoD Instrument Approach Procedure
AFSS	Automated Flight Service Station	DoD	Department of Defense
AG	Agriculture	DSN	Defense Switching Network (Telephone)
A-GEAR	Arresting Gear	dsplcd	displaced
AGL	above ground level	durn	duration
AHP	Army heliport	eff	effective
ALS	Approach Light System	emerg	emergency
alt	altitude	EOR	End of Runway
AMC	Air Mobility Command	ETA	Estimated Time of Arrival
ANGS	Air National Guard Station	ETD	Estimated Time of Departure
apch	approach	exc	except
Apr	April	extd	extend
APU	Auxiliary Power Unit	FB0	fixed-base operator
ARB	Air Reserve Base	Feb	February
arpt	airport	fld	field
ARS	Air Reserve Station	FLIP	Flight Information Publication
AS	Air Station	flt	flight
ASDE-X	Airport Surface Detection Equipment—	flw	follow
	Model X	Fri	Friday
ASU	Aircraft Starting Unit	FSS	Flight Service Station
ATC	Air Traffic Control	GA	glide angle
Aug	August	GCA	Ground Controlled Approach
AUW	All Up Weight (gross weight)	GS	glide slope
avbl	available	haz	hazard
bcn	beacon	HQ	Headquarters
blo	below		

CONTINUED ON NEXT PAGE

CONTINUED FROM PRECEDING PAGE

hr hour non precision instrument ΙΔΡ Instrument Approach Procedure NS ABTMT Noise Abatement ICAC International Civil Aviation Organization NSTD nonstandard IFR Instrument Flight Rules ntc notice ILS Instrument Landing System obsn observation IM Inner Marker Oct October IMG Immigration OI F Outlying Field

incr increase onr operate, operator, operational

indet indefinite ons operations intensity OTS out of service ints invof in the vicinity of ovrn overrun

personnel and equipment working IMC Instrument Meteorological Conditions PAFW

lan nat pattern Jet Aircraft Starting Unit IASI p-line power line

JOAP Joint Oil Analysis Program **PMSV** Pilot-to-Metro Service IOSAC Joint Operational Support Airlift Center PΩI Petrol, Oils and Lubricants IRB Joint Reserve Base PPR prior permission required Jul July PRM Precision Runway Monitoring Jun June PTD Pilot to Dispatcher

Κt Knots RAMCC Regional Air Movement Control Center

LAA Local Airport Advisory rea request LAHSO Land and Hold Short Operations rgt tfc right traffic RON Remain Overnight lhs nounds ldg landing rar require lighted rstd lgtd restricted

RSRS løts lights reduced same runway separation

LMM Compass locator at Middle Marker ILS rw/v runway LOC Localizer Sat Saturday

LOM Compass locator at Outer Marker ILS SFLE Strategic Expeditionary Landing Field

limited Sen Itd September

MACC Military Area Control Center SFA Single Frequency Approach March efe Mar

surface SFRA

MCAF Marine Corps Air Facility Special Flight Rules Area SOAP MCALE Marine Corps Auxiliary Landing Field Spectrometric Oil Analysis Program

SOF Supervisor of Flying MCAS

Marine Corps Air Station Marine Corps Base SPR MCB Seaplane Base SP med medium sunrise

SS METRO Pilot-to-Metro voice call sunset Mil military std standard min minute Sur Sunday MLS Microwave Landing System SVC service MM Middle Marker of ILS tfc traffic Mon Monday thld threshold MP Maintenance Period Thu Thursday MSI mean sea level tkf take-off MSAW minimum safe altitude warning tmnrv temporary NAAS Naval Auxiliary Air Station tran transient

Naval Air Development Center

NADC

NADER Naval Air Depot twr tower Naval Air Engineering Center NAEC twv taxiway NAFS Naval Air Engineering Station UC **Under Construction** Naval Air Facility USA United States Army NAF

NALCO Naval Air Logistics Control Office USAF United States Air Force USCG NALO Navy Air Logistics Office United States Coast Guard NALE Naval Auxiliary Landing Field USN United States Navy

NAS Naval Air Station Defense Switching Network (telephone,

Tue

Tuesday

NAWC Naval Air Warfare Center formerly AUTOVON) NAWS Naval Air Weapons Station VFR Visual Flight Rules VIP night Very Important Person ngt

NOLF Naval Outlying Field VMC Visual Meteorological Conditions

Nov November Wed Wednesday wx weather

DIRECTORY LEGEND SAMPI F CITY NAME AIRPORT NAME (ALTERNATE NAME) (LTS) (KLTS) CIV/MIL 3 N UTC-6(-5DT) N34°41.93′ W99°20.20′ JACKSONVILLE S4 FUEL 100 OX 1 TPA-1000(800) AOE Class IV. ARFF Index A NOTAM FILE ORL Not insp. H-4G I-19C (19) (20) IAP. DIAP. AD (11)(12)(13)(14)(15)(16)(18)(21) RWY 18-36: H12004X200 (ASPH-CONC-GRVD) 9 S-90, D-160, DT-300 PCN 80 R/B/W/T HIRL RWY 18: LDIN, MALSF, TDZL, REIL, PAPI(P2R)-GA 3.0° TCH 36'. Rwy 173-353: 3515 X 150 Thid dspicd 300'. Trees. Rgt tfc. 0.3% up. RWY 36: ALSF1. 0.4% down. 81 Č ä RWY 09-27: H6000X150 (ASPH) MIRL G G 000 RWY 173-353: H3515X150 (ASPH-PFC) AUW PCN 59 F/A/W/T 113 LAND AND HOLD SHORT OPERATIONS Ø €3 DIST AVRI HOLD SHORT POINT LANDING Ø C3 €3 €3 **RWY 18** 09-27 6500 2004 X **RWY 36** 09-27 5400 8 RUNWAY DECLARED DISTANCE INFORMATION 353 RWY 18: TORA-12004 TODA-12704 ASDA-11704 LDA-11504 q١ RWY 36: TORA-12004 TODA-12004 ASDA-12004 LDA-11704 6000 X 150 ARRESTING GEAR/SYSTEM RWY 18 → HOOK E5 (65' OVRN) BAK-14 BAK-12B (1650') BAK-14 BAK-12 (B) (1087') HOOK E5 (74' OVRN) ← RWY 36 MILITARY SERVICE: A-GEAR E-5 connected on dep end, disconnected on JASU 3(AM32A-60) 2(A/M32A-86) apch end. 33 36 (24) (25)→ FUEL J8(Mil) (NC-100, A) FLUID W SP PRESAIR LOX ← (10) OIL 0-128 TRAN ALERT Avbl 1300-0200Z‡, svc limited weekends. 27 (28 AIRPORT REMARKS: Special Air Traffic Rules—Part 93, see Regulatory Notices. Attended 1200-0300Z‡. Parachute Jumping, Deer invof arpt, Heavy jumbo jet training surface to 9000', Twy A clsd indef, Flight Notification Service (ADCUS) avbl. (30) MILITARY REMARKS: ANG PPR/Official Business Only. Base OPS DSN 638-4390, C503-335-4222. Ctc Base OPS 15 minutes prior to Idg and after dep. Limited tran parking. (31)WEATHER DATA SOURCES: AWOS-1 120.3 (202) 426-8000. LLWAS. COMMUNICATIONS: SFA ATIS 127.25 273.5 (202) 426-8003 UNICOM 122.95 PTD 372.2 NAME FSS (ORL) on arpt. 123.65 122.65 122.2 NAME RC0 112.2T 112.1R (NAME RADIO) R NAME APP/DEP CON 128.35 257.725 (1200-0400Z‡) TOWER 119.65 255.6 (1200-0400Z‡) GND CON 121.7 GCO 135.075 (ORLANDO CLNC) **CLNC DEL** 125.55 NAME COMD POST (GERONIMO) 311.0 321.4 6761 PMSV METRO 239.8 NAME OPS 257 5 (33)→ AIRSPACE: CLASS B See VFR Terminal Area Chart. RADIO AIDS TO NAVIGATION: NOTAM FILE ORL. VHF/DF ctc FSS.

Chan 59 N28°32.55' W81°20.12' (H) VORTAC 112.2 MCO at fld. (H) TACAN Chan 29 CBU (109.2) N28°32.65′ W81°21.12′ at fld. 1115/8E. HERNY NDB (LOM) 221 OR N28°37.40′ W81°21.05′ 177° 5.4 NM to fld.

ILS/DME 108.5 I-ORL Chan 22 Rwy 18. Class IIE. LOM HERNY NDB

ASR/PAR (1200-0400Z‡)

COMM/NAV/WEATHER REMARKS: Emerg frequency 121.5 not avbl at twr.

HELIPAD H1: H100X75 (ASPH)

HELIPAD H2: H60X60 (ASPH)

HELIPORT REMARKS: Helipad H1 lctd on general aviation side and H2 lctd on air carrier side of arpt.

187 TPA 1000(813)

WATERWAY 15-33: 5000X425 (WATER)

SEAPLANE REMARKS: Birds roosting and feeding areas along river banks. Seaplanes operating adjacent to SW side of arpt not visible from twr and are required to ctc twr.

All bearings and radials are magnetic unless otherwise specified.
All mileages are nautical unless otherwise noted.
All times are Coordinated Universal Time (UTC) except as noted.
All elevations are in feet above/below Mean Sea Level (MSL) unless otherwise noted.
The horizontal reference datum of this publication is North American Datum of 1983 (NAD83), which for charting purposes is considered equivalent to World Geodetic System 1984 (WGS 84).

10 SKETC	H LEGEND
runways/landing areas	radio aids to navigation
Hard Surfaced	VORTAC
Metal Surface	VOR/DME NDB
Sod, Gravel, etc	TACAN TO NDB/DME
Light Plane,	MISCELLANEOUS AERONAUTICAL FEATURES
Closed	Airport Beacon
Helicopter Landings Area	Wind Cone
Displaced Threshold 0	Tetrahedron
Taxiway, Apron and Stopways	
ANGCELLANICOUG BACE AND CHITLIDAL	APPROACH LIGHTING SYSTEMS
MISCELLANEOUS BASE AND CULTURAL FEATURES	A dot "•" portrayed with approach lighting letter identifier indicates sequenced flashing lights (F) installed with the approach lighting
Buildings	system e.g. (A) Negative symbology, e.g., (A) w indicates Pilot Controlled Lighting (PCL).
Power Lines	Runway Centerline Lighting
Fence	Approach Lighting System ALSF-2 I
Towers	Approach Lighting System ALSF-1
Tanks	Short Approach Lighting System SALS/SALSF. Simplified Short Approach Lighting System (SSALR) with RAII
Oil Well	System (SSALR) with RAIL
Smoke Stack	and SSALF)
5812 Obstruction	As System (MALSR) and RAIL
Controlling Obstruction	Lighting System (ODALS)
G & G.	(‡) Air Force Overrun
Trees	Visual Approach Slope Indicator with Standard Threshold Clearance provided
Populated Places	Pulsating Visual Approach Slope Indicator (PVASI)
Cuts and Fills Fill HITTITI	Visual Approach Slope Indicator with a threshold crossing height to accomodate long bodied or jumbo aircraft
Cliffs and Depressions	Tri-color Visual Approach Slope Indicator (TRCV)
Ditch	(V3) Approach Path Alignment Panel (APAP)
Hill	P Precision Approach Path Indicator (PAPI)

LEGEND

This directory is a listing of data on record with the FAA on all open to the public airports, military facilities and selected private use facilities specifically requested by the Department of Defense (DoD) for which a DoD Instrument Approach Procedure has been published in the U.S. Terminal Procedures Publication. Additionally this listing contains data for associated terminal control facilities, air route traffic control centers, and radio aids to navigation within the conterminous United States, Puerto Rico and the Virgin Islands. Joint civil/military and civil airports are listed alphabetically by state, associated city and airport name and cross-referenced by airport name. Military facilities are listed alphabetically by state and official airport name and cross-referenced by associated city name. Navaids, flight service stations and remote communication outlets that are associated with an airport, but with a different name, are listed alphabetically under their own name, as well as under the airport with which they are associated.

The listing of an open to the public airport in this directory merely indicates the airport operator's willingness to accommodate transient aircraft, and does not represent that the facility conforms with any Federal or local standards, or that it has been approved for use on the part of the general public. Military and private use facilities published in this directory are open to civil pilots only in an emergency or with prior permission. See Special Notice Section, Civil Use of Military Fields.

The information on obstructions is taken from reports submitted to the FAA. Obstruction data has not been verified in all cases. Pilots are cautioned that objects not indicated in this tabulation (or on the airports sketches and/or charts) may exist which can create a hazard to flight operation. Detailed specifics concerning services and facilities tabulated within this directory are contained in the Aeronautical Information Manual, Basic Flight Information and ATC Procedures.

The legend items that follow explain in detail the contents of this Directory and are keyed to the circled numbers on the sample on the preceding pages.

1 CITY/AIRPORT NAME

Civil and joint civil/military airports and facilities in this directory are listed alphabetically by state and associated city. Where the city name is different from the airport name the city name will appear on the line above the airport name. Airports with the same associated city name will be listed alphabetically by airport name and will be separated by a dashed rule line. A solid rule line will separate all others. FAA approved helipads and seaplane landing areas associated with a land airport will be separated by a dotted line. Military airports are listed alphabetically by state and official airport name.

2 ALTERNATE NAME

Alternate names, if any, will be shown in parentheses.

(3) LOCATION IDENTIFIER

The location identifier is a three or four character FAA code followed by a four-character ICAO code assigned to airports. ICAO codes will only be published at joint civil/military, and military facilities. If two different military codes are assigned, both codes will be shown with the primary operating agency's code listed first. These identifiers are used by ATC in lieu of the airport name in flight plans, flight strips and other written records and computer operations. Zeros will appear with a slash to differentiate them from the letter "O".

(4) OPERATING AGENCY

Α

Airports within this directory are classified into two categories, Military/Federal Government and Civil airports open to the general public, plus selected private use airports. The operating agency is shown for military, private use and joint civil/military airports. The operating agency is shown by an abbreviation as listed below. When an organization is a tenant, the abbreviation is enclosed in parenthesis. No classification indicates the airport is open to the general public with no military tenant.

MC

Marine Corps

AFRC Air Force Reserve Command N Navv US Air Force Naval Air Facility ΔF NAF ANG Air National Guard NAS Naval Air Station ΔR US Army Reserve NASA National Air and Space Administration

ARNG US Army National Guard P US Civil Airport Wherein Permit Covers
CG US Coast Guard Use by Transient Military Aircraft
CIV/MIL Joint Use Civil/Military PVT Private Use Only (Closed to the Public)

DND Department of National Defense Canada

US Army

5 AIRPORT LOCATION

Airport location is expressed as distance and direction from the center of the associated city in nautical miles and cardinal points, e.g., 4 NE.

6 TIME CONVERSION

Hours of operation of all facilities are expressed in Coordinated Universal Time (UTC) and shown as "Z" time. The directory indicates the number of hours to be subtracted from UTC to obtain local standard time and local daylight saving time UTC-5(-4DT). The symbol ‡ indicates that during periods of Daylight Saving Time effective hours will be one hour earlier than shown. In those areas where daylight saving time is not observed the (-4DT) and ‡ will not be shown. Daylight saving time is in effect from 0200 local time the second Sunday in March to 0200 local time the first Sunday in November. Canada and all U.S. Conterminous States observe daylight saving time except Arizona and Puerto Rico, and the Virgin Islands. If the state observes daylight saving time and the operating times are other than daylight saving times, the operating hours will include the dates, times and no ‡ symbol will be shown, i.e., April 15-Aug 31 0630-1700Z, Sep 1-Apr 14 0600-1700Z.

7 GEOGRAPHIC POSITION OF AIRPORT—AIRPORT REFERENCE POINT (ARP)

Positions are shown as hemisphere, degrees, minutes and hundredths of a minute and represent the approximate geometric center of all usable runway surfaces.

8 CHARTS

Charts refer to the Sectional Chart and Low and High Altitude Enroute Chart and panel on which the airport or facility is located. Helicopter Chart locations will be indicated as COPTER.

9 INSTRUMENT APPROACH PROCEDURES, AIRPORT DIAGRAMS

IAP indicates an airport for which a prescribed (Public Use) FAA Instrument Approach Procedure has been published. DIAP indicates an airport for which a prescribed DoD Instrument Approach Procedure has been published in the U.S. Terminal Procedures. See the Special Notice Section of this directory, Civil Use of Military Fields and the Aeronautical Information Manual 5–4–5 Instrument Approach Procedure Charts for additional information. AD indicates an airport for which an airport diagram has been published. Airport diagrams are located in the back of each A/FD volume alphabetically by associated city and airport name.

10 AIRPORT SKETCH

The airport sketch, when provided, depicts the airport and related topographical information as seen from the air and should be used in conjunction with the text. It is intended as a guide for pilots in VFR conditions. Symbology that is not self-explanatory will be reflected in the sketch legend. The airport sketch will be oriented with True North at the top. Airport sketches will be added incrementally.

11 ELEVATION

The highest point of an airport's usable runways measured in feet from mean sea level. When elevation is sea level it will be indicated as "00". When elevation is below sea level a minus "-" sign will precede the figure.

(12) ROTATING LIGHT BEACON

B indicates rotating beacon is available. Rotating beacons operate sunset to sunrise unless otherwise indicated in the AIRPORT REMARKS or MILITARY REMARKS segment of the airport entry.

S8: Minor powerplant repairs.

(13) SERVICING—CIVIL

S1:	Minor airframe repairs.	S5:	Major airframe repairs.
S2:	Minor airframe and minor powerplant repairs.	S6:	Minor airframe and major powerplant repairs.
53.	Major airframe and minor nowerplant renairs	S7.	Major nowernlant renairs

S4: Major airframe and major powerplant repairs.

(14) FUEL

CODE	FUEL	CODE	FUEL
80	Grade 80 gasoline (Red)	B+	Jet B, Wide-cut, turbine fuel with FS-II*, FP**
100	Grade 100 gasoline (Green)		minus 50° C.
100LL	100LL gasoline (low lead) (Blue)	J4 (JP4)	(JP-4 military specification) FP** minus
115	Grade 115 gasoline (115/145 military		58° C.
	specification) (Purple)	J5 (JP5)	(JP-5 military specification) Kerosene with
A	Jet A, Kerosene, without FS-II*, FP** minus		FS-11, FP** minus 46°C.
	40° C.	J8 (JP8)	(JP-8 military specification) Jet A-1, Kerosene
A+	Jet A, Kerosene, with FS-II*, FP** minus		with FS-II*, FP** minus 47°C.
	40°C.	J8+100	(JP-8 military specification) Jet A-1, Kerosene
A1	Jet A-1, Kerosene, without FS-II*, FP**		with FS-II*, FP** minus 47°C, with-fuel
	minus 47°C.		additive package that improves thermo
A1+	Jet A-1, Kerosene with FS-II*, FP** minus		stability characteristics of JP-8.
	47° C.	J	(Jet Fuel Type Unknown)
В	Jet B, Wide-cut, turbine fuel without FS-II*,	MOGAS	Automobile gasoline which is to be used
	FP** minus 50° C.		as aircraft fuel.

CODE

NOTE: Certai

Certain automobile gasoline may be used in specific aircraft engines if a FAA supplemental type certificate has been obtained. Automobile gasoline, which is to be used in aircraft engines, will be identified as "MOGAS", however, the grade/type and other octane rating will not be published.

Data shown on fuel availability represents the most recent information the publisher has been able to acquire. Because of a variety of factors, the fuel listed may not always be obtainable by transient civil pilots. Confirmation of availability of fuel should be made directly with fuel suppliers at locations where refueling is planned.

15 OXYGEN—CIVIL

OX 1 High Pressure OX 3 High Pressure—Replacement Bottles
OX 2 Low Pressure OX 4 Low Pressure—Replacement Bottles

16 TRAFFIC PATTERN ALTITUDE

Traffic Pattern Altitude (TPA)—The first figure shown is TPA above mean sea level. The second figure in parentheses is TPA above airport elevation. Multiple TPA shall be shown as "TPA—See Remarks" and detailed information shall be shown in the Airport or Military Remarks Section. Traffic pattern data for USAF bases, USN facilities, and U.S. Army airports (including those on which ACC or U.S. Army is a tenant) that deviate from standard pattern altitudes shall be shown in Military Remarks.

^{*(}Fuel System Icing Inhibitor)

^{**(}Freeze Point)

AIRPORT OF ENTRY. LANDING RIGHTS, AND CUSTOMS USER FEE AIRPORTS

U.S. CUSTOMS USER FEE AIRPORT-Private Aircraft operators are frequently required to pay the costs associated with customs processing.

AOE—Airport of Entry. A customs Airport of Entry where permission from U.S. Customs is not required to land. However, at least one hour advance notice of arrival is required.

LRA—Landing Rights Airport. Application for permission to land must be submitted in advance to U.S. Customs. At least one hour advance notice of arrival is required.

NOTE: Advance notice of arrival at both an AOE and LRA airport may be included in the flight plan when filed in Canada or Mexico. Where Flight Notification Service (ADCUS) is available the airport remark will indicate this service. This notice will also be treated as an application for permission to land in the case of an LRA. Although advance notice of arrival may be relayed to Customs through Mexico, Canada, and U.S. Communications facilities by flight plan, the aircraft operator is solely responsible for ensuring that Customs receives the notification. (See Customs, Immigration and Naturalization, Public Health and Agriculture Department requirements in the International Flight Information Manual for further details.)

US Customs Air and Sea Ports, Inspectors and Agents

Northeast Sector (New England and Atlantic States—ME to MD)	407-975-1740
Southeast Sector (Atlantic States—DC, WV, VA to FL)	407-975-1780
Central Sector (Interior of the US, including Gulf states—MS, AL, LA)	407-975-1760
Southwest East Sector (OK and eastern TX)	407-975-1840
Southwest West Sector (Western TX, NM and AZ)	407-975-1820
Pacific Sector (WA, OR, CA, HI and AK)	407-975-1800

(18) CERTIFICATED AIRPORT (14 CFR PART 139)

Airports serving Department of Transportation certified carriers and certified under 14 CFR part 139 are indicated by the Class and the ARFF Index; e.g. Class I, ARFF Index A, which relates to the availability of crash, fire, rescue equipment. Class I airports can have an ARFF Index A through E, depending on the aircraft length and scheduled departures. Class II, III, and IV will always carry an Index A.

14 CFR PART 139 CERTIFICATED AIRPORTS AIRPORT CLASSIFICATIONS

Type of Air Carrier Operation	Class I	Class II	Class III	Class IV
Scheduled Air Carrier Aircraft with 31 or more passenger seats	Х			
Unscheduled Air Carrier Aircraft with 31 or more passengers seats	Х	Х		Х
Scheduled Air Carrier Aircraft with 10 to 30 passenger seats	Х	Х	Х	

14 CFR-PART 139 CERTIFICATED AIRPORTS

INDICES AND AIRCRAFT RESCUE AND FIRE FIGHTING EQUIPMENT REQUIREMENTS

Airport Index	Required No. Vehicles	Aircraft Length	Scheduled Departures	Agent + Water for Foam
А	1	<90′	≥1	500#DC or HALON 1211 or 450#DC + 100 gal H₂O
В	1 or 2	≥90′, <126′	≥5	Index A + 1500 gal H ₂ O
		≥126′, <159′	<5	
С	2 or 3	≥126′, <159′	≥5	Index A + 3000 gal H ₂ O
		≥159′, <200′	<5	
D	3	≥159′, <200′		Index A + 4000 gal H ₂ O
		>200′	<5	
Е	3	≥200′	≥5	Index A + 6000 gal H ₂ O

> Greater Than; < Less Than; ≥ Equal or Greater Than; ≤ Equal or Less Than; H₂O-Water; DC-Dry Chemical.

NOTE: The listing of ARFF index does not necessarily assure coverage for non-air carrier operations or at other than prescribed times for air carrier. ARFF Index Ltd .-- indicates ARFF coverage may or may not be available, for information contact airport manager prior to flight.

(19) NOTAM SERVICE

All public use landing areas are provided NOTAM "D" (distant dissemination) and NOTAM "L" (local dissemination) service. Airport NOTAM file identifier is shown for individual airports, e.g. "NOTAM FILE IAD". See AIM, Basic Flight Information and ATC Procedures for detailed description of NOTAM's. Current NOTAMs are available from Flight Service Stations at 1–800–WX–BRIEF. Real time Military NOTAMs are available using the DoD Internet NOTAM Distribution System (DINS) www.notams.jcs.mil.

20 FAA INSPECTION

All airports not inspected by FAA will be identified by the note: Not insp. This indicates that the airport information has been provided by the owner or operator of the field.

21 RUNWAY DATA

Runway information is shown on two lines. That information common to the entire runway is shown on the first line while information concerning the runway ends is shown on the second or following line. Runway direction, surface, length, width, weight bearing capacity, lighting, and slope, when available are shown for each runway. Multiple runways are shown with the longest runway first. Direction, length, width, and lighting are shown for sea-lanes. The full dimensions of helipads are shown, e.g., 50X150. Runway data that requires clarification will be placed in the remarks section.

RUNWAY DESIGNATION

Runways are normally numbered in relation to their magnetic orientation rounded off to the nearest 10 degrees. Parallel runways can be designated L (left)/R (right)/C (center). Runways may be designated as STOL, Ultralight, or assault strips. Assault strips are shown by magnetic bearing.

RUNWAY DIMENSIONS

Runway length and width are shown in feet. Length shown is runway end to end including displaced thresholds, but excluding those areas designed as overruns.

RUNWAY SURFACE AND LENGTH

Runway lengths prefixed by the letter "H" indicate that the runways are hard surfaced (concrete, asphalt, or part asphalt–concrete). If the runway length is not prefixed, the surface is sod, clay, etc. The runway surface composition is indicated in parentheses after runway length as follows:

(AFSC)—Aggregate friction seal coat	(GRVL)—Gravel, or cinders	(PSP)—Pierced steel plank
(ASPH)—Asphalt	(MATS)—Pierced steel planking,	(RFSC)—Rubberized friction seal coat
(CONC)—Concrete	landing mats, membranes	(TURF)—Turf
(DIRT)—Dirt	(PEM)—Part concrete, part asphalt	(TRTD)—Treated
(GRVD)—Grooved	(PFC)—Porous friction courses	(WC)—Wire combed

RUNWAY WEIGHT BEARING CAPACITY

Runway strength data shown in this publication is derived from available information and is a realistic estimate of capability at an average level of activity. It is not intended as a maximum allowable weight or as an operating limitation. Many airport pavements are capable of supporting limited operations with gross weights in excess of the published figures. Permissible operating weights, insofar as runway strengths are concerned, are a matter of agreement between the owner and user. When desiring to operate into any airport at weights in excess of those published in the publication, users should contact the airport management for permission. Runway strength figures are shown in thousand of pounds, with the last three figures being omitted. Add 000 to figure following S, D, 2S, 2T, AUW, SWL, etc., for gross weight capacity. A blank space following the letter designator is used to indicate the runway can sustain aircraft with this type landing gear, although definite runway weight bearing capacity figures are not available, e.g., S, D. Applicable codes for typical gear configurations with S=Single, D=Dual, T=Triple and Q=Quadruple:

CURRENT	NEW	NEW DESCRIPTION
S	S	Single wheel type landing gear (DC3), (C47), (F15), etc.
D	D	Dual wheel type landing gear (BE1900), (B737), (A319), etc.
T	D	Dual wheel type landing gear (P3, C9).
ST	28	Two single wheels in tandem type landing gear (C130).
TRT	2T	Two triple wheels in tandem type landing gear (C17), etc.
DT	2D	Two dual wheels in tandem type landing gear (B707), etc.
TT	2D	Two dual wheels in tandem type landing gear (B757,
		KC135).
SBTT	2D/D1	Two dual wheels in tandem/dual wheel body gear type
		landing gear (KC10).
None	2D/2D1	Two dual wheels in tandem/two dual wheels in tandem body
		gear type landing gear (A340–600).
DDT	2D/2D2	Two dual wheels in tandem/two dual wheels in double
		tandem body gear type landing gear (B747, E4).
TTT	3D	Three dual wheels in tandem type landing gear (B777), etc.
TT	D2	Dual wheel gear two struts per side main gear type landing
		gear (B52).
TDT	C5	Complex dual wheel and quadruple wheel combination
		landing gear (C5).

AUW—All up weight. Maximum weight bearing capacity for any aircraft irrespective of landing gear configuration.

SWL—Single Wheel Loading. (This includes information submitted in terms of Equivalent Single Wheel Loading (ESWL) and Single Isolated Wheel Loading).

PSI—Pounds per square inch. PSI is the actual figure expressing maximum pounds per square inch runway will support, e.g., (SWL 000/PSI 535).

Omission of weight bearing capacity indicates information unknown.

The ACN/PCN System is the ICAO standard method of reporting pavement strength for pavements with bearing strengths greater than 12,500 pounds. The Pavement Classification Number (PCN) is established by an engineering assessment of the runway. The PCN is for use in conjunction with an Aircraft Classification Number (ACN). Consult the Aircraft Flight Manual, Flight Information Handbook, or other appropriate source for ACN tables or charts. Currently, ACN data may not be available for all aircraft. If an ACN table or chart is available, the ACN can be calculated by taking into account the aircraft weight, the pavement type, and the subgrade category. For runways that have been evaluated under the ACN/PCN system, the PCN will be shown as a five-part code (e.g. PCN 80 R/B/W/T). Details of the coded format are as follows:

- (1) The PCN NUMBER—The reported PCN indicates that an aircraft with an ACN equal or less than the reported PCN can operate on the pavement subject to any limitation on the tire pressure.
- (2) The type of pavement:
 - R Rigid
 - F Flexible
- (3) The pavement subgrade category:
 - A High
 - B Medium
 - C Low
 - D Ultra-low

- $\begin{tabular}{ll} (4) The maximum tire pressure authorized for the pavement: \\ \end{tabular}$
 - W High, no limit
 - X Medium, limited to 217 psi
 - ${\rm Y}$ Low, limited to 145 psi
- Z Very low, limited to 73 psi(5) Pavement evaluation method:
 - T Technical evaluation
 - U By experience of aircraft using the pavement

NOTE: Prior permission from the airport controlling authority is required when the ACN of the aircraft exceeds the published PCN or aircraft tire pressure exceeds the published limits.

RUNWAY LIGHTING

Lights are in operation sunset to sunrise. Lighting available by prior arrangement only or operating part of the night and/or pilot controlled lighting with specific operating hours are indicated under airport or military remarks. At USN/USMC facilities lights are available only during airport hours of operation. Since obstructions are usually lighted, obstruction lighting is not included in this code. Unlighted obstructions on or surrounding an airport will be noted in airport or military remarks. Runway lights nonstandard (NSTD) are systems for which the light fixtures are not FAA approved L-800 series: color, intensity, or spacing does not meet FAA standards. Nonstandard runway lights, VASI, or any other system not listed below will be shown in airport remarks or military service. Temporary, emergency or limited runway edge lighting such as flares, smudge pots, lanterns or portable runway lights will also be shown in airport remarks or military service. Types of lighting are shown with the runway or runway end they serve.

NSTD—Light system fails to meet FAA standards.

LIRL-Low Intensity Runway Lights.

MIRL—Medium Intensity Runway Lights.

HIRL—High Intensity Runway Lights.

RAIL—Runway Alignment Indicator Lights.

REIL—Runway End Identifier Lights.

CL—Centerline Lights.

TDZL—Touchdown Zone Lights.

ODALS-Omni Directional Approach Lighting System.

AF OVRN-Air Force Overrun 1000' Standard

Approach Lighting System.

LDIN-Lead-In Lighting System.

MALS-Medium Intensity Approach Lighting System.

MALSF—Medium Intensity Approach Lighting System with Sequenced Flashing Lights.

MALSR—Medium Intensity Approach Lighting System with Runway Alignment Indicator Lights.

SALS—Short Approach Lighting System.

SALSF—Short Approach Lighting System with Sequenced Flashing Lights.

SSALS—Simplified Short Approach Lighting System.

SSALF—Simplified Short Approach Lighting System with Sequenced Flashing Lights.

SSALR—Simplified Short Approach Lighting System with Runway Alignment Indicator Lights.

ALSAF—High Intensity Approach Lighting System with Sequenced Flashing Lights.

ALSF1—High Intensity Approach Lighting System with Sequenced Flashing Lights, Category I, Configuration.

ALSF2—High Intensity Approach Lighting System with Se-

quenced Flashing Lights, Category II, Configuration. SF—Sequenced Flashing Lights.

OLS-Optical Landing System.

WAVE-OFF.

NOTE: Civil ALSF2 may be operated as SSALR during favorable weather conditions. When runway edge lights are positioned more than 10 feet from the edge of the usable runway surface a remark will be added in the "Remarks" portion of the airport entry. This is applicable to Air Force, Air National Guard and Air Force Reserve Bases, and those joint civil/military airfields on which they are tenants.

VISUAL GLIDESLOPE INDICATORS

APAP—A sv	stem of panels, which may or may not be lighted, used f	or alignme	ent of approach path.					
PNIL	APAP on left side of runway	PNIR	APAP on right side of runway					
PAPI—Preci	sion Approach Path Indicator							
P2L	2-identical light units placed on left side of	P4L	4-identical light units placed on left side of					
	runway		runway					
P2R	2-identical light units placed on right side of	P4R	4-identical light units placed on right side of					
	runway		runway					
PVASI—Puls	sating/steady burning visual approach slope indicator, n	ormally a	single light unit projecting two colors.					
PSIL	PVASI on left side of runway	PSIR	PVASI on right side of runway					
SAVASI—Simplified Abbreviated Visual Approach Slope Indicator								
S2L	2-box SAVASI on left side of runway	S2R	2-box SAVASI on right side of runway					

TRCV—Tri-color visual approach slope indicator, normally a single light unit projecting three colors.

TRIL	TRCV on left side of runway	TRIR	TRCV on right side of runway
VASI-Visua	al Approach Slope Indicator		
V2L	2-box VASI on left side of runway	V6L	6-box VASI on left side of runway
V2R	2-box VASI on right side of runway	V6R	6-box VASI on right side of runway
V4L	4-box VASI on left side of runway	V12	12-box VASI on both sides of runway
V4R	4-box VASI on right side of runway	V16	16-box VASI on both sides of runway

NOTE: Approach slope angle and threshold crossing height will be shown when available; i.e., -GA 3.5° TCH 37'.

PILOT CONTROL OF AIRPORT LIGHTING

Key Mike	Function
7 times within 5 seconds	Highest intensity available
5 times within 5 seconds	Medium or lower intensity (Lower REIL or REIL-Off)
3 times within 5 seconds	Lowest intensity available
	(Lower REIL or REIL-Off)

Available systems will be indicated in the airport or military remarks, e.g., ACTIVATE HIRL Rwy 07–25, MALSR Rwy 07, and VASI Rwy 07—122.8.

Where the airport is not served by an instrument approach procedure and/or has an independent type system of different specification installed by the airport sponsor, descriptions of the type lights, method of control, and operating frequency will be explained in clear text. See AIM, "Basic Flight Information and ATC Procedures," for detailed description of pilot control of airport lighting.

When available, runway slope data will only be provided for those airports with an approved FAA instrument approach procedure. Runway slope will be shown only when it is 0.3 percent or greater. On runways less than 8000 feet, the direction of the slope up will be indicated, e.g., 0.3% up NW. On runways 8000 feet or greater, the slope will be shown (up or down) on the runway end line, e.g., RWY 13: 0.3% up, RWY 21: Pole. Rgt ffc. 0.4% down.

RUNWAY END DATA

Information pertaining to the runway approach end such as approach lights, touchdown zone lights, runway end identification lights, visual glideslope indicators, displaced thresholds, controlling obstruction, and right hand traffic pattern, will be shown on the specific runway end. "Rgt tfc"—Right traffic indicates right turns should be made on landing and takeoff for specified runway end.

LAND AND HOLD SHORT OPERATIONS (LAHSO)

LAHSO is an acronym for "Land and Hold Short Operations." These operations include landing and holding short of an intersection runway, an intersecting taxiway, or other predetermined points on the runway other than a runway or taxiway. Measured distance represents the available landing distance on the landing runway, in feet.

Specific questions regarding these distances should be referred to the air traffic manager of the facility concerned. The Aeronautical Information Manual contains specific details on hold–short operations and markings.

RUNWAY DECLARED DISTANCE INFORMATION

TORA—Take-off Run Available. The length of runway declared available and suitable for the ground run of an aeroplane take-off.

TODA—Take-off Distance Available. The length of the take-off run available plus the length of the clearway, if provided.

ASDA—Accelerate-Stop Distance Available. The length of the take-off run available plus the length of the stopway, if provided. LDA—Landing Distance Available. The length of runway which is declared available and suitable for the ground run of an aeroplane landing.

22 ARRESTING GEAR/SYSTEMS

Arresting gear is shown as it is located on the runway. The a–gear distance from the end of the appropriate runway (or into the overrun) is indicated in parentheses. A–Gear which has a bi–direction capability and can be utilized for emergency approach end engagement is indicated by a (B). The direction of engaging device is indicated by an arrow. Up to 15 minutes advance notice may be required for rigging A–Gear for approach and engagement. Airport listing may show availability of other than US Systems. This information is provided for emergency requirements only. Refer to current aircraft operating manuals for specific engagement weight and speed criteria based on aircraft structural restrictions and arresting system limitations.

Following is a list of current systems referenced in this publication identified by both Air Force and Navy terminology:

BI-DIRECTIONAL CABLE (B)

12

TYPE DESCRIPTION

BAK-9 Rotary friction brake.

BAK-12A Standard BAK-12 with 950 foot run out, 1-inch cable and 40,000 pound weight setting. Rotary

friction brake.

BAK-12B Extended BAK-12 with 1200 foot run, 1¼ inch Cable and 50,000 pounds weight setting. Rotary

friction brake.

E28 Rotary Hydraulic (Water Brake).
M21 Rotary Hydraulic (Water Brake) Mobile.

The following device is used in conjunction with some aircraft arresting systems:

BAK-14 A device that raises a hook cable out of a slot in the runway surface and is remotely positioned

for engagement by the tower on request. (In addition to personnel reaction time, the system

requires up to five seconds to fully raise the cable.)

H A device that raises a hook cable out of a slot in the runway surface and is remotely positioned

for engagement by the tower on request. (In addition to personnel reaction time, the system

requires up to one and one-half seconds to fully raise the cable.)

UNI-DIRECTIONAL CABLE

TYPE DESCRIPTION

MB60 Textile brake—an emergency one-time use, modular braking system employing the tearing of

specially woven textile straps to absorb the kinetic energy.

E5/E5-1/E5-3 Chain Type. At USN/USMC stations E-5 A-GEAR systems are rated, e.g., E-5 RATING-13R-1100

HW (DRY), 31L/R-1200 STD (WET). This rating is a function of the A-GEAR chain weight and length and is used to determine the maximum aircraft engaging speed. A dry rating applies to a stabilized surface (dry or wet) while a wet rating takes into account the amount (if any) of wet overrun that is not capable of withstanding the aircraft weight. These ratings are published under

Military Service.

FOREIGN CABLE

TYPE DESCRIPTION US EQUIVALENT

44B–3H Rotary Hydraulic) (Water Brake)

CHAG Chain E-5

UNI-DIRECTIONAL BARRIER

TYPE DESCRIPTION

MA-1A Web barrier between stanchions attached to a chain energy absorber.

BAK-15 Web barrier between stanchions attached to an energy absorber (water squeezer, rotary friction,

chain). Designed for wing engagement.

NOTE: Landing short of the runway threshold on a runway with a BAK–15 in the underrun is a significant hazard. The barrier in the down position still protrudes several inches above the underrun. Aircraft contact with the barrier short of the runway threshold can cause damage to the barrier and substantial damage to the aircraft.

OTHER

TYPE DESCRIPTION

EMAS Engineered Material Arresting System, located beyond the departure end of the runway, consisting of

high energy absorbing materials which will crush under the weight of an aircraft.

23 MILITARY SERVICE

Specific military services available at the airport are listed under this general heading. Remarks applicable to any military service are shown in the individual service listing.

24 JET AIRCRAFT STARTING UNITS (JASU)

The numeral preceding the type of unit indicates the number of units available. The absence of the numeral indicates ten or more units available. If the number of units is unknown, the number one will be shown. Absence of JASU designation indicates non-availability.

The following is a list of current JASU systems referenced in this publication:

USAF JASU (For variations in technical data, refer to T.O. 35-1-7.)

ELECTRICAL STARTING UNITS:

A/M32A-86 AC: 115/200v, 3 phase, 90 kva, 0.8 pf, 4 wire

DC: 28v, 1500 amp, 72 kw (with TR pack)

MC-1A AC: 115/208v, 400 cycle, 3 phase, 37.5 kva, 0.8 pf, 108 amp, 4 wire

DC: 28v, 500 amp, 14 kw

MD-3 AC: 115/208v, 400 cycle, 3 phase, 60 kva, 0.75 pf, 4 wire

DC: 28v, 1500 amp, 45 kw, split bus

MD-3A AC: 115/208v, 400 cycle, 3 phase, 60 kva, 0.75 pf, 4 wire

DC: 28v, 1500 amp, 45 kw, split bus

MD-3M AC: 115/208v, 400 cycle, 3 phase, 60 kva, 0.75 pf, 4 wire

DC: 28v, 500 amp, 15 kw

AC: 120/208y, 400 cycle, 3 phase, 62.5 kya, 0.8 pf, 175 amp, "WYE" neutral ground, 4 wire, 120y, MD-4 400 cycle, 3 phase, 62.5 kva, 0.8 pf, 303 amp, "DELTA" 3 wire, 120v, 400 cycle, 1 phase, 62.5

kva. 0.8 pf. 520 amp. 2 wire

AIR STARTING UNITS

ΔM32-95 150 + -5 lb/min (2055 + -68 cfm) at 51 + -2 psiaAM32A-95 150 +/- 5 lb/min @ 49 +/- 2 psia (35 +/- 2 psig)

LASS 150 +/- 5 lb/min @ 49 +/- 2 psia

MA-1A 82 lb/min (1123 cfm) at 130° air inlet temp, 45 psia (min) air outlet press

MC-1 15 cfm, 3500 psia MC-1A 15 cfm, 3500 psia MC-2A 15 cfm, 200 psia

MC-11 8,000 cu in cap, 4000 psig, 15 cfm

COMBINED AIR AND ELECTRICAL STARTING UNITS:

AGPU AC: 115/200v, 400 cycle, 3 phase, 30 kw gen

DC: 28v, 700 amp

AIR: 60 lb/min @ 40 psig @ sea level

AM32A-60* AIR: 120 + - 4 lb/min (1644 + - 55 cfm) at 49 + - 2 psia

AC: 120/208v, 400 cycle, 3 phase, 75 kva, 0.75 pf, 4 wire, 120v, 1 phase, 25 kva

DC: 28v, 500 amp, 15 kw

AIR: 150 + -5 lb/min (2055 + -68) cfm at 51 + -9 psia ΔM324-604 AC: 120/208v, 400 cycle, 3 phase, 75 kva, 0.75 pf, 4 wire

DC: 28v. 200 amp. 5.6 kw

AM32A-60B* AIR: 130 lb/min, 50 psia

AC: 120/208v, 400 cycle, 3 phase, 75 kva, 0.75 pf, 4 wire

DC: 28v, 200 amp, 5.6 kw

*NOTE: During combined air and electrical loads, the pneumatic circuitry takes preference and will limit the amount of electrical power available.

USN IASU

FLECTRICAL STARTING UNITS:

NC-8A/A1 DC: 500 amp constant, 750 amp intermittent, 28v;

AC: 60 kva @ .8 pf, 115/200v, 3 phase, 400 Hz. NC-10A/A1/B/C

DC: 750 amp constant, 1000 amp intermittent, 28v:

AC: 90 kva, 115/200v, 3 phase, 400 Hz.

AIR STARTING UNITS:

GTC-85/GTE-85 120 lbs/min @ 45 psi. MSU-200NAV/A/U47A-5 204 lbs/min @ 56 psia.

WELLS AIR START 180 lbs/min @ 75 psi or 120 lbs/min @ 45 psi. Simultaneous multiple start capability.

SYSTEM

COMBINED AIR AND ELECTRICAL STARTING UNITS:

NCPP-105/RCPT 180 lbs/min @ 75 psi or 120 lbs/min @ 45 psi. 700 amp, 28v DC. 120/208v, 400 Hz AC,

30 kva.

JASU (ARMY)

28v, 7.5 kw, 280 amp. 59R2-1R

ELECTRICAL STARTING UNITS (DND):

CF12 AC 115/200v, 140 kva, 400 Hz, 3 phase CF13 AC 115/200v, 60 kva, 400 Hz, 3 phase

CE14 AC/DC 115/200v, 140 kva, 400 Hz, 3 phase, 28vDC, 1500 amp CF15 DC 22-35v, 500 amp continuous 1100 amp intermittent CF16 DC 22-35v, 500 amp continuous 1100 amp intermittent soft start

AIR STARTING UNITS (DND):

ASA 45.5 psig, 116.4 lb/min COMBINED AIR AND ELECTRICAL STARTING UNITS (DND)

AC 120/208v, 60 kva, 400 Hz, 3 phase DC 28v, 75 amp CEA1

AIR 112.5 lb/min, 47 psig

ELECTRICAL STARTING UNITS (OTHER)

C-26 28v 45kw 115-200v 15kw 380-800 Hz 1 phase 2 wire

C-26-B, C-26-C 28v 45kw: Split Bus: 115-200v 15kw 380-800 Hz 1 phase 2 wire

DC 28v/10kw

AIR STARTING UNITS (OTHER):

40 psi/2 lb/sec (LPAS Mk12, Mk12L, Mk12A, Mk1, Mk2B) Α4

MA-1 150 Air HP, 115 lb/min 50 psia MA-2 250 Air HP, 150 lb/min 75 psia

CARTRIDGE:

MXU-4A USAF



Fuel available through US Military Base supply, DESC Into-Plane Contracts and/or reciprocal agreement is listed first and is followed by (Mil). At commercial airports where Into-Plane contracts are in place, the name of the refueling agent is shown. Military fuel should be used first if it is available. When military fuel cannot be obtained but Into-Plane contract fuel is available, Government aircraft must refuel with the contract fuel and applicable refueling agent to avoid any breach in contract terms and conditions. Fuel not available through the above is shown preceded by NC (no contract). When fuel is obtained from NC sources, local purchase procedures must be followed. The US Military Aircraft Identaplates DD Form 1896 (Jet Fuel), DD Form 1897 (Avgas) and AF Form 1245 (Avgas) are used at military installations only. The US Government Aviation Into-Plane Reimbursement (AIR) Card (currently issued by AVCARD) is the instrument to be used to obtain fuel under a DESC Into-Plane Contract and for NC purchases if the refueling agent at the commercial airport accepts the AVCARD. A current list of contract fuel locations is available online at www.desc.dla.mil/Static/ProductsAndServices.asp; click on the Commercial Airports button.

See legend item 14 for fuel code and description.

26 SUPPORTING FLUIDS AND SYSTEMS—MILITARY

CODE

ADI Anti-Detonation Injection Fluid—Reciprocating Engine Aircraft.

W Water Thrust Augmentation—Jet Aircraft.

WAI Water-Alcohol Injection Type, Thrust Augmentation—Jet Aircraft.

SP Single Point Refueling.

PRESAIR Air Compressors rated 3,000 PSI or more.

De-Ice Anti-icing/De-icing/Defrosting Fluid (MIL-A-8243).

OXYGEN:

LPOX Low pressure oxygen servicing.
HPOX High pressure oxygen servicing.
LHOX Low and high pressure oxygen servicing.

LOX Liquid oxygen servicing.

OXRB Oxygen replacement bottles. (Maintained primarily at Naval stations for use in acft where oxygen can be

replenished only by replacement of cylinders.)

OX Indicates oxygen servicing when type of servicing is unknown.

NOTE: Combinations of above items is used to indicate complete oxygen servicing available;

LHOXRB Low and high pressure oxygen servicing and replacement bottles;

LPOXRB Low pressure oxygen replacement bottles only, etc.

NOTE: Aircraft will be serviced with oxygen procured under military specifications only. Aircraft will not be serviced with medical oxygen.

NITROGEN:

LPNIT — Low pressure nitrogen servicing.

HPNIT — High pressure nitrogen servicing.

LHNIT — Low and high pressure nitrogen servicing

27 OIL-MILITARY

US AVIATION OILS (MIL SPECS):

 CODE
 GRADE, TYPE

 0-113
 1065, Reciprocating Engine Oil (MIL-L-6082)

 0-117
 1100, Reciprocating Engine Oil (MIL-L-6082)

 0-117+
 1100, 0-117 plus cyclohexanone (MIL-L-6082)

 0-123
 1065, (Dispersant), Reciprocating Engine Oil (MIL-L-22851 Type III)

 0-128
 1100, (Dispersant), Reciprocating Engine Oil (MIL-L-22851 Type II)

0-132 1005, Jet Engine Oil (MIL-L-6081) 0-133 1010, Jet Engine Oil (MIL-L-6081)

0-147 None, MIL-L-6085A Lubricating Oil, Instrument, Synthetic 0-148 None, MIL-L-7808 (Synthetic Base) Turbine Engine Oil None Aircraft Turbine Engine Synthetic 7 5c St

0-149 None, Aircraft Turbine Engine Synthetic, 7.5c St 0-155 None, MIL-L-6086C, Aircraft, Medium Grade

0-156 None, MIL-L-23699 (Synthetic Base), Turboprop and Turboshaft Engines

JOAP/SOAP Joint Oil Analysis Program. JOAP support is furnished during normal duty hours, other times on request.

(JOAP and SOAP programs provide essentially the same service, JOAP is now the standard joint service

supported program.)

28 TRANSIENT ALERT (TRAN ALERT)—MILITARY

Tran Alert service is considered to include all services required for normal aircraft turn-around, e.g., servicing (fuel, oil, oxygen, etc.), debriefing to determine requirements for maintenance, minor maintenance, inspection and parking assistance of transient aircraft. Drag chute repack, specialized maintenance, or extensive repairs will be provided within the capabilities and priorities of the base. Delays can be anticipated after normal duty hours/holidays/weekends regardless of the hours of transient maintenance operation. Pilots should not expect aircraft to be serviced for TURN-AROUNDS during time periods when servicing or maintenance manpower is not available. In the case of airports not operated exclusively by US military, the servicing indicated by the remarks will not always be available for US military

aircraft. When transient alert services are not shown, facilities are unknown. NO PRIORITY BASIS—means that transient alert services will be provided only after all the requirements for mission/tactical assigned aircraft have been accomplished.

(29) AIRPORT REMARKS

The Attendance Schedule is the months, days and hours the airport is actually attended. Airport attendance does not mean watchman duties or telephone accessibility, but rather an attendant or operator on duty to provide at least minimum services (e.g., repairs, fuel, transportation).

Airport Remarks have been grouped in order of applicability. Airport remarks are limited to those items of information that are determined essential for operational use, i.e., conditions of a permanent or indefinite nature and conditions that will remain in effect for more than 30 days concerning aeronautical facilities, services, maintenance available, procedures or hazards, knowledge of which is essential for safe and efficient operation of aircraft. Information concerning permanent closing of a runway or taxiway will not be shown. A note "See Special Notices" shall be applied within this remarks section when a special notice applicable to the entry is contained in the Special Notices section of this publication.

Parachute Jumping indicates parachute jumping areas associated with the airport. See Parachute Jumping Area section of this publication for additional Information.

Landing Fee indicates landing charges for private or non-revenue producing aircraft. In addition, fees may be charged for planes that remain over a couple of hours and buy no services, or at major airline terminals for all aircraft.

Note: Unless otherwise stated, remarks including runway ends refer to the runway's approach end.

30 MILITARY REMARKS

Military Remarks published at a joint Civil/Military facility are remarks that are applicable to the Military. At Military Facilities all remarks will be published under the heading Military Remarks. Remarks contained in this section may not be applicable to civil users. The first group of remarks is applicable to the primary operator of the airport. Remarks applicable to a tenant on the airport are shown preceded by the tenant organization, i.e., (A) (AF) (N) (ANG), etc. Military airports operate 24 hours unless otherwise specified. Airport operating hours are listed first (airport operating hours will only be listed if they are different than the airport attended hours or if the attended hours are unavailable) followed by pertinent remarks in order of applicability. Remarks will include information on restrictions, hazards, traffic pattern, noise abatement, customs/agriculture/immigration, and miscellaneous information applicable to the Military.

Type of restrictions:

CLOSED: When designated closed, the airport is restricted from use by all aircraft unless stated otherwise. Any closure applying to specific type of aircraft or operation will be so stated. USN/USMC/USAF airports are considered closed during non-operating hours. Closed airports may be utilized during an emergency provided there is a safe landing area.

OFFICIAL BUSINESS ONLY: The airfield is closed to all transient military aircraft for obtaining routine services such as fueling, passenger drop off or pickup, practice approaches, parking, etc. The airfield may be used by aircraws and aircraft if official government business (including civilian) must be conducted on or near the airfield and prior permission is received from the airfield manager.

AF OFFICIAL BUSINESS ONLY OR NAVY OFFICIAL BUSINESS ONLY: Indicates that the restriction applies only to service indicated.

PRIOR PERMISSION REQUIRED (PPR): Airport is closed to transient aircraft unless approval for operation is obtained from the appropriate commander through Chief, Airfield Management or Airfield Operations Officer. Official Business or PPR does not preclude the use of US Military airports as an alternate for IFR flights. If a non-US military airport is used as a weather alternate and requires a PPR, the PPR must be requested and confirmed before the flight departs. The purpose of PPR is to control volume and flow of traffic rather than to prohibit it. Prior permission is required for all aircraft requiring transient alert service outside the published transient alert duty hours. All aircraft carrying hazardous materials must obtain prior permission as outlined in AFJI 11–204, AR 95–27, OPNAVINST 3710.7.

Note: OFFICIAL BUSINESS ONLY AND PPR restrictions are not applicable to Special Air Mission (SAM) or Special Air Resource (SPAR) aircraft providing person or persons on aboard are designated Code 6 or higher as explained in AFJMAN 11–213, AR 95–11, OPNAVINST 3722–8J. Official Business Only or PPR do not preclude the use of the airport as an alternate for IFR flights.

31) WEATHER DATA SOURCES

Weather data sources will be listed alphabetically followed by their assigned frequencies and/or telephone number and hours of operation.

ASOS—Automated Surface Observing System. Reports the same as an AWOS-3 plus precipitation identification and intensity, and freezing rain occurrence (future enhancement).

AWOS-Automated Weather Observing System

AWOS-A—reports altimeter setting (all other information is advisory only).

AWOS-1—reports altimeter setting, wind data and usually temperature, dewpoint and density altitude.

AWOS-2-reports the same as AWOS-1 plus visibility.

AWOS-3—reports the same as AWOS-1 plus visibility and cloud/ceiling data.

See AIM, Basic Flight Information and ATC Procedures for detailed description of AWOS.

HIWAS—See RADIO AIDS TO NAVIGATION

LAWRS—Limited Aviation Weather Reporting Station where observers report cloud height, weather, obstructions to vision, temperature and dewpoint (in most cases), surface wind, altimeter and pertinent remarks.

LLWAS—indicates a Low Level Wind Shear Alert System consisting of a center field and several field perimeter anemometers. SAWRS—identifies airports that have a Supplemental Aviation Weather Reporting Station available to pilots for current weather information.

SWSL—Supplemental Weather Service Location providing current local weather information via radio and telephone.

TDWR—indicates airports that have Terminal Doppler Weather Radar.

WSP—indicates airports that have Weather System Processor.

When the automated weather source is broadcast over an associated airport NAVAID frequency (see NAVAID line), it shall be indicated by a bold ASOS, AWOS, or HIWAS followed by the frequency, identifier and phone number, if available.



Airport terminal control facilities and radio communications associated with the airport shall be shown. When the call sign is not the same as the airport name the call sign will be shown. Frequencies shall normally be shown in descending order with the primary frequency listed first. Frequencies will be listed, together with sectorization indicated by outbound radials, and hours of operation. Communications will be listed in sequence as follows:

Single Frequency Approach (SFA), Common Traffic Advisory Frequency (CTAF), Automatic Terminal Information Service (ATIS) and Aeronautical Advisory Stations (UNICOM) or (AUNICOM) along with their frequency is shown, where available, on the line following the heading "COMMUNICATIONS." When the CTAF and UNICOM frequencies are the same, the frequency will be shown as CTAF/LINICOM 122.8.

The FSS telephone nationwide is toll free 1–800–WX–BRIEF (1–800–992–7433). When the FSS is located on the field it will be indicated as "on arpt". Frequencies available at the FSS will follow in descending order. Remote Communications Outlet (RCO) providing service to the airport followed by the frequency and FSS RADIO name will be shown when available.

FSS's provide information on airport conditions, radio aids and other facilities, and process flight plans. Airport Advisory Service (AAS) is provided on the CTAF by FSS's for select non-tower airports or airports where the tower is not in operation.

(See AIM, Para 4-1-9 Traffic Advisory Practices at Airports Without Operating Control Towers or AC 90-42C.)

Aviation weather briefing service is provided by FSS specialists. Flight and weather briefing services are also available by calling the telephone numbers listed.

Remote Communications Outlet (RCO)—An unmanned air/ground communications facility that is remotely controlled and provides UHF or VHF communications capability to extend the service range of an FSS.

Civil Communications Frequencies-Civil communications frequencies used in the FSS air/ground system are operated on 122.0, 122.2, 123.6; emergency 121.5; plus receive-only on 122.1.

- a. 122.0 is assigned as the Enroute Flight Advisory Service frequency at selected FSS RADIO outlets.
- b. 122.2 is assigned as a common enroute frequency.
- c. 123.6 is assigned as the airport advisory frequency at select non-tower locations. At airports with a tower, FSS may provide airport advisories on the tower frequency when tower is closed.
- d. 122.1 is the primary receive-only frequency at VOR's.
- e. Some FSS's are assigned 50 kHz frequencies in the 122–126 MHz band (eg. 122.45). Pilots using the FSS A/G system should refer to this directory or appropriate charts to determine frequencies available at the FSS or remoted facility through which they wish to communicate.

Emergency frequency 121.5 and 243.0 are available at all Flight Service Stations, most Towers, Approach Control and RADAR facilities.

Frequencies published followed by the letter "T" or "R", indicate that the facility will only transmit or receive respectively on that frequency. All radio aids to navigation (NAVAID) frequencies are transmit only.

TERMINAL SERVICES

SFA—Single Frequency Approach.

CTAF—A program designed to get all vehicles and aircraft at airports without an operating control tower on a common frequency.

ATIS—A continuous broadcast of recorded non-control information in selected terminal areas.

D-ATIS—Digital ATIS provides ATIS information in text form outside the standard reception range of conventional ATIS via landline & data link communications and voice message within range of existing transmitters.

AUNICOM—Automated UNICOM is a computerized, command response system that provides automated weather, radio check capability and airport advisory information selected from an automated menu by microphone clicks.

UNICOM—A non-government air/ground radio communications facility which may provide airport information.

PTD—Pilot to Dispatcher.

APP CON—Approach Control. The symbol (R) indicates radar approach control.

TOWER—Control tower.

GCA—Ground Control Approach System.

GND CON-Ground Control.

GCO—Ground Communication Outlet—An unstaffed, remotely controlled, ground/ground communications facility. Pilots at uncontrolled airports may contact ATC and FSS via VHF to a telephone connection to obtain an instrument clearance or close a VFR or IFR flight plan. They may also get an updated weather briefing prior to takeoff. Pilots will use four "key clicks" on the

VHF radio to contact the appropriate ATC facility or six "key clicks" to contact the FSS. The GCO system is intended to be used only on the ground.

DEP CON—Departure Control. The symbol (R) indicates radar departure control.

CLNC DEL-Clearance Delivery.

PRE TAXI CLNC-Pre taxi clearance.

VFR ADVSY SVC—VFR Advisory Service. Service provided by Non-Radar Approach Control.

Advisory Service for VFR aircraft (upon a workload basis) ctc APP CON.

COMD POST—Command Post followed by the operator call sign in parenthesis.

PMSV—Pilot-to-Metro Service call sign, frequency and hours of operation, when full service is other than continuous.

PMSV installations at which weather observation service is available shall be indicated, following the frequency and/or

hours of operation as "Wx obsn svc 1900–0000Z‡" or "other times" may be used when no specific time is given. PMSV facilities manned by forecasters are considered "Full Service". PMSV facilities manned by weather observers are listed as "Limited Service".

OPS—Operations followed by the operator call sign in parenthesis.

CON

RANGE

FLT FLW-Flight Following

MEDIVAC

NOTE: Communication frequencies followed by the letter "X" indicate frequency available on request.

33 AIRSPACE

Information concerning Class B, C, and part-time D and E surface area airspace shall be published with effective times. Class D and E surface area airspace that is continuous as established by Rulemaking Docket will not be shown.

CLASS B-Radar Sequencing and Separation Service for all aircraft in CLASS B airspace.

CLASS C—Separation between IFR and VFR aircraft and sequencing of VFR arrivals to the primary airport.

TRSA—Radar Sequencing and Separation Service for participating VFR Aircraft within a Terminal Radar Service Area.

Class C, D, and E airspace described in this publication is that airspace usually consisting of a 5 NM radius core surface area that begins at the surface and extends upward to an altitude above the airport elevation (charted in MSL for Class C and Class D). Class E surface airspace normally extends from the surface up to but not including the overlying controlled airspace.

When part-time Class C or Class D airspace defaults to Class E, the core surface area becomes Class E. This will be formatted as:

AIRSPACE: CLASS C svc "times" ctc APP CON other times CLASS E:

0

AIRSPACE: CLASS D svc "times" other times CLASS E.

When a part-time Class C, Class D or Class E surface area defaults to Class G, the core surface area becomes Class G up to, but not including, the overlying controlled airspace. Normally, the overlying controlled airspace is Class E airspace beginning at either 700' or 1200' AGL. This will be formatted as:

AIRSPACE: CLASS C svc "times" ctc APP CON other times CLASS G, with CLASS E 700' (or 1200') AGL & abv:

0

 $\textbf{AIRSPACE: CLASS D} \ \text{svc ''times'' other times CLASS G with CLASS E 700' (or 1200') AGL \& abv: \\$

٥r

AIRSPACE: CLASS E svc "times" other times CLASS G with CLASS E 700' (or 1200') AGL & abv.

NOTE: AIRSPACE SVC "TIMES" INCLUDE ALL ASSOCIATED ARRIVAL EXTENSIONS. Surface area arrival extensions for instrument approach procedures become part of the primary core surface area. These extensions may be either Class D or Class E airspace and are effective concurrent with the times of the primary core surface area. For example, when a part-time Class C, Class D or Class E surface area defaults to Class G, the associated arrival extensions will default to Class G at the same time. When a part-time Class C or Class D surface area defaults to Class E, the arrival extensions will remain in effect as Class E airspace.

NOTE: CLASS E AIRSPACE EXTENDING UPWARD FROM 700 FEET OR MORE ABOVE THE SURFACE, DESIGNATED IN CONJUNCTION WITH AN AIRPORT WITH AN APPROVED INSTRUMENT PROCEDURE.


Class E 700′ AGL (shown as magenta vignette on sectional charts) and 1200′ AGL (blue vignette) areas are designated when necessary to provide controlled airspace for transitioning to/from the terminal and enroute environments. Unless otherwise specified, these 700′/1200′ AGL Class E airspace areas remain in effect continuously, regardless of airport operating hours or surface area status. These transition areas should not be confused with surface areas or arrival extensions.

(See Chapter 3, AIRSPACE, in the Aeronautical Information Manual for further details)



The Airport/Facility Directory lists, by facility name, all Radio Aids to Navigation that appear on National Aeronautical Charting Office Visual or IFR Aeronautical Charts and those upon which the FAA has approved an Instrument Approach Procedure, with exception of selected TACANs. Military TACAN information will be published for Military facilities contained in this publication. All VOR, VORTAC, TACAN, ILS and MLS equipment in the National Airspace System has an automatic monitoring and shutdown feature in the event of malfunction. Unmonitored, as used in this publication, for any navigational aid, means that monitoring personnel cannot observe the malfunction or shutdown signal. The NAVAID NOTAM file identifier will be shown as "NOTAM FILE IAD" and will be listed on the Radio Aids to Navigation line. When two or more NAVAIDS are listed and the NOTAM file identifier is different from that shown on the Radio Aids to Navigation line, it will be shown with the NAVAID listing. NOTAM file identifiers for ILSs and its components (e.g., NDB (LOM) are the same as the associated airports and are not repeated. Automated Surface Observing System (ASOS), Automated Weather Observing System (AWOS), and Hazardous Inflight Weather Advisory Service (HIWAS) will be shown when this service is broadcast over selected NAVAIDs.

NAVAID information is tabulated as indicated in the following sample:



Restriction within the normal altitude/range of the navigational aid (See primary alphabetical listing for restrictions on VORTAC and VOR/DME).

Note: Those DME channel numbers with a (Y) suffix require TACAN to be placed in the "Y" mode to receive distance information

HIWAS—Hazardous Inflight Weather Advisory Service is a continuous broadcast of inflight weather advisories including summarized SIGMETs, convective SIGMETs, AIRMETs and urgent PIREPs. HIWAS is presently broadcast over selected VOR's and will be implemented throughout the conterminous U.S.

ASR/PAR—Indicates that Surveillance (ASR) or Precision (PAR) radar instrument approach minimums are published in the U.S. Terminal Procedures. Only part-time hours of operation will be shown.

RADIO CLASS DESIGNATIONS

VOR/DME/TACAN Standard Service Volume (SSV) Classifications

SSV Class	Altitudes	Distance
		(NM)
(T) Terminal	1000' to 12,000'	25
(L) Low Altitude	1000' to 18,000'	40
(H) High Altitude	1000' to 14,500'	40
	14,500' to 18,000'	100
	18,000' to 45,000'	130
	45.000' to 60.000'	100

NOTE: Additionally, (H) facilities provide (L) and (T) service volume and (L) facilities provide (T) service. Altitudes are with respect to the station's site elevation. Coverage is not available in a cone of airspace directly above the facility.

CONTINUED ON NEXT PAGE

CONTINUED FROM PRECEDING PAGE

The term VOR is, operationally, a general term covering the VHF omnidirectional bearing type of facility without regard to the fact that the power, the frequency protected service volume, the equipment configuration, and operational requirements may vary between facilities at different locations.

AB	Automatic Weather Broadcast.
DF	
DME	
DME(Y)	UHF standard (TACAN compatible) distance measuring equipment that require TACAN to be placed in the "Y" mode to receive DME.
GS	Glide slope.
Н	 Non-directional radio beacon (homing), power 50 watts to less than 2,000 watts (50 NM at all altitudes).
HH	Non-directional radio beacon (homing), power 2,000 watts or more (75 NM at all altitudes).
H-SAB	Non-directional radio beacons providing automatic transcribed weather service.
ILS	_ Instrument Landing System (voice, where available, on localizer channel).
IM	Inner marker.
ISMLS	Interim Standard Microwave Landing System.
LDA	Localizer Directional Aid.
LMM	Compass locator station when installed at middle marker site (15 NM at all altitudes).
LOM	Compass locator station when installed at outer marker site (15 NM at all altitudes).
MH	Non-directional radio beacon (homing) power less than 50 watts (25 NM at all altitudes).
MLS	Microwave Landing System.
MM	Middle marker.
OM	Outer marker.
S	_ Simultaneous range homing signal and/or voice.
SABH	 Non-directional radio beacon not authorized for IFR or ATC. Provides automatic weather broadcasts.
SDF	_ Simplified Direction Facility.
TACAN	
VOR	VHF navigational facility-omnidirectional course only.
VOR/DME	
VORTAC	Collocated VOR and TACAN navigational facilities.
W	
Z	

ILS FACILITY PEFORMANCE CLASSIFICATION CODES

Codes define the ability of an ILS to support autoland operations. The two portions of the code represent Official Category and farthest point along a Category I, II, or III approach that the Localizer meets Category III structure tolerances.

Official Category: I. II. or III: the lowest minima on published or unpublished procedures supported by the ILS.

Farthest point of satisfactory Category III Localizer performance for Category I, II, or III approaches: A-4 NM prior to runway threshold, B-3500 ft prior to runway threshold, C-glide angle dependent but generally 750–1000 ft prior to threshold, T-runway threshold, D-3000 ft after runway threshold, and E-2000 ft prior to stop end of runway.

ILS information is tabulated as indicated in the following sample:



FREQUENCY PAIRING PLAN AND MLS CHANNELING

	I REGULACI I AIRING I LAN AND MES CHANNELING								
MLS	VHF	TACAN	MLS	VHF	TACAN	MLS	VHF	TACAN	
CHANNEL	FREQUENCY	CHANNEL	CHANNEL	FREQUENCY	CHANNEL	CHANNEL	FREQUENCY	CHANNEL	
500	108.10	18X	568	109.45	31Y	636	114.15	88Y	
502	108.30	20X	570	109.55	32Y	638	114.25	89Y	
504	108.50	22X	572	109.65	33Y	640	114.35	90Y	
506	108.70	24X	574	109.75	34Y	642	114.45	91Y	
508	108.90	26X	576	109.85	35Y	644	114.55	92Y	
510	109.10	28X	578	109.95	36Y	646	114.65	93Y	
512	109.30	30X	580	110.05	37Y	648	114.75	94Y	
514	109.50	32X	582	110.15	38Y	650	114.85	95Y	
516	109.70	34X	584	110.25	39Y	652	114.95	96Y	
518	109.90	36X	586	110.35	40Y	654	115.05	97Y	
520	110.10	38X	588	110.45	41Y	656	115.15	98Y	
522	110.30	40X	590	110.55	42Y	658	115.25	99Y	
524	110.50	42X	592	110.65	43Y	660	115.35	100Y	
526	110.70	44X	594	110.75	44Y	662	115.45	101Y	
528	110.90	46X	596	110.85	45Y	664	115.55	102Y	
530	111.10	48X	598	110.95	46Y	666	115.65	103Y	
532	111.30	50X	600	111.05	47Y	668	115.75	104Y	
534	111.50	52X	602	111.15	48Y	670	115.85	105Y	
536	111.70	54X	604	111.25	49Y	672	115.95	106Y	
538	111.90	56X	606	111.35	50Y	674	116.05	107Y	
540	108.05	17Y	608	111.45	51Y	676	116.15	108Y	
542	108.15	18Y	610	111.55	52Y	678	116.25	109Y	
544	108.25	19Y	612	111.65	53Y	680	116.35	110Y	
546	108.35	20Y	614	111.75	54Y	682	116.45	111Y	
548	108.45	21Y	616	111.85	55Y	684	116.55	112Y	
550	108.55	22Y	618	111.95	56Y	686	116.65	113Y	
552	108.65	23Y	620	113.35	80Y	688	116.75	114Y	
554	108.75	24Y	622	113.45	81Y	690	116.85	115Y	
556	108.85	25Y	624	113.55	82Y	692	116.95	116Y	
558	108.95	26Y	626	113.65	83Y	694	117.05	117Y	
560	109.05	27Y	628	113.75	84Y	696	117.15	118Y	
562	109.15	28Y	630	113.85	85Y	698	117.25	119Y	
564	109.25	29Y	632	113.95	86Y				
566	109.35	30Y	634	114.05	87Y				

FREQUENCY PAIRING PLAN AND MLS CHANNELING

The following is a list of paired VOR/ILS VHF frequencies with TACAN channels and MLS channels.

TACAN	VHF	MLS	TACAN	VHF	MLS	TACAN	VHF	MLS
CHANNEL	FREQUENCY	CHANNEL	CHANNEL	FREQUENCY	CHANNEL	CHANNEL	FREQUENCY	CHANNEL
2X	134.5	-	19Y	108.25	544	25X	108.80	-
2Y	134.55	-	20X	108.30	502	25Y	108.85	556
11X	135.4	-	20Y	108.35	546	26X	108.90	508
11Y	135.45	-	21X	108.40	-	26Y	108.95	558
12X	135.5	-	21Y	108.45	548	27X	109.00	-
12Y	135.55	-	22X	108.50	504	27Y	109.05	560
17X	108.00	-	22Y	108.55	550	28X	109.10	510
17Y	108.05	540	23X	108.60	-	28Y	109.15	562
18X	108.10	500	23Y	108.65	552	29X	109.20	-
18Y	108.15	542	24X	108.70	506	29Y	109.25	564
19X	108.20	-	24Y	108.75	554	30X	109.30	512

30V 109.35 566 63X 133.60 . 95V 114.85 650 31X 109.40 . 63V 133.65 . 96X 114.90 652 32X 109.50 514 64V 133.75 . 96V 114.95 652 32X 109.55 570 66X 133.80 . 97V 115.05 654 33X 109.60 . 65V 133.85 . 98X 115.15 656 33X 109.60 . 65V 133.85 . 98X 115.15 656 34X 109.70 516 66V 133.95 . 98V 115.15 656 34X 109.70 516 66V 133.95 . 98V 115.20 . 34Y 109.75 574 67X 134.00 . 99Y 115.25 658 35X 109.80 . 67Y 134.05 . 100X 115.30 . 35Y 109.85 578 68X 134.15 . 100X 115.30 . 36X 109.95 518 68X 134.15 . 101X 115.40 . 36X 109.95 518 68X 134.15 . 101X 115.40 . 37Y 110.06 50 70V 112.35 . 101X 115.45 660 38X 110.10 520 70V 112.35 . 102X 115.65 664 38X 110.10 520 70V 112.35 . 102X 115.65 668 40X 110.30 522 72Y 112.50 . 104Y 115.75 668 40X 110.30 522 72Y 112.50 . 104Y 115.75 668 40X 110.30 522 72Y 112.50 . 104Y 115.75 668 40X 110.30 522 72Y 112.50 . 104Y 115.75 668 40X 110.30 522 72Y 112.50 . 104Y 115.75 668 40X 110.30 524 74Y 112.70 . 106Y 115.85 670 44X 110.40 . 73Y 112.60 . 105Y 115.85 670 44X 110.40 . 73Y 112.65 . 106X 115.90 . 74Y 112.65 . 106X 115.95 672 42X 110.50 594 77X 112.26 . 106Y 115.55 664 44X 110.30 524 74Y 112.75 . 107X 116.00 . 74Y 112.65 . 106X 115.95 672 42X 110.50 594 77X 112.80 . 106Y 115.85 670 44X 110.60 588 74X 112.70 . 106Y 115.85 670 44X 110.60 588 74X 112.70 . 106Y 115.85 670 44X 110.60 588 74X 112.70 . 106Y 115.95 672 42X 110.55 590 75X 112.80 . 107Y 116.05 674 44X 110.60 596 78X 113.10 . 110X 116.35 680 46X 110.80 596 78X 113.10 . 110X 116.35 680 46X 110.80 596 78X 113.15 . 110X 116.05 674 44X 110.60 508 80X 113.35 600 113X 116.60 . 640 55X 111.85 606 83X 113.15 . 110X 116.35 680 56X 110.80 596 78X 113.15 . 110X 116.35 680 56X 110.80 596 78X 113.15 . 110X 116.35 680 56X 110.80 596 78X 113.15 . 110X 116.35 680 56X 110.80 596 78X 113.15 . 110X 116.35 680 56X 110.80 596 78X 113.15 . 110X 116.35 680 57X 111.55 606 88X 113.80 . 117Y 116.55 688 58X 110.60 534 84Y 113.75 628 117X 117.00 . 560 56X 111.85 606 83X 113.80 . 117Y 116.05 694 57X 111.65 612 86X 113.80 . 111Y 117.55 698 51X 111.65 612 86X 113.80 . 111X 117	TACAN Channel	VHF Frequency	MLS Channel	TACAN Channel	VHF Frequency	MLS Channel	TACAN Channel	VHF Frequency	MLS Channel
31X 109.40 - 63Y 133.65 - 96X 114.95 62.22 32X 109.50 514 64Y 133.75 - 97X 115.00 - 32Y 109.55 570 66X 133.80 - 97Y 115.00 - 33X 109.65 572 66X 133.90 - 98Y 115.10 - 34X 109.75 574 67X 134.00 - 99Y 115.20 - 35X 109.85 576 66X 133.90 - 99Y 115.20 - 35X 109.85 576 66X 134.10 - 100Y 115.25 68 36X 109.85 576 66X 134.10 - 101Y 115.35 660 36X 109.95 578 66X 134.20 - 101Y 115.45 62 37X 110.05 580 70X 112.35 <td></td> <td></td> <td></td> <td></td> <td></td> <td>-</td> <td></td> <td></td> <td></td>						-			
32Y 109.50 514 64Y 133.75 - 97X 115.00 654 32Y 109.55 570 65X 133.80 - 99X 115.15 654 33X 109.60 - 66Y 133.90 - 98Y 115.15 656 34X 109.70 516 66Y 133.95 - 99X 115.20 - 34X 109.75 574 67X 134.00 - 99Y 115.25 658 35X 109.80 - 67Y 134.05 - 100X 115.30 - 35Y 109.85 576 68X 134.10 - 100Y 115.35 660 36X 109.90 518 68Y 134.10 - 100Y 115.35 660 36X 109.90 518 68Y 134.10 - 101X 115.40 - 36Y 109.95 578 68X 134.20 - 101Y 115.45 662 37X 110.00 - 66Y 134.25 - 102X 115.50 - 37Y 110.05 580 70X 112.35 - 102X 115.50 664 38X 110.10 520 70Y 112.35 - 103X 115.60 - 38Y 110.15 582 71X 112.40 - 103Y 115.65 666 39X 110.20 - 71Y 112.45 - 104X 115.70 - 39Y 110.25 584 72X 112.50 - 104X 115.70 - 40X 110.30 522 72Y 112.55 - 105X 115.80 - 40X 110.30 522 72Y 112.55 - 105X 115.80 - 41X 110.40 - 73Y 112.60 - 105Y 115.85 670 41X 110.40 - 73Y 112.60 - 105Y 115.85 670 41X 110.40 - 73Y 112.60 - 105Y 115.85 672 42X 110.50 524 74Y 112.75 - 106X 115.90 - 42X 110.50 524 74Y 112.75 - 106X 115.90 - 43X 110.60 - 75Y 112.85 - 105X 115.80 - 44X 110.70 526 76Y 112.85 - 105X 115.80 - 44X 110.70 526 76Y 112.85 - 105X 115.80 - 44X 110.70 526 76Y 112.85 - 105X 115.80 - 44X 110.75 594 77X 113.00 - 105Y 115.85 672 44X 110.75 594 77X 113.00 - 105Y 116.65 674 44X 110.75 594 77X 113.00 - 105Y 116.85 678 45Y 110.85 596 78X 113.15 - 110X 116.50 - 4 44X 110.75 596 78Y 112.85 - 105X 116.80 - 4 44Y 111.05 596 78Y 112.85 - 105X 116.80 - 4 44Y 111.05 596 78Y 113.15 - 110X 116.50 - 4 44Y 111.05 596 78Y 113.15 - 110X 116.50 - 4 44Y 111.05 596 78Y 113.15 - 110X 116.50 - 5 45Y 110.85 596 78Y 113.15 - 110X 116.50 - 5 44Y 11.15 602 88X 113.90 - 115Y 116.15 680 40X 111.25 604 88X 113.90 - 115Y 116.75 688 50X 111.50 688 88X 113.90 - 115Y 116.75 688 50X 111.50 688 88X 113.90 - 115Y 116.75 688 50X 111.50 618 88X 113.90 - 115Y 116.55 684 50X 111.50 618 88X 113.90 - 115Y 116.55 684 50X 111.50 618 88X 113.90 - 115Y 117.75 699 50X 111.55 610 88X 113.90 - 115Y 117.75 699 50X 111.55 618 88X 114.10 - 129Y 117.75 699 50X 111.55 618 88X 114.10 - 129Y 117.75 699 50X 111.55 618 88X 114.10 - 12	31X	109.40				-	96X		-
32Y	31Y	109.45	568	64X	133.70	-	96Y	114.95	652
33X 109.60 - 66Y 133.85 - 98X 115.10 - 33Y 109.65 572 66X 133.90 - 98Y 115.15 665 668 133.90 - 98Y 115.15 665 668 133.91 - 99X 115.20 - 34X 109.70 516 66Y 133.95 - 99X 115.20 - 35X 109.80 - 67Y 134.05 - 100X 115.30 658 35X 109.80 - 67Y 134.05 - 100X 115.30 - 35Y 109.85 576 68X 134.10 - 100Y 115.35 660 36X 109.90 518 68Y 134.15 - 101X 115.40 - 36Y 109.95 578 66X 134.20 - 101Y 115.40 - 37Y 110.00 - 66Y 134.25 - 102X 115.50 - 37Y 110.00 - 66Y 134.25 - 102X 115.50 - 37Y 110.05 580 70X 112.30 - 102Y 115.55 664 38X 110.10 520 70Y 112.35 - 102X 115.50 - 38Y 110.15 582 71X 112.40 - 103X 115.60 - 38Y 110.15 582 71X 112.40 - 103Y 115.60 668 39X 110.20 - 71Y 112.45 - 104X 115.70 668 40X 110.35 584 72X 112.50 - 104X 115.70 668 40X 110.35 586 72X 112.80 - 105X 115.80 670 41Y 110.35 586 72X 112.80 - 105X 115.80 670 41Y 110.45 588 74X 112.70 - 106X 115.80 670 41Y 110.45 588 74X 112.70 - 106X 115.80 674 41Y 110.45 588 74X 112.70 - 106X 115.80 674 41Y 110.55 590 75X 112.80 - 107X 116.05 674 41Y 110.55 590 75X 112.80 - 107X 116.05 674 41Y 110.55 590 75X 112.80 - 107X 116.05 674 41Y 110.65 594 77X 112.85 - 106X 115.80 674 41Y 110.55 590 75X 112.80 - 106X 115.90 674 41Y 110.55 590 75X 112.80 - 106X 115.90 674 41Y 110.55 590 75X 112.80 - 106X 115.90 674 41Y 110.55 590 75X 112.80 - 106X 115.90 674 41Y 110.55 590 75X 112.80 - 106X 115.90 674 41Y 110.55 590 75X 112.80 - 106X 115.90 674 41Y 110.55 590 75X 112.80 - 106X 115.90 674 41Y 110.55 590 75X 112.80 - 106X 115.90 674 41Y 110.55 590 75X 112.80 - 106X 115.90 674 41Y 110.55 590 75X 112.80 - 106X 115.90 674 41Y 110.55 590 75X 112.80 - 106X 115.90 674 41Y 110.55 590 75X 112.80 - 106X 115.90 674 41Y 110.55 590 75X 112.80 - 106X 115.90 674 41Y 110.55 590 75X 112.80 - 106X 115.90 674 41Y 110.55 590 75X 112.80 - 106X 115.90 675 678 678 678 678 678 678 678 678 678 678	32X	109.50	514	64Y	133.75	-	97X	115.00	-
34X 109.65 572 66K 133.90 - 98Y 115.15 656 34X 109.70 516 66V 133.95 - 99X 115.20 - 34Y 109.75 574 67X 134.00 - 99Y 115.25 658 35X 109.80 - 67Y 134.05 - 100X 115.30 60 36X 109.90 518 68X 134.10 - 100Y 115.35 660 36X 109.90 518 68X 134.10 - 100Y 115.35 660 36X 109.90 518 68X 134.25 - 100X 115.30 - 36Y 109.95 578 60X 134.20 - 101Y 115.45 662 37X 110.00 - 69Y 134.25 - 100X 115.50 - 37Y 110.05 580 70X 112.30 - 100Y 115.55 664 38X 110.10 520 70Y 112.35 - 103X 115.65 - 38Y 110.15 582 71X 112.45 - 104X 115.70 - 38Y 110.25 584 72X 112.50 - 104X 115.70 - 39Y 110.25 584 72X 112.50 - 104X 115.70 - 40X 110.30 522 72Y 112.55 - 105X 115.80 - 40X 110.30 522 72Y 112.55 - 105X 115.80 - 41X 110.40 - 73Y 112.60 - 105Y 115.85 670 41X 110.40 - 73Y 112.60 - 105Y 115.85 672 42X 110.55 590 75X 112.80 - 107X 116.00 - 4 42X 110.50 524 74Y 112.75 - 107X 116.00 - 4 42X 110.50 524 74Y 112.70 - 106Y 115.75 672 42X 110.50 590 75X 112.80 - 107Y 116.05 674 43X 110.60 - 75Y 112.85 - 106X 115.90 - 4 43X 110.60 - 75Y 112.85 - 106X 116.30 - 6 44X 110.70 526 76Y 112.95 - 106X 116.30 - 6 44X 110.70 526 76Y 112.95 - 106X 116.50 - 6 44X 110.70 526 76Y 112.95 - 106X 116.50 - 6 44X 110.70 526 76Y 112.95 - 106X 116.50 - 6 44X 110.70 526 76Y 112.95 - 106X 116.50 - 6 44X 110.70 526 76Y 112.95 - 106X 116.50 - 6 44X 110.70 526 76Y 112.95 - 106X 116.50 - 6 44X 110.70 526 76Y 112.95 - 106X 116.50 - 6 44X 110.70 526 76Y 112.95 - 106X 116.50 - 6 45Y 110.85 596 78X 113.15 - 111X 116.40 - 6 45Y 110.85 596 78X 113.15 - 111X 116.60 - 6 45Y 110.85 596 78X 113.15 - 111X 116.60 - 6 45Y 110.85 596 78X 113.15 - 111X 116.60 - 6 46Y 110.95 598 79X 113.25 - 112X 116.50 - 6 50Y 111.55 604 80Y 113.55 620 113X 116.60 - 6 50Y 111.55 610 80Y 113.55 620 113X 116.60 - 6 50Y 111.55 610 80Y 113.55 620 113X 116.60 - 6 50Y 111.55 610 80Y 113.55 620 113X 116.60 - 6 50Y 111.55 610 80Y 113.55 620 113X 116.60 - 6 50Y 111.55 610 80Y 113.55 620 113X 116.60 - 6 50Y 111.55 610 80Y 113.55 620 113X 116.60 - 6 50Y 111.55 610 80Y 113.55 620 113X 116.60 - 6 50Y 111.55 618 80Y 113.55 620 113X 116.6	32Y	109.55	570	65X	133.80	-	97Y	115.05	654
34X 109.70 516 66Y 133.95 - 99X 115.20 - 38X 109.80 - 67X 134.00 - 99Y 115.25 68S 38X 109.80 - 67Y 134.05 - 100X 115.30 - 68D 38X 109.90 518 68X 134.15 - 101X 115.40 - 36Y 109.95 578 69X 134.20 - 101Y 115.45 662 37X 110.05 580 70X 112.36 - 102X 115.50 - 37Y 110.05 580 70X 112.36 - 103X 115.60 - 38X 110.16 582 71X 112.40 - 103X 115.60 - 38X 110.15 582 72X 112.40 - 103X 115.60 - 38X 110.15 582 72X 112.55 - 104X 115.75 668 - 40X 110.35	33X	109.60	-	65Y	133.85	-	98X	115.10	-
34Y 109.75 574 67X 134.00 - 99Y 115.25 688 35X 109.85 576 68X 134.10 - 100Y 115.35 668 36Y 109.90 518 68Y 134.15 - 101X 115.45 662 37X 110.00 69Y 134.20 - 101Y 115.45 662 37X 110.00 590 70X 112.30 - 102Y 115.55 664 38X 110.15 582 71X 112.40 - 103X 115.60 - 664 38X 110.25 584 72X 112.50 - 104Y 115.75 668 40X 110.35 584 72X 112.50 - 104Y 115.75 668 40X 110.35 586 73X 112.60 - 105Y 115.85 670 41X 110.45 587 74X	33Y	109.65	572	66X	133.90	-	98Y	115.15	656
35X 109.80 - 67Y 134.05 - 100X 115.30 - 36X 109.90 518 68Y 134.15 - 101X 115.40 - 36Y 109.95 578 69X 134.20 - 101Y 115.45 662 37X 110.05 580 70X 112.35 - 102X 115.50 - 37Y 110.05 580 70X 112.35 - 103X 115.60 - 38Y 110.15 582 71X 112.46 - 103X 115.65 664 38Y 110.20 - 71Y 112.45 - 104X 115.75 668 38X 110.15 582 72X 112.50 - 104X 115.75 666 38Y 110.25 584 72X 112.55 - 106X 115.75 668 40X 110.30 52 72Y 112.5	34X	109.70	516	66Y	133.95	-	99X	115.20	-
36X 109.95 576 68X 134.15 - 101X 115.35 660 68Y 130.95 578 69X 134.25 - 101X 115.45 662 37X 110.00 - 69Y 134.25 - 102X 115.55 664 38X 110.10 520 70Y 112.35 - 103X 115.60 - 38Y 110.15 582 71X 112.40 - 103Y 115.55 664 38X 110.10 520 70Y 112.35 - 103X 115.65 666 39X 110.20 - 71Y 112.45 - 104X 115.70 - 39Y 110.25 584 72X 112.50 - 104Y 115.75 668 40X 110.30 522 72Y 112.55 - 105X 115.80 - 104X 115.70 - 105X 115.80 - 107X 110.55 566 73X 112.60 - 105Y 115.85 670 41X 110.45 586 74X 112.70 - 106Y 115.85 672 42X 110.50 524 74Y 112.75 - 106X 115.90 - 42X 110.50 524 74Y 112.75 - 107X 116.00 - 43X 110.60 - 75Y 112.85 - 107X 116.00 - 43X 110.60 - 75Y 112.85 - 107X 116.00 - 44X 110.70 526 76X 112.90 - 108X 116.15 676 44X 110.70 526 76Y 112.95 - 108X 116.10 - 44X 110.75 594 77X 113.00 - 109Y 116.25 678 44X 110.75 594 77X 113.00 - 109Y 116.25 678 44X 110.70 526 78X 113.10 - 110X 116.30 - 44X 110.75 598 79X 113.15 - 111X 116.40 - 44X 110.75 598 79X 113.15 - 111X 116.40 - 44X 110.75 598 79X 113.15 - 111X 116.40 - 44X 110.75 598 79X 113.20 - 111Y 116.55 684 49X 111.15 602 81X 113.10 - 110Y 116.55 684 49X 111.15 602 81X 113.10 - 110Y 116.55 684 49X 111.15 602 81X 113.15 - 111X 116.40 - 51X 111X 116.40 - 51X 111X 116.40 - 88Y 113.15 - 111X 116.60 - 51X	34Y	109.75	574	67X	134.00	-	99Y	115.25	658
36X 109.90 518 68Y 134.20 - 101X 115.40 - 37X 110.00 - 69Y 134.25 - 102X 115.50 - 37X 110.05 580 70X 112.30 - 102X 115.50 - 38X 110.15 582 71X 112.35 - 103X 115.65 664 38X 110.20 - 71Y 112.45 - 104X 115.70 - 38Y 110.25 584 72X 112.50 - 104X 115.75 668 40X 110.30 522 72Y 112.55 - 106X 115.75 668 40X 110.35 586 73X 112.60 - 106X 115.85 670 41Y 110.45 588 74X 112.70 - 106X 115.95 - 24X 110.60 - 75X 112.80 - </td <td>35X</td> <td>109.80</td> <td>-</td> <td>67Y</td> <td>134.05</td> <td>-</td> <td>100X</td> <td>115.30</td> <td>-</td>	35X	109.80	-	67Y	134.05	-	100X	115.30	-
36Y 109.95 578 69X 134.20 - 101X 115.50 - 37Y 110.05 580 70X 112.30 - 102X 115.55 - 38X 110.10 520 70Y 112.35 - 103X 115.60 - 38Y 110.15 582 71X 112.40 - 103Y 115.65 666 38X 110.20 - 71Y 112.45 - 104X 115.76 - 40X 110.30 522 72Y 112.55 - 105X 115.86 - 40Y 110.35 586 73X 112.60 - 105Y 115.85 670 41X 110.40 - 73Y 112.65 - 106X 115.95 672 41X 110.40 - 73Y 112.65 - 106X 115.95 672 42Y 110.55 588 74X 112.70 </td <td>35Y</td> <td>109.85</td> <td>576</td> <td>68X</td> <td>134.10</td> <td>-</td> <td>100Y</td> <td>115.35</td> <td>660</td>	35Y	109.85	576	68X	134.10	-	100Y	115.35	660
37X 110.00 - 69Y 134.25 - 102Y 115.55 664 38X 110.10 520 70Y 112.35 - 103Y 115.65 664 38Y 110.15 582 71X 112.40 - 103Y 115.65 666 39X 110.25 584 72X 112.50 - 104X 115.70 - 39Y 110.25 584 72X 112.50 - 104Y 115.75 668 40X 110.30 522 72Y 112.55 - 108X 115.80 - 40Y 110.35 586 73X 112.65 - 106X 115.80 - 41X 110.40 - 73Y 112.65 - 106X 115.80 - 41X 110.65 589 75X 112.85 - 106X 115.99 - 42X 110.55 590 75X 112.85	36X	109.90	518	68Y	134.15	-	101X	115.40	-
37Y 110.05 580 70X 112.30 - 102Y 115.55 664 38Y 110.10 520 70Y 112.35 - 103X 115.65 666 38Y 110.20 - 71Y 112.45 - 103X 115.65 666 39Y 110.25 584 72X 112.50 - 104X 115.76 688 40X 110.30 522 72Y 112.55 - 105X 115.86 67 41X 110.40 - 73Y 112.60 - 106Y 115.85 67 41X 110.40 - 73Y 112.65 - 106X 115.95 67 41X 110.40 - 73Y 112.65 - 106X 115.95 672 41Y 110.65 588 74X 112.70 - 106Y 116.00 - 42Y 110.55 590 75X 112.8	36Y	109.95	578	69X	134.20	-	101Y	115.45	662
38X 110.10 520 70Y 112.35 - 103X 115.65 666 39X 110.15 582 71X 112.40 - 103Y 115.65 666 39X 110.25 584 72X 112.50 - 104Y 115.70 - 39Y 110.25 584 72X 112.55 - 105X 115.70 - 40X 110.30 522 72Y 112.55 - 105X 115.80 - 40Y 110.35 586 73X 112.65 - 106X 115.90 - 41Y 110.45 588 74X 112.70 - 106X 115.90 - 42X 110.50 594 75X 112.80 - 107Y 116.00 - 43X 110.60 - 75Y 112.85 - 108X 116.10 - 43X 110.60 - 77Y 113.00 <td>37X</td> <td>110.00</td> <td>-</td> <td>69Y</td> <td>134.25</td> <td>-</td> <td>102X</td> <td>115.50</td> <td>-</td>	37X	110.00	-	69Y	134.25	-	102X	115.50	-
38Y 110.15 582 71X 112.40 . 103Y 115.65 666 39Y 110.25 584 72X 112.50 . 104Y 115.75 668 40X 110.30 522 72Y 112.55 . 105X 115.85 670 41X 110.04 . 73Y 112.65 . 106X 115.95 672 41X 110.40 . 73Y 112.65 . 106X 115.95 672 41X 110.40 . 588 74X 112.75 . 106X 115.95 672 42X 110.50 524 74Y 112.75 . 107X 116.00 . 42Y 110.55 590 75X 112.85 . 108X 116.10 . 43X 110.60 . 75Y 112.85 . 109X 116.20 . 44X 110.70 526 76X 112.90 . 108X 116.15 676 45Y 110.85 596 78X 113.10<	37Y	110.05	580	70X	112.30	-	102Y	115.55	664
39X 110.20 . 71Y 112.45 . 104X 115.75 668 40X 110.30 522 72Y 112.55 . 105X 115.80 . 40Y 110.35 586 73X 112.60 . 105Y 115.85 . 41X 110.40 . 73Y 112.65 . 106Y 115.95 . 41Y 110.45 588 74X 112.70 . 106Y 115.95 . 42X 110.55 590 75X 112.80 . 107Y 116.00 . 43X 110.60 . 75Y 112.85 . 108X 116.10 . 43X 110.60 . 75Y 112.85 . 108X 116.10 . 43Y 110.65 592 76X 112.90 . 108Y 116.25 678 44Y 110.70 526 76Y 112.95	38X	110.10	520	70Y	112.35	-	103X	115.60	-
39Y 110.25 584 72X 112.50 . 104Y 115.75 668 40X 110.30 522 72Y 112.55 . 105X 115.80 . 40Y 110.35 586 73X 112.60 . 105Y 115.85 670 41X 110.40 . 73Y 112.65 . 106X 115.95 672 41Y 110.45 588 74X 112.70 . 106Y 115.95 672 42X 110.50 524 74Y 112.75 . 107X 116.00 . 42Y 110.55 590 75X 112.80 . 107Y 116.05 674 43X 110.65 592 76X 112.90 . 108Y 116.15 676 44X 110.75 594 77X 113.00 . 109Y 116.20 . 45Y 110.85 596 78X 113.10 . 110Y 116.30 . 45Y 110.85 596	38Y	110.15	582	71X	112.40	-	103Y	115.65	666
40X 110.30 522 72Y 112.55 . 105X 115.80 . 40Y 110.35 586 73X 112.60 . 105Y 115.85 670 41X 110.40 . 73Y 112.65 . 106X 115.90 . 41Y 110.45 588 74X 112.75 . 106Y 115.95 672 42X 110.55 590 75X 112.85 . 107Y 116.05 672 42Y 110.65 592 76X 112.85 . 108X 116.10 . 43Y 110.65 592 76X 112.90 . 108Y 116.25 676 44X 110.70 526 76Y 112.95 . 109X 116.25 676 45X 110.80 . 77Y 113.00 . 110Y 116.25 678 45Y 110.85 596 78X 11	39X	110.20	-	71Y	112.45	-	104X	115.70	-
40Y 110.35 586 73X 112.60 - 105Y 115.85 670 41X 110.40 - 73Y 112.65 - 106X 115.90 - 41Y 110.45 588 74X 112.70 - 106Y 115.95 672 42X 110.50 524 74Y 112.75 - 107X 116.00 - 43X 110.60 - 75Y 112.85 - 108X 116.10 - 43Y 110.65 592 76X 112.95 - 109X 116.15 676 44X 110.75 594 77X 113.00 - 109Y 116.25 678 45Y 110.85 596 78X 113.10 - 110Y 116.35 680 46X 110.95 598 79X 113.20 - 111Y 116.45 682 47X 111.00 - 79Y 113.	39Y	110.25	584	72X	112.50	-	104Y	115.75	668
41X 110.40 - 73Y 112.65 - 106X 115.90 - 41Y 110.45 588 74X 112.70 - 106Y 115.95 672 42X 110.55 590 75X 112.80 - 107Y 116.05 674 43X 110.65 592 76X 112.90 - 108Y 116.15 676 44X 110.70 526 76Y 112.95 - 108Y 116.15 676 44X 110.70 526 76Y 112.95 - 109X 116.25 678 44Y 110.75 594 77X 113.05 - 110X 116.30 - 45X 110.80 - 77Y 113.05 - 110X 116.30 - 45Y 110.85 596 78X 113.15 - 111X 116.40 - 47Y 110.05 600 80X 113.	40X	110.30	522	72Y	112.55	-	105X	115.80	-
41Y 110.45 588 74X 112.70 - 106Y 115.95 672 42X 110.55 590 75X 112.80 - 107Y 116.00 - 43X 110.60 - 75Y 112.85 - 108X 116.10 - 43Y 110.65 592 76X 112.90 - 108Y 116.15 676 44X 110.70 526 76Y 112.95 - 109X 116.20 - 44Y 110.75 594 77X 113.05 - 110X 116.20 - 45X 110.80 - 77Y 113.05 - 110X 116.30 - 46X 110.95 598 79X 113.20 - 111Y 116.40 - 47Y 111.05 600 80X 113.30 - 112Y 116.55 684 48X 111.10 530 80Y 113.35 </td <td>40Y</td> <td>110.35</td> <td>586</td> <td>73X</td> <td>112.60</td> <td>-</td> <td>105Y</td> <td>115.85</td> <td>670</td>	40Y	110.35	586	73X	112.60	-	105Y	115.85	670
42X 110.50 524 74Y 112.75 - 107X 116.00 - 42Y 110.55 590 75X 112.80 - 107Y 116.05 674 43X 110.65 592 76X 112.90 - 108Y 116.15 676 44X 110.75 594 77X 113.00 - 109Y 116.25 678 45X 110.80 - 77Y 113.05 - 110X 116.30 - 45Y 110.85 596 78X 113.10 - 110Y 116.35 680 46X 110.90 528 78Y 113.15 - 111X 116.40 - 47Y 111.05 600 80X 113.20 - 1112Y 116.50 - 47Y 111.05 600 80X 113.30 - 112Y 116.55 684 48X 111.15 602 81X 1	41X	110.40	-	73Y	112.65	-	106X	115.90	-
42Y 110.55 590 75X 112.80 - 107Y 116.05 674 43X 110.60 - 75Y 112.85 - 108X 116.10 - 43Y 110.65 592 76X 112.95 - 109X 116.20 - 44Y 110.70 526 76Y 112.95 - 109X 116.20 - 44Y 110.70 526 76Y 112.95 - 109X 116.20 - 44Y 110.80 . 77Y 113.00 - 110Y 116.30 - 45Y 110.85 596 78X 113.10 - 110Y 116.35 680 46X 110.95 598 79X 113.20 - 111Y 116.45 682 47X 111.00 . 79Y 113.25 - 112X 116.50 . . 47Y 111.05 500 80Y	41Y	110.45	588	74X	112.70	-	106Y	115.95	672
43X 110.60 - 75Y 112.85 - 108X 116.10 - 43Y 110.65 592 76X 112.90 - 108Y 116.15 676 44X 110.70 526 76Y 112.95 - 109Y 116.20 - 44Y 110.75 594 77X 113.00 - 109Y 116.25 678 45Y 110.85 596 78X 113.10 - 110Y 116.35 680 46X 110.90 528 78Y 113.15 - 111X 116.40 - 46Y 110.90 528 78Y 113.20 - 111Y 116.45 682 47X 111.00 - 79Y 113.25 - 112X 116.50 - 47X 111.10 530 80Y 113.35 620 113X 116.60 - 48X 111.15 602 81X 113.	42X	110.50	524	74Y	112.75	-	107X	116.00	-
43Y 110.65 592 76X 112.90 - 108Y 116.15 676 44X 110.70 526 76Y 112.95 - 109X 116.20 - 44Y 110.75 594 77X 113.00 - 109Y 116.25 678 45X 110.80 - 77Y 113.05 - 110X 116.30 - 45Y 110.85 596 78X 113.10 - 110Y 116.35 680 46X 110.95 598 79X 113.25 - 111X 116.40 - 47X 111.05 600 80X 113.30 - 1112Y 116.55 684 48X 111.10 530 80Y 113.30 - 112Y 116.65 686 48X 111.10 - 81Y 113.40 - 113Y 116.65 686 49X 111.20 - 81Y 113	42Y	110.55	590	75X	112.80	-	107Y	116.05	674
44X 110.70 526 76Y 112.95 - 109X 116.25 678 44Y 110.75 594 77X 113.00 - 109Y 116.25 678 45Y 110.85 596 78X 113.10 - 110Y 116.35 680 46X 110.90 528 78Y 113.15 - 111X 116.40 - 46Y 110.95 598 79X 113.20 - 111Y 116.45 682 47X 111.00 - 79Y 113.25 - 112X 116.50 - 47Y 111.05 600 80X 113.35 620 113X 116.60 - 48X 111.15 602 81X 113.40 - 113Y 116.65 686 49X 111.25 604 82X 113.50 - 114Y 116.70 - 49Y 111.25 604 82X	43X	110.60	-	75Y	112.85	-	108X	116.10	-
44Y 110.75 594 77X 113.00 - 109Y 116.25 678 45X 110.80 - 77Y 113.05 - 110X 116.35 - 45Y 110.85 596 78X 113.10 - 110Y 116.35 680 46X 110.90 528 78Y 113.15 - 111X 116.40 - 46Y 110.95 598 79X 113.25 - 111Y 116.50 - 47X 111.05 600 80X 113.30 - 112Y 116.55 684 48X 111.10 530 80Y 113.35 620 113X 116.65 686 49X 111.20 - 81Y 113.45 622 114X 116.70 - 49Y 111.25 604 82X 113.55 624 115X 116.80 - 50Y 111.35 606 83X	43Y	110.65	592	76X	112.90	-	108Y	116.15	676
45X 110.80 - 77Y 113.05 - 110X 116.30 - 45Y 110.85 596 78X 113.10 - 110Y 116.35 680 46Y 110.95 598 79X 113.20 - 111Y 116.40 - 47Y 111.00 - 79Y 113.25 - 111Y 116.50 - 47Y 111.05 600 80X 113.30 - 112Y 116.50 - 48X 111.10 530 80Y 113.35 620 113X 116.60 - 48Y 111.25 602 81X 113.40 - 113Y 116.65 686 49X 111.25 604 82X 113.50 - 114Y 116.70 - 49Y 111.25 604 82X 113.50 - 114Y 116.70 - 50X 111.30 532 82Y 113.55 </td <td>44X</td> <td>110.70</td> <td>526</td> <td>76Y</td> <td>112.95</td> <td>-</td> <td>109X</td> <td>116.20</td> <td>-</td>	44X	110.70	526	76Y	112.95	-	109X	116.20	-
45Y 110.85 596 78X 113.10 - 110Y 116.35 680 46X 110.90 528 78Y 113.15 - 111X 116.40 - 46Y 110.95 598 79X 113.20 - 111Y 116.50 - 47X 111.00 - 79Y 113.25 - 112X 116.50 - 47Y 111.05 600 80X 113.30 - 112Y 116.55 684 48X 111.15 602 81X 113.40 - 113Y 116.65 686 49X 111.20 - 81Y 113.50 - 114Y 116.70 - 49Y 111.25 604 82X 113.50 - 114Y 116.75 688 50X 111.30 532 82Y 113.55 624 115X 116.80 - 51Y 111.45 608 84X 113.	44Y	110.75	594	77X	113.00	-	109Y	116.25	678
46X 110.90 528 78Y 113.15 - 111X 116.40 - 46Y 110.95 598 79X 113.20 - 111Y 116.50 - 47X 111.00 - 79Y 113.25 - 112X 116.50 - 47Y 111.05 600 80X 113.30 - 112Y 116.55 684 48X 111.10 530 80Y 113.35 620 113X 116.60 - 48Y 111.15 602 81X 113.40 - 113Y 116.65 686 49X 111.25 604 82X 113.50 - 114Y 116.75 688 50X 111.30 532 82Y 113.55 624 115X 116.80 - 50Y 111.35 606 83X 113.60 - 115Y 116.85 690 51X 111.40 - 83Y 11	45X	110.80	-	77Y	113.05	-	110X	116.30	-
46Y 110.95 598 79X 113.20 - 111Y 116.45 682 47X 111.00 - 79Y 113.25 - 112X 116.50 - 47Y 111.05 600 80X 113.30 - 112Y 116.50 - 48X 111.10 530 80Y 113.35 620 113X 116.60 - 48Y 111.15 602 81X 113.40 - 113Y 116.65 686 49X 111.25 604 82X 113.50 - 114Y 116.75 688 50X 111.35 606 83X 113.50 - 115Y 116.85 690 51X 111.40 - 83Y 113.65 626 116X 116.80 - 51Y 111.45 608 84X 113.70 - 116Y 116.95 692 52X 111.50 534 84Y	45Y	110.85	596	78X	113.10	-	110Y	116.35	680
47X 111.00 - 79Y 113.25 - 112X 116.50 - 47Y 111.05 600 80X 113.30 - 112Y 116.55 684 48X 111.10 530 80Y 113.35 620 113X 116.60 - 48Y 111.15 602 81X 113.40 - 113Y 116.65 686 49X 111.20 - 81Y 113.45 622 114X 116.70 - 49Y 111.25 604 82X 113.50 - 114Y 116.75 688 50X 111.35 606 83X 113.60 - 115Y 116.80 - 50Y 111.35 606 83X 113.60 - 115Y 116.85 690 51X 111.45 608 84X 113.70 - 116Y 116.90 - 51Y 111.50 534 84Y 11		110.90			113.15	-		116.40	-
47Y 111.05 600 80X 113.30 - 112Y 116.55 684 48X 111.10 530 80Y 113.35 620 113X 116.60 - 48Y 111.15 602 81X 113.40 - 113Y 116.65 686 49X 111.25 604 82X 113.50 - 114Y 116.75 688 50X 111.35 606 83X 113.55 624 115X 116.80 - 50Y 111.35 606 83X 113.65 626 116X 116.80 - 51X 111.40 - 83Y 113.65 626 116X 116.90 - 51Y 111.45 608 84X 113.70 - 116Y 116.95 692 52X 111.50 534 84Y 113.75 628 117X 117.00 - 52Y 111.55 610 85X	46Y	110.95	598	79X	113.20	-	111Y	116.45	682
48X 111.10 530 80Y 113.35 620 113X 116.60 - 48Y 111.15 602 81X 113.40 - 113Y 116.65 686 49X 111.20 - 81Y 113.45 622 114X 116.70 - 49Y 111.25 604 82X 113.55 - 114Y 116.75 688 50X 111.30 532 82Y 113.55 624 115X 116.80 - 50Y 111.35 606 83X 113.60 - 115Y 116.85 690 51X 111.40 - 83Y 113.65 626 116X 116.90 - 51Y 111.45 608 84X 113.70 - 116Y 116.95 692 52X 111.50 534 84Y 113.75 628 117X 117.00 - 52Y 111.55 610 85X	47X	111.00	-	79Y	113.25	-	112X	116.50	-
48Y 111.15 602 81X 113.40 - 113Y 116.65 686 49X 111.20 - 81Y 113.45 622 114X 116.70 - 49Y 111.25 604 82X 113.50 - 114Y 116.75 688 50X 111.30 532 82Y 113.55 624 115X 116.80 - 50Y 111.35 606 83X 113.60 - 115Y 116.85 690 51X 111.40 - 83Y 113.65 626 116X 116.90 - 51Y 111.45 608 84X 113.70 - 116Y 116.95 692 52X 111.50 534 84Y 113.70 - 116Y 116.95 692 52X 111.55 610 85X 113.80 - 117Y 117.00 - 53X 111.60 - 85Y		111.05			113.30	-	112Y	116.55	684
49X 111.20 - 81Y 113.45 622 114X 116.70 - 49Y 111.25 604 82X 113.50 - 114Y 116.75 688 50X 111.30 532 82Y 113.55 624 115X 116.80 - 50Y 111.35 606 83X 113.60 - 115Y 116.85 690 51X 111.40 - 83Y 113.65 626 116X 116.90 - 51Y 111.45 608 84X 113.70 - 116Y 116.95 692 52X 111.50 534 84Y 113.75 628 117X 117.00 - 52Y 111.55 610 85X 113.85 630 118X 117.10 - 53Y 111.65 612 86X 113.95 632 119X 117.20 - 54X 111.70 536 86Y	48X	111.10	530	80Y	113.35	620	113X	116.60	-
49Y 111.25 604 82X 113.50 - 114Y 116.75 688 50X 111.30 532 82Y 113.55 624 115X 116.80 - 50Y 111.35 606 83X 113.60 - 115Y 116.80 - 51X 111.40 - 83Y 113.65 626 116X 116.90 - 51Y 111.45 608 84X 113.70 - 116Y 116.95 692 52X 111.50 534 84Y 113.75 628 117X 117.00 - 52Y 111.55 610 85X 113.85 630 118X 117.10 - 53X 111.60 - 85Y 113.85 630 118X 117.10 - 53Y 111.65 612 86X 113.90 - 118Y 117.15 696 54X 111.70 536 86Y <t< td=""><td></td><td></td><td>602</td><td></td><td>113.40</td><td></td><td></td><td>116.65</td><td>686</td></t<>			602		113.40			116.65	686
50X 111.30 532 82Y 113.55 624 115X 116.80 - 50Y 111.35 606 83X 113.60 - 115Y 116.85 690 51X 111.40 - 83Y 113.65 626 116X 116.90 - 51Y 111.45 608 84X 113.70 - 116Y 116.95 692 52X 111.50 534 84Y 113.75 628 117X 117.00 - 52Y 111.55 610 85X 113.80 - 117Y 117.05 694 53X 111.60 - 85Y 113.85 630 118X 117.10 - 53Y 111.65 612 86X 113.90 - 118Y 117.15 696 54X 111.70 536 86Y 113.95 632 119X 117.20 - 54X 111.75 614 87X	49X	111.20	-	81Y	113.45	622	114X	116.70	-
50Y 111.35 606 83X 113.60 - 115Y 116.85 690 51X 111.40 - 83Y 113.65 626 116X 116.90 - 51Y 111.45 608 84X 113.70 - 116Y 116.95 692 52X 111.50 534 84Y 113.75 628 117X 117.00 - 52Y 111.55 610 85X 113.80 - 117Y 117.05 694 53X 111.60 - 85Y 113.85 630 118X 117.10 - 53Y 111.65 612 86X 113.90 - 118Y 117.15 696 54X 111.70 536 86Y 113.95 632 119X 117.20 - 54Y 111.75 614 87X 114.00 - 119Y 117.25 698 55X 111.80 - 87Y <t< td=""><td></td><td></td><td></td><td></td><td>113.50</td><td>_</td><td>114Y</td><td>116.75</td><td>688</td></t<>					113.50	_	114Y	116.75	688
51X 111.40 - 83Y 113.65 626 116X 116.90 - 51Y 111.45 608 84X 113.70 - 116Y 116.95 692 52X 111.50 534 84Y 113.75 628 117X 117.00 - 52Y 111.55 610 85X 113.80 - 117Y 117.05 694 53X 111.60 - 85Y 113.85 630 118X 117.10 - 53Y 111.65 612 86X 113.90 - 118Y 117.15 696 54X 111.70 536 86Y 113.95 632 119X 117.20 - 54Y 111.75 614 87X 114.00 - 119Y 117.25 698 55X 111.80 - 87Y 114.05 634 120X 117.30 - 55Y 111.85 616 88X <t< td=""><td></td><td>111.30</td><td></td><td>82Y</td><td>113.55</td><td>624</td><td>115X</td><td>116.80</td><td>-</td></t<>		111.30		82Y	113.55	624	115X	116.80	-
51Y 111.45 608 84X 113.70 - 116Y 116.95 692 52X 111.50 534 84Y 113.75 628 117X 117.00 - 52Y 111.55 610 85X 113.80 - 117Y 117.05 694 53X 111.60 - 85Y 113.85 630 118X 117.10 - 53Y 111.65 612 86X 113.90 - 118Y 117.15 696 54X 111.70 536 86Y 113.95 632 119X 117.20 - 54Y 111.75 614 87X 114.00 - 119Y 117.25 698 55X 111.80 - 87Y 114.05 634 120X 117.30 - 55Y 111.85 616 88X 114.10 - 120Y 117.35 - 56X 111.90 538 88Y <t< td=""><td>50Y</td><td>111.35</td><td>606</td><td>83X</td><td>113.60</td><td>-</td><td>115Y</td><td>116.85</td><td>690</td></t<>	50Y	111.35	606	83X	113.60	-	115Y	116.85	690
52X 111.50 534 84Y 113.75 628 117X 117.00 - 52Y 111.55 610 85X 113.80 - 117Y 117.05 694 53X 111.60 - 85Y 113.85 630 118X 117.10 - 53Y 111.65 612 86X 113.90 - 118Y 117.15 696 54X 111.70 536 86Y 113.95 632 119X 117.20 - 54Y 111.75 614 87X 114.00 - 119Y 117.25 698 55X 111.80 - 87Y 114.05 634 120X 117.30 - 55Y 111.85 616 88X 114.10 - 120Y 117.35 - 56X 111.90 538 88Y 114.15 636 121X 117.40 - 57Y 112.00 - 89Y						626			_
52Y 111.55 610 85X 113.80 - 117Y 117.05 694 53X 111.60 - 85Y 113.85 630 118X 117.10 - 53Y 111.65 612 86X 113.90 - 118Y 117.15 696 54X 111.70 536 86Y 113.95 632 119X 117.20 - 54Y 111.75 614 87X 114.00 - 119Y 117.25 698 55X 111.80 - 87Y 114.05 634 120X 117.30 - 55Y 111.85 616 88X 114.10 - 120Y 117.35 - 56X 111.90 538 88Y 114.15 636 121X 117.40 - 56Y 111.95 618 89X 114.20 - 121Y 117.45 - 57Y 112.00 - 89Y 11			608		113.70	-	116Y	116.95	692
53X 111.60 - 85Y 113.85 630 118X 117.10 - 53Y 111.65 612 86X 113.90 - 118Y 117.15 696 54X 111.70 536 86Y 113.95 632 119X 117.20 - 54Y 111.75 614 87X 114.00 - 119Y 117.25 698 55X 111.80 - 87Y 114.05 634 120X 117.30 - 55Y 111.85 616 88X 114.10 - 120Y 117.35 - 56X 111.90 538 88Y 114.15 636 121X 117.40 - 56Y 111.95 618 89X 114.20 - 121Y 117.45 - 57X 112.00 - 89Y 114.25 638 122X 117.50 - 57Y 112.05 - 90X 114.	52X	111.50	534	84Y	113.75	628	117X	117.00	-
53Y 111.65 612 86X 113.90 - 118Y 117.15 696 54X 111.70 536 86Y 113.95 632 119X 117.20 - 54Y 111.75 614 87X 114.00 - 119Y 117.25 698 55X 111.80 - 87Y 114.05 634 120X 117.30 - 55Y 111.85 616 88X 114.10 - 120Y 117.35 - 56X 111.90 538 88Y 114.15 636 121X 117.40 - 56Y 111.95 618 89X 114.20 - 121Y 117.45 - 57X 112.00 - 89Y 114.25 638 122X 117.50 - 57Y 112.05 - 90X 114.30 - 122Y 117.55 - 58X 112.10 - 90Y 114.35			610			-			694
54X 111.70 536 86Y 113.95 632 119X 117.20 - 54Y 111.75 614 87X 114.00 - 119Y 117.25 698 55X 111.80 - 87Y 114.05 634 120X 117.30 - 55Y 111.85 616 88X 114.10 - 120Y 117.35 - 56X 111.90 538 88Y 114.15 636 121X 117.40 - 56Y 111.95 618 89X 114.20 - 121Y 117.45 - 57X 112.00 - 89Y 114.25 638 122X 117.50 - 57Y 112.05 - 90X 114.33 - 122Y 117.55 - 58X 112.10 - 90Y 114.35 640 123X 117.60 - 58Y 112.15 - 91X 114.40 </td <td></td> <td></td> <td></td> <td></td> <td></td> <td>630</td> <td></td> <td>117.10</td> <td>-</td>						630		117.10	-
54Y 111.75 614 87X 114.00 - 119Y 117.25 698 55X 111.80 - 87Y 114.05 634 120X 117.30 - 55Y 111.85 616 88X 114.10 - 120Y 117.35 - 56X 111.90 538 88Y 114.15 636 121X 117.40 - 56Y 111.95 618 89X 114.20 - 121Y 117.45 - 57X 112.00 - 89Y 114.25 638 122X 117.50 - 57Y 112.05 - 90X 114.30 - 122Y 117.55 - 58X 112.10 - 90Y 114.35 640 123X 117.60 - 58Y 112.15 - 91X 114.40 - 123Y 117.65 - 59X 112.20 - 91Y 114.45		111.65			113.90			117.15	696
55X 111.80 - 87Y 114.05 634 120X 117.30 - 55Y 111.85 616 88X 114.10 - 120Y 117.35 - 56X 111.90 538 88Y 114.15 636 121X 117.40 - 56Y 111.95 618 89X 114.20 - 121Y 117.45 - 57X 112.00 - 89Y 114.25 638 122X 117.50 - 57Y 112.05 - 90X 114.30 - 122Y 117.55 - 58X 112.10 - 90Y 114.35 640 123X 117.60 - 58Y 112.15 - 91X 114.40 - 123Y 117.65 - 59X 112.20 - 91Y 114.45 642 124X 117.70 - 59Y 112.25 - 92X 114.50			536	86Y	113.95	632	119X	117.20	-
55Y 111.85 616 88X 114.10 - 120Y 117.35 - 56X 111.90 538 88Y 114.15 636 121X 117.40 - 56Y 111.95 618 89X 114.20 - 121Y 117.45 - 57X 112.00 - 89Y 114.25 638 122X 117.50 - 57Y 112.05 - 90X 114.30 - 122Y 117.55 - 58X 112.10 - 90Y 114.35 640 123X 117.60 - 58Y 112.15 - 91X 114.40 - 123Y 117.65 - 59X 112.20 - 91Y 114.45 642 124X 117.70 - 59Y 112.25 - 92X 114.50 - 124Y 117.75 - 60X 133.30 - 92Y 114.55	54Y	111.75	614	87X	114.00	-	119Y	117.25	698
56X 111.90 538 88Y 114.15 636 121X 117.40 - 56Y 111.95 618 89X 114.20 - 121Y 117.45 - 57X 112.00 - 89Y 114.25 638 122X 117.50 - 57Y 112.05 - 90X 114.30 - 122Y 117.55 - 58X 112.10 - 90Y 114.35 640 123X 117.60 - 58Y 112.15 - 91X 114.40 - 123Y 117.65 - 59X 112.20 - 91Y 114.45 642 124X 117.70 - 59Y 112.25 - 92X 114.50 - 124Y 117.75 - 60X 133.30 - 92Y 114.55 644 125X 117.80 - 60Y 133.35 - 93X 114.60						634			-
56Y 111.95 618 89X 114.20 - 121Y 117.45 - 57X 112.00 - 89Y 114.25 638 122X 117.50 - 57Y 112.05 - 90X 114.30 - 122Y 117.55 - 58X 112.10 - 90Y 114.35 640 123X 117.60 - 58Y 112.15 - 91X 114.40 - 123Y 117.65 - 59X 112.20 - 91Y 114.45 642 124X 117.70 - 59Y 112.25 - 92X 114.50 - 124Y 117.75 - 60X 133.30 - 92Y 114.55 644 125X 117.80 - 60Y 133.35 - 93X 114.60 - 125Y 117.85 - 61X 133.40 - 93Y 114.65	55Y	111.85			114.10	-	120Y	117.35	-
57X 112.00 - 89Y 114.25 638 122X 117.50 - 57Y 112.05 - 90X 114.30 - 122Y 117.55 - 58X 112.10 - 90Y 114.35 640 123X 117.60 - 58Y 112.15 - 91X 114.40 - 123Y 117.65 - 59X 112.20 - 91Y 114.45 642 124X 117.70 - 59Y 112.25 - 92X 114.55 644 125X 117.80 - 60X 133.30 - 92Y 114.55 644 125X 117.80 - 60Y 133.35 - 93X 114.60 - 125Y 117.85 - 61X 133.40 - 93Y 114.65 646 126X 117.90 - 62X 133.50 - 94X 114.75 648						636			-
57Y 112.05 - 90X 114.30 - 122Y 117.55 - 58X 112.10 - 90Y 114.35 640 123X 117.60 - 58Y 112.15 - 91X 114.40 - 123Y 117.65 - 59X 112.20 - 91Y 114.45 642 124X 117.70 - 59Y 112.25 - 92X 114.50 - 124Y 117.75 - 60X 133.30 - 92Y 114.55 644 125X 117.80 - 60Y 133.35 - 93X 114.60 - 125Y 117.85 - 61X 133.40 - 93Y 114.65 646 126X 117.90 - 61Y 133.45 - 94X 114.75 648			618						-
58X 112.10 - 90Y 114.35 640 123X 117.60 - 58Y 112.15 - 91X 114.40 - 123Y 117.65 - 59X 112.20 - 91Y 114.45 642 124X 117.70 - 59Y 112.25 - 92X 114.50 - 124Y 117.75 - 60X 133.30 - 92Y 114.55 644 125X 117.80 - 60Y 133.35 - 93X 114.60 - 125Y 117.85 - 61X 133.40 - 93Y 114.65 646 126X 117.90 - 61Y 133.45 - 94X 114.70 - 126Y 117.95 - 62X 133.50 - 94Y 114.75 648			-			638			-
58Y 112.15 - 91X 114.40 - 123Y 117.65 - 59X 112.20 - 91Y 114.45 642 124X 117.70 - 59Y 112.25 - 92X 114.50 - 124Y 117.75 - 60X 133.30 - 92Y 114.55 644 125X 117.80 - 60Y 133.35 - 93X 114.60 - 125Y 117.85 - 61X 133.40 - 93Y 114.65 646 126X 117.90 - 61Y 133.45 - 94X 114.70 - 126Y 117.95 - 62X 133.50 - 94Y 114.75 648			-			-			-
59X 112.20 - 91Y 114.45 642 124X 117.70 - 59Y 112.25 - 92X 114.50 - 124Y 117.75 - 60X 133.30 - 92Y 114.55 644 125X 117.80 - 60Y 133.35 - 93X 114.60 - 125Y 117.85 - 61X 133.40 - 93Y 114.65 646 126X 117.90 - 61Y 133.45 - 94X 114.70 - 126Y 117.95 - 62X 133.50 - 94Y 114.75 648			-			640			-
59Y 112.25 - 92X 114.50 - 124Y 117.75 - 60X 133.30 - 92Y 114.55 644 125X 117.80 - 60Y 133.35 - 93X 114.60 - 125Y 117.85 - 61X 133.40 - 93Y 114.65 646 126X 117.90 - 61Y 133.45 - 94X 114.70 - 126Y 117.95 - 62X 133.50 - 94Y 114.75 648			-			-			-
60X 133.30 - 92Y 114.55 644 125X 117.80 - 60Y 133.35 - 93X 114.60 - 125Y 117.85 - 61X 133.40 - 93Y 114.65 646 126X 117.90 - 61Y 133.45 - 94X 114.70 - 126Y 117.95 - 62X 133.50 - 94Y 114.75 648			-			642			-
60Y 133.35 - 93X 114.60 - 125Y 117.85 - 61X 133.40 - 93Y 114.65 646 126X 117.90 - 61Y 133.45 - 94X 114.70 - 126Y 117.95 - 62X 133.50 - 94Y 114.75 648			-			-			-
61X 133.40 - 93Y 114.65 646 126X 117.90 - 61Y 133.45 - 94X 114.70 - 126Y 117.95 - 62X 133.50 - 94Y 114.75 648		133.30	-		114.55	644		117.80	-
61Y 133.45 - 94X 114.70 - 126Y 117.95 - 62X 133.50 - 94Y 114.75 648			-			-			-
62X 133.50 - 94Y 114.75 648			-			646			-
			-			-	126Y	117.95	-
62Y 133.55 - 95X 114.80 -			-			648			
	62Y	133.55	-	95X	114.80	-			

35 COMM/NAV/WEATHER REMARKS:

These remarks consist of pertinent information affecting the current status of communications, NAVAIDs and weather.

ABERDEEN MUNI (U36) 2 SW UTC-7(-6DT) N42°55.27′ W112°52.85′

4470 B NOTAM FILE BOI

RWY 06-24: H3650X50 (ASPH) MIRL

RWY 06: Road. RWY 24: Fence.


AIRPORT REMARKS: Attended irregularly Mon-Sat dalgt hrs.

Considerable agriculture ops during growing season. Irregular winter maintenance. +30' sprinkler and terrain at 230' from southwest end of rwy may be in position. Rwy 24 + 50' tree at 400', 125' left. ACTIVATE MIRL Rwy 06–24—CTAF.

COMMUNICATIONS: CTAF 122.9

RADIO AIDS TO NAVIGATION: NOTAM FILE PIH.

POCATELLO (H) VORTACW 112.6 PIH Chan 73 N42°52.22′ W112°39.13′ 270° 10.5 NM to fld. 4433/17E.



ALLEN H TIGERT (See SODA SPRINGS)

AMERICAN FALLS (UØ1) 2 NE UTC-7(-6DT) N42°47.84′ W112°49.51′

4419 B S4 **FUEL** 100LL, JET A NOTAM FILE BOI

RWY 03-21: H4900X50 (ASPH) MIRL

RWY 03: Fence. RWY 21: TRCV(TRIL)—GA 3.5° TCH 24'. Hill.

AIRPORT REMARKS: Attended 1500–0100Z‡. Ultralight, agriculture acft and helicopter ops during summer months. No line of sight between rwy ends. Irregular snow removal. ACTIVATE MIRL Rwy 03–21 and TRCV Rwy 21—CTAF.


COMMUNICATIONS: CTAF/UNICOM 122.8

RADIO AIDS TO NAVIGATION: NOTAM FILE PIH.

POCATELLO (H) VORTACW 112.6 PIH Chan 73 N42°52.22′ W112°39.13′ 223° 8.8 NM to fld. 4433/17E.

SALT LAKE CITY L-11C

SALT LAKE CITY



ANTELOPE VALLEY (See GROUSE)

ARCO-BUTTE CO (AOC) 3 SW UTC-7(-6DT) N43°36.21′ W113°20.06′

5332 B S2 **FUEL** 100LL NOTAM FILE BOI **RWY 06–24**: H6600X75 (ASPH) S–300 MIRL

RWY 06: REIL. PAPI (P2L)-GA 3.0° TCH 40'.

RWY 24: REIL. PAPI(P2L)—GA 3.0° TCH 40'. P-line.

AIRPORT REMARKS: Attended continuously. ACTIVATE MIRL Rwy 06–24, REIL Rwy 06 and Rwy 24 and PAPI Rwy 06 and Rwy 24—CTAF.

COMMUNICATIONS: CTAF/UNICOM 122.8

SALT LAKE CENTER APP/DEP CON 128.35

RADIO AIDS TO NAVIGATION: NOTAM FILE PIH.

POCATELLO (H) VORTACW 112.6 PIH Chan 73 N42°52.22′

W112°39.13′ 309° 53.2 NM to fld. 4433/17E.

NDB (MHW) 200 AOC N43°35.94′ W113°20.53′ at fld. NOTAM FILE BOI. SHUTDOWN.

NDB unusable:


030°-121° byd 25 NM

 122° byd 33 NM

123°-220° byd 25 NM

 $270^{\circ}\text{--}030^{\circ}$ byd 5 NM

220°-270° byd 10 NM



ASHTON N44°33.75′ W111°26.68′ **RCO** 123.625 (BOISE RADIO)

SALT LAKE CITY L-13C

SALT LAKE CITY

SALT LAKE CITY

H-3D. L-11C

ATLANTA

ATLANTA (55H) 1 NW UTC-7(-6DT) N43°48.81′ W115°08.10′


5500 NOTAM FILE BOI

RWY 16-34: 2460X75 (TURF-DIRT)

RWY 16: Tree. RWY 34: Trees. Rgt tfc.

AIRPORT REMARKS: Unattended. No winter maintenance. Recommended for use by mountain proficient pilots using high performance aircraft. Arpt is located in mountainous area; high timbered ridges limit maneuvering area. Land Rwy 34, depart Rwy 16. Approach up Boise River making right circling pattern over valley to check traffic at Greene arpt. Depart with right turnout down Boise River. Announce Intentions on 122.9. No go-around due to rising terrain and trees. Rwy 16–34 edges and Rwy 34 thld marked with white rocks. Rwy 16 thld not defined. Ground vehicle traffic has access to rwy. No telephone avbl at arpt.

COMMUNICATIONS: CTAF 122.9



GRAHAM USFS (U45) 11 NW UTC-7(-6DT) N43°57.31′ W115°16.36′

SALT LAKE CITY

5726 NOTAM FILE BOI

RWY 18-36: 2900X50 (TURF-GRVL)

RWY 18: Trees. RWY 36: Road.

AIRPORT REMARKS: Unattended. Big game animals on and in vicinity of arpt. No winter maintenance. Recommend Idg Rwy 36; tkf Rwy 18 when wind conditions allow. No line of sight between rwy ends. Rwy 18–36 lower one third of rwy soft and unusable during early spring. Rwy 18–36 thIds marked with rocks. No telephone avbl at arpt.

COMMUNICATIONS: CTAF 122.9

WEATHERBY USFS (52U) 9 NW UTC-7(-6DT) N43°49.49′ W115°19.91′ SAIT LAKE CITY

4494 NOTAM FILE BOI

RWY 03-21: 2200X60 (TURF-GRVL)
RWY 03: Tree. RWY 21: Trees.

AIRPORT REMARKS: Unattended. No winter maintenance. Arpt located in narrow river canyon subject to local turbulence caused by the terrain configuration. Recommended ldg Rwy 03; tkf Rwy 21 when wind conditions allow. Rwy 03–21 thlds and edges marked with unpainted rocks. No telephone avbl at arpt.

COMMUNICATIONS: CTAF 122.9

ATOMIC CITY

BIG SOUTHERN BUTTE (U46) 10 W UTC-7(-6DT) N43°25.96′ W113°03.33′

SALT LAKE CITY

5073 NOTAM FILE BOI

RWY 01-19: 2600X110 (DIRT)

RWY 01: Ground. RWY 19: Road.

AIRPORT REMARKS: Unattended. Livestock on and in vicinity of arpt. Rwy 01–19 surface may be poor due to damage by livestock, ground vehicles and rodents. Rwy 01–19 +1.5' berm and -1' ditch adjacent to entire perimeter of rwy. No winter maintenance. Rwy 01–19 edges and thids marked with white rock.

COMMUNICATIONS: CTAF 122.9

COXS WELL (U48) 23 SW UTC-7(-6DT) N43°13.07′ W113°13.65′

SALT LAKE CITY

5034 NOTAM FILE BOI

RWY 08-26: 2700X100 (TURF)

RWY 08: Road. RWY 26: Fence.

AIRPORT REMARKS: Unattended. Rwy 08–26 surface may be poor due to damage by livestock, ground vehicles and rodents. No winter maintenance. Rwy 08–26 edges and thids marked with white rock.

COMMUNICATIONS: CTAF 122.9

MIDWAY (U37) 1 N UTC-7(-6DT) N43°27.22′ W112°48.44′

SALT LAKE CITY

5017 NOTAM FILE BOI

RWY 02-20: 3800X175 (GRVL-DIRT)

RWY 02: Road. RWY 20: Road.

AIRPORT REMARKS: Unattended. No winter maintenance. First 1500' of Rwy 02 is dirt, remainder is gravel. Rwy 02–20 edges and thIds marked with white rocks.

COMMUNICATIONS: CTAF 122.9

BANCROFT MUNI (U51) 1 E UTC-7(-6DT) N42°43.25′ W111°52.05′

SALT LAKE CITY

5435 NOTAM FILE BOI

RWY 07-25: 3280X30 (GRVL)

RWY 07: Road.

AIRPORT REMARKS: Unattended. CAUTION: Unmarked turf crosswind landing area located SE adjacent to rwy. No winter maintenance.

COMMUNICATIONS: CTAF 122.9

BEAR LAKE CO (See PARIS)

BEAR TRAP (See MINIDOKA)

BERNARD USFS (U54) O NE UTC-7(-6DT) N44°58.78′ W114°44.09′

GREAT FALLS

3626 NOTAM FILE BOI

RWY 17-35: 1900X150 (TURF-DIRT)

RWY 17: Hill. RWY 35: Hill.

AIRPORT REMARKS: Unattended. No winter maintenance. Land Rwy 35, tkf Rwy 17, no touch and go landing or stop and go ldgs. Go arounds not recommended due to steep rising terrain off N end of Rwy 17. Rwy 17–35 rwy edges and thresholds marked with white rock markers. Flying B arpt located ½ mile upstream. No telephone avbl at arpt.

COMMUNICATIONS: CTAF 122.9

BIG CREEK (U6Ø) O NE UTC-7(-6DT) N45°07.99' W115°19.31'

5743 NOTAM FILE BOI

RWY 01-19: 3550X110 (TURF)

RWY 01: Road. RWY 19: Trees.

AIRPORT REMARKS: Unattended. Big game animals on and in vicinity of arpt. Open to ski equipped acft in winter; acft use sides of strip during ski operations. Recommend land to south, takeoff to north when conditions allow. No winter maintenance. Be alert for sprinklers on rwy. Rwy 01–19 edges and thids marked with white rock. No telephone avbl at arpt.

COMMUNICATIONS: CTAF 122.9

BIG CREEK RANGER STATION

CABIN CREEK USFS (IØ8) 17 E UTC-7(-6DT) N45°08.61' W114°55.74'

GREAT FALLS

GREAT FALLS

4289 NOTAM FILE BOI

RWY 02-20: 1750X40 (TURF-DIRT)

RWY 02: Tree RWY 20: Hill

AIRPORT REMARKS: Unattended. Big game animals and livestock on and invof rwy. Land Rwy 02, takeoff Rwy 20, go around not possible due to high terrain at end of Rwy 20. Rwy 02–20 15' wide bare dirt strip down center of rwy. No telephone avbl at arpt. Rubber water bar strips on rwy.

COMMUNICATIONS: CTAF 122.9

BIG SOUTHERN BUTTE (See ATOMIC CITY)

BLACKFOOT

McCARLEY FLD (UØ2) 1 N UTC-7(-6DT) N43°12.74′ W112°20.80′

4488 B S4 FUEL 100LL, JET A NOTAM FILE BOI

RWY 01-19: H4314X75 (ASPH) S-12.5 MIRL

RWY 01: PAPI(P2L)—GA 3.0° TCH 40'. Fence.

RWY 19: PAPI(P2L)—GA 3.0° TCH 37'. Tree.

AIRPORT REMARKS: Attended Mon–Sat 1500–0000Z‡. Considerable air ground ops during growing season.

COMMUNICATIONS: CTAF/UNICOM 122.8

SALT LAKE CENTER APP/DEP CON 128.35

RADIO AIDS TO NAVIGATION: NOTAM FILE PIH.


POCATELLO (H) VORTACW 112.6 PIH Chan 73 N42°52.22′ W112°39.13′ 016° 24.3 NM to fld. 4433/17E.

IDAHO FALLS (H) VORW/DME 113.85 IDA Chan 85(Y)

N43°31.14′ W112°03.84′ 199° 22.4 NM to fld.

4724/15E. NOTAM FILE IDA.

SALT LAKE CITY L-11C



BLISS N42°54.99′ W114°47.05′. **RCO** 122.4 (BOISE RADIO)

SALT LAKE CITY

L-11C

BOISE AIR TERMINAL (GOWEN FLD) (BOI) 3 S UTC-7(-6DT) N43°33.86′ W116°13.37′
2871 B S2 FUEL 100LL, JET A1 + OX 1, 3 AOE Class I, ARFF Index B
NOTAM FILE BOI

RWY 10L-28R: H10000X150 (ASPH-GRVD) S-100, D-210, ST-175, DT-446, DDT-947 RWY 10L: REIL. VASI(V4L)—GA 3.0° TCH 53'. Antenna. 0.5% up.

 $\label{eq:RWY 28R: VASI(V4L)} $$ RWY 10R-28L: H9763X150 (ASPH-PFC) S-100, D-210, ST-175, DT-430, DDT-994 HIRL CL$

RWY 10R: SSALR. TDZL. VASI(V4L)—GA 3.0° TCH 55'. Rgt tfc. 0.5% up.

RWY 28L: MALSR. TDZL. VASI(V4L)-GA 3.0° TCH 50'.

AIRPORT REMARKS: Attended continuously. Extensive copter operations surface to 3500' within 1 NM E and W and 5 NM S of Rwy 10R–28L. Moderate migratory bird activity within 5 NM of the arpt Oct–Mar. Security requires PPR with fixed base operator due to locked gates and fencing between hours 0500–14002‡ for ingress/egress to arpt. Portions of Twy A and the northwest ramp not visible to twr. Do not use Twy Z for tkf roll on Rwy 10L. Rwy 28R midfield runway visual range avbl. Rwy 10R and Rwy 28L touchdown runway visual range avbl. Rwy 10R rollout runway visual range avbl. Flight Notification Service (ADCUS) available Mon–Fri 1500–0000Z‡, weekends if notified by Thur 0000Z‡.

WEATHER DATA SOURCES: ASOS (208) 388-4640 COMMUNICATIONS: D-ATIS 123.9 UNICOM 122.95

BOISE RCO 122.6 122.2 (BOISE RADIO)
(R) APP/DEP CON 126.9 (North) 119.6 (South)

TOWER 118.1 119.0 GND CON 121.7 CLNC DEL 125.9

AIRSPACE: CLASS C svc ctc APP CON

RADIO AIDS TO NAVIGATION: NOTAM FILE BOI.

(H) VORTACW 113.3 BOI Chan 80 N43°33.17′ W116°11.53′ 281° 1.5 NM to fld. 2876/17E. VOR portion unusable:

 001° -044° byd 22 NM blo 11,000′ 001° -044° byd 32 NM blo 14,500′

DME portion unusable: 010°-060° byd 12 NM blo 13,000′

010°-060° byd 27 NM blo 15,500′ 113°-155° byd 30 NM blo 7,000′

USTIK NDB (HW/LOM) 359 BO N43°35.81′ W116°18.91′ 099° 4.5 NM to fld.

 $\begin{array}{ll} \textbf{LS/DME} \ 110.15 & \textbf{I-AAD} & \textbf{Chan 38(Y)} & \textbf{Rwy 28R.} & \textbf{DME unuable byd 10 NM blo 6000', byd 12 NM blo 5500', byd 16 NM blo 6000'. GS unusable byd 6 NM blo 4700'. LOC unusable byd 10 NM blo 6000', byd 12 NM blo 5500', byd 13 NM blo 6200', byd 16 NM blo 6000', byd 20° right of course \\ \end{array}$

 $\begin{array}{ll} \textbf{LS/DME} \ 111.1 & \textbf{I} - \textbf{BOI} & \textbf{Chan} \ \textbf{48} & \textbf{Rwy} \ \textbf{10R}. & \textbf{Class IIE.} & \textbf{LOM USTIK NDB. Localizer backcourse} \\ \textbf{unusable byd} \ \textbf{10}^{\circ} \ \textbf{north} \ \textbf{and south side of course. Localizer backcourse} \ \textbf{unusable byd} \ \textbf{10} \ \textbf{NM blo} \ \textbf{5900'} \ \textbf{and} \\ \textbf{byd} \ \textbf{15.1} \ \textbf{NM blo} \ \textbf{6800'}. \\ \end{array}$

BONNERS FERRY

BOUNDARY CO (65S) 2 NE UTC-8(-7DT) N48°43.56′ W116°17.71′

2337 B S3 **FUEL** 100LL, JET A NOTAM FILE BOI

RWY 02–20: H4002X75 (ASPH) S–25 MIRL

RWY 20: VASI(V2L)—GA 4.0° TCH 31'. Road.


AIRPORT REMARKS: Attended Mon-Sat 1600-0100Z‡, Sun

1600-2100Z‡. ACTIVATE MIRL Rwy 02-20, VASI Rwy 20—CTAF.

COMMUNICATIONS: CTAF/UNICOM 123.0

RADIO AIDS TO NAVIGATION: NOTAM FILE MLP.

MULLAN PASS (H) VORW/DME 117.8 MLP Chan 125 47°27.42′ W115°38.76′ 321° 80.5 NM to fld. 6100/20E. HIWAS.



045°-071° byd 32 NM blo 12,500′

072°-084° bvd 32 NM blo 10.500'


348°-010° byd 20 NM blo 13,000′

348°-010° byd 27 NM blo 15,500′

SALT LAKE CITY

H-1C, 3C, L-11B

IAP. AD



GREAT FALLS

BOUNDARY CO (See BONNERS FERRY)

BROOKS SPB (See COEUR D'ALENE)

BRUCE MEADOWS (See STANLEY)

BUHL MUNI (UØ3) 2 W UTC-7(-6DT) N42°35.49′ W114°47.80′

3660 B S4 **FUEL** 100LL, MOGAS NOTAM FILE BOI

RWY 09-27: H3900X60 (ASPH) S-12.5 LIRL

RWY 09: P-line. RWY 27: Hill.


AIRPORT REMARKS: Attended Tue-Sat 1530-0000Z‡. Phone

208–543–8539 for svc when arpt unattended. Limit acft on Twy B and Twy C to 50' wingspan. ACTIVATE LIRL Rwy 09–27—CTAF.

COMMUNICATIONS: CTAF 122.9

RADIO AIDS TO NAVIGATION: NOTAM FILE TWF.

TWIN FALLS (L) VORTACW 115.8 TWF Chan 105 N42°28.79' W114°29.37' 278° 15.2 NM to fld. 4140/18E.



BURLEY N42°34.82′ W113°51.95′ NOTAM FILE BYI.

(L) VORW/DME 114.1 BYI Chan 88 100° 4.8 NM to Burley Muni. 4230/18E.

SALT LAKE CITY H-3C, L-11C

SALT LAKE CITY

I-11C

SALT LAKE CITY

L-11C

VOR/DME unusable

120°–150° byd 30 NM blo 15,000′

210°-230° byd 10 NM blo 7,000′ 210°-230° byd 23 NM blo 8.800′

210°-230° byd 29 NM blo 11,000′ 210°-230° byd 34 NM blo 13,000′

BURLEY MUNI (BYI) 1 NE UTC-7(-6DT) N42°32.56′ W113°46.29′ 4150 B S4 **FUEL** 100LL. JET A OX 2 NOTAM FILE BYI

RWY 02-20: H4094X80 (ASPH) S-12.5, D-12.5 MIRL 0.3% up SW

RWY 02: VASI(V4L)—GA 3.5° TCH 40'. Thid dsplcd 620'. Road. RWY 20: REIL. VASI(V2R)—GA 3.0° TCH 24'. Thid dsplcd 300'.

Trees.

RWY 06-24: H4067X75 (ASPH) S-23 MIRL **RWY 06**: Thid dspicd 410', Railroad.

RWY 24: VASI(V2R)-GA 3.0° TCH 47'. Poles.

AIRPORT REMARKS: Attended sunrise to sunset. Birds in vicinity of all rwys, especially apch end Rwy 20 and apch end Rwy 24. Agricultural activity between rwy and twy Apr thru Oct. Marked helipad on ramp in front of FBO building. ACTIVATE MIRL Rwy 02–20 and Rwy 06–24—CTAF. VASI Rwy 02, Rwy 20 and Rwy 24

opr continuously.

WEATHER DATA SOURCES: ASOS 135.575 (208) 677-3604.

COMMUNICATIONS: CTAF 122.9

CONNERS RCO 122.05 (BOISE RADIO)


TWIN FALLS APP/DEP CON 126.7 (1300-0400Z‡)

SALT LAKE CENTER APP/DEP CON 118.05 (0400-1300Z‡)

RADIO AIDS TO NAVIGATION: NOTAM FILE BYI.

(L) VORW/DME 114.1 BYI Chan 88 N42°34.82′ W113°51.95′ 100° 4.8 NM to fld. 4230/18E.

CABIN CREEK USFS (See BIG CREEK RANGER STATION)



CALDWELL INDUSTRIAL (EUL) 3 SE UTC-7(-6DT) N43°38.51′ W116°38.15′

2432 B S4 FUEL 100LL, JET A NOTAM FILE EUL

RWY 12-30: H5500X100 (ASPH) S-72, D-86, ST-109 MIRL

RWY 12: PAPI(P4L)-GA 3.0° TCH 42'. Road.

RWY 30: PAPI(P4L)-GA 3.0° TCH 45'. Rgt tfc.

AIRPORT REMARKS: Attended Mar-Oct 1500-0200Z‡, Nov-Feb

1500–0000Z‡. Parachute Jumping. + 363' radio tower located 1.4 miles north of arpt. General aviation acft use inner twy, outer twy reserved for helicopters. PAPI Rwy 12 and Rwy 30 opr continuously. MIRL Rwy 12–30 ACTIVATE—CTAF.

WEATHER DATA SOURCES: AWOS-3 135.075 (208) 454-3953.

COMMUNICATIONS: CTAF/UNICOM 122.7


SQUAW BUTTE RCO 122.45 (BOISE RADIO)

R BOISE APP/DEP CON 119.6

RADIO AIDS TO NAVIGATION: NOTAM FILE BOI.

BOISE (H) VORTACW 113.3 BOI Chan 80 N43°33.17' W116°11.53' 269° 20.1 NM to fld. 2876/17E.

MERIDIAN NDB (MHW) 238 MPA N43°36.20′ W116°32.34′ 283° 4.8 NM to fld.



CAMAS CO (See FAIRFIELD)

CAREY (U65) 0 E UTC-7(-6DT) N43°18.53′ W113°56.16′

SALT LAKE CITY

SALT LAKE CITY

H-1C. L-11B

4783 NOTAM FILE BOI

RWY 07-25: 2650X170 (TURF)

RWY 07: Fence. RWY 25: Fence.

AIRPORT REMARKS: Unattended. Recommend land Rwy 25, tkf Rwy 07 when wind conditions permit. Be alert for sprinklers on rwy. Rwy 07–25 edges and thIds marked with concrete markers.

COMMUNICATIONS: CTAF 122.9

CASCADE (U7Ø) 2 SE UTC-7(-6DT) N44°29.54′ W116°00.89′

4742 B S6 **FUEL** 100LL, JET A OX 2 NOTAM FILE BOI **RWY 12-30**: H4300X60 (ASPH) S-12.5 MIRL

RWY 30: Fence. Rgt tfc.

AIRPORT REMARKS: Attended Dec-Apr 1600-0000Z‡, May-Nov 1500-0100Z‡. To avoid apch/dep over town; land Rwy 30 and dep Rwy 12 when wind conditions permit. Rwy 12 and Rwy 30 rwy numbers and centerline not visible. Retro reflective reflectors on twys and ramp edges.


COMMUNICATIONS: CTAF 122.9

RCO 122.35 (BOISE RADIO)

RADIO AIDS TO NAVIGATION: NOTAM FILE MYL.

DONNELLY (H) VORTACW 116.2 DNJ Chan 109 N44°46.03′ W116°12.38′ 134° 18.4 NM to fld. 7333/19E.

SALT LAKE CITY L-13B



CAVANAUGH BAY (See COOLIN)

CAVANAUGH BAY

TANGLEFOOT SPB (D28) 1 NW UTC-8(-7DT) N48°32.33′ W116°49.93′

GREAT FALLS

CREAT FALLS

L-13B

2438 NOTAM FILE BOI

WATERWAY 15-33: 10000X2000 (WATER)

WATERWAY 15: Rgt tfc.

SEAPLANE REMARKS: Attended Apr-Oct dawn-dusk. Tie downs available at floating docks; parking avbl on beach. Rwy 15–33 +5' no wake buoy located in ldg area. Recommend landing seaplane waterway 15; departure seaplane waterway 33, when winds permit. Cavanaugh Bay arpt located adjacent south, announce intentions—CTAF. COMMUNICATIONS: CTAF 122.9

CHALLIS

CHALLIS (LLJ) 1 NE UTC-7(-6DT) N44°31.42′ W114°13.08′

5072 B S4 **FUEL** 100, JET A NOTAM FILE LLJ

RWY 16-34: H4600X60 (ASPH) S-30 MIRL

RWY 16: Fence

RWY 34: PAPI(P4L)-GA 3.0° TCH 40'.

AIRPORT REMARKS: Attended 1400-0000Z‡. Deer on and in vicinity of arpt. Be alert helicopter ops adjacent southeast end of arpt. Recommend land Rwy 16, tkf Rwy 34 when wind conditions permit.

WEATHER DATA SOURCES: ASOS 119.275 (208) 879-5121. SAWRS

COMMUNICATIONS: CTAF/UNICOM 122.8

RADIO AIDS TO NAVIGATION: NOTAM FILE SMN.

SALMON (H) VORW/DME 113.5 LKT Chan 82 N45°01.28′ W114°05.06′ 173° 30.4 NM to fld. 9258/18E.



UPPER LOON CREEK USFS (U72) 26 NW UTC-7(-6DT) N44°35.49′ W114°49.39′

GREAT FALLS

5500 NOTAM FILE BOI

RWY 04-22: 2500X75 (TURF-DIRT)

RWY 04: Tree. RWY 22: Trees.

AIRPORT REMARKS: Unattended. Recommend land Rwy 22; Tkf Rwy 04 when wind conditions permit. No winter maintenance. Recommended for experienced mountain pilots only. Rwy 04–22 edges and thids marked with white rocks.

COMMUNICATIONS: CTAF 122.9

CHAMBERLAIN USFS (See CHAMBERLAIN GUARD STATION)

CHAMBERLAIN GUARD STATION

CHAMBERLAIN USFS (U79) 0 E UTC-7(-6DT) N45°22.74′ W115°11.81′

GREAT FALLS

5765 NOTAM FILE BOI **RWY 07-25:** 4100X200 (TURF)

RWY 07: Trees. RWY 25: Tree.

KWI U7: 11665. KWI ZJ: 1166

RWY 15-33: 2700X140 (TURF)

RWY 15: Hill. RWY 33: Trees.

AIRPORT REMARKS: Unattended. Rwy 07–25 W 500' CLOSED indef. Rwy 07–25 rough sfc. No twy available. Arpt subject to temporary closure early spring due to soft rwys. Rwy 07–25 and Rwy 15–33 thids marked and rwys outlined with yellow rocks. Rwy 15–33 has +2' pipe and -2' ditch across rwy North of rwy 07–25 intersection. No twy from rwy 15–33 to Campgrounds. Rwy 15 120' timbered hill 1200' on centerline. Some rodent activity on both rwys. No telephone avbl at arpt. Private Stone Breaker Arpt located 1 NM NE of Chamberlain USFS.

COMMUNICATIONS: CTAF 122.9

30 INAHN

COFUR D'ALFNE

BROOKS SPB (S76) 0 SW UTC-8(-7DT) N47°40.33′ W116°47.16′

GREAT FALLS

GREAT FALLS

H-1C I-13B

IΛP

2125 FUEL 100LL NOTAM FILE BOI WATERWAY 11-29: 15000X2000 (WATER)

WATERWAY 11: Rgt tfc.

WATERWAY 15-33: 15000X2000 (WATER)

WATERWAY 15: Rgt tfc.

SEAPLANE REMARKS: Attended 1700-dusk. Heavy boat tfc and parasail activity on and in vicinity of seaplane base Idg area. Fly patterns over lake, do not overfly city. Helicopter ops in vicinity of Seaplane Base. Ultralight acft operate in vicinity of SPB landing area. Adjacent boat marina may have dock space avbl. COMMUNICATIONS: CTAF 122.9

COEUR D'ALENE-PAPPY BOYINGTON FLD (COE) 9 NW UTC-8(-7DT)

N47°46.46' W116°49.18'

2320 B S4 FUEL 100, JET A OX 1, 2, 3, 4 Class IV, ARFF Index A NOTAM FILE COE

RWY 05-23: H7400X100 (ASPH-GRVD) S-57, D-95, ST-121, DT-165 HIRI 0.6% up NF RWY 05: MALSR, PAPI(P4R)-GA 3.0° TCH 56'.

RWY 23: REIL. PAPI(P4R)-GA 3.0° TCH 50'.

RWY 01-19: H5400X75 (ASPH) S-50, D-83, ST-105, DT-150

MIRL 0.3% up N

RWY 01: REIL, PAPI(P2L)-GA 3.0° TCH 39', Rgt tfc.

RWY 19: PAPI(P2L)-GA 3.0° TCH 41'.

AIRPORT REMARKS: Attended Mon-Fri 1500-0100Z±. For after hrs. fuel-self svc avbl or call 208-772-6404, 208-661-4174, 208-661-7449, 208-699-5433. Self svc fuel avbl with credit card. 48 hr PPR for unscheduled ops with more than 30 passenger seats call arpt manager 208-446-1860. Migratory birds on and invof arpt Oct-Nov. Remote cntl airstrip is 2.3 miles west AER 05. Arpt conditions avbl on AWOS. Rwy 05 NSTD MALSR, thid bar extends 5' byd rwy edge Igts each side. ACTIVATE MIRL Rwy 01-19, HIRL Rwy 05-23, REIL Rwy 01 and Rwy 23, MALSR Rwy 05 and PAPI Rwy 01, Rwy 19, Rwy 05, and Rwy 23-CTAF. REIL Rwy 23 opr only when HIRL on high ints.

WEATHER DATA SOURCES: AWOS-3 135.075 (208) 772-8215.

HIWAS 108.8 COE.

COMMUNICATIONS: CTAF/UNICOM 122.8

RC0 122.05 (BOISE RADIO) R SPOKANE APP/DEP CON 132.1

AIRSPACE: CLASS E svc continuous.

RADIO AIDS TO NAVIGATION: NOTAM FILE COE.

(T) VORW/DME 108.8 COE Chan 25 N47°46.42′ W116°49.24′ at fld. 2290/19E.

DME portion unusable: 220°-240° byd 15 NM

280°-315° byd 15 NM blo 11,000'.

८३ ८३

POST FALLS NDB (MHW) 347 LEN N47°44.57′ W116°57.66′ 053° 6.0 NM to fld.

ILS 110.7 I-COE Rwy 05 Class ID. Post Falls NDB. Localizer unusable 25° left and right of course. ______

MAGEE (S77) 23 NE UTC-8(-7DT) N47°50.24′ W116°15.81′

GREAT FALLS

NOTAM FILE BOI

RWY 18-36: 2450X150 (TURF)

RWY 18: Thid dspicd 300'. Brush. RWY 36: Hill.

AIRPORT REMARKS: Unattended. Rwy 18-36 north 100' CLOSED Apr 1-Jul 15. Rwy 18-36 first 300' of north end very rough. Heavy snowmobile activity during winter months. Rwy 18-36 edges and thids marked with white rocks. Rwy 18 dsplcd thld marked with white rock markers, Recommend land Rwy 18; tkf Rwy 36 when wind conditions permit. No winter maintenance.

COMMUNICATIONS: CTAF 122.9

COLD MEADOWS USFS (See COLD MEADOWS GUARD STATION)

COLD MEADOWS GUARD STATION

COLD MEADOWS USFS (U81) 00 NW UTC-7(-6DT) N45°17.61′ W114°56.72′

GREAT FALLS

7030 NOTAM FILE BOI

RWY 16-34: 4550X90 (TURF-DIRT)

RWY 16: Trees. RWY 34: Trees.

AIRPORT REMARKS: Unattended. No winter maintenance. Rodent activity on and in vicinity of arpt. Big game animals and livestock on and invof rwy. When wind conditions permit land Rwy 34 depart Rwy 16. Be advised U.S. Forestry Service recommends left turn down Cotton Wood Creek after departing Rwy 16. Rwy 34 125' ridge at 350' and 200' left. Very high density altitude factor during summer months. Rwy 16–34 center 20' portion of rwy length is DIRT. Rwy may be soft in early spring. Rubber water bar strips on rwy. Rwy 16–34 unpainted rock boundary markers. Rwy 16–34 South 3500' very rough. No telephone avbl at arpt.

COMMUNICATIONS: CTAF 122.9

RCO 122.05 (BOISE RADIO)

CONNERS N42°21.61′ W113°27.43′.

SALT LAKE CITY

L-11C

CUULIN

CAVANAUGH BAY (66S) 3 N UTC-8(-7DT) N48°31.12′ W116°49.33′

GREAT FALLS

2484 NOTAM FILE BOI

RWY 15-33: 3100X120 (TURF) RWY 15: Tree. Rgt tfc.

RWY 33: Tree.

AIRPORT REMARKS: Attended Jun-Aug, Thu-Mon, 1600–0100Z‡. Watch for sprinklers on rwy. No line of sight between Rwy ends. Seaplane ops conducted in bay north and adjacent to arpt monitor CTAF. Rwy 15–33 edges and thids marked with white rocks. No winter maintenance. Heavy snowmobiles activity during winter months.

COMMUNICATIONS: CTAF 122.9

COPPER BASIN (See MACKAY)

COTTONWOOD MUNI (\$84) 1 SE UTC-8(-7DT) N46°02.33′ W116°19.89′ 3474 B NOTAM FILE BOI

GREAT FALLS L-13B

RWY 07-25: H3100X50 (ASPH) MIRL

RWY 07: Fence. **RWY 25:** PVASI(PSIR)—GA 5.0° TCH 50'.

AIRPORT REMARKS: Attended irregularly. Rwy 07–25 marked with numbers only. ACTIVATE MIRL Rwy 07–25, PVASI Rwy 25 and windsock lgts—CTAF. ACTIVATE rotating beacon—CTAF.

COMMUNICATIONS: CTAF 122.9

CASCADE RCO 122.35 (BOISE RADIO)

RADIO AIDS TO NAVIGATION: NOTAM FILE PUW.

PULLMAN (L) VORW/DME 109.0 PUW Chan 27 N46°40.46′ W117°13.41′ 116° 53.2 NM to fld. 2720/20E. HIWAS. DME unmonitored. Sewage Logoons

COUNCIL MUNI (U82) 1 NW UTC-7(-6DT) N44°45.02′ W116°26.70′

2963 B S2 FUEL 100LL NOTAM FILE BOI

RWY 17-35: H3600X60 (ASPH) S-12.5 MIRL

RWY 17: Brush.


AIRPORT REMARKS: Unattended. Arpt surrounded by mountains all quadrants. ACTIVATE MIRL Rwy 17–35—CTAF.

 ${\color{red}\textbf{COMMUNICATIONS: CTAF/UNICOM}~122.8}$

CASCADE RCO 122.35 (BOISE RADIO)

RADIO AIDS TO NAVIGATION: NOTAM FILE BOI.

DONNELLY (H) VORTACW 116.2 DNJ Chan 109 N44°46.03′ W116°12.38′ 245° 10.3 NM to fld. 7333/19E.



COXS WELL (See ATOMIC CITY)

CRAIGMONT MUNI (S89) O N UTC-8(-7DT) N46°14.86′ W116°28.76′

GREAT FALLS

GREAT FALLS

3805 B S2 NOTAM FILE BOI

RWY 07–25: H2800X50 (ASPH) MIRL **RWY 25:** Thid dspicd 300'. Ground.

AIRPORT REMARKS: Attended Apr-Oct dalgt hours, Nov-Mar irregularly. CLOSED during heavy snowfall. Heavy crop dusting operations Mar 1-July 31. Recommend landing Rwy 25, departing Rwy 07, when wind conditions permit. Rwy 25 thld dsplcd 300' at ngt, marked with dsplcd thld lights and rwy markings.

COMMUNICATIONS: CTAF 122.9

DIXIE USFS (AØ5) 3 SW UTC-8(-7DT) N45°31.24′ W115°31.06′

GREAT FALLS

5148 NOTAM FILE BOI

RWY 18-36: 4500X100 (TURF)

RWY 18: Trees. RWY 36: Hill.

AIRPORT REMARKS: Unattended. Airstrip is located in high timber mountain basin. Base heliport for initial attack fire suppression, 1 copter working Jun–Sep. Recommend landing Rwy 36; when wind conditions permit. Recommend departure Rwy 18, make right turn down Crooked Creek after departure. No winter maintenance. No telephone avol at arpt. Rwy 18–36 ends marked with logs painted white.

COMMUNICATIONS: CTAF 122.9

DONALD D. COSKI MEM (See DONNELLY)

DONNELLY N44°46.03′ W116°12.38′ NOTAM FILE MYL.

GREAT FALLS H-1C. L-13B

(H) VORTACW 116.2 DNJ Chan 109 012° 8.6 NM to McCall Muni. 7333/19E.

DONNELLY

DONALD D. COSKI MEM (U84) 1 W UTC-7(-6DT) N44°43.74′ W116°05.56′

GREAT FALLS

4860 NOTAM FILE BOI

RWY 18-36: 2500X125 (TURF)

RWY 18: Trees. RWY 36: Trees.

AIRPORT REMARKS: Unattended. No winter maintenance. Recommend land Rwy 36 and take off Rwy 18 when wind conditions permit. No telephone avbl at arpt. Rwy 18–36 may not be mowed full width.

COMMUNICATIONS: CTAF 122.9

CASCADE RCO 122.35 (BOISE RADIO).

DOWNEY (HYDE MEM) (U58) 1E UTC-7(-6DT) N42°25.45′ W112°06.57′

4906 B NOTAM FILE BOI

RWY 17-35: H3550X50 (ASPH) LIRL


RWY 17: Tank. RWY 35: Road.

AIRPORT REMARKS: Unattended. Farm machinery to 20' high may be located within 500' of apch to Rwy 17. For LIRL Rwy 17–35 and rotating beacon—key 122.8, five times.

COMMUNICATIONS: CTAF 122.9

RADIO AIDS TO NAVIGATION: NOTAM FILE MLD.

MALAD CITY (H) VOR/DME 117.4 MLD Chan 121 N42°11.99′ W112°27.07′ 031° 20.3 NM to fld. 7330/17E.



DRIGGS-REED MEM (DIJ) 1 N UTC-7(-6DT) N43°44.55′ W111°05.87′

6229 B S4 **FUEL** 100LL, JET A, OX 2 NOTAM FILE DIJ

RWY 03–21: H7302X75 (ASPH) S–30, D–60 MIRL 1.2% up NE

RWY 03: PAPI(P4L)—GA 3.0 TCH 45'.

RWY 21: REIL. PAPI(P4L)—GA 3.0 TCH 40'. Road. Rgt tfc. AIRPORT REMARKS: Attended Oct-May 1500-0000Z‡, Jun-Sep

1400–0200Z‡. After hrs call 208–354–3100. Sailplane ops, heavy during summer months. Gliders use right traffic for Rwy 03 and left traffic for Rwy 21. Median between Rwy 03–21 and parallel twy not authorized for ldgs and takeoffs. ACTIVATE MIRL Rwy 03–21 and REIL Rwy 21—CTAF. PAPI Rwys 03 and 21 ops 24 hrs

WEATHER DATA SOURCES: ASOS 120.775 (208) 354-6661.

COMMUNICATIONS: CTAF/UNICOM 122.7

SALT LAKE CENTER APP/DEP CON 132.4


RADIO AIDS TO NAVIGATION: NOTAM FILE BOI.

DUBDIS (H) VORTACW 116.9 DBS Chan 116 N44°05.33′ W112°12.56′ 098° 52.5 NM to fld. 4915/15E.

SALT LAKE CITY H-3D, L-11D IAP

SALT LAKE CITY

L-11D



DUBOIS N44°05.33′ W112°12.56′ NOTAM FILE BOI.

SALT LAKE CITY

(H) VORTACW 116.9 DBS Chan 116 206° 19.1 NM to Mud Lake (West Jefferson Co). 4915/15E. H-1D, L-11D

DUBOIS MUNI (U41) 1 SE UTC-7(-6DT) N44°09.74′ W112°13.24′

SALT LAKE CITY

5123 NOTAM FILE BOI

RWY 16-34: 4600X100 (TURF)

RWY 16: Road. RWY 34: Rgt tfc.

AIRPORT REMARKS: Unattended. No winter maintenance. Rwy 16–34 is centered between boundary markers. Rwy 16–34 cone boundary markers 125' each side of rwy centerline and wood panels across both thlds. Rwy 16 +6' fence at 100' and 250' from thld on centerline. +75' steeple 1400' from thld, 100' left.

COMMUNICATIONS: CTAF 122.9

ECKHART INTL (See PORTHILL)

FIK CITY (\$90) 0 SW UTC-8(-7DT) N45°49.36' W115°26.39'

4097 S2 NOTAM FILE BOI

RWY 14-35: 2600X150 (TURF-GRVL) RWY 14. Trees RWY 35: Trees

AIRPORT REMARKS: Unattended. Land Rwy 14, tkf Rwy 35 when wind condition allow. Rwy 14-35 is a curved rwy. Rwy 14-35 50' usable width. Rwy 14-35 may not be moved to full width. Rwy 14 thld is not defined. Rwy not maintained in winter

COMMUNICATIONS, CTAE 122 O

EMMETT MUNI (S78) 3 SW UTC-7(-6DT) N43°51.16′ W116°32.35′

2350 B FUEL 100LL NOTAM FILE BOI

RWY 10-28: H3250X50 (ASPH) S-8 MIRI


RWY 10: Thid dsplcd 385'. RWY 28: Thid dsplcd 260'. Fence. AIRPORT REMARKS: Unattended, Fuel avbl 24 hrs self serve credit card. Golf course on both sides of rwy. Golf course road crosses near Rwy 28 thld. Watch for golfers on rwy, 1800X20 private GRVL agriculture rwy located adjacent NW of arpt. Rwy 28 dsplcd thld marked with white bar and white chevrons only.

COMMUNICATIONS: CTAF 122.9

SQUAW BUTTE RCO 122.45 (BOISE RADIO)

RADIO AIDS TO NAVIGATION: NOTAM FILE BOI.

BOISE (H) VORTACW 113.3 BOI Chan 80 N43°33.17' W116°11.53' 303° 23.5 NM to fld. 2876/17E.



FAIRFIELD

CAMAS CO (U86) 0 S UTC-7(-6DT) N43°20.51′ W114°47.90′

SALT LAKE CITY

GREAT FALLS

SALT LAKE CITY

NOTAM FILE BOI RWY 07-25: 2950X40 (DIRT)

RWY N7. Road RWY 25: P-line.

AIRPORT REMARKS: Unattended. Irregular winter maintenance and snow removal, check rwy condition before using. **COMMUNICATIONS: CTAF 122.9**

FISH LAKE (USFS) (S92) 0 E UTC-8(-7DT) N46°19.81′ W115°03.79′

GREAT FALLS

NOTAM FILE BOI

RWY 04-22: 2650X50 (TURF)

RWY 22. Brush

AIRPORT REMARKS: Unattended. No winter maintenance. Do not park acft in front of USFS administrative site. Rwy 04-22 soft when wet. Land Rwy 22 take off Rwy 04 no touch and go landings or stop and go landings, go arounds not recommended due to steep rising terrain off west end of Rwy 04-22. Rwy 04-22 additional 400' of length available for takeoff on the end of Rwy 04. Down drafts prevalent over lake. Ctc USFS arpt manager 208-983-4060 for briefings and rwy conditions. Recommend early morning and late evening operations during summer months. Normally mowed to a usable width of 50'-75'. Rwy 22 end marked with concrete 'T' marker. Rwy 04 and Rwy 22 ends marked with orange cones. No telephone avbl at arpt.

COMMUNICATIONS: CTAF 122.9

FRIEDMAN MEM (See HAILEY)

GALENA

SMILEY CREEK (U87) 6 NW UTC-7(-6DT) N43°54.73′ W114°47.76′

SALT LAKE CITY

NOTAM FILE BOI RWY 14-32: 4900X150 (TURF)

RWY 14: Fence. RWY 32: Fence.

AIRPORT REMARKS: Unattended. No winter maintenance. Extremely high density altitude conditions exist during

summer months. Recommend land Rwy 14, tkf Rwy 32, when wind conditions allow. Be alert for sprinklers/stand pipes on edge of rwy. Rwy 14-32 edges and thids marked with white rock.

COMMUNICATIONS: CTAF 122.9

GARDEN VALLEY (U88) 2 SE UTC-7(-6DT) N44°04.02′ W115°55.88′

SALT LAKE CITY

3177 NOTAM FILE BOI RWY 10-28: 3850X125 (TURF)

RWY 10. Fence RWY 28: Fence

AIRPORT REMARKS: Unattended. USFS heliport opns adjacent to SE end of arpt. Watch for sprinkler heads on rwy. Arpt located in mountain valley. No winter maintenance. Recommend landing Rwy 10, takeoff Rwy 28, if winds allow.

Rwy 10-28 edges and thresholds marked with white rocks. No telephone avbl at arpt.

COMMUNICATIONS: CTAF 122.9

GLENGARY

LAKE PEND OREILLE SPB (\$96) 1 SE UTC-8(-7DT) N48°13.00′ W116°21.64′

GREAT FALLS

2062 B NOTAM FILE BOI

WATERWAY 14-32: 15000X4000 (WATER)

SEAPLANE REMARKS: Attended continuously. Unmarked helipad located on beach to the west adjacent to docks with non-standard helicopter VASI located on winch platform. Helicopter operation on and in vicinity of Seaplane Base.

COMMUNICATIONS: CTAF/UNICOM 122.8

GLENNS FERRY MUNI (U89) 1 SW UTC-7(-6DT) N42°56.62′ W115°19.81′ SALT LAKE CITY

I-11C

2536 B NOTAM FILE BOI

RWY 08-26: H3050X60 (ASPH)

MIRL


RWY 26: Trees.

AIRPORT REMARKS: Unattended. Rwy 08-26 distance to go markers every 1000' south side of rwy. Rwy 08-26 white reflectors on both edges of rwy; green reflectors on both thids. Roating bcn OTS indef. ACTIVATE MIRL Rwy 08-26-CTAF.

COMMUNICATIONS: CTAF 122.9

RADIO AIDS TO NAVIGATION: NOTAM FILE TWF.

TWIN FALLS (L) VORTACW 115.8 TWF Chan 105 N42°28.79' W114°29.37' 289° 46.4 NM to fld. 4140/18E.



 GODDING MUNI
 (GNG)
 3 SW
 UTC -7(-6DT)
 N42°55.03′ W114°45.91′
 SALT LAKE CITY

 3732
 B
 S4
 FUEL
 100LL, JET A
 NOTAM FILE BOI
 L-11C

 RWY 07-25: H4745X75 (ASPH)
 S-12.5
 MIRL
 1.4% up NE
 IAP

RWY 07-25: H4745X75 (ASPH) S-12.5 MIRL 1.4% up N RWY 07: Road.

AIRPORT REMARKS: Attended 1500–0000Z‡. For arpt attendant after hours call 208–539–5934 or 208–934–8298. Considerable helicopter ops. ACTIVATE MIRL Rwy 07–25—CTAF. 3 clicks medium ints–5 clicks high ints.

COMMUNICATIONS: CTAF/UNICOM 122.8

BLISS RCO 122.4 (BOISE RADIO)


SALT LAKE CENTER APP/DEP CON 118.05

RADIO AIDS TO NAVIGATION: NOTAM FILE TWF.

TWIN FALLS (L) VORTACW 115.8 TWF Chan 105 N42°28.79′ W114°29.37′ 317° 28.9 NM to fld. 4140/18E.

STEELHEAD NDB (MHW) 211 HDG N42°54.97'

W114°40.45′ 255° 4.0 NM to fld. NOTAM FILE BOI.



GRAHAM USFS (See ATLANTA)

GRANGEVILLE

IDAHO CO (S8Ø) 1 N UTC-8(-7DT) N45°56.55′ W116°07.41′

3314 B S2 FUEL 100LL, JET A NOTAM FILE BOI

RWY 07-25: H5101X75 (ASPH) S-75, D-95, DT-145 MIRL 0.5% up E

RWY 07: REIL. Thid dsplcd 100'. Road.


AIRPORT REMARKS: Unattended. 24 hr self svc credit card fueling facility. Considerable USFS Fire retardant opns during summer months. Parachute activity May thru Aug. ACTIVATE REIL Rwy 07—CTAF.

COMMUNICATIONS: CTAF 122.9

R SEATTLE CENTER APP/DEP CON 123.95

RADIO AIDS TO NAVIGATION: NOTAM FILE MYL.

DONNELLY (H) VORTACW 116.2 DNJ Chan 109 N44°46.03′ W116°12.38′ 344° 70.6 NM to fld. 7333/19E.



GRASMERE (U91) 0 S UTC-7(-6DT) N42°22.40′ W115°52.77′

SALT LAKE CITY

GREAT FALLS

H-1C. L-13B

IAP

5134 NOTAM FILE BOI

RWY 05-23: 2750X150 (DIRT)

RWY 05: Fence.

AIRPORT REMARKS: Unattended. Rwy 05–23 surface may be poor due to damage by livestock, ground vehicles and rodents. Rwy 05, 4' fence at 90' on centerline, 7' road at 150' on center, 65' marked powerline at 900' on centerline. Rwy 05–23 edges and thids marked with white rocks. No winter maintenance. No telephone avbl at arryt

GROUSE

ANTELOPE VALLEY (U92) 1 W UTC-7(-6DT) N43°40.63' W113°36.16'

SALT LAKE CITY

6180 NOTAM FILE BOI RWY 05-23: 3450X130 (TURF)

RWY 05: Road. RWY 23: P-line.

AIRPORT REMARKS: Unattended. CLOSED to wheeled acft winters. No winter maintenance. Recommend ldg Rwy 05; tkf Rwy 23 when wind conditions allow. Arpt located in mountain valley surrounded by high terrain. Rwy 05–23 edges and thid marked with white rock. +5' sagebrush adjacent to both rwy edges and Rwy 05 thid.

COMMUNICATIONS: CTAF 122.9

HAILEY N43°19.75′ W114°14.55′ NOTAM FILE SUN.

SALT LAKE CITY

NDB/DME (MHW) 220 HLE Chan 25 332° 10.8 NM to Friedman Mem. NDB unmonitored.

L-11C

DME unmonitored.

NDB portion unusable: 310°-350° byd 6 NM DME unusable: 280°-080° byd 12NM

080°-280°.

RCO 122.4 (BOISE RADIO)

HAILEY

FRIEDMAN MEM (SUN) 1 SE UTC-7(-6DT) N43°30.23′ W114°17.73′

SALT LAKE CITY H-3C, L-11C IAP, AD

5318 B S4 FUEL 100LL, JET A1 + 0X 1, 3 Class I, ARFF Index A NOTAM FILE SUN RWY 13-31: H7550X100 (ASPH-GRVD) S-65, D-95, DT-150 HIRL 0.8% up NW RWY 13: Thid dspicd 1701'. Road.

RWY 31: PAPI(P4L)-GA 3.5° TCH 55'. Tree.


RUNWAY DECLARED DISTANCE INFORMATION

 RWY 13:
 TORA-7150
 TODA-7550
 ASDA-7150
 LDA-5450

 RWY 31:
 TORA-5850
 TODA-7550
 ASDA-6631
 LDA-6631

 AIRPORT REMARKS:
 Attended dawn-dusk. Fuel avbl after dusk PPR

208–788–9511. Airfield sfc conditions not monitored between the hours of 06002‡ and 14002‡. Bird activity SE end Rwy 31. When twr closed land Rwy 31—tkf Rwy 13 due to opposite direction traffic; use landing lights in traffic pattern. Due to opposite traffic: approach Rwy 31 along E side of valley: depart Rwy 13 along W side of valley: show landing light. Ctc aprt manager 208–788–4956 or 208–788–3702 for noise abatement procedures. APU ops Itd to 30 minutes maximum run time. Not recommended for night use or in marginal weather by unfamiliar pilots due to mountainous terrain. Twy A open between Twys A2 and A3 daylight hours only. Twys A-5 and B-5 restricted to acft with wingspans of 49' or less (Acft Design Group I) only. PPR for all unscheduled acft ops utilizing acft with a type certificate for



more than 30 passenger seats. PPR for all scheduled air carrier ops between 0600–1300Z‡ call arpt manager 208–788–4956. No locked brake turns. ACTIVATE HIRL Rwy 13–31—CTAF when twr clsd. PAPI Rwy 31 opr 24 hrs. Ldg fee for acft greater than 6,000 lbs.

WEATHER DATA SOURCES: AWOS-3 128.225 (208) 788-9213. LAWRS.

COMMUNICATIONS: CTAF 125.6 ATIS 128.225 (208) 788-2108 UNICOM 122.95

HAILEY RCO 122.4 (BOISE RADIO)

SALT LAKE CENTER APP/DEP CON 118.05.

HAILEY TOWER 125.6 (1400-0600Z‡) GND CON 121.7

AIRSPACE: CLASS D svc 1400-0600Z‡ other times CLASS G.

RADIO AIDS TO NAVIGATION: NOTAM FILE BYI.

 BURLEY (L) VORW/DME 114.1
 BYI
 Chan 88
 N42°34.82′ W113°51.95′
 323° 58.6 NM to fld. 4230/18E.

 HAILEY NDB/DME (MHW) 220
 HLE
 Chan 25
 N43°19.75′ W114°14.55′
 332° 10.8 NM to fld. NOTAM FILE

 SUN. NDB unmonitored. DME unmonitored.

 $\textbf{COMM/NAV/WEATHER REMARKS:} \ Emerg \ frequency \ \textbf{121.5} \ not \ avbl \ at \ twr.$

38

MAGIC RESERVOIR (U93) 15 SW UTC-7(-6DT) N43°16.84′ W114°23.78′

NOTAM FILE BOI

RWY 03-21: 4000X100 (TURF-GRVL)

RWY 03. Road RWY 21. Fence

RWY 09-27: 1750X100 (TURF)

RWY 09: Sign.

RWY 27: Trees.

AIRPORT REMARKS: Unattended. No winter maintenance. When wind conditions allow, land Rwy 03 or Rwy 09, tkf Rwy 21 or Rwy 27 to avoid flying over resort area. Rwy 09-27 no line of sight between rwy ends. Rwy 03-21 edges and thid marked with white rocks. No telephone avbl at arpt.

COMMUNICATIONS: CTAF 122.9

HAZELTON MUNI (U94) 1 S UTC-7(-6DT) N42°34.57′ W114°08.16′

SALT LAKE CITY

SALT LAKE CITY

NOTAM FILE BOI

RWY 06-24: 2800X90 (GRVL)

RWY 06: Road. RWY 24: Tank.

AIRPORT REMARKS: Unattended, No winter maintenance, Rwy 06-24 no line of sight between rwy ends, Rwy 06-24 has a 300' gryl stopway on northeast end.

COMMUNICATIONS: CTAF 122.9

HENRY'S LAKE (See LAKE)

HOLLOW TOP (See MARTIN)

HOMEDALE MUNI (S66) 1 SE UTC-7(-6DT) N43°36.88′ W116°55.29′

SALT LAKE CITY

2210 S1 NOTAM FILE BOI

RWY 13-31: H2900X50 (ASPH) S-6 LIRL (NSTD)

RWY 13: Thid depict 335', Brush.

AIRPORT REMARKS: Unattended. No telephone avbl at arpt. Rwy 13-31 first 600' Rwy 31-LIRL; Rwy 31 has low ints thid lets.

COMMUNICATIONS: CTAF 122.9

HOWE (U97) 4 NW UTC-7(-6DT) N43°50.34′ W113°02.80′

SALT LAKE CITY

NOTAM FILE BOI 4930

RWY 13-31: 3800X25 (GRVL)

RWY 13: Road. RWY 31: Road.

AIRPORT REMARKS: Unattended. Arpt used heavily by spray planes during summer. +15' to +20' farm machinery may be parked on apch to Rwy 13; 230' from end of rwy. Rwy 13 +12' sprinkler may be in position at 200' on centerline. Rwy 31 thId defined with white blocks and reflectors.

COMMUNICATIONS: CTAF 122.9

IDAHO CITY USFS (U98) 1 SW UTC-7(-6DT) N43°49.24′ W115°51.06′

SALT LAKE CITY

3920 NOTAM FILE BOI

RWY 03-21: 3400X50 (GRVL-TURF)

RWY 03: Trees. RWY 21: Trees.

AIRPORT REMARKS: Unattended. Recommend land Rwy 03, tkf Rwy 21 when wind conditions permit. West 700' of rwy is turf, remainder is grvl. Rwy 03-21 edges and thIds marked with white rock. No winter maintenance. No telephone avbl at arpt.

COMMUNICATIONS: CTAF 122.9

IDAHO CO (See GRANGEVILLE)

IDAHO FALLS RGNL (IDA) 2 NW UTC-7(-6DT) N43°30.82′ W112°04.25′

4744 B S4 FUEL 100LL, JET A1 0X 1, 2, 3, 4 TPA-See remarks Class I, ARFF Index B H-3D, L-11D NOTAM FILE IDA

RWY 02-20: H9002X150 (ASPH-GRVD) S-140, D-175, ST-175, DT-270 HIRL

RWY 02: REIL. VASI(V4L)-GA 3.0° TCH 50'.

RWY 20: MALSR. PAPI(P4L)—GA 3.0° TCH 49'.

RWY 17-35: H4051X75 (ASPH) S-43, D-58 MIRL

RWY 17: PAPI(P4L)-GA 3.0° TCH 40'.

RWY 35: PAPI(P4L)-GA 3.5° TCH 45'. Antenna.

AIRPORT REMARKS: Attended 1200–0600Z‡. Flocks of birds and waterfowl on and invof arpt all year. Extensive agricultural ops. Acft ops be alert for possible incursions, no line of sight between rwys. 24 hr PPR for unscheduled air carrier ops with more than 30 passenger seats call arpt manager 208–529–1221. TPA–6244 (1500) multi–engine/turbojet acft, 5744 (1000) single–engine acft, 5244 (500) rotorcraft. Rwy 20 touchdown runway visual range avbl. When twr is clsd, Twy A between Twy A1 and the hold short line for Rwy 17 is clsd in order to protect Rwy 20 precision apchs. When twr clsd, ACTIVATE HIRL Rwy 02–20, REIL Rwy 02 and MALSR Rwy 20—CTAF.

WEATHER DATA SOURCES: ASOS 135.325 (208) 524-4553 or (208) 524-6048.

COMMUNICATIONS: CTAF 118.5 ATIS 135.325 (208) 524-6048.

UNICOM 122.95

RCO 122.55 (BOISE RADIO)

(R) SALT LAKE CENTER APP/DEP CON 128.35

TOWER 118.5 (1400-0300Z±) GND CON 121.7 CLNC DEL 121.7 (1400-0300Z±)

128.35 (SALT LAKE CITY CENTER 0300-1400Z‡)

AIRSPACE: CLASS D svc 1400-0300Z t other times CLASS E.

RADIO AIDS TO NAVIGATION: NOTAM FILE IDA.

(H) VORW/DME 113.85 IDA Chan 85(Y) N43°31.14′ W112°03.84′ at fld. 4724/15E.

SWEDEN NDB (MHW) 350 SWU N43°25.93′ W112°09.75′ 024° 6.3 NM to fld.

NDB unusable 025°-080° beyond 20 NM all altitudes.

UCONN NDB (LOM) 324 ID N43°35.87′ W111°58.84′ 201° 6.4 NM to fld.

ILS/DME 111.1 I-IDA Chan 48 Rwy 20 Class IB. LOM UCONN NDB.

COMM/NAV/WEATHER REMARKS: Emerg frequency 121.5 not avbl at twr.

INDIAN CREEK USFS (S81) O NE UTC-7(-6DT) N44°45.67′ W115°06.44′

GREAT FALLS

SALT LAKE CITY

4701 NOTAM FILE BOI

RWY 04-22: 4650X40 (DIRT)

RWY 04: Tree. RWY 22: Tree.

AIRPORT REMARKS: Unattended. No winter maintenance. Tfc observance in vicinity of Pistol Creek Arpt located 2.5 miles upstream. Be advised USFS recommends, when departing up or down stream remain in main canyon. Do not attempt to climb outside canyons. Rwy 04–22 edges and thids marked with white rocks, Rwy 04–22 40′ useable width, rwy edge markers are 100′ apart.

JEROME CO (JER) 3 E UTC-7(-6DT) N42°43.60′ W114°27.40′

4053 B S4 FUEL 100LL, JET A NOTAM FILE JER

RWY 09-27: H5001X75 (ASPH) S-12.5 MIRL 1.8% up E

RWY 09: PAPI(P4L)-GA 3.0° TCH 40'. Rgt tfc.

RWY 27. Fence

AIRPORT REMARKS: Attended continuously. Deer and wildlife on arpt. CAUTION: Tower 688' AGL located 1.5 E of arpt. Reflectors on parallel twy. ACTIVATE MIRL Rwy 09-27 and arpt bcn-CTAF.

WEATHER DATA SOURCES: ASOS 135.225 (208) 324-7076.

COMMUNICATIONS: CTAF/UNICOM 122.8

TWIN FALLS APP/DEP CON 126.7 (1300-0400Z‡)

SALT LAKE CENTER APP/DEP CON 118.05 (0400-1300Z±)


RADIO AIDS TO NAVIGATION: NOTAM FILE TWF.

TWIN FALLS (L) VORTACW 115.8 TWF Chan 105 N42°28.79' W114°29.37' 348° 14.9 NM to fld. 4140/18E.



GREAT FALLS

GREAT FALLS



JOHNSON CREEK (See YELLOW PINE)

JOSLIN FLD-MAGIC VALLEY RGNL (See TWIN FALLS)

KAMIAH MUNI (S73) 1 SE UTC-8(-7DT) N46°13.19′ W116°00.83′

NOTAM FILE BOI

RWY 14-32: 3000X90 (TURF) LIRL (NSTD)

RWY 32: Fence. RWY 14: Brush. Rgt tfc.

AIRPORT REMARKS: Attended irregularly. Numerous obstructions on both rwy apchs. Downdrafts prevalent over river on Rwy 32 apch. Canadian geese on and in vicinity of arpt. Not recommended transient pilots land after dark without first becoming familiar with arpt due to high terrain 0.5 mi from rwy. For rwy conditions during winter months call arpt manager 208-935-0089. ACTIVATE LIRL Rwv 14-32-CTAF.

COMMUNICATIONS: CTAF 122.9

1194 TPA-2194(1000)

KFIIOGG

SHOSHONE CO (S83) 3 W UTC-8(-7DT) N47°32.84′ W116°11.32′

2223 B S3 FUEL 100LL TPA-3223(1000) NOTAM FILE BOI

RWY 07-25: H5500X75 (ASPH) S-14 MIRL

RWY 07: Tree, Rgt tfc. RWY 25: Thid dspicd 1000'. Tree.

AIRPORT REMARKS: Attended daylight hours. ACTIVATE MIRL Rwy


07-25-CTAF.


COMMUNICATIONS: CTAF/UNICOM 122.8

RADIO AIDS TO NAVIGATION: NOTAM FILE MLP.

MULLAN PASS (H) VORW/DME 117.8 MLP Chan 125 N47°27.42'

W115°38.76' 264° 22.7 NM to fld. 6100/20E. HIWAS.





KETCHUM

TWIN BRIDGES (U61) 22 NE UTC-7(-6DT) N43°56.62' W114°06.62'

SALT LAKE CITY

6893 NOTAM FILE BOI RWY 03-21: 4450X100 (TURF)

RWY 03: Berm. RWY 21: Hill.

AIRPORT REMARKS: Unattended. Rwy 03–21 SW 560' rutted and unusable. Rwy 03–21 –1' ditch and +1' and 2' dirt berm entire perimeter of rwy. No winter maintenance. Arpt located in high mountain valley surrounded by high mountains. Be alert arpt subject to ongoing damage by livestock, ground vehicles and rodents. Rwy 03–21 edges and thids marked with white rocks.

COMMUNICATIONS: CTAF 122.9

KIMAMA

LAIDLAW CORRALS (U99) 12 N UTC-7(-6DT) N43°02.22' W113°44.02'

SALT LAKE CITY

4427 NOTAM FILE BOI RWY 07-25: 2250X130 (TURF)

RWY U7-23: 2250X130 (TURF)

RWY 07: Hill. RWY 25: Road.

AIRPORT REMARKS: Unattended. Rwy 07–25 surface subject to ongoing damage by rodents, ground vehicles and livestock. Rwy 07–25 edges and thids marked with white rocks. No winter maintenance. Rwy 25 +15' road 30'-50' left.

COMMUNICATIONS: CTAF 122.9

KOOSKIA MUNI (S82) 1 S UTC-8(-7DT) N46°07.96′ W115°58.73′

GREAT FALLS

1263 NOTAM FILE BOI RWY 14-32: 1900X100 (TURF)

RWY 14: Road. RWY 32: Road.

AIRPORT REMARKS: Unattended. Rwy 14–32 road crosses rwy near center. Geese on and invof arpt. Numerous obstructions in all quadrant around arpt. Rwy 14–32 width varies due to mowing and maintenance. Rwy 32 thld marked with red reflectors.

COMMUNICATIONS: CTAF 122.9

KRASSEL (See MC CALL)

LAIDLAW CORRALS (See KIMAMA)

LAKE (ISLAND PARK)

HENRY'S LAKE (U53) 3 SE UTC-7(-6DT) N44°38.09' W111°20.56'

GREAT FALLS

6596 NOTAM FILE BOI

RWY 06-24: 4600X170 (TURF)

RWY 06: Fence. RWY 24: Fence. Rgt tfc.

AIRPORT REMARKS: Unattended. Livestock and big game animals have access to rwy during fall, winter and spring. Do not leave acft unattended during these seasons. No winter maintenance. Rwy 06–24 edges and thids marked with white rocks. Recommend land Rwy 06, tkf Rwy 24 when wind conditions allow.

COMMUNICATIONS: CTAF 122.9

LAKE PEND OREILLE SPB (See GLENGARY)

LANDMARK USFS (ØUØ) 1 SE UTC-7(-6DT) N44°38.54′ W115°32.01′

GREAT FALLS

6662 NOTAM FILE BOI

RWY 16-34: 4000X100 (TURF-DIRT)

RWY 16: Trees. RWY 34: Tree.

AIRPORT REMARKS: Unattended. Wildlife on and in vicinity of arpt. No winter maintenance. No line of sight between rwy ends. Arpt located in high mountain valley surrounded by high terrain. Rwy 16–34 edges marked with white rock markers. No telephone avbl at arpt.

LEADORE (UØØ) OS UTC-7(-6DT) N44°40.39′ W113°21.15′

RWY 34: Fence.

6018 NOTAM FILE BOI

RWY 11-29: 3500X140 (ASPH-TURF) RWY LGTS (NSTD)

RWY 11: Poles. RWY 29: Fence.

RWY 16-34: 2900X90 (TURF)

RWY 16: Building.

AIRPORT REMARKS: Unattended. Numerous buildings in apch to Rwy 11. Rwy 11–29 2300' asph section starting at Rwy 11 end. Rwy 16 –3' road at 200' on centerline, +30' pole 250' 60' left, numerous other obstruction to +10' at 100' to 400' in the apch zone. Agricultural irrigation equipment +15' may be located within 50' of AER 34. Rwy 11–29 surface rough. Rwy 16–34 surface rough. Rwy 11 last 1200' not lgtd.

COMMUNICATIONS: CTAF 122.9

LEE WILLIAMS MEM (See MIDVALE)

LEMHI CO (See SALMON)

LEWISTON

LEWISTON-NEZ PERCE CO (LWS) 2 S UTC-8(-7DT) N46°22.47′ W117°00.92′

1442 B S4 **FUEL** 100, 100LL, JET A TPA—See Remarks Class I, ARFF Index A NOTAM FILE LWS

RWY 08-26: H6511X150 (ASPH-PFC) S-150, D-180, ST-175, DT-400 HIRL

RWY 08: REIL. VASI(V4L)—GA 3.0° TCH 45'. Rgt tfc. RWY 26: MALSR. PAPI(P4L)—GA 3.0° TCH 50'. Tree.

RWY 12–30: H5002X100 (ASPH–GRVD) S–70, D–94, ST–119,

DT-150 MIRL 1.4% up SE

RWY 12: REIL. PAPI(P4L)-GA 3.0° TCH 40'. Rgt tfc.

RWY 30: VASI(V4R)-GA 3.0° TCH 47', Antenna.

AIRPORT REMARKS: Attended 1330–0500Z‡. CLOSED to unscheduled air carrier ops with more than 30 passenger seats 1500–0100Z‡ except PPR call arpt manager 208–746–7962 other times call station number 4 208–743–0172. Frequent no radio agricultural acft activity invof arpt. TPA—Heavy and turbine powered acft 3002(1560) all others 2502(1060). When twr clsd ACTIVATE MALSR Rwy 26, REIL Rwy 08 and Rwy 12—CTAF.

WEATHER DATA SOURCES: ASOS 135.575 (208) 746-4185. LAWRS.

COMMUNICATIONS: CTAF 119.4 UNICOM 122.95

RC0 122.35 (BOISE RADIO)

SEATTLE CENTER APP/DEP CON 123.95

TOWER 119.4 (1400-0600Z‡) GND CON 121.9

AIRSPACE: CLASS D svc 1400-0600Z‡ other times CLASS E.

RADIO AIDS TO NAVIGATION: NOTAM FILE LWS.

NEZ PERCE (L) VORW/DME 108.2 MQG Chan 19 N46°22.89′ W116°52.17′ 246° 6.1 NM to fld. 1720/20E. DME unmonitored.

Golf Co

+16' Ridge

ILS 109.7 I–LWS Rwy 26. Class IE. ILS unmonitored when tower closed. Autopilot coupled approaches not applicable blo 2500 ft.

SNAKE RIVER SPB (78U) 1 SW UTC-8(-7DT) N46°23.99′ W117°03.06′

SEATTLE

-%

GREAT FALLS

SEATTLE

IAP, AD

H-1C I-13B

735 NOTAM FILE BOI

WATERWAY N-S: 3000X150 (WATER)

WATERWAY S: P-line.

SEAPLANE REMARKS: Attended Apr-Oct 1500Z‡-dusk and Nov-Mar irregularly. P-lines cross Snake River approximately 2 miles north and 1 mile south of landing area, in addition other p-lines, telephone lines cross Snake River above and below landing area. Bridge across Snake River N of landing area. CAUTION: Landing area within Lewiston-Nez Perce County CLASS D airspace, ctc Lewiston twr. Waterway N-S waterlane length and width varies. Heavy boat traffic in vicinity of Seaplane Base.

COMMUNICATIONS: CTAF 122.9

LIBERATOR N42°58.96′ W115°46.46′ NOTAM FILE BOI.

(L) VORW 114.9 LIA 354° 9.1 NM to Mountain Home Muni.

SALT LAKE CITY

LOWMAN

WARM SPRINGS CREEK (ØU1) 13 NE UTC-7(-6DT) N44°08.53' W115°18.84'

SALT LAKE CITY

4831 NOTAM FILE BOI RWY 02-20: 2850X135 (TURF)

RWY 02: Brush. RWY 20: Trees.

AIRPORT REMARKS: Unattended. Recommend land Rwy 02, takeoff Rwy 20, when wind conditions allow. Steep hill and timber on apch to Rwy 20. No winter maintenance. Rwy 02–20 edges and thids marked with white rocks. No telephone avbl at arpt.

COMMUNICATIONS: CTAF 122.9

MACKAY

COPPER BASIN (ØU2) 12 SW UTC-7(-6DT) N43°48.12' W113°49.89'

SALT LAKE CITY

7920 NOTAM FILE BOI

RWY 12-30: 4700X100 (TURF)

RWY 12: Road.

AIRPORT REMARKS: Unattended, CLOSED to wheeled acft winters. Livestock on and in vicinity of arpt. No winter maintenance. Twy to midfield tiedowns 15' wide, -1' ditch adjacent to edges of twy. Rwy 12-30 edges and thresholds marked with white rocks. Arpt located in high mountain valley surrounded by high mountains. COMMUNICATIONS: CTAF 122.9

COMMONICATIONS: CIAI 122.5

MACKAY (U62) 1 SE UTC-7(-6DT) N43°54.60′ W113°36.14′

SALT LAKE CITY

5892 NOTAM FILE BOI RWY 12-30: H4389X60 (ASPH)

RWY 12: Pline. RWY 30: Trees.

AIRPORT REMARKS: Unattended. Recommend land Rwy 30, depart Rwy 12 when winds permit. Rwy 12–30 very rough chip seal.


COMMUNICATIONS: CTAF 122.9

RADIO AIDS TO NAVIGATION: NOTAM FILE BOI.

DUBDIS (H) VORTACW 116.9 DBS Chan 116 N44°05.33′ W112°12.56′ 245° 61.3 NM to fld 4915/15E.

HELIPORT REMARKS: Square helipad located between rwy and parking area

RWY 21: Hill.



MAGEE (See COEUR D'ALENE)

MAGIC RESERVOIR (See HAILEY)

MAHONEY CREEK USFS (ØU3) 2 SE UTC-7(-6DT) N44°44.68' W114°55.28'

GREAT FALLS

4618 NOTAM FILE BOI

RWY 03-21: 2150X15 (DIRT)

RWY 03: Hill.

AIRPORT REMARKS: Unattended. Recommend ldg Rwy 21, tkf Rwy 03 when wind conditions allow. No winter maintenance. -1' ditch located 20' from centerline both sides of rwy. Rwy 03 NE end first 500' extremely rough. Rwy 03–21 thlds and edges have wood boundary markers, edge markers set at 65' width. First 500' of Rwy 21 has -1.5' to -2' deep holes. Rwy 21 has 15' elk wallow located adjacent S rwy 21 thld. No telephone avbl at arpt.

44 INAHN

MALAD CITY N42°11.99′ W112°27.07′. NOTAM FILE MLD.

SALT LAKE CITY (H) VOR/DME 117.4 MLD Chan 121 087° 7.4 NM to Malad City. 7330/17E. H-3D. L-11C

VOR portion unusable:

157°-167° bvd 25 NM blo 11.000′.

DME portion unusable:

005°-025° bvd 30 NM blo 14.000'

RC0 122.65 (BOISE RADIO)

157°-167° byd 25 NM blo 11,000'.

MALAD CITY (MLD) 3 SW UTC-7(-6DT) N42°10.23′ W112°17.36′

4503 B NOTAM FILE MLD

RWY 16-34: H4950X60 (ASPH)

RWY 16: Thid dsplcd 150'. Sprinkler.

RWY 34: Thid dsplcd 210'. P-line.


AIRPORT REMARKS: Attended Mon-Sat 1500-0000Z‡. Rwy 16-34 no dsplcd thid arrows, marked by dsplcd thid lgts and thid painted bar, ACTIVATE MIRL Rwv 16-34-CTAF.

COMMUNICATIONS: CTAF 122.9

RCO 122.65 (BOISE RADIO).

RADIO AIDS TO NAVIGATION: NOTAM FILE MLD.

(H) VOR/DME 117.4 MLD Chan 121 N42°11.99 W112°27.07' 087° 7.4 NM to fld. 7330/17E.



MARTIN

HOLLOW TOP (ØU7) 11 S UTC-7(-6DT) N43°19.43′ W113°35.43′

SALT LAKE CITY

SALT LAKE CITY

NOTAM FILE BOI RWY 05-23: 2500X140 (TURF)

AIRPORT REMARKS: Unattended. CLOSED to wheeled acft winters. Animals on and in vicinity of arpt. No line of sight between rwy ends. Rwy 05-23 surface may be poor due to damage by livestock, ground vehicles and rodents. Rwy 05-23 edges and thids marked with white rocks.

COMMUNICATIONS: CTAF 122.9

MAY (ØU8) 1 NE UTC-7(-6DT) N44°36.62′ W113°53.69′

GREAT FALLS

NOTAM FILE BOI 5324

RWY 09-27: 4950X200 (TURF)

RWY N9. Pole RWY 27. Fence

AIRPORT REMARKS: Unattended. Recommend Idg Rwy 09, tkf Rwy 27, when wind conditions permit. No winters maintenance. Rwy 09 +40' pole 600' apch end rwy 50' R. Fence markers located on apch end of Rwy 27. Arpt located in high mountain valley surrounded by high terrain. Rwy 09-27 edges and thlds marked with white rocks. **COMMUNICATIONS: CTAF 122.9**

MC CALL

KRASSEL USFS (24K) 17 NE UTC-7(-6DT) N44°58.45′ W115°43.79′

GREAT FALLS

NOTAM FILE BOI

RWY 17-35: 1500X150 (TURF)

RWY 17: Tree. RWY 35: Trees

AIRPORT REMARKS: Unattended. Extensive helicopter ops during Summer months. Rwy 17-35 land Rwy 17, tkf Rwy 35 when wind conditions permit. Considerable rodent activity on rwy. +80' to +120' trees adjacent to both sides of rwy. Rwy 17-35 may not be mowed to full width. Rwy 17-35 rwy surface rough due to rodent holes.

I (3

8

34

MC CALL MUNI (MYL) 0 S UTC-7(-6DT) N44°53.32′ W116°06.11′

5024 B S4 **FUEL** 100LL, JET A, A1+ NOTAM FILE MYL

GREAT FALLS H-1C, L-13B

RWY 16-34: H6108X75 (ASPH) S-45, D-78, DT-135 MIRL 0.3% up N

10-34: H01U8X/5 (ASPH) 5-45, D-78, D1-135 WIRL

IG, L-ISB IAP

RWY 16: REIL. PAPI(P2L)—GA 3.0° TCH 40'. Road.

RWY 34: REIL. VASI(V2L)-GA 3.0° TCH 40'. Ground.

AIRPORT REMARKS: Attended daylight hours. 2 hr prior notice rqr for snow removal at night call (208) 634–1488/630–4659. Big game animals may be on or in vicinity of rwy. Rwy 16–34 straight in VFR landings prohibited recommend landing Rwy 34, tkf Rwy 16, when wind conditions permit. Rwy 16 has a marked 50' blast pad. USFS practices parachute jumps invof arpt. No helicopter parking in fixed wing tie down areas. Increased Forest Service flight opns during summer months. Parallel twy closed winter months.

WEATHER DATA SOURCES: ASOS 119.925 (208) 634-7198.

COMMUNICATIONS: CTAF/UNICOM 122.8

CASCADE RCO 122.35 (BOISE RADIO)
SALT LAKE CENTER APP/DEP CON 128.05

RADIO AIDS TO NAVIGATION: NOTAM FILE MYL.

W116°12.38' 012° 8.6 NM to fld. 7333/19E.

NDB (MHW) 363 $\,$ IOM $\,$ N44°48.34′ W116°06.14′ $\,$ 343° 5.0 NM to fld. NOTAM FILE MYL. NDB unusable byd 15 NM.

to fid. NOTAM FILE MYL. NDB unusable byd 15 NM.

HELIPAD H1: H100X80 (ASPH)

HELIPORT REMARKS: Helipad H1 lighted.

McCarley FLD (See Blackfoot)

MERIDIAN N43°36.20′ W116°32.34′ NOTAM FILE BOI.

NDB (MHW) 238 MPA 136° 1.5 NM to Nampa Muni.

SALT LAKE CITY

L-11B

MIDVALE

LEE WILLIAMS MEM (ØU9) 1 SW UTC-7(-6DT) N44°27.69′ W116°45.46′

SALT LAKE CITY

2617 NOTAM FILE BOI

RWY 08-26: H2875X60 (ASPH)

RWY 08: Fence. RWY 26: Fence.

AIRPORT REMARKS: Unattended. No winter maintenance, arpt CLOSED when snow conditions indicate. Rwy 26 +30' pline at 600' on cenerline +35' bldg at 400' on centerline, +150' pline at 5000' on centerline. Rwy 08–26 250' gravl ovrn each end. No telephone avbl at arpt.

COMMUNICATIONS: CTAF 122.9

CASCADE RCO 122.35 (BOISE RADIO)

MIDWAY (See ATOMIC CITY)

MINIDOKA

BEAR TRAP (1UØ) 15 NE UTC-7(-6DT) N42°58.52′ W113°21.05′

SALT LAKE CITY

4716 NOTAM FILE BOI **RWY 06-24:** 2250X120 (TURF-DIRT)

RWY NG. Road

AIRPORT REMARKS: Unattended. Rwy 06–24 subject to ongoing damage by livestock, ground vehicles and rodents. No winter maintenance. No line of sight between rwy ends. Rwy 06–24 edges and thids marked with white rock.

MOOSE CREEK RANGER STATION

MOOSE CREEK (USFS) (1U1) 0 SW UTC-7(-6DT) N46°07.25' W114°55.64'

GREAT FALLS

2454 NOTAM FILE BOI

RWY 01-19: 4100X250 (TURF)

RWY 01: Trees. RWY 19: Trees.

RWY 04-22: 2300X200 (TURF)

RWY 04: Trees. RWY 22: Trees.

AIRPORT REMARKS: Unattended. Rwy 01–19 CLOSED Nov 1 thru Memorial Day weekend, except for skis on snow. Ctc USFS arpt manager 208–926–4258, for briefings and rwy conditions. Rwy 01–19 recommend ldg Rwy 19 ffk Rwy 01 when wind conditions permit. Land Rwy 04, tkf Rwy 22, go around not recommended. Rwy 01–19 muddy spring and winter. Use Rwy 04–22 early spring and late fall/winter when possible due to better drainage and firmer surface. Rwys subject to temporary closures. Big game animals on and in vicinity of arpt. Skis winter months. No winter maintenance.

COMMUNICATIONS: CTAF 122.9

 MOUNTAIN HOME AFB
 (MUO)(KMUO)
 AF
 10 SW
 UTC-7(-6DT)
 N43°02.62′ W115°52.35′
 SALT LAKE CITY

 2996
 B
 TPA—See Remarks
 NOTAM FILE MUO
 Not insp.
 H-3C, L-118

 RWY 12-30: H13501X200 (PEM)
 S-155, D-200, DT-330 PCN 91 F/A/W/T
 HIRL
 DIAP, AD

 RWY 12: ALSF1. PAPI.
 RWY 30: ALSF1. PAPI.
 RWY 30: ALSF1. PAPI.

RUNWAY DECLARED DISTANCE INFORMATION

RWY 12: TODA-13501 ASDA-13501 RWY 30: TODA-13501 ASDA-13501

ARRESTING GEAR/SYSTEM

RWY 12 HOOK BAK-12B(B) (964')

HOOK BAK-12B(B) (964') RWY 30

MILITARY SERVICE: LGT Rwy 12–30 PAPI unusable byd 5° from rwy centerline. Rwy 12–30 ILS and PAPI runway reference point not coincidental. Thid lgt gated for fighter actt. A-GEAR Rwy 12–30 BAK-12B in raised position, requires 30 minutes prior notice for removal. JASU 2(AM32A-60) FUEL JB FLUID LHOX LOX De-ice 0IL 0-148-156 JOAP TRAM ALERT Opr Mon-Thu 1400-0700Z±. Fri 1400-0100Z±. clsd weekends and holidays.

MILITARY REMARKS: Opr Mon-Thu 1400-0700Z‡, Fri 1400-0100Z‡, clsd weekends and holidays. See FLIP AP/1 Supplementary Arpt Remark. RST0 Dep acft restricted to 4700′ until passing 3 DME. PPR only except VIP Code 6 or above, AIREVAC and SAAM. Minimum 24 hrs notice required and no more than 7 days prior. Acft requiring customs must coordinate for PPR no later than 48 hrs prior. All acft must adhere to PPR estimated time of arrival +/- 30 minutes or PPR is invalid. Ctc Base OPS DSN 728-2222, C208-828-2222, fax extension 4128. CAUTION Taxi-lines in end of rwy are made for acft with wingspans of 43′ or less only. Waterfowl hazard. TFC PAT TPA—Overhead 5200(2204). Rectangular 4300(1304), lgt acft/helicopter 3800(804). NS ABTMT Command quiet hr policy in effect 0530-1300Z‡. CSTMS/AG/IMG Consult base ops prior planning mission. Acft req support must ctc 366 SFS police DSN 728-2256, com 208-828-2256 and/or afld manager DSN 728-2222, com 208-828-2222 at least 24 hr prior arrival. Failure to comply may result in delays. 366 SFS police provide customs for US military personnel. Customs required for all cargo and non-US military personnel must be completed by US customs office, Boise. Ensure aircrew remain at acft until customs arrive. MISC Afld subject to short notice closures. First 1280′ Rwy 12-30 conc, mid 10940′ asphaltic conc. Acft carry drag chutes to park or advise twr. Standard USAF RSRS applied. ACC acft expect reduced rwy separation: ACC acft not wishing to

C208-828-6303, FAX extension 4438.

COMMUNICATIONS: ATIS 273.5 PTD 138.9 372.2

RCO 122.6 (BOISE RADIO)

RUI 122.6 (BOISE RADIO)

(R) APP CON 124.8 259.1 (Mon-Thu 1400-0700Z‡, Fri 1400-0100Z‡, clsd weekends and holidays

TOWER 133.85 253.5 (Mon-Thu 1400-0700Z‡, Fri 1400-0100Z‡, clsd weekends and holidays. GND CON 120.5

275.8 CLNC DEL 127.1 290.425

participate in RSRS will make intentions known on initial ctc with twr. Afld wx is monitored by AN/FMQ-19 automated observing system and augmented by human observer during opr hr. DSN 728-6303.

R DEP CON 371.2 (Mon-Thu 1400-0700Z‡, Fri 1400-0100Z‡, clsd weekends and holidays.

ACC COMD POST 311.0 321.0 15091 (Have QUICK timing avbl 381.3) (RAYMOND 27) PMSV METRO 342.5 Full svc available from WX during airfield operating hours. Remote briefing svc available from 25 OWS Davis Monthan AFB, DSN 228–6598, COM (520) 228–6598.

AIRSPACE: CLASS D svc Mon-Thu 1400-0700Z‡, Fri 1400-0100Z‡, clsd weekends and holidays, other times CLASS E.

RADIO AIDS TO NAVIGATION: NOTAM FILE BOI.

(L) TACAN MUO (114.0) Chan 87 N43°02.43′ W115°52.48′ at fld. 3000/18E. Unmonitored when clsd. No NOTAM MP Wed 1100–1400Z‡.

LIBERATOR (L) VORW 114.9 LIA N42°58.96′W115°46.46′ 292° 5.7 NM to fld.

ILS 110.3 I-MUO Rwy 12. Unmonitored when clsd. No-NOTAM MP Mon/Tue/Fri 1100-1400Z‡.
ILS 111.7 I-BRN Rwy 30. Unmonitored when clsd. No-NOTAM MP Mon/Tue/Fri 1100-1400Z‡.

COMM/NAV/WEATHER REMARKS: Radar maintenance Thu 1230-1400Z±.

INAHN 47

MOUNTAIN HOME MUNI (U76) 2 W UTC-7(-6DT) N43°07.90' W115°43.83'

3167 B S4 FUEL 100LL NOTAM FILE BOI RWY 10-28: H5000X75 (ASPH) S-42, D-53

RWY 10: REIL. PAPI(P2L)-GA 3.0° TCH 40'. Fence.

RWY 28: REIL PAPI(P2L)—GA 3.0° TCH 33'. P-line.

AIRPORT REMARKS: Attended Mon-Fri 1500-0000Z‡. Arpt attended after hours emerg only. Fuel avbl 24 hrs with credit card. High performance military jet operations conducted at Mountain Home AFB 8 NM Southwest of arpt. Extensive agricultural ops. ACTIVATE MIRL Rwy 10-28, PAPI Rwy 10 and Rwy 28 and REIL Rwy 10 and Rwv 28-CTAF.

WEATHER DATA SOURCES: AWOS-3 122.8 (617) 262-3825. OTS indef. COMMUNICATIONS: CTAF/UNICOM 122.8

RCO 122.6 (BOISE RADIO)

R APP/DEP CON 124.8 (Mon-Thu 1400-0700Z‡, Fri 1400-0100Z‡, clsd weekends and holidays)

SALT LAKE CENTER APP/DEP CON 118.05

RADIO AIDS TO NAVIGATION: NOTAM FILE BOI.

BOISE (H) VORTACW 113.3 BOI Chan 80 N43°33.17' W116°11.53' 124° 32.4 NM to fld. 2876/17E.

LIA N42°58.96′ W115°46.46′ LIBERATOR (L) VORW 114.9

354° 9.1 NM to fld.

STURGEON NDB (MHW) 333 STI N43°06.80' W115°39.51' 272° 3.4 NM to fld. Unusable 320°-020° byd 15

contact Mountain Home APP CON on 124.8 for traffic advisory due to intensive military training in area.

SALT LAKE CITY

H-3C, L-11B

ΙΔΡ

COMM/NAV/WEATHER REMARKS: NOTE: See SPECIAL NOTICE—All aircraft operating within 20 NM of VOR are requested to

MUD LAKE (WEST JEFFERSON CO) (1U2) 1 NW UTC-7(-6DT)

N43°51.06′ W112°30.08′

4787 B NOTAM FILE BOI

RWY 02-20: H3300X40 (ASPH) LIRL (NSTD)

RWY 02: Thid dsplcd 400'. Fence. RWY 20. Road

AIRPORT REMARKS: Attended May-Oct 1500-0000Z‡, Nov-Apr

irregular. LIRL Rwy 20 and rotating bcn inoperative each year 1 Nov-1 Apr. Rwy 20 has low ints thid lgts; first 600' rwy has low ints edge lgts, remaining 2700' of rwy illuminated with white edge reflectors. Dsplcd thld marked with retroreflective reflectors and thid bar. Rwy 20 +40' pole at 700', 200' right. Confirm snow removal and winter condition with arpt manager, 208-663-4328 or 208-529-3875. Night operations recommended only to pilots familiar with airport approaches and surrounding terrain.

COMMUNICATIONS: CTAF 122.9

RADIO AIDS TO NAVIGATION: NOTAM FILE BOI.

DUBOIS (H) VORTACW 116.9 DBS Chan 116 N44°05.33' W112°12.56' 207° 19.1 NM to fld. 4915/15E.

1_110

MULLAN PASS N47°27.42′ W115°38.76′ NOTAM FILE MLP. GREAT FALLS H-1C, L-13B

SALT LAKE CITY

Chan 125 (H) VORW/DME 117.8 MLP 264° 22.7 NM to Shoshone Co. 6100/20E. HIWAS. VOR portion unusable 055°-085° byd 20 NM blo 9,500'

RC0 122.15 (BOISE RADIO)

ASOS 135.475 MLP N47°27.42′ W115°38.77′/6028. (208) 744-1721.

MURPHY (1U3) O E UTC-7(-6DT) N43°12.96' W116°32.90' SALT LAKE CITY

2855 NOTAM FILE BOI

RWY 12-30: H2500X45 (ASPH)

RWY 30: Road.

AIRPORT REMARKS: Unattended, Recommend land Rwy 12, tkf Rwy 30 when wind condition permits, Rwy 12-30 thlds marked with painted rocks. Ctc sheriff's office in courthouse across hwy from arpt for assistance.

MURPHY HOT SPRINGS (See THREE CREEK)

NAMPA MUNI (S67) 0 E UTC-7(-6DT) N43°34.88′ W116°31.38′

2537 B S4 **FUEL** 100LL, JET A 0X 2 TPA—3537(1000) NOTAM FILE BOI

RWY 11-29: H5000X75 (ASPH) S-26, D-50, DT-60 MIRL RWY 11: PAPI(P2L)—GA 3.0° TCH 40'. Building.

RWY 29: PAPI(P2L)—GA 3.62° TCH 45'. Trees.

AIRPORT REMARKS: Attended 1400-0000Z‡. 1500-0100Z‡ summer

months. ACTIVATE PAPI Rwy 11 and Rwy 29—CTAF.

COMMUNICATIONS: CTAF/UNICOM 122.7

SQUAW BUTTE RCO 122.45 (BOISE RADIO)


R BOISE APP/DEP CON 119.6

RADIO AIDS TO NAVIGATION: NOTAM FILE BOI.

BOISE (H) VORTACW 113.3 BOI Chan 80 N43°33.17' W116°11.53' 260° 14.5 NM to fld. 2876/17E.

MERIDIAN NDB (MHW) 238 MPA N43°36.20′

W116°32.34′ 136° 1.5 NM to fld.



GREAT FALLS

SALT LAKE CITY

H-1C. L-11B

908 NOTAM FILE BOI

RWY 14-32: 2400X150 (TURF-GRVL)

RWY 14: Fence. RWY 32: Tree. Rgt tfc.

AIRPORT REMARKS: Unattended. No winter maintenance. No line of sight between rwy ends. Rwy 14–32 edges and thlds marked with white rocks. Rwy 14–32 South half 20' wide gravel strip with loose rocks up to 2", North half sparse gravel up to 2", grass may be high. No telephone avbl at arpt.

COMMUNICATIONS: CTAF 122.9

CASCADE RCO 122.35 (BOISE RADIO)

NEZ PERCE N46°22.89′ W116°52.17′ NOTAM FILE LWS.

SEATTLE

(L) VORW/DME 108.2 MQG Chan 19 246° 6.1 NM to Lewiston-Nez Perce Co. 1720/20E. L-13B

DME unmonitored.

VOR portion unusable:

075°-115° byd 20 NM blo 12,000′ 115°-155° byd 25 NM blo 6,900′

280°-290° byd 20 NM blo 4,200′ 290°-335° byd 25 NM blo 4,000′

NEZ PERCE MUNI (ØS5) O N UTC-8(-7DT) N46°14.31′ W116°14.31′

GREAT FALLS

3201 NOTAM FILE BOI

RWY 15-33: H2400X30 (ASPH)

RWY 15: Hill. RWY 33: P-line.

AIRPORT REMARKS: Attended Apr-Oct Mon-Fri 1600-0100Z‡, Nov-Mar irregularly. 55' AGL unmarked/unlgtd steel grain twr located 1350' south of Rwy 33, 116' left of extended centerline.

COMMUNICATIONS: CTAF 122.9

NORDMAN

PRIEST LAKE USFS (67S) 3 S UTC-8(-7DT) N48°34.50′ W116°57.81′

GREAT FALLS

2611 NOTAM FILE BOI

RWY 14-32: 4400X175 (TURF-GRVL)

RWY 14: Road. RWY 32: Road.

AIRPORT REMARKS: Unattended. USFS helipad private use. No winter maintenance. Rwy 14–32 may not be mowed to full width. Rwy 32 +14' road at 300' on centerline, 60' trees at 500' to 1000' on centerline. Rwy 14–32 thlds marked with concrete strips. Do not park acft within 100' of wx station.

OAKLEY MUNI (1U6) 0 S UTC-7(-6DT) N42°14.03′ W113°52.66′

4650 NOTAM FILE BOI

RWY 16-34: 3800X40 (GRVL)

RWY 16: Road. RWY 34: Fence.

AIRPORT REMARKS: Unattended. CAUTION: Rwy surface soft during early spring. No winter maintenance. Difficult to tell edges of grvl rwy from ditch along rwy edges.

COMMUNICATIONS: CTAF 122.9

ONTARIO N44°00.70′ W116°24.36′

KLAMATH FALLS L-11B

SALT LAKE CITY

RCO 122.3 (MC MINNVILLE RADIO)

OROFINO MUNI (S68) 1 NW UTC-8(-7DT) N46°29.48′ W116°16.61′

GREAT FALLS

1005 FUEL 100LL NOTAM FILE BOI

οT.

RWY 09–27: H2500X50 (ASPH) S–17

RWY U9-21: H2500X50 (ASPH) S-17

RWY 09: Trees. Rgt tfc. RWY 27: Road.

AIRPORT REMARKS: Attended irregularly. Two 1968' MSL (250' AGL) radio towers located approximately 1 mile E Rwy 27 300' left. High terrain in all quads around arpt.

COMMUNICATIONS: CTAF/UNICOM 122.8

OROGRANDE (75C) 1 NE UTC-8(-7DT) N45°43.81′ W115°31.68′

GREAT FALLS

4405 NOTAM FILE BOI

RWY 01-19: 2800X50 (TURF-DIRT)

RWY 01: Trees. RWY 19: Trees.

AIRPORT REMARKS: Unattended. Land Rwy 19; depart Rwy 01 when wind conditions permit. Big game animals on and invof arpt. Vehicles have access to rwy. Recommended use early morning and late evening in summer.

COMMUNICATIONS: CTAF 122.9

PARIS

BEAR LAKE CO (1U7) 3 E UTC-7(-6DT) N42°14.99′ W111°20.50′ 5928 B **FUEL** 100LL NOTAM FILE BOI

SALT LAKE CITY H-3D. L-11D

RWY 10-28: H5730X75 (ASPH)

S-12.5 MIRL (NSTD)

RWY 10: P-line.

RWY 16-34: H4590X70 (ASPH) S-50, D-64, DT-102


RWY 16. Road

AIRPORT REMARKS: Attended Mon-Sat continuously. Rwy 16-34 unmarked. Birds on and invof arpt. Rwy 10-28 NSTD MIRL mounted approximately 40 inches above ground, 10 feet from edge of pavement.

COMMUNICATIONS: CTAF/UNICOM 122.8

RADIO AIDS TO NAVIGATION: NOTAM FILE MLD.

MALAD CITY (H) VOR/DME 117.4 MLD Chan 121 N42°11.99′ W112°27.07′ 069° 49.6 NM to fld. 7330/17E.



PARMA (5ØS) 1 S UTC-7(-6DT) N43°46.73′ W116°56.31′

SALT LAKE CITY

2228 NOTAM FILE BOI

RWY 12-30: H2700X50 (ASPH)

RWY 12: Tree. Rgt tfc. RWY 30: Fence.

AIRPORT REMARKS: Attended irregularly. Recommend land Rwy 30, tkf Rwy 12 when wind condition permit. Rwy 12–30 +3' wooden rwy thld markers on Rwy 12, + 1.5' thld markers on Rwy 30, reflectors on rwy edges. Rwy 30 has +4' fence 185' from end of rwy on centerline.

PAYETTE MUNI (S75) 2 NE UTC-7(-6DT) N44°05.67′ W116°54.22′

2228 B S8 NOTAM FILE BOI

RWY 13-31: H3000X50 (ASPH) S-8 LIRL

RWY 13: Thid dsplcd 250'. Trees.

AIRPORT REMARKS: Unattended. Golfers adjacent to rwy edges and Rwy 13 thld. Arpt CLOSED to acft over 10,000 lbs gross weight. Rwy 31 thlds marked with white concrete markers and white concrete boundary markers. 2885' MSL (405' AGL) marked and Igtd steel tower located 2.2 miles S of arpt. ACTIVATE LIRL Rwy

13-31-CTAF

COMMUNICATIONS: CTAF 122.9

RADIO AIDS TO NAVIGATION: NOTAM FILE BOI.

BOISE (H) VORTACW 113.3 BOI Chan 80 N43°33.17' W116°11.53' 300° 44.8 NM to fld. 2876/17E.



SALT LAKE CITY

SALT LAKE CITY

PINF (1U9) 1 S UTC-7(-6DT) N43°27.74′ W115°18.55′

4232 NOTAM FILE BOI

RWY 16-34: 2300X125 (TURF-DIRT)

RWY 34: Brush. Rgt tfc.

AIRPORT REMARKS: Unattended. No winter maintenance. Dog-leg north end of strip. Rwy 16-34 edges and thids marked with white rocks.

COMMUNICATIONS: CTAF 122.9

POCATELLO RGNL (PIH) 7 NW UTC-7(-6DT) N42°54.59′ W112°35.76′

SALT LAKE CITY 4452 B S4 FUEL 100LL, JET A1, A1 + OX 3, 4 Class II, ARFF Index A H-3D. L-11C NOTAM FILE PIH RWY 03-21: H9060X150 (ASPH-PFC) S-100, D-160, ST-175, DT-265

RWY 03: ODALS, VASI(V4L)-GA 3.0° TCH 53'.

RWY 21: MALSR. PAPI(P4L)-GA 3.0° TCH 58'.

RWY 17-35: H7150X100 (ASPH) S-60 MIRL RWY 17: REIL. PAPI(P4L)-GA 3.0° TCH 45'.

RWY 35: PAPI(P4L)-GA 3.0° TCH 45'. Pole.

AIRPORT REMARKS: Attended 1300-0500Z‡. Flocks of waterfowl invof arpt. Twy G has no edge lights or reflectors, restricted to day use only. Radio controlled acft 1 mile east of arpt blo 400' AGL. PPR for unscheduled air carrier ops with more than 30 passenger seats, call arpt manager 208-234-6154 or 208-237-4738. Rwy 17-35 not available to air carrier ops with more than 30 passenger seats. After twr closed ACTIVATE MIRL Rwy 17-35, HIRL Rwy 03-21, ODALS Rwy 03, MALSR Rwy 21-CTAF.

WEATHER DATA SOURCES: ASOS 135.625 (208) 235-1287.

COMMUNICATIONS: CTAF 119.1 ATIS 135.625 (208) 232-2269 UNICOM 122.95

RC0 122.35 (BOISE RADIO)

R SALT LAKE CENTER APP/DEP CON 128.35

TOWER 119.1 (1300-0500Z‡) **GND CON 121.9**

AIRSPACE: CLASS D svc 1300-0500Z‡ other times CLASS E.


RADIO AIDS TO NAVIGATION: NOTAM FILE PIH.

Chan 73 N42°52.22' W112°39.13' 029° 3.4 NM to fld. 4433/17E. (H) VORTACW 112.6 PIH VOR portion unusable 060°-130° beyond 25 NM below 13,500'.

DME portion unusable 060°-130° beyond 25 NM below 13,500'.

TYHEE NDB (LOM) 383 PI N42°57.83′ W112°30.98′ 210° 4.8 NM to fld. Unmonitored when twr clsd. IIS/DMF 110 3 I_PIH Chan 40 Rwy 21. Class IE. LOM TYHEE NDB. LOC unmonitored when twr

COMM/NAV/WEATHER REMARKS: Freq 121.5 not avbl at tower. FBO monitors 122.95 and 123.0.



PORTHILL

ECKHART INTL (1S1) 0 W UTC-8(-7DT) N48°59.75′ W116°30.06′

GREAT FALLS

1756 LRA NOTAM FILE BOI RWY 15-33: 3650X175 (TURF)

RWY 15: Trees.

RWY 33: Road

AIRPORT REMARKS: Unattended. Rwy 15 do not use asph twy for tkf. Recommend land Rwy 33; tkf Rwy 15 when wind condition permits. No winter maintenance. Rwy 15-33 edges and thld marked with white rocks.

COMMUNICATIONS: CTAF/UNICOM 122.8

POST FALLS N47°44.57′ W116°47.66′ NOTAM FILE COE.

GREAT FALLS

NDB (MHW) 347 LEN 053° 6.0 NM to Coeur D'Alene-Pappy Boyington Fld.

L-13B

PRAIRIF

SALT LAKE CITY

SALT LAKE CITY

4958 NOTAM FILE BOI

RWY 05-23: 5400X150 (TURF)

RWY 05: Fence RWY 23: Fence.

AIRPORT REMARKS: Unattended. No winter maintenance. Recommend land Rwv 05, tkf Rwv 23, when wind conditions permit. Rwy 05-23 edges and thids marked with white rocks. No telephone avbl at arpt.

COMMUNICATIONS: CTAF 122.9

PRESTON (U1Ø) 2 NW UTC-7(-6DT) N42°06.42′ W111°54.75′

4728 B S2 FUEL 100LL NOTAM FILE BOI

RWY 03-21: H3457X50 (ASPH) S-12 LIRL(NSTD)

RWY 21: Thid dsplcd 330'. Highway.

RWY 16-34: 2437X30 (GRVL)


RWY 16: Road.

AIRPORT REMARKS: Attended dalgt hours. Rwy 16-34 CLOSED winters. Located on plateau. Sharp dropoff near thid, Rwys 03, 16, and 34. Rwy 03-21 lgts located 50' from edge of pavement. Rwy 21 dsplcd thid marked with dsplcd thid lgts only. ACTIVATE LIRL Rwy 03-21-CTAF.

COMMUNICATIONS: CTAF/UNICOM 122.8

RADIO AIDS TO NAVIGATION: NOTAM FILE MLD.

MALAD CITY (H) VOR/DME 117.4 MLD Chan 121 N42°11.99' W112°27.07′ 086° 24.7 NM to fld. 7330/17E.



PRIEST LAKE USFS (See NORDMAN)

PRIEST RIVER MUNI (1S6) 1 N UTC-8(-7DT) N48°11.44′ W116°54.59′

GREAT FALLS

NOTAM FILE BOI 2187

RWY 01-19: H2950X48 (ASPH) S-12.5 LIRL(NSTD)

RWY 01: Tree. RWY 19: Trees.

AIRPORT REMARKS: Unattended. Night operations land Rwy 01 and dep Rwy 19. Rwy 01-19 has NSTD LIRL, Rwy 01 first 200' unlighted. Rwy 01-19 LIRL not in svc Dec 1-Apr 1. ACTIVATE LIRL-CTAF.

COMMUNICATIONS: CTAF 122.9

PULLMAN/MOSCOW RGNL

(See PULLMAN/MOSCOW, WA)

REXBURG-MADISON CO (RXE) 1 NW UTC-7(-6DT) N43°50.03′ W111°48.31′ 4858 B S4 **FUEL** 100LL, JET A OX 3 NOTAM FILE RXE

RWY 17-35: H4200X75 (ASPH) S-30 MIRL

RWY 17: VASI(V4R)—GA 3.0°TCH 50'. Thid dspicd 300'. Tree. **RWY 35:** REIL. VASI(V4L)—GA 3.0°TCH 40'. Trees.

RUNWAY DECLARED DISTANCE INFORMATION

RWY 17: TORA-4200 TODA-4200 ASDA-4200 LDA-3900 **RWY 35:** TORA-4200 TODA-4200 ASDA-3900 LDA-3900

AIRPORT REMARKS: Attended Mon-Sat 1500-0100Z‡. ACTIVATE VASI Rwv 17 and Rwv 35 and REIL Rwv 35-CTAF.

WEATHER DATA SOURCES: ASOS 135.075 (208) 356-0986.

COMMUNICATIONS: CTAF/UNICOM 122.8

R SALT LAKE CENTER APP/DEP CON 128.35

RADIO AIDS TO NAVIGATION: NOTAM FILE IDA.

IDAHO FALLS (H) VORW/DME 113.85 IDA Chan 85(Y)
N43°31.14′ W112°03.84′ 016° 22.0 NM to fld.
4724/15E.



SALT LAKE CITY

SALT LAKE CITY

I-11D

RIGBY-JEFFERSON CO (U56) 2 S UTC-7(-6DT) N43°38.55′ W111°55.76′

4845 B **FUEL** 100LL NOTAM FILE BOI

RWY 01–19: H3500X50 (ASPH) LIRL RWY 19: Thid dsplcd 200'. Road.


AIRPORT REMARKS: Unattended. Noise abatement procedures in effect.

Call arpt manager 208–754–4352. ACTIVATE LIRL Rwy
01–19—CTAF.

COMMUNICATIONS: CTAF 122.9

RADIO AIDS TO NAVIGATION: NOTAM FILE BOI.

DUBDIS (H) VORTACW 116.9 DBS Chan 116 N44°05.33′ W112°12.56′ 140° 29.4 NM to fld. 4915/15E.



ROCKFORD MUNI (2U4) 0 E UTC-7(-6DT) N43°11.37′ W112°31.91′

SALT LAKE CITY

4465 NOTAM FILE BOI

RWY 16-34: H2800X50 (ASPH)

RWY 16: Railroad. RWY 34: Fence.

AIRPORT REMARKS: Unattended. Rwy 16 use extreme CAUTION: railroad boxcars are often parked on centerline.

Considerable agriculture ops during growing season. No winter maintenance.

ST ANTHONY

STANFORD FLD (U12) 1 SE UTC-7(-6DT) N43°57.01′ W111°41.08′

4966 B TPA-5766(800) NOTAM FILE BOI

RWY 04-22: H4500X50 (ASPH) MIRL

RWY 04: Thid dsplcd 300'. P-line.


RWY 22: Thid dsplcd 540'. Tree.

AIRPORT REMARKS: Unattended. CAUTION: Acft opr from gravel rwy SE of paved rwy during agriculture season. Rwy 04-22 no dsplcd thld arrow markings on dsplcd thld.

COMMUNICATIONS: CTAF 122.9

RADIO AIDS TO NAVIGATION: NOTAM FILE BOI.

DUBOIS (H) VORTACW 116.9 DBS Chan 116 N44°05.33' W112°12.56' 095° 24.2 NM to fld. 4915/15E.



ST MARIES MUNI (S72) 1 NW UTC-8(-7DT) N47°19.57′ W116°34.66′ 2127 B S2 FUEL 100LL NOTAM FILE BOI

GREAT FALLS

SALT LAKE CITY

L-11D

L-13B

RWY 10-28: H4250X60 (ASPH) S-12.5 MIRL (NSTD) RWY 10: PAPI(P2L)—GA 4.0°. TCH 39'. Thid dsplcd 715'. Trees. Rgt tfc.


RWY 28: Trees.

AIRPORT REMARKS: Attended on call 208-852-0941. Ultralight acft pattern established for Rwy 10 NW of rwy, rgt tfc. Rwy 10-28 NSTD MIRL first 715' west end not lgtd. Rwy 10 NSTD dsplcd thld marking yellow chevrons. ACTIVATE NSTD MIRL Rwy 10-28 and PAPI Rwy 10-CTAF.

COMMUNICATIONS: CTAF/UNICOM 122.8

RADIO AIDS TO NAVIGATION: NOTAM FILE MLP.

MULLAN PASS (H) VORW/DME 117.8 MLP Chan 125 N47°27.42' W115°38.76' 239° 38.8 NM to fld. 6100/20E. HIWAS.



SALMON N45°01,28′ W114°05.06′ NOTAM FILE SMN.

(H) VORW/DME 113.5 LKT Chan 82 036° 10.6 NM to Lemhi Co. 9258/18E. RCO 122.55 (BOISE RADIO)

GREAT FALLS H-1C. L-13C

SALMON

LEMHI CO (SMN) 4 S UTC-7(-6DT) N45°07.43' W113°52.88' 4043 B S4 FUEL 100. JET A NOTAM FILE SMN

RWY 17-35: H5150X60 (ASPH) S-12.5 MIRL

RWY 17: REIL. PAPI(P4L)-GA 3.5°. TCH 55'.

AIRPORT REMARKS: Attended 1500-0000Z‡. Rwy 17-35 N 500' sharp drop-off on W shoulder. Rwy 17 use rgt tfc pattern for ngt ops only. Bcn OTS indef. ACTIVATE MIRL Rwy 17-35, REIL and PAPI Rwv 17—CTAF

WEATHER DATA SOURCES: AWOS-3 135.075 (208) 756-4381.


COMMUNICATIONS: CTAF/UNICOM 122.8

SALMON RCO 122.55 (BOISE RADIO)

SALT LAKE CENTER APP/DEP CON 132.4

RADIO AIDS TO NAVIGATION: NOTAM FILE SMN.

SALMON (H) VORW/DME 113.5 LKT Chan 82 N45°01.28' W114°05.06′ 036° 10.6 NM to fld. 9258/18E.



SANDPOE N48°17.44′ W116°33.79′ NOTAM FILE BOI.

NDB (MHW) 264 SZT at Sandpoint. NDB unusable 360°-170° byd 15 NM; 170°-200° byd 20 NM; 200°-360° all distances and altitudes.

SANDPOINT (SZT) 2 N UTC-8(-7DT) N48°17.97′ W116°33.61′

2131 B S4 FUEL 100LL, JET A OX 3, 4 NOTAM FILE SZT

RWY 01-19: H5501X75 (ASPH) S-40 MIRL

RWY 01: REIL. PAPI(P2L)-GA 3.75° TCH 28'. Tree.

RWY 19: REIL. PAPI(P2L)-GA 3.75° TCH 28'. Trees.

AIRPORT REMARKS: Attended 1500-0300Z‡ Summer, 1600-0100Z‡ Winter. Wildlife invof arpt. Rwy 01 additional obstruction: +23' railroad at 730' centerline, +65' P-line at 1800' on centerline, and +85' trees at 1900' on centerline. ACTIVATE MIRL Rwy 01-19 and REIL Rwy 01 and Rwy 19-CTAF. PAPI Rwy 01 and Rwy 19 opr continuously.

WEATHER DATA SOURCES: AWOS-3 135.425 (208) 263-3074.

COMMUNICATIONS: CTAF/UNICOM 122 7

R SEATTLE CENTER APP/DEP CON 123.95

RADIO AIDS TO NAVIGATION: NOTAM FILE GEG.

SPOKANE (H) VORTACW 115.5 GEG Chan 102 N47°33.90' W117°37.61' 023° 61.6 NM to fld. 2755/21E. HIWAS. SANDPOE NDB (MHW) 264 SZT N48°17.44′ W116°33.79′ at fld. NOTAM FILE BOI.

ILS/DME 109.1 I-RPO Chan 28 Rwy 01. Localizer unusable from 1 NM to rwy thld.




GREAT FALLS

L-13B

GREAT FALLS

H-1C. L-13C

ΙΔΡ



SHEARER (USFS) (2U5) 0 S UTC-8(-7DT) N45°59.37' W114°50.48'

GREAT FALLS

RWY 18-36: 2000X15 (TURF)

2634

NOTAM FILE BOL RWY 18: Hill. RWY 36: Trees.

AIRPORT REMARKS: Unattended. CLOSED during winter months. Inexperienced pilots should use for emergencies only. Recommend early morning or late evening operations during summer. Rwy 18-36 first 300' of rwy rough. Big game animals on and invof arpt. Located in narrow winding river canyon. Land Rwy 18, takeoff Rwy 36. Blind apch to Rwy18; before landing/takeoff call on frequency. 122.9; monitor same. Ctc arpt manager 208-983-4060, for briefings and rwy conditions.

COMMUNICATIONS: CTAF 122.9

SHOSHONE CO (See KELLOGG)

SLATE CREEK (1S7) 3 NW UTC-8(-7DT) N45°40.31′ W116°18.34′

1660 NOTAM FILE BOI

RWY 11-29: 2600X165 (TURF)

RWY 11: Fence. RWY 29: P-line.

AIRPORT REMARKS: Unattended. No winter maintenance. No line of sight between rwy ends. Rwy 11–29 edges and thids marked with white rock boundary markers. No telephone avbl at arpt.

COMMUNICATIONS: CTAF 122.9

SMILEY CREEK (See GALENA)

SMITH PRAIRIE (See PRAIRIE)

SNAKE RIVER SPB (See LEWISTON)

SODA SPRINGS

ALLEN H TIGERT (U78) 1 SE UTC-7(-6DT) N42°38.91′ W111°34.91′

SALT LAKE CITY

GREAT FALLS

5839 B **FUEL** 100LL NOTAM FILE U78

RWY 16-34: H3500X50 (ASPH) S-12 LIRL (NSTD)

RWY 16: TRCV(TRIL)—GA 4.0° TCH 25'. Thid dspicd 300'. Road. RWY 34: TRCV(TRIL)—GA 3.0° TCH 15'.

RWY 13-31: H2500X50 (ASPH)

RWY 13: Tree. RWY 31: Railroad.

AIRPORT REMARKS: Attended irregularly. Telephone


208–547–9927/2600 for svc. Sharply descending terrain near end of Rwy 31 and Rwy 34. Rwy 16–34 first 300' Rwy 16 pavement breaking up. Rwy 16–34 NSTD LIRL first 300' Rwy 16 not lgtd. Rwy 16 thid dsplcd 300' at ngt, 3200' of Rwy 16–34 lgtd at ngt. ACTIVATE LIRL Rwy 16–34, TRCV Rwy 16 and Rwy 34—click CTAF 5 times.

WEATHER DATA SOURCES: SAWRS (dalgt observation only).

COMMUNICATIONS: CTAF/UNICOM 122.8

RADIO AIDS TO NAVIGATION: NOTAM FILE MLD.

MALAD CITY (H) VOR/DME 117.4 MLD Chan 121 N42°11.99′ W112°27.07′ 038° 47.1 NM to fld. 7330/17E.



SOLDIER BAR USFS (85U) 1 SW UTC-7(-6DT) N45°05.99′ W114°48.06′

GREAT FALLS

4190 NOTAM FILE BOI

RWY 07-25: 1650X15 (DIRT)

RWY 25: Hill. RWY 07: Trees.

AIRPORT REMARKS: Unattended. Steep canyon walls in all directions. Cabin Creek arpt approximately 7 miles west up Big Creek Canyon. Arpt on bench 500' above Big Creek on south side. West ½ of rwy has 4° slope down to the north. Go arounds not recommended. Rwy 07–25 sharp dog leg on W ½ of rwy to the north. Land Rwy 25, tkf Rwy 07. Rwy 25 thld marked with rocks. No telephone avbl at arpt.

COMMUNICATIONS: CTAF 122.9

RC0 122.45 (BOISE RADIO)

SQUAW BUTTE N44°00.71′ W116°24.36′

SALT LAKE CITY

L-11B

STANFORD FLD (See ST ANTHONY)

STANLEY N44°10.19′ W114°55.87′

SALT LAKE CITY L-11C

RCO 122.6 (BOISE RADIO)

56 INAHN

STANLFY

BRUCE MEADOWS (U63) 20 NW UTC-7(-6DT) N44°24.93′ W115°19.01′

SALT LAKE CITY

NOTAM FILE BOI

RWY 05-23: 5000X110 (TURF-DIRT)

RWY 05: Fence. RWY 23: Fence.

AIRPORT REMARKS: Unattended. Livestock and big game animals have access to rwy. Rwy 23 6' fence at 40' on centerline; 200' timbered ridge at 2000' on centerline; 13' road at 300' on centerline 20' pole at 300' on centerline; 20' pole at 400' 50' left. No winter maintenance. Recommend land Rwy 05, tkf Rwy 23 when wind conditions permit. Arpt is located on a high mountain valley surrounded by mountains. Rwy 05-23 fences with yellow and black warning panels 45' from AER 05, 40' from end of AER 23. Rwy 05-23 edges and thids marked

with white rocks. 20' wide dirt strip down center of Rwy 05-23.

COMMUNICATIONS: CTAF 122.9

STANLEY (2U7) 1 SE UTC-7(-6DT) N44°12.51′ W114°56.07′

SALT LAKE CITY

6403 NOTAM FILE BOL

RWY 17-35: 4300X150 (TURF-DIRT)

RWY 35: Fence RWY 17. Trees

AIRPORT REMARKS: Unattended. No winter maintenance. Arpt located in valley surrounded by high mountainous terrain. Numerous air taxi operations during the summer months. Rwy 17-35 rwy edges and thlds marked with white rocks

COMMINICATIONS: CTAF 122 9

RCO 122.6 (BOISE RADIO)

THOMAS CREEK (2U8) 31 N UTC-7(-6DT) N44°43.58′ W115°00.21′

GREAT FALLS

4400 NOTAM FILE BOI RWY 03-21: 2100X75 (TURF-DIRT)

RWY 21. Trees

AIRPORT REMARKS: Unattended. No winter maintenance. Recommend ldg Rwy 21, tkf Rwy 03, go arounds extremely difficult. Rwy 03 first 400' is dog leg with a heading of 360°. Acft loading and unloading at the south end of Rwy 21. Considerable air taxi operations mid to late summer, Rwy 03-21 usable width may vary from 75' to 100'. Arpt is located on plateau 100-150' abv river.

COMMUNICATIONS: CTAF 122.9

STEELHEAD N42°54.97′ W114°40.45′ NOTAM FILE BOI.

SALT LAKE CITY L-11C

NDB (MHW) 211 HDG 255° 4.0 NM to Gooding Muni.

STRIK N42°28.72′ W114°21.27′ NOTAM FILE TWF. NDB (LOM) 389 TW 256° 5.9 NM to Joslin Fld-Magic Valley Rgnl. SALT LAKE CITY

STURGEON N43°06.80′ W115°39.51′ NOTAM FILE BOI. NDB (MHW) 333 STI 272° 3.4 NM to Mountain Home Muni, Unusable 320°-020° bvd 15 NM. SALT LAKE CITY

I-11R

SWEDEN N43°25.93′ W112°09.75′ NOTAM FILE IDA.

SALT LAKE CITY

NDB (MHW) 350 SWU 024° 6.3 NM to Idaho Falls Rgnl.

L-11D

NDB unusable 025°-080° bevond 20 NM all altitude.

TANGLEFOOT SPB (See CAVANAUGH BAY)

THOMAS CREEK (See STANLEY)

THREE CREEK

MURPHY HOT SPRINGS (3UØ) 9 SW UTC-7(-6DT) N42°01.41′ W115°20.13′

SALT LAKE CITY

NOTAM FILE BOI 5829

RWY 01-19: 5250X120 (TURF)

RWY 01: Fence. RWY 19: Fence.

AIRPORT REMARKS: Unattended. Rwy 01-19 rodent damage. No winter maintenance. No line of sight between rwy ends. Recommend land Rwy 19 and depart Rwy 01 when wind conditions permit. Rwy 01-19 edges and thids marked with white rock. No telephone avbl at arpt.

COMMUNICATIONS: CTAF 122.9

TWIN BRIDGES (See KETCHUM)

INAHN 57

TWIN FALLS N42°28.79′ W114°29.37′ NOTAM FILE TWF. SALT LAKE CITY (L) VORTACW 115.8 TWF Chan 105 at Joslin Fld-Magic Valley Rgnl. 4140/18E. H-3C, L-11C VOR portion unusable

115°-160° byd 30 NM blo 11,000′ DME unusable

115°-160° bvd 33 NM blo 12.000'

105°-160° byd 20 NM blo 15,000′ RC0 122.25 (BOISE RADIO)

TWIN FALLS

JOSLIN FLD-MAGIC VALLEY RGNL (TWF) 4 S UTC-7(-6DT)

SALT LAKE CITY H-3C, L-11C

IAP. AD

N42°28.91′ W114°29.27′

4154 B S4 FUEL 100LL, JET A1 + OX 1, 3 Class II, ARFF Index A NOTAM FILE TWF

RWY 07-25: H8703X150 (ASPH-PFC) S-75, D-200, ST-175,

DT-250 HIRL

RWY 07: REIL. VASI(V4L)-GA 3.0° TCH 50'.

RWY 25: MALSR. PAPI(P4L)-GA 3.0° TCH 55'.

RWY 12-30: H3224X150 (ASPH) S-19 1.3% up SF

RWY 12. Trees RWY 30: Antenna.

LAND AND HOLD SHORT OPERATIONS

LANDING HOLD SHORT POINT DIST AVRI PWV N7 12-30 4500 **RWY 25** 12-30 3600

AIRPORT REMARKS: Attended 1330-0300Z‡. Additional fuel service fee between 0300-1330Z‡, call 208-733-5920 or 539-4034 for information. PPR for unscheduled air carrier ops with more than 30 passenger seats call arpt manager 208-733-5215. Rwy 12-30 and Twy G, Twy H, Twy J and Twy K non-air carrier movement area. When twr clsd ACTIVATE HIRL Rwy 07-25, MALSR Rwy 25, REIL Rwy 07—CTAF. Landing fee for all FAR Part 121, 135 operators and general aviation Part 91 acft greater than 12,500 lbs maximum gross landing weight. For information ctc airport manager 208-733-5215.

WEATHER DATA SOURCES: ASOS 135.025 (208) 733-1878.

COMMUNICATIONS: CTAF 118.2 UNICOM 122.95

TWIN FALLS RCO 122.25 (BOISE RADIO)

TWIN FALLS APP/DEP 126.7 (1300-0400Z‡) TWIN FALLS TOWER 118.2 (1300-0400Z‡) R) SALT LAKE CENTER APP/DEP CON 118.05 (0400-1300Z‡)

GND CON 121.7 AIRSPACE: CLASS D svc 1300-0400Z± other times CLASS E.

RADIO AIDS TO NAVIGATION: NOTAM FILE TWF.

TWIN FALLS (L) VORTACW 115.8 TWF Chan 105 N42°28.79' W114°29.37' at fld. 4140/18E. STRIK NDB (LOM) 389 TW N42°28.72′ W114°21.27′ 256° 5 9 NM to fld

I-TWF Rwy 25. Class IE. LOM STRIK NDB. ILS unmonitored when twr closed.

COMM/NAV/WEATHER REMARKS: Freq 121.5 not avbl at twr.

TYHEE N42°57.83′ W112°30.98′ NOTAM FILE PIH. SALT LAKE CITY NDB (LOM) 383 PI 210° 4.8 NM to Pocatello Rgnl. Unmonitored when twr clsd. I-11C

UCONN N43°35.87′ W111°58.84′ NOTAM FILE IDA. SALT LAKE CITY

NDB (LOM) 324 ID 201° 6.4 NM to Idaho Falls Rgnl.

UPPER LOON CREEK USFS (See CHALLIS)

USTIK N43°35.81′ W116°18.91′ NOTAM FILE BOI. SALT LAKE CITY NDR (HW/LOM) 359 BO 099° 4.5 NM to Boise Air Terminal (Gowen Fld). I_11R

WARM SPRINGS CREEK (See LOWMAN)

WARREN (USFS) (3U1) 0 NW UTC-7(-6DT) N45°16.09' W115°41.01'

GREAT FALLS

5896 NOTAM FILE BOI **RWY 11–29:** 2765X50 (DIRT)

RWY 11: Trees. RWY 29: Road.

AIRPORT REMARKS: Unattended. No winter maintenance. Rwy width varies from 65' to 85'. Rwy 11–29 thIds marked with white rock. Recommend land Rwy 11, tkf Rwy 29 when wind conditions allow. Downdrafts prevalent Rwy 11 summer months. Recommended use early morning and late evening in summer. Not recommended for inexperienced pilots. Road crosses rwy approximately 800' from Rwy 11 thId. No telephone avbl at arpt. Rwy 11–29 has some loose rocks to 2 inches in diameter, isolated spots of embedded flat rocks to 6 inches in diameter and some spotty weed growth to 12 inches.

COMMUNICATIONS: CTAF 122.9

WEATHERBY USFS (See ATLANTA)

WEISER MUNI (S87) 3 S UTC-7(-6DT) N44°12.28′ W116°57.63′

2120 B S3 **FUEL** 100LL NOTAM FILE BOI

SALT LAKE CITY L-11B

RWY 12-30: H4000X60 (ASPH) S-12.5 MIRL

RWY 12: REIL. Trees.

RWY 30: REIL. PAPI(P4L)-GA 3.0° TCH 50'.


AIRPORT REMARKS: Attended continuously. Birds on and in vicinity of arpt. Extensive agricultural ops Mar–Oct. ACTIVATE MIRL Rwy 12–30 and REIL Rwy 12 and Rwy 30—CTAF. PAPI Rwy 30 opr continuously.

COMMUNICATIONS: CTAF/UNICOM 122.8

SALT LAKE CENTER APP/DEP CON 128.05

RADIO AIDS TO NAVIGATION: NOTAM FILE BOI.

DONNELLY (H) VORTACW 116.2 DNJ Chan 109 N44°46.03′ W116°12.38′ 205° 46.8 NM to fld. 7333/19E.



YELLOW PINE

JOHNSON CREEK (3U2) 3 S UTC-7(-6DT) N44°54.73′ W115°29.14′

GREAT FALLS

4933 NOTAM FILE BOI

RWY 17-35: 3400X150 (TURF)

RWY 17: Ridge. RWY 35: Fence.

AIRPORT REMARKS: Attended Jun-Aug, Thu-Mon 1500–0000Z‡. Big game animals on and invof arpt. No winter maintenance. Recommend land Rwy 17, tkf Rwy 35 when wind conditions allow. Rwy 17–35 plus 60' trees 100' each side of centerline. Be alert for sprinklers on rwy. Additional 250' of length avbl for tkf on Rwy 35 end. Rwy 17–35 edges and thlds marked with white rocks. Special considerations should be given to density altitude, turbulence and mountain flying proficiency.

2009 U.S. & CANADIAN MILITARY AERIAL AIRCRAFT/PARACHUTE DEMONSTRATIONS

During CY 2009, the U.S. and Canadian Military Aerial Demonstration Teams (Thunderbirds, Blue Angels, Snowbirds, and Golden Knights) will be performing on the dates and locations listed below.

Pilots should expect Temporary Flight Restrictions (TFR) in accordance with 14 CFR Section 91.145, Management of aircraft operations in the vicinity of aerial demonstrations and major sporting events. The dimensions and effective times of the TFRs may vary based upon the specific aerial demonstration event and will be issued via the U.S. NOTAM system. Pilots are strongly encouraged to check FDC NOTAMs to verify they have the most current information regarding these airspace restrictions.

The currently scheduled 2009 aerial demonstration locations, subject to change without notice, are:

DATE:		USAF Thunderbirds	USN Blue Angels	Canadian Snowbirds	USA Golden Knights
October	24-25		Fort Worth, TX		Fort Worth, TX
	24-25				Pinehurst, NC
	31		Houston, TX		
					•
November	1		Houston, TX		
	7-8	Homestead AFB, FL	Jacksonville Beach, FL		
	13-14		NAS Pensacola, FL		
	14-15	Nellis AFB, NV			

Note: Dates and locations are scheduled "show dates" only and do not reflect arrival or practice date TFR periods that may precede the specific aerial demonstration events listed above. Again, pilots are strongly encouraged to check FDC NOTAMs to verify they have the most current information regarding any airspace restrictions.

VFR ADVISORY AREA Canadian Airspace VICTORIA-VANCOUVER (Effective: Until Further Notice)

Effective 0901 UTC August 6, 1994, a VFR Advisory Area was permanently established between the two Canadian control zones, from above 1,200′ MSL up to 2,500′ MSL. Vancouver and Victoria Towers provide radar traffic information to all participating aircraft within the VFR Advisory Area.

PROCEDURES


Victoria/Vancouver

- *All aircraft operating between Victoria and Vancouver within the VFR Advisory Area should follow the routes shown on the graphic.
 - *Northbound: Change from Victoria Tower, 119.1, to Vancouver Tower, 124.0, when instructed by ATC.
 - *Southbound: Change from Vancouver Tower, 124.0, to Victoria Tower, 119.1, when instructed by ATC.
 - *Set transponder codes as requested.

TRANSITING TRAFFIC

- *Call Vancouver Tower on 124.0 when north of the Active Pass/Samuel Island Line.
- *Call Victoria Tower on 119.1 when south of the Active Pass/Samuel Island Line.
- *Set Transponder codes as requested.

Routes and recommended altitudes will not be useable by all aircraft at all times because of weather and regulations pertaining to flight over water. Higher altitudes may be requested. If unable to maintain VFR, advice ATC.



CONTROLLED FIRING Fort Harrison Controlled Firing Area Helena, Montana

Controlled firing occurs in the vicinity of the Helena, Montana VORTAC (HLN) 24 hours daily, 5'800 MSL and BELOW. The area defined by the following radial/DME coordinates HLN258008, HLN258005, HLN250008, HLN250005.

CONTROLLED FIRING Limestone Hills Controlled Firing Area Helena, Montana

Controlled firing occurs in the vicinity of the Helena, Montana VORTAC (HLN) 24 hours daily, FL180 and BELOW. The area defined by the following radial/DME coordinates HLN125026, HLN127028, HLN140025, HLN125028.

SPECIAL NORTH ATLANTIC, CARIBBEAN AND PACIFIC AREA COMMUNICATIONS

VHF air-to-air frequencies enable aircraft engaged in flights over remote and oceanic areas out of range of VHF ground stations to exchange necessary operational information and to facilitate the resolution of operational problems.

Frequencies have been designated as follows:

North Atlantic area: 123.45 MHz
Caribbean area: 123.45 MHz
Pacific area: 123.45 MHz

MOUNT ST. HELENS NATIONAL VOLCANIC MONUMENT. WASHINGTON

The U.S. Geological Survey (USGS) and the U.S. Forest Service (USFS) conduct low level flights to and from monitor station within the monument and within the crater itself. Due to this activity, the volatility of the volcano and a high volume of sightseeing flights in the area, the following procedures are recommended in the interest of flying safety.

- 1. VFR aircraft are encouraged to transmit an initial position report on 122.75 MHz in the blind when flying at altitudes of less than 10,000 feet MSL within 10 nautical miles of the Mount St. Helens volcano crater.
- 2. VFR flight below 3000 feet AGL strongly not recommended.
- 3. VFR flight above 3000 feet AGL fly a counterclockwise pattern, no closer than 3 miles to the volcano summit.

VFR rules of "see and be seen" and good airmanship practices will prevail. Approval to land can only be obtained through appropriate Federal or State authority. Any significant information will be broadcast on the transcribed weather broadcasts by the Seattle and McMinnville Flight Service Stations and available on the Portland and Seattle ATIS. Marginal radar coverage limits Seattle Center's ability to provide radar flight following to aircraft in orbit of the volcano.

DEVILS TOWER NATIONAL MONUMENT, WYOMING

For reasons of national welfare, pilots are requested to avoid flights within 3 nautical miles of Devils Tower National Monument.

BIRD HAZARD OREGON AND WASHINGTON

Heavy concentration of migratory and wintering flocks of large waterfowl from the Canadian to California borders annually November to May. Caution advised at all airports or while transiting area.

SIMULTANEOUS OPERATIONS Boeing Field/King County International Airport Seattle. Washington

All users: Boeing Field Airport Traffic Control Tower is authorized to conduct simultaneous same direction operations to parallel runways, between sunrise and sunset, for Category II aircraft and smaller.

Spokane International Airport Spokane, Washington

Application of visual separation for simultaneous operations. When weather conditions at Spokane International Airport are 1500' ceiling and 5 miles visibility or greater Spokane International Airport controllers may provide visual separation of aircraft landing and departing simultaneously at Spokane International Airport and Fairchild Airforce Base.

LASER LIGHT DEMONSTRATIONS Bozeman, Montana

A laser light demonstration will be conducted daily between 0000 and 2359 MDT until June 24, 2010 at Montana State University BZN VORTAC 129 radial at 8 NM LAT 45–39–59N/Long 111–02–44W. The laser beam elevation will be a maximum of 090 and a minimum of 089. The beam may be injurious to eyes when viewed within 12000 feet AGL vertically and 500 feet laterally of the light source. Cockpit illumination–flash blindness may occur beyond these distances.

SEATTLE-TACOMA INTL SEATTLE, WASHINGTON

Gatehold Procedures:

During peak departure periods, gatehold procedures are implemented for all IFR departures. Additional information will be broadcast on ATIS.

Oceanic Departures:

- 1. Contact Clearance Delivery *only* when you will be ready to taxi within ten minutes. State destination, requested altitude, "ten minutes to taxi."
- 2. If ATC delays are more than 15 minutes for your filed altitude/route, alternatives with less delay will be offered.
- 3. Failure to depart the gate within ten minutes or reach the runway at the release time specified in the IFR clearance may result in the cancellation of your clearance.

MOUNTAIN HOME, IDAHO

All aircraft operating within 20 NM of the Liberator VOR are requested to contact Mountain Home APP CON on 124.8 for traffic advisory due to intensive military training in the Mountain Home area.

MILITARY TRAINING ROUTES

The DOD Flight Information Publication AP/1B provides textual and graphic descriptions and operating instructions for all military training routes (IR, VR, SR) and refueling tracks/anchors. Complete and more comprehensive information relative to policy and procedures for IRs and VRs is published in FAA Handbook 7610.4 (Special Military Operations) which is agreed to by the DOD and therefore directive for all military flight operations. The AP/1B is the official source of route data for military users.

CIVIL USE OF MILITARY FIELDS:

U.S. Army, Air Force, Navy and Coast Guard Fields are open to civil fliers only in emergency or with prior permission. Army installations, prior permission is required from the Commanding Officer of the installation.

For Air Force installations, prior permission should be requested at least 30 days prior to first intended landing from either Headquarters USAF (PRPOC) or the Commander of the installation concerned (who has authority to approve landing rights for certain categories of civil aircraft). For use of more than one Air Force installation, requests should be forwarded direct to Hq USAF (PRPOC), Washington, D.C. 20330.

Use of USAF installations must be specifically justified.

For Navy and Marine Corps installations, prior permission should be requested at least 30 days prior to first intended landing. An Aviation Facility License must be approved and executed by the Navy prior to any landing by civil aircraft.

Forms and further information may be obtained from the nearest U.S. Navy or Marine Corps aviation activity.

For Coast Guard fields prior permission should be requested from the Commandant, U.S. Coast Guard via the Commanding Officer of the field.

When instrument approaches are conducted by civil aircraft at military airports, they shall be conducted in accordance with the procedures and minimums approved by the military agency having jurisdiction over the airport.

AIRCRAFT LANDING RESTRICTIONS

Landing of aircraft at locations other than public use airports may be a violation of Federal or local law. All land and water areas are owned or controlled by private individuals or organizations, states, cities, local governments, or U.S. Government agencies. Except in emergency, prior permission should be obtained before landing at any location that is not a designated public use airport or seaplane base.

Landing of aircraft is prohibited on lands or water administered by the National Park Service, U.S. Fish and Wildlife Service, U.S. Forest Service, and on many areas controlled by the U.S. Army Corps of Engineers, unless prior authorization is obtained from the respective agency.

CONTINUOUS POWER FACILITIES

In order to insure that a basic ATC system remains in operation despite an areawide or catastrophic commercial power failure, key equipment and certain airports have been designated to provide a network of facilities whose operational capability can be utilized independent of any commercial power supply.

In addition to those facilities comprising the basic ATC system, the following approach and lighting aids have been included in this program for a selected runway.

- 1. ILS (Localizer, Glide Slope, COMLO, Inner, Middle and Outer Markers)
- 2. Wind Measuring Capability
- 3. Approach Light System (ALS) or Short ALS (SALS)
- 4. Ceiling Measuring Capability
- 5. Touchdown Zone Lighting (TDZL)
- 6. Centerline Lighting (CL)
- 7. Runway Visual Range (RVR)
- 8. High Intensity Runway Lighting (HIRL)
- 9. Taxiway Lighting
- 10. Apron Light (Perimeter Only)

The following have been designated "Continuous Power Airports," and have independent back up capability for the equipment installed.

Airport/Ident	Runway No.	Airport/Ident	Runway No.
Albuquerque, NM (ABQ)	08	Milwaukee, WI (MKE)	01L
Andrews AFB, MD (ADW)	01L	Minneapolis, MN (MSP)	30L
Anchorage, AK (ANC)	07R	Nashville, TN (BNA)	02L
Atlanta, GA (ATL)	09R	New Orleans, LA (MSY)	10
Baltimore, MD (BWI)	10	New York, NY (JFK)	04R
Bismarck, ND (BIS)	31	New York, NY (LGA)	22
Boise, ID (BOI)	10R	Newark, NJ (EWR)	04R
Boston, MA (BOS)	04R	Oklahoma City, OK (OKC)	35R
Charlotte, NC (CLT)	36L	Omaha, NE (OMA))	14R
Chicago, IL (ORD)	14R	Ontario, CA (ONT)	26L
Cincinnati, OH (CVG)	36C	Philadelphia, PA (PHL)	09R
Cleveland, OH (CLE)	06R	Phoenix, AZ (PHX)	08
Dallas/Fort Worth, TX (DFW)	17C	Pittsburgh, PA (PIT)	10L
Denver, CO (DEN)	35R	Reno, NV (RNO)	16R
Des Moines, IA (DSM)	31	Salt Lake City, UT (SLC)	34L
Detroit, MI (DTW)	03R	San Antonio, TX (SAT)	12R
El Paso, TX (ELP)	22	San Diego, CA (SAN)	09
Fairbanks, AK (FAI)	01L	San Francisco, CA (SFO)	28R
Great Falls, MT (GTF)	03	San Juan, PR (SJU)	08
Honolulu, HI (HNL)	08L	Seattle, WA (SEA)	16C
Houston, TX (IAH)	26L	St. Louis, MO (STL)	30R
Indianapolis, IN (IND)	05L	Tampa, FL (TPA)	36L
Jacksonville, FL (JAX)	07	Tulsa, OK (TUL)	36R
Kansas City, MO (MCI)	19R	Washington, DC (DCA)	01
Los Angeles, CA (LAX)	24R	Washington, DC (IAD)	01R
Memphis, TN (MEM)	36L	Wichita, KS (ICT)	01L
Miami, FL (MIA)	08R		

NOTE—The existing CPA runway is listed. Pending and future changes at some locations will require a revised runway designation.

Night Vision Lights Out Operations Yakima Training Center, Washington

Military helicopter activity will be conducted for night vision lights out training at Yakima Training Center, Washington. Position lights will be extinguished or greatly reduced in intensity. The training will be conducted within the confines of the YTC reservation but outside of the restricted airspace. The general description of the night vision goggle (NVG) training area is that airspace bordered by R-6714H on the south, Highline Canal on the west, the southern edge of Interstate 90 on the north, and Ginko State Park Petified Forest on the east.

The boundaries of the NVG area are:

Beginning at lat. $46^\circ55'03''N$, long. $120^\circ01'34''W$; to lat. $46^\circ55'40''N$, long. $120^\circ01'35''W$; to lat. $46^\circ55'39''N$, long. $120^\circ02'52''W$; to lat. $46^\circ56'15''N$, long. $120^\circ02'52''W$ thence west along the southern edge of Interstate 90; to lat. $46^\circ57'21''N$, long. $120^\circ18'08''W$; thence west/southwest along the Highline Canal; to lat. $46^\circ55'24''N$, long. $120^\circ19'55''W$; to point of beginning.

Times of use: Sunset to sunrise, daily.


Request Publication date of May 22, 1997.

Please refer any questions to James Riley, ANM-532.2, at (206) 227-2537.

LIGHTS-OUT OPERATIONS Hays MOA, Montana

Lights—out night vision goggle training operations conducted within the Hays MOA at all altitudes from sunset to sunrise when MOA is active by NOTAM. Contact Salt Lake City ARTCC on 133.4 or 119.75 or Great Falls FSS for schedule and NOTAM information.

FIREFIGHTING TRAFFIC AREAS



Pilots are advised to stay clear of Firefighting Traffic Areas. Remain 15 miles from the area of activity. If you must over-fly the area, do so at an altitude of 5000 feet AGL above. However, to remain safe and out of the way of working aircraft, it is best to circumnavigate the area.

The wild-land fire environment can be very complex and involve a large number and variety of aircraft types including fixed and rotary wing aircraft. Some of the aircraft are small single and multi-engine command and control platforms that can be especially difficult to see and may give the appearance that the fire is not staffed. The aircraft participating in firefighting can orbit as far out as 12 miles from the perimeter of the fire. Any intrusion by aircraft not directly involved in the firefighting operation could delay the delivery of much needed retardant or water to ground firefighters and will adversely affect the safety of participating aircraft. Please stay well away from wild-land fires even if you feel that aircraft are not working the fire; they may be en route or unseen.

If you see a fire developing along your route, report it immediately to air traffic control who will advise the US Forest Service. The firefighting community would welcome this information

The following narratives summarize the FAR Part 93 Special Air Traffic Rules, and Airport Traffic Patterns in effect as prescribed in the rule. This information is advisory in nature and in no way relieves the pilot from compliance with the specific rules set forth in FAR Parts 91 and 93.

Special Airport Traffic Areas prescribed in Part 93 are depicted on Sectional Aeronautical Charts, World Aeronautical Charts, Enroute Low Altitude Charts, and where applicable, on VFR Terminal Area Charts.

OPERATIONS RESERVATIONS FOR HIGH DENSITY TRAFFIC AIRPORTS KENNEDY. LAGUARDIA. AND WASHINGTON REAGAN NATIONAL

The Federal Aviation Administration (FAA) has designated New York's Kennedy and LaGuardia Airports and Washington Reagan National Airport as High Density Traffic Airports (HDTA), Title 14, Code of Federal Regulations, part 93, subpart K, and has prescribed air traffic rules and requirements for operating aircraft (excluding helicopters) to and from those airports during certain hours.

Reservations are required for operations from 6 a.m. through 11:59 p.m. local time at LaGuardia Airport and Washington Reagan National Airport. Reservations at Kennedy Airport are required from 3 p.m. through 7:59 p.m. local time.

Reservation procedures are detailed in Advisory Circular 93–1, Reservations for Unscheduled Operations at High Density Traffic Airports. A copy of the advisory circular is available on the FAA website at http://www.faa.gov. Reservations for unscheduled operations are allocated through the Enhanced Computer Voice Reservation System (e-CVRS) accessible via telephone or the Internet. This system may not be used to make reservations for scheduled air carrier or commuter flights.

The toll–free telephone number for accessing e–CVRS is 1–800–875–9694 and is available for calls originating within the United States, Canada, and the Caribbean. Users outside the toll–free areas may access e–CVRS by calling the toll number of 703–707–0568. The Internet web address for accessing the e–CVRS is http://www.fly.faa.gov/ecvrs. If you have any questions about reservation requirements or are experiencing problems with the system, you may telephone the Airport Reservation Office at the Air Traffic Control System Command Center at (703) 904–4452.

Requests for instrument flight rules (IFR) reservations will be accepted beginning 72 hours prior to the proposed time of operation at the high-density airport. For example, a request for an 11 a.m. reservation on a Thursday will be accepted beginning at 11 a.m. on the previous Monday.

IFR reservations must be obtained prior to IFR landing or takeoff at an HDTA during slot controlled hours. An air traffic control (ATC) clearance does not constitute a reservation. A reservation does not constitute permission to operate at an HDTA if additional operational limits or procedures are required by NOTAM and/or regulation.

Aircraft involved in medical emergencies will be handled by ATC without regard to a reservation after obtaining prior approval of the ATC System Command Center on (703) 904–4452. ATC will accommodate declared other emergency situations without regard to slot reservations.

NOTE: Visual flight rule (VFR) reservations via ATC for unscheduled operations at LaGuardia are not authorized from 7 a.m. through 8:59 a.m. local time and 4 p.m. through 6:59 p.m. local time, Monday through Friday and Sunday evenings, unless otherwise announced by NOTAM. Both IFR and VFR operations during those time periods must obtain an advance reservation through e–CVRS.

FSS Telephone numbers

Flight Service Station (FSS) facilities provide flight planning and weather briefing services to pilots. FSS services in the contiguous United States, Hawaii and Purerto Rico, are provided by a network of large hub facilities and smaller remote facilities which are interconnected with the hubs.

Selected remote FSS facilities across the contiguous United States have variable part–time operating hours. Because of the interconnectivity between remote and hub facilities, all FSS services are available continuously using published telephone numbers and radio frequencies.

NORTHWEST U.S.

WASHINGTON: Seattle, Boeing Field/King County International (BFI)-SEA FSS

<u>Telephone Information Briefing Service (TIBS)</u> is a FSS service that provides continuous recordings of meteorological and/or aeronautical information including area and/or route briefings, airspace procedures and special announcements. A touch-tone telephone is required to fully utilize this service.

Further information can be found in the Aeronautical Information Manual (AIM).

NATIONAL FSS TELEPHONE NUMBER

	, , , , , , , , , , , , , , , , , , , ,	. , , , , , , , , , , , , , , , , , , ,
(Clearance Delivery Only	1-888-766-8267
ı	Lifeguard Flights Only	1-877-LIF-GRD3 (1-877-543-4733)
1	Flights within DC SFRA & FRZ *	1-866-225-7410

^{*} District of Columbia Special Flight Rules Area & Flight Restricted Zone

KEY to AERODROME FORECAST (TAF) and AVIATION ROUTINE WEATHER REPORT (METAR)

TAF KPIT 091730Z 091818 15005KT 5SM HZ.FEW020 WS010/31022KT FM1930 30015G25KT 3SM SHRA OVC015 TEMPO 2022 1/2SM +TSRA OVC008CB

FM0100 27008KT 5SM SHRA BKN020 OVC040 PROB40 0407 1SM -RA BR FM1015 18005KT 6SM -SHRA OVC020 BECMG 1315 P6SM NSW SKC

METAR KPIT 091955Z COR 22015G25KT 3/4SM R28L/2600FT TSRA OVC010CB 18/16 A2992 RMK SLP045 T01820159

Forecast	Explanation	Report
TAF	Message type: <u>TAF</u> -routine or <u>TAF AMD</u> -amended forecast, <u>METAR</u> -hourly, <u>SPECI</u> -special or <u>TESTM</u> -non-commissioned ASOS report	METAR
KPIT	ICAO location indicator	KPIT
091730Z	Issuance time: ALL times in UTC "Z", 2-digit date, 4-digit time	091955Z
091818	Valid period: 2-digit date, 2-digit beginning, 2-digit ending times	
	In U.S. METAR : <u>COR</u> rected ob; or <u>AUTO</u> mated ob for automated report with no human intervention; omitted when observer logs on	COR
15005KT	Wind: 3 digit true-north direction, nearest 10 degrees (or <u>VaRiaBle</u>); next 2-3 digits for speed and unit, <u>KT</u> (KMH or MPS); as needed, <u>G</u> ust and maximum speed; 00000KT for calm; for METAR , if direction varies 60 degrees or more, <u>V</u> ariability appended, e.g. 180 <u>V</u> 260	22015G25KT
5SM	Prevailing visibility: in U.S., Statute Miles & fractions; above 6 miles in TAF Plus6SM. (Or, 4-digit minimum visibility in meters and as required, lowest value with direction)	3/4SM
	Runway Visual Range: R; 2-digit runway designator Left, Center, or Right as needed; "/"; Minus or Plus in U.S., 4-digit value, FeeT in U.S., (usually meters elsewhere); 4-digit value Variability 4-digit value (and tendency Down, Up or No change)	R28L/2600FT
HZ	Significant present, forecast and recent weather: see table (on back)	TSRA
FEW020	Cloud amount, height and type: SKy Clear 0/8, FEW >0/8-2/8, SCaTtered 3/8-4/8, BroKeN 5/8-7/8, OVerCast 8/8; 3-digit height in hundreds of ft; Towering CUmulus or CumulonimBus in METAR; in TAF, only CB. Vertical Visibility for obscured sky and height "VV004". More than 1 layer may be reported or forecast. In automated METAR reports only, CLeaR for "clear below 12,000 feet"	OVC010CB
	Temperature: degrees Celsius; first 2 digits, temperature "/" last 2 digits, dew-point temperature; Minus for below zero, e.g., M06	18/16
	Altimeter setting: indicator and 4 digits; in U.S., A-inches and hundredths; (Q-hectoPascals, e.g., Q1013)	A2992

KEY to AERODROME FORECAST (TAF) and **AVIATION ROUTINE WEATHER REPORT** (METAR)

Forecast	Explanation	Report
WS010/31022KT	In U.S. TAF , non-convective low-level (≤2,000 ft) <u>Wind Shear; 3-digit height (hundreds of ft); "/"; 3-digit wind direction and 2-3 digit wind speed above the indicated height, and unit, <u>KT</u></u>	
	In METAR , <u>ReMarK</u> indicator & remarks. For example: <u>Sea-Level Pressure in hectoPascals & tenths</u> , as shown: 1004.5 hPa; <u>Temp/dew-point in tenths</u> °C, as shown: temp. 18.2°C, dew-point 15.9°C	RMK SLP045 T01820159
FM1930	<u>FroM</u> and 2-digit hour and 2-digit minute beginning time: indicates significant change. Each FM starts on new line, indented 5 spaces.	
TEMPO 2022	TEMPOrary: changes expected for < 1 hour and in total, < half of 2-digit hour beginning and 2-digit hour ending time period	
PROB40 0407	PROBability and 2-digit percent (30 or 40): probable condition during 2-digit hour beginning and 2-digit hour ending time period	
BECMG 1315	BECoMinG: change expected during 2-digit hour beginning and 2-digit hour ending time period	

Table of Significant Present, Forecast and Recent Weather - Grouped in categories and used in the order listed below; or as needed in TAF. No Significant Weather.

QUA	LIFIER						
Intens	ity or Proximity	1					
- Li	ght	"no	sign* Moderate	+ 1	leavy		
VC	Vicinity: but not	at a	erodrome; in U.S. M	ETA	R, between 5 and	10SM	of the point(s) of
	observation; in	U.S.	TAF, 5 to 10SM from	n ce	nter of runway con	nplex ((elsewhere within 8000m)
Descr	iptor				·	•	,
MI	Shallow	BC	Patches	PR	Partial	TŞ	Thunderstorm
BL	Blowing	SH	Showers	DR	Drifting	FΖ	Freezing
WEA	THER PHENO	OME	:NA				
Precip	itation						
	Drizzie		Rain	SN	Snow	SG	Snow grains
IC	Ice crystals	PL	Ice pellets	GR	Hail	GS	Small hail/snow pellets
UP	Unknown precip	oitatio	on in automated obse	ervat	tions		
Obscu	ıration						
BR	Mist (≥5/8SM)		Fog (<5/8SM)	FU	Smoke	VA	Volcanic ash
SA	Sand	ΗZ	Haze	PΥ	Spray	DU	Widespread dust
Other							
SQ	Squall	SS	Sandstorm	DS	Duststorm	PO	Well developed
FC	Funnel cloud	+FC	tornado/waterspout				dust/sand whirls
			B/ AB to dt - Ac - 1966		4		

- Explanations in parentheses "()" indicate different worldwide practices.
- Ceiling is not specified; defined as the lowest broken or overcast layer, or the vertical visibility.
 NWS TAFs exclude turbulence, icing & temperature forecasts; NWS METARs exclude trend fosts
- Although not used in US, Ceiling And Visibility OK replaces visibility, weather and clouds if: visibility ≥10 km; no cloud below 5000 ft (1500 m) or below the highest minimum sector altitude, whichever is greater and no CB; and no precipitation, TS, DS, SS, MIFG, DRDU, DRSA or DRSN.

 UNITED STATES DEPARTMENT OF COMMERCE

NOAA/PA 96052 National Oceanic and Atmospheric Administration—National Weather Service

Air Traffic Control System Command Center

Main Number......703–904–4400

RGNL AIR TRAFFIC DIVISIONS			
REGION	TELEPHONE		
Alaskan	907-271-5464		
Central	816-329-2500		
Eastern	718-553-4502		
Great Lakes	847-294-7202		
New England	781-238-7500		
Northwest Mountain	425-227-2500		
Southern	404-305-5500		
Southwest	817-222-5500		
Western Pacific	310-725-6500		

AIR ROUTE TRAFFIC CONTROL CENTERS (ARTCCs)				
*24 HR RGNL DUTY OFFICE TELEPHONE #	BUSINESS HOURS	BUSINESS TELEPHONE #		
817-222-5006	7:30 a.m4:00 p.m.	505-856-4300		
907-271-5936	7:30 a.m4:00 p.m.	907-269-1137		
404-305-5180	7:30 a.m5:00 p.m.	770-210-7601		
617-238-7001	7:30 a.m4:00 p.m.	603-879-6633		
847-294-8400	8:00 a.m4:00 p.m.	630-906-8221		
847-294-8400	8:00 a.m4:00 p.m.	440-774-0310		
425-227-1389	7:30 a.m4:00 p.m.	303-651-4100		
817-222-5006	7:30 a.m4:00 p.m.	817-858-7300		
817-222-5006	7:30 a.m4:00 p.m.	281-230-5300		
847-294-8400	8:00 a.m4:00 p.m.	317-247-2231		
404-305-5180	8:00 a.m4:30 p.m.	904-549-1501		
816-329-3000	7:30 a.m4:00 p.m.	913-254-8500		
661-265-8200	7:30 a.m4:00 p.m.	661-265-8200		
404-305-5180	7:30 a.m4:00 p.m.	901-368-8103		
404-305-5180	7:00 a.m3:30 p.m.	305-716-1500		
847-294-8400	8:00 a.m4:00 p.m.	651-463-5580		
718-995-5426	8:00 a.m4:40 p.m.	516-468-1001		
310-725-3300	6:30 a.m3:00 p.m.	510-745-3331		
425-227-1389	7:30 a.m4:00 p.m.	801-320-2500		
425-227-1389	7:30 a.m4:00 p.m.	253-351-3500		
718-995-5426	8:00 a.m4:30 p.m.	703-771-3401		
	*24 HR RGNL DUTY OFFICE TELEPHONE # 817-222-5006 907-271-5936 404-305-5180 617-238-7001 847-294-8400 447-294-8400 425-227-1389 817-222-5006 817-222-5006 847-294-8400 404-305-5180 816-329-3000 661-265-8200 404-305-5180 847-294-8400 718-995-5426 310-725-3300 425-227-1389 425-227-1389	*24 HR RGNL DUTY OFFICE TELEPHONE # 817-222-5006 7:30 a.m4:00 p.m. 907-271-5936 7:30 a.m4:00 p.m. 404-305-5180 7:30 a.m4:00 p.m. 617-238-7001 847-294-8400 8:00 a.m4:00 p.m. 847-294-8400 8:00 a.m4:00 p.m. 847-225-006 7:30 a.m4:00 p.m. 817-222-5006 7:30 a.m4:00 p.m. 817-222-5006 7:30 a.m4:00 p.m. 817-222-5006 7:30 a.m4:00 p.m. 817-222-5006 7:30 a.m4:00 p.m. 817-229-8400 8:00 a.m4:00 p.m. 847-294-8400 8:00 a.m4:00 p.m. 661-265-8200 7:30 a.m4:00 p.m. 404-305-5180 7:30 a.m4:00 p.m. 61-265-8200 7:30 a.m4:00 p.m. 7:30 a.m4:00 p.m.		

IVIAJ	OR TERMINAL RADAR	APPROACH CONTROLS (TR	(ACONS)
TRACON NAME	*24 HR RGNL DUTY OFFICE TELEPHONE #	BUSINESS HOURS	BUSINESS TELEPHONE #
Atlanta	404-305-5180	7:00 a.m3:30 p.m.	404-669-1200
Chicago	847-294-8400	8:00 a.m4:00 p.m.	847-608-5509
Dallas/Ft. Worth	817-222-5006	7:30 a.m4:00 p.m.	972-615-2500
Denver	425-227-1389	7:30 a.m4:00 p.m.	303-342-1500
Houston	817-222-5006	7:30 a.m4:00 p.m.	281-230-8400
New York	718-995-5426	8:00 a.m4:30 p.m.	516-683-2901
Northern CA	310-725-3300	7:00 a.m3:30 p.m.	916-366-4001
Southern CA	310-725-3300	7:30 a.m4:00 p.m.	858-537-5800

^{*}Facilities can be contacted through the RgnI Duty Officer during non-business hours.

FAA AND NWS KEY AIR TRAFFIC FACILITIES

DAILY NAS REPORTABLE AIRPORTS

AIRPORT NAME	*24 HR RGNL DUTY OFFICE TELEPHONE #	BUSINESS HOURS	BUSINESS TELEPHONE #
Albuquerque Intl Sunport, NM	817-222-5006	8:00 a.m5:00 p.m.	505-842-4366
Andrews AFB, MD	718-995-5426	8:00 a.m4:30 p.m.	301-735-2380
Baltimore/Washington			
Intl Thurgood Marshall, MD	718-995-5426	8:00 a.m4:30 p.m.	410-962-3555
Boston Logan Intl, MA	781-238-7001	7:30 a.m4:00 p.m.	617-455-3100
Bradley Intl, CT	617-238-7001	7:30 a.m4:00 p.m.	203-627-3428
Burbank/Bob Hope, CA	310-725-3300	7:00 a.m5:30 p.m.	818-567-4806
Charlotte Douglas Intl, NC	404-305-5180	8:00 a.m4:30 p.m.	704–344–6487
Chicago Midway, IL	847-294-8400	8:00 a.m4:00 p.m.	773–884–3670
Chicago O'Hare Intl, IL	847-294-8400	8:00 a.m4:00 p.m.	773-601-7600
Cleveland Hopkins Intl, OH	847-294-8400	8:00 a.m4:00 p.m.	216-898-2020
Covington/Cincinnati, OH	708–294–7401	8:00 a.m4:30 p.m.	606-767-1006
Dallas/Ft. Worth Intl, TX	817-222-5006	8:30 a.m5:00 p.m.	972-615-2531
Dayton Cox Intl, OH	847–294–8400	7:30 a.m4:00 p.m.	937–454–7300
Denver Intl, CO	425-227-1389	7:30 a.m4:00 p.m.	303-342-1600
Detroit Metro, MI	847-294-8400	8:00 a.m4:00 p.m.	734–955–5000
Fairbanks Intl, AK	907–271–5936	7:30 a.m4:00 p.m.	907–474–0050
Fort Lauderdale Intl, FL	404–305–5180	7:00 a.m3:30 p.m.	305–356–7932
George Bush	047 000 5000	7.00	740 000 0400
Intercontinental/Houston, TX	817-222-5006	7:30 a.m4:00 p.m.	713-230-8400
Hartsfield-Jackson Atlanta Intl, GA	404-305-5180	7:00 a.m3:30 p.m.	404-669-1200
Honolulu Intl, HI	310-643-3200	7:30 a.m4:00 p.m.	808-840-6100
Houston Hobby, TX	817-222-5006	8:00 a.m.–5:00 p.m.	713-847-1400
Indianapolis Intl, IN	847-294-8400	8:00 a.m4:00 p.m.	317-484-6600
Kahului/Maui, HI	310-643-3200	7:30 a.m4:00 p.m.	808-877-0725
Kansas City Intl, MO	816-329-3000	7:30 a.m4:00 p.m. 7:30 a.m4:00 p.m.	816-329-2700
Las Vegas McCarran, NV Los Angeles Intl, CA	310-725-3300 310-725-3300	· ·	702–262–5978 310–342–4900
	817-222-5006	7:00 a.m3:30 p.m.	504-471-4300
Louis Armstrong New Orleans Intl, LA Memphis Intl, TN	404-305-5180	7:00 a.m4:30 p.m. 7:30 a.m4:00 p.m.	901–322–3350
Miami Intl, FL	404-305-5180	7:00 a.m.–4:00 p.m.	305-869-5400
Minneapolis/St. Paul, MN	847-294-8400	8:00 a.m.–4:00 p.m.	612-713-4000
Nashville Intl, TN	404-305-5180	7:00 a.m.–3:30 p.m.	615-781-5460
New York Kennedy Intl, NY	718-995-5426	8:00 a.m4:30 p.m.	718-656-0335
New York La Guardia, NY	718-995-5426	8:00 a.m4:30 p.m.	718-335-5461
Newark Liberty Intl, NJ	718-995-5426	8:00 a.m.–4:30 p.m.	973-645-3103
Norman Y. Mineta San Jose Intl, CA	310-643-3200	7:30 a.m.–4:00 p.m.	408-982-0750
Ontario Intl, CA	310-643-3200	7:30 a.m.–4:00 p.m.	909-983-7518
Orlando Intl, FL	404-305-5180	7:30 a.m.–5:00 p.m.	407-850-7000
Philadelphia Intl, PA	718-995-5426	8:00 a.m4:30 p.m.	215-492-4100
Phoenix Sky Harbor Intl, AZ	310-643-3200	7:30 a.m4:00 p.m.	602-379-4226
Pittsburgh Intl, PA	718-995-5426	8:00 a.m4:30 p.m.	412-269-9237
Portland Intl, OR	425-227-1389	7:30 a.m4:00 p.m.	503-493-7500
Raleigh-Durham, NC	404-305-5180	8:00 a.m4:30 p.m.	919-840-5544
Ronald Reagan Washington			
National, DC	718-995-5426	8:00 a.m4:30 p.m.	703-413-1535
Salt Lake City, UT	425-227-1389	7:30 a.m4:00 p.m.	801-325-9600
San Antonio Intl, TX	817-222-5006	8:00 a.m4:30 p.m.	210-805-5507
San Diego Lindbergh Intl, CA	310-725-3300	8:00 a.m4:30 p.m.	619-299-0677
San Francisco Intl, CA	310-643-3200	7:00 a.m3:30 p.m.	650-876-2883
San Juan Intl, PR	404-305-5180	7:30 a.m5:00 p.m.	809-253-8663
Seattle-Tacoma Intl, WA	425-227-1389	7:30 a.m4:00 p.m.	206-214-4600
St. Louis Lambert, MO	816-329-3000	7:30 a.m4:00 p.m.	314-890-1000
Tampa Intl, FL	404-305-5180	7:30 a.m4:00 p.m.	813-371-7700
Ted Stevens Anchorage Intl, AK	907-271-5936	7:30 a.m4:00 p.m.	907-271-2700
Teterboro, NJ	718-995-5426	8:00 a.m4:30 p.m.	201-288-1889
Washington Dulles Intl, DC	718-995-5426	8:00 a.m4:30 p.m.	703-661-6031
West Palm Beach, FL	404-305-5180	8:00 a.m4:30 p.m.	407-683-1867
Westchester Co, NY	718-995-5426	8:00 a.m4:30 p.m.	914-948-6520
		*	

^{*}Facilities can be contacted through the Rgnl Duty Officer during non-business hours.

Air Route Traffic Control Center frequencies and their remoted transmitter sites are listed below for the coverage of this volume. Bold face type indicates high altitude frequencies, light face type indicates low altitude frequencies. To insure unrestricted IFR operations within the high altitude enroute sectors, the use of 720 channel communications equipment (25 kHz channel spacing) is required.

```
RDENVER CENTER - 125.9
                                                            H-1-2-3-4-5-6, L-8-9-10-11-12-13-14-15
  Casper - 135.6 118.925
                                                                                                (KZDV)
  Cherokee - 132.1
  Cheyenne - 134.575 133.175 132.1 125.9
  Laramie - 125.9
  Lusk - 135.6
  Medicine Bow - 133.175 132.1 126.5
  Rock Springs - 128.5
  Sundance - 135.6 133.675
RSALT LAKE CITY CENTER
                                                                            H-1-2-3. L-9-11-12-13-14
  Ashton - 132.4 132.4 128.35 128.35
                                                                                                (KZLC)
  Baker - 128.05
  Big Piney - 128.35 128.35
  Billings - 127.75 127.75
  Blackfoot - 128.35 128.35
  Bliss - 128.55 118.05
  Boise - 118.05
  Bozeman - 132.4 132.4
  Burley - 118.05
  Butte - 133.4 133.4 132.4 132.4
  Cascade - 121.15
  Francis Peak - 127.7
  Glasgow - 126.85 126.85
  Great Falls - 133.4 133.4 132.425
  Green River - 124.35 124.35
  Jackson - 133.25 133.25
  Judith Mountain - 133.4 133.4 126.85 126.85
  Lakeside - 133.4
  Lovell - 133.25 133.25
  Malad City - 126.75
  Miles City - 126.85 126.85
  Missoula - 133.4 119.75 119.75
  Rome - 128.05
  Salmon - 132.4 132.4
  Sheridan - 127.75 127.75
  Squaw Butte - 128.05 121.15
  Thermopolis - 133.25 133.25 124.35 124.35
(R)SEATTLE CENTER
                                                                                  H-1-3, L-1-2-11-13
  Antelope Mountain - 124.85
                                                                                                (KZSE)
  Arcata - 124.85
  Badger Mountain - 127.05 127.05 134.95 134.95
  Beacon Hill - 127.05 127.05 120.3 120.3
  Cottonwood - 123.95 118.55
  Dallesport - 126.6 126.6
  Fort Lawton - 127.05 127.05
  Hoguiam - 128.3
  Horton - 132.075 125.8 121.4
  Kimberly - 135.45
  Klamath Falls - 134.9 127.6
  Lakeside - 123.95
  Lakeview - 135.35 127.6
  Larch Mountain - 128.3 128.3 126.6 126.6
  Marlin - 126 1
  Medford - 135.15 124.85 121.4
  Mohler - 128.45
  Mullan Pass - 128.45
  Nassel - 124.2
  Neah Bay - 125.1 125.1
  Redmond - 121.35 134.9 135.35 128.15
  Rex-Parrett - 121.35
  Scappoose - 124.2 128.15
  Spokane - 123.95 119.225
  Stampede Pass - 134.95 134.95
  The Dalles - 135.45 119.65
  Wallula - 132.6
  Wenatchee - 126.1
```

Whidbey Island - 134.95 134.95 128.5 125.1 125.1 Yakima - 135.525 135.525 132.6 120.3 120.3 118.55

VHF frequencies available at Flight Service Stations and at their remote communication outlets (RCO's) are listed below for the coverage of this volume. Frequencies in bold type are available all altitudes but recommended for use FL180 and above. "T" indicates transmit only and "R" indicates receive only. RCO's available at NAVAID's are listed after the NAVAID name. RCO's not at NAVAID's are listed by name.

BOISE AFSS

ASHTON RCO 123.625

BLISS RCO 122.4

BOISE RCO 122.2 122.6

CASCADE RCO 122.35

CONNERS RCO 122.05

COEUR D'ALENE RCO 122.05

HAILEY RCO 122.4

IDAHO FALLS RCO 122.55

LEWISTON RCO 122.35

MALAD CITY RCO 122.65

MOUNTAIN HOME RCO 122.6

MULLAN PASS RCO 122.15

POCATELLO RCO 122.35

ROME RCO 122.65

SALMON RCO 122.55 SQAW BUTTE RCO 122.45

STANLEY RCO 122.6

TWIN FALLS RCO 122.25

CASPER AFSS

ANTELOPE GAP RCO 122.2

BIG PINEY RCO 122.3

BOYSEN RESERVOIR RCO 122.3

CASPER RCO 122.2 122.4

CHEROKEE RCO 122.4

CHEYENNE RCO 122.3

CODY RCO 122.3

CONVERSE RCO 121.975

CRAZY WOMAN RCO 122.025

DUNIOR RCO 122.6

FORT BRIDGER RCO 122.3

GILLETTE RCO 122.3

JACKSON RCO 122.05

LARAMIE RCO 122.6 MEDICINE BOW RCO 122.5

NEWCASTLE RCO 122.5

RAWLINS RCO 122.2

RIVERTON RCO 122.2

ROCK SPRINGS RCO 122.6

SHERIDAN RCO 122.5

WORLAND RCO 122.4

GREAT FALLS AFSS

BILLINGS 122.55

BOZEMAN RCO 122.5

BUTTE RCO 122.2 122.4

COPPERTOWN RCO 122.65

CUT BANK RCO 122.2

DILLON RCO 122.15

GLASGOW RCO 122.25

GLENDIVE RCO 122.55

GREAT FALLS RCO 122.6

HARLOWTON RCO 122.4 HAVRE RCO 123.65

HELENA RCO 122.55

JUDITH MOUNTAIN RCO 122.2

LAKESIDE RCO 122.5

LEWISTOWN RCO 122.35

LIVINGSTON RCO 122.2

MILES CITY RCO 122.2

MILLER PEAK RCO 122.45

SIDNEY RCO 123.65 TOWER HILL RCO 122.3

WOLF POINT RCO 122.45

YELLOWSTONE RCO 122.45

Mc MINNVILLE AFSS

ASTORIA RCO 122.3

AUGSPURGER RCO 122.3

BEAVER MOUNTAIN RCO 122.4

BURNS RCO 122.5

CAPE BLANCO RCO 122.4

ENTERPRISE RCO 122.5

EUGENE RCO 122.3

KIMBERLY RCO 122.6

KLAMATH FALLS RCO 122.6

LA GRANDE RCO 122.5

LAKEVIEW RCO 122.3

MC MINNVILLE RCO 122.45

MEDFORD RCO 122.65 NEWBERG RCO 122.45

NEWPORT RCO 122.5

NORTH BEND RCO 122.4

ONTARIO RCO 122.3

PENDLETON RCO 122.2

PORTLAND RCO 122.6

REDMOND RCO 122.5

ROSEBURG RCO 122.55

SALEM RCO 122.6

SEXTON SUMMIT RCO 122.5

SUNRIVER RCO 122.3

WALLULA RCO 122.6

SEATTLE AFSS 122.5

BADGER MOUNTAIN RCO 122.3

BELLINGHAM RCO 122.15

BUCKHORN MTN RCO 122.2

ELLENSBURG RCO 122.2

EPHRATA RCO 122.2

HOQUIAM RCO 122.2

JUMP-OFF-JOE RCO 122.4

KELSO RCO 122.55

KELSO-LONGVIEW RCO 122.25

MOSES LAKE RCO 122.4 MT CONSTITUTION RCO 122.3

OCEAN SHORES RCO 122.4

OMAK RCO 122.2

PAINE RCO 122.55

PORT ANGELES RCO 122.6

PULLMAN RCO 122.6

SEATTLE RCO 122.5 123.65

SPOKANE RCO 122.2 122.55 122.65

TATOOSH RCO 122.25

THE DALLES RCO 122.65

VANCOUVER RCO 122.35

WALLA WALLA RCO 122.3

WENATCHEE RCO 122.6

YAKIMA RCO 122.5

FSD0

FLIGHT STANDARDS DISTRICT OFFICES (FSDO)

Below is a list of FSDO's in the area of coverage of this directory. These offices serve the aviation industry and the general public on matters relating to certification and operation of general aviation aircraft. Address letters to Manager, Flight Standards District Office–Federal Aviation Administration.

IDAHO

3295 Elder Street, Suite 350 Airport Plaza Boise, ID 83705

Telephone: 208-334-1238

MONTANA

Helena Airport 2725 Skyway Drive Helena, MT 59601 Telephone: 406-449-5270 1-800-457-9917

OREGON

Portland Flight Standards District Office 3180 NW 229th Avenue Hillsboro, Oregon 97124 Telephone: 503–615–3200 FAX 503–615–3300

WASHINGTON

Seattle FSD0 1601 Lind Ave. S. W. Renton, WA 98057 Telephone: 425–227–2813

Spokane FSDO Felts Field 6133 E. Rutter Avenue Spokane, WA 99212 Telephone: 509-532-2340

ROUTES PREFERRED IFR ROUTES

A system of preferred routes has been established to guide pilots in planning their route of flight, to minimize route changes during the operational phase of flight, and to aid in the efficient orderly management of the air traffic using federal airways. The preferred IFR routes which follow are designed to serve the needs of airspace users and to provide for a systematic flow of air traffic in the major terminal and en route flight environments. Cooperation by all pilots in filing preferred routes will result in fewer traffic delays and will better provide for efficient departure, en route and arrival air traffic service.

The following lists contain preferred IFR routes for the low altitude stratum and the high altitude stratum. The high altitude list is in two sections; the first section showing terminal to terminal routes and the second section showing single direction route segments. Also, on some high altitude routes low altitude airways are included as transition routes.

The following will explain the terms/abbreviations used in the listing:

- 1. Preferred routes beginning/ending with an airway number indicate that the airway essentially overlies the airport and flight are normally cleared directly on the airway.
- 2. Preferred IFR routes beginning/ending with a fix indicate that aircraft may be routed to/from these fixes via a Standard Instrument Departure (SID) route, radar vectors (RV), or a Standard Terminal Arrival Route (STAR).
- 3. Preferred IFR routes for major terminals selected are listed alphabetically under the name of the departure airport. Where several airports are in proximity they are listed under the principal airport and categorized as a metropolitan area; e.g., New York Metro Area.
- 4. Preferred IFR routes used in one direction only for selected segments, irrespective of point of departure or destination, are listed numerically showing the segment fixes and the direction and times effective.
 - 5. Where more than one route is listed the routes have equal priority for use.
 - 6. Official location identifiers are used in the route description for VOR/VORTAC navaids.
 - 7. Intersection names are spelled out.
- 8. Navaid radial and distance fixes (e.g., ARD201113) have been used in the route description in an expediency and intersection names will be assigned as soon as routine processing can be accomplished. Navaid radial (no distance stated) may be used to describe a route to intercept a specified airway (e.g., MIV MIV101 V39); another navaid radial (e.g., UIM UIM255 GSW081); or an intersection (e.g., GSW081 FITCH).
- 9. Where two navaids, an intersection and a navaid, a navaid and a navaid radial and distance point, or any navigable combination of these route descriptions follow in succession, the route is direct.
- 10. The effective times for the routes are in UTC. During periods of daylight saving time effective times will be one hour earlier than indicated. All states observe daylight saving time except Arizona, Puerto Rico and the Virgin Islands. Pilots planning flight between the terminals or route segments listed should file for the appropriate preferred IFR route.
 - 11. (90-170 incl) altitude flight level assignment in hundred of feet.
- 12. The notations "pressurized" and "unpressurized" for certain low altitude preferred routes to Kennedy Airport indicate the preferred route based on aircraft performance.
 - 13. High Altitude Preferred IFR Routes are in effect during the following time periods unless otherwise noted.

Sun	
Mon thru Fri	0701-2259 local time.
Sat	0701-1459 local time.

- 14. Use current SIDs and STARSs for flight planning.
- 15. For high altitude routes, the portion of the routes contained in brackets [] is suggested but optional. The portion of the route outside the brackets will likely be required by the facilities involved.

SPECIAL LOW ALTITUDE DIRECTIONAL ROUTES

		Effective Times
	Route	(UTC)
Low altitude IFR traffic 13000 feet and below	overflying the Portland, OR Area:	
Southbound/southwestbound	OLM V165 UBG	1400-0700
Northbound	UBG V165 OLM	1400-0700
Low Altitude IFR traffic 9000 feet and below or	verflying the Seattle, WA Area:	
Southbound/Southwestbound	V165	1400-0700
Northbound	V165	1400-0700
Eastbound	V004 SEA V002	1400-0700
Low Altitude IFR traffic 10000 to 15000 overfl	ying the Seattle, WA Area:	
Southbound	V165 V495	1400-0700
Southbound	V023 V165 DIGGN V495	1400-0700
Eastbound	V004 SEA V2	1400-0700
Low Altitude IFR traffic 10000 to 15000 overfl	ying the Seattle, WA Area landing in PDX area:	
Southbound	V165 V495 SEA HELNS-STAR	1400-0700
Southbound	V023 V165 DIGGN V495 SEA HELNS-STAR	1400-0700
Low Altitude IFR traffic from the North terminal	ing at McMinnville, OR, Aurora State, OR, or Hillsboro,	OR:
	V165 UBG	1400-0700

PREFERRED IFR ROUTES SPECIAL LOW ALTITUDE DIRECTIONAL ROUTES

Effective

Terminals	Route	Times (UTC)
From the Eugene, OR Area: (props and turbop		4400 0700
Northbound	V481 CV0 V495 UBG	1400-0700
Southbound	V448 0ED	1400–0700
	HIGH ALTITUDE	
Terminals	Route	Effective Times (UTC)
PORTLAND (PDX)		
Burbank (BUR)	J67 LIN J189 AVE FIM	1300-0600
Chicago O'Hare (ORD)	J16 MCW JVL-STAR	0000-2359
Detroit Metro-Wayne Co (DTW)	ODI J34 BAE MKG POLAR-STAR	
Houston (HOU)	(Turbojets) PNH MQP EUVR TEXNN-STAR	
Houston (IAH)	PNH MQP RIICE-STAR	
Long Beach (LGB)	J67 LIN J189 AVE FIM	1300-0600
Los Angeles (LAX)	J67 LIN J189 AVE FIM	1300-0600
Ontario (ONT)	J67 LKV J5 EHF PMD	1300-0600
Santa Ana (SNA) SEATTLE BOEING FLD (BFI)	J67 LIN J189 AVE FIM	1300-0600
Burbank (BUR)	SEA J5 LKV J67 LIN J189 AVE FIM	1300-0600
Long Beach (LGB)	SEA J5 LKV J67 LIN J189 AVE FIM	1300-0600
Los Angeles (LAX)	SEA J5 LKV J67 LIN J189 AVE FIM	1300-0600
Ontario (ONT)	SEA J5 EHF ZIGGY-STAR	1300-0600
Santa Ana (SNA)	SEA J5 LKV J67 LIN J189 AVE FIM	1300-0600
SEATTLE/TACOMA (SEA)	SEA 35 ERV 307 ERV 3105 AVE TRVI	1300-0000
Anchorage (ANC)	(RNAV only) SQUIM AKWAY AKHOG LAIRE AKZOO	
Andridage (ANO)	JOH	
Burbank (BUR)	SUMMA-DP SUMMA J5 LKV J67 LIN J189 AVE	
Bulbalik (BOK)	FIM	1200 0000
Cleveland Metro Area (CLE) (CGF) (BKL)	FIWI	1300-0600
(LNN) (LPR)	BAE J34 GRR HIMEZ-STAR	
Detroit Metro-Wayne Co. (DTW)	J90 HLN J34 BAE MKG POLAR-STAR	
Houston (HOU)	(Turbojets) PNH MQP EUVR TEXNN–STAR	
Houston (IAH)	PNH MQP RIICE-STAR	
Kennedy (JFK)	J90 HLN J34 ODI J30 J90 OBK J584 CRL J554	
Nomical (311)	JHW J70 LVZ LENDY-STAR	
Long Beach (LGB)	SUMMA-DP SUMMA J5 LKV J67 LIN J189 AVE	
Long Deach (Lab)	FIM	1300-0600
Los Angeles (LAX)	SUMMA-DP SUMMA J5 LKV J67 LIN J189 AVE	1300-0000
LOS AIIGCICS (LAX)		1300-0600
Newark (EWR)	FIM J90 ABR J70 GEP DLL J34 CRL J584 SLT	1300-0600
Newark (LWIN)	FOM-STAR	
Ontario (ONT)	SUMMA-DP SUMMA J5 EHF PMD	1200 0000
	SUMMA-DP SUMMA J5 EHF PMDSUMMA-DP SUMMA J5 LKV J67 LIN J189 AVE	1300-0600
Santa Ana (SNA)		4000 0000
CDOVANE (CEC)	FIM	1300-0600
SPOKANE (GEG)	(FLOAD and above Todaylate) to lain DES 143	
Chicago O'Hare (ORD)	(FL240 and above, Turbojets) to join DPR J16	0000 0050
	MCW JVL-STAR	0000–2359

O-ROUTES REGULATORY

Q1, Q3, Q5, Q7, Q9 and Q11 are preferred single direction (Southbound) Q routes; flight planning Northbound not authorized.

Q routes are RNAV routes that require the use of GNSS or DME/DME/IRU RNAV, unless otherwise indicated. Please note that this section does not apply to Q routes in the Gulf of Mexico. Gulf of Mexico Q routes are explained in the Southeast and South Central A/FD volumes. Q routes listed in this A/FD volume have at least part of one of their leg segments within this volume's area of coverage.

GNSS and DME/DME/IRU RNAV operations are authorized along Q routes at FL 180 and above. GNSS and DME/DME/IRU RNAV MEAs will only be published if above FL 180.

DME facilities that have been assessed for RNAV operations are listed below. Q routes with no DME facilities listed are limited to GNSS RNAV operations only. Those routes will have an enroute chart note "GNSS REQUIRED".

Route	Segment	DME
Q1	ELMAA-ERAVE	BTG, OLM, HQM, HUH, UBG
	ERAVE-EASON	BTG, OLM, HQM, HUH, LTJ, CVO, DSD, OED, UBG, ONP, EUG
	EASON-EBINY	CVO, DSD, OED, BTG, UBG, ONP, EUG, LMT
	EBINY-ENVIE	CVO, OED, EUG, LMT, RBL, ENI, ONP, FJS
	ENVIE-ETCHY	OED, PYE, OAK, LIN, ECA, LMT, RBL, ENI, SAC, FJS
00	ETCHY-POINT REYES	LIN, ECA, RBL, ENI, SAC, OAK
Q2	BOILE-HEDVI	HEC, PDZ, OCN, PMD, LAX, RZS, IPL, TRM, PKE, BLH, EED, BZA, GBN, PXR
	HEDVI-HOBOL	BZA, GBN, BLH, EED, PXR, IPL, TFD, DRK, TUS
	HOBOL-ITUCO	TFD, GBN, BLH, PXR, TUS, CIE, SSO
03	ITUCO-NEWMAN	EWM, TFD, PXR, CIE, SSO, TUS, TCS
Q3	FEPOT-FAMUK	OLM, TOU, HQM, CVO, BTG, DSD, LTJ, UBG, ONP, EUG
	FAMUK-FRFLY	BTG, DSD, OED, CVO, EUG, ONP, UBG, RBL, LMT
	FRFLY-FINER	OED, EUG, RBL, LMT, ENI, CVO, FJS
	FINER-FOWND	OED, PYE, ECA, LIN, OAK, ENI, RBL, LMT, SAC, FJS
04	FOWND-POINT REYES	LIN, ECA, PYE, RBL, SAC, ENI
Q4	BOILE-HEDVI	HEC, PDZ, OCN, PMD, LAX, RZS, IPL, TRM, PKE, BLH, EED, BZA, GBN, PXR EED, BLH, BZA, GBN, TRM, IPL, TFD
	HEDVI-SCOLE SCOLE-SPTFR	EED, BLH, BZA, GBN, TRM, IPL, TFD EED, BLH, BZA, GBN, TRM, IPL, TFD
	SPTFR-ZEBOL	EED, IPL, BZA, GBN, TRM, IPL, TID
	ZEBOL-SKTTR	PXR, BLH, BZA, GBN, TFD, TUS, SSO, CIE, SVC, TCS
	SKTTR-EL PASO	EWM, CUS, SVC, TCS, SSO, CIE, ELP, DMN, CME
Q5	HAROB-HISKU	OLM, ONP, CVO, EUG, HQM, UBG, BTG, LTJ, DSD, HUH
ŲΣ	HISKU-HARPR	ONP, CVO, EUG, LTJ, DSD, UBG, BTG, RBL, OED, LMT, FJS, LKV
	HARPR-HOMEG	CVO, EUG, OED, RBL, LMT, ENI, FJS, LKV
	HOMEG-HUPTU	SAC, PYE, LIN, OAK, ECA, LMT, RBL, ENI, OED, FJS
	HUPTU-STIKM	OAK, ECA, PYE, LIN, SAC, ENI, RBL
Q7	JINMO-JOGEN	CVO, HQM, LTJ, UBG, BTG, ONP, IMB, EUG, OLM, DSD, YKM, PDT, SEA
Ψ,	JOGEN-JUNEJ	LTJ, IMB, UBG, EUG, CVO, RBL, LMT, FMG, DSD, LKV, OED, BTG
	JUNEJ-JAGWA	RBL, LMT, FMG, LIN, SAC, ECA, ENI, MOD, SWR, OAK, LKV, CZQ, AVE, SNS
	JAGWA-AVENAL	OAK, MOD, ECA, EHF, PRB, AVE, SNS, CZQ
Q9	SUMMA-SMIGE	OLM, UBG, SEA, YKM, BTG, ONP, IMB, HQM, PDT, EUG, LTJ, CVO, DSD, OED,
-		EPH, MWH
	SMIGE-SUNBE	IMB, UBG, EUG, IMB, RBL, LMT, FMG, SAC, OED, CVO, LKV, DSD, BTG
	SUNBE-REBRG	RBL, LMT, FMG, SAC, ECA, MVA, CZQ, OAK, EHF, PMD, LKV, LIN, MOD, AVE, OED,
		SWR
	REBRG-DERBB	CZQ, PMD, EHF, LAX, RZS, AVE, MOD, ECA
Q11	PAAGE-PAWLI	EPH, UBG, CVO, EUG, HQM, YKM, OLM, PDT, BTG, ONP, IMB, LTJ, DSD, LKV,
-		OED, SEA
	PAWLI-PITVE	EUG, FMG, SAC, IMB, LKV, OED, DSD, RBL, LMT, CVO, REO
	PITVE-PUSHH	FMG, SAC, LIN, SWR, MOD, OAL, RBL, LKV, LMT, MVA, CZQ
	PUSHH-LOS ANGELES	SAC, ECA, FMG, LIN, OAL, MOD, EHF, LAX, PMD, PDZ, HEC, OCN, CZQ, AVE, RZS
Q13	All segments	None; GNSS required
Q15	All segments	None; GNSS required
Q19	PLESS-NASHVILLE	ENL, GQO, PXV, BNA, IIU, FAM, BWG, CSX
Q20	CORONA-HONDS	CNX, ABQ, ACH, ONM, TXO, LVS, TCC, CME
-	HONDS-UNNOS	CNX, INK, CME, TXO, TCC
	UNNOS-FUSCO	FST, ACH, INK, CME, SJT, TXO, TCC
	FUSCO-JUNCTION	ABI, CWK, CSI, INK, LZZ, JCT, SJT, STV, FST
Q21	JONEZ-RAZORBACK	BYP, EOS, TUL, TXK, ADM, RZC, OKM
Q22	GUSTI-OYSTY	AEX, DAS, MCB, LLA, BTR, LCH, HRV, LFT, LEV
	OYSTY-ACMES	RQR, GCV, MCB, BTR, PCU, GPT, HRV, LEV, SJI
	ACMES-CATLN	SJI, MGM, MCB, BFM, GPT, GCV, HRV, CEW, MVC, PCU, MEI
Q23	FORT SMITH-RAZORBACK	OKM, RZC, EOS, TUL

240 Q-ROUTES

Route	Segment	DME
Q24	LAKE CHARLES-BATON	AEX, DAS, LCH, MCB, LFT, BTR
	ROUGE BATON ROUGE-IRUBE	AEX, LEV, MCB, LCH, RQR, HRV, BTR, GCV, MCB, PCU, SJI, LBY
	IRUBE-PAYTN	GCV, MCB, JYU, PCU, MEI, HRV, CEW, SJI
Q25	MEEOW-WALNUT RIDGE	ELD, MEM, LIT, FAM, RZC
	WALNUT RIDGE-WLSUN	MEM, STL, BWG, PXV, ENL, FAM, ARG, BNA, CSX, TTH
	WLSUN-POCKET CITY	BWG, PXV, ENL, BNA, TTH
Q26	WALNUT RIDGE-DEVAC	LIT, JKS,GQO, MEM, BNA, FAM, ARG, DYR, VUZ, RMG
Q27 Q28	FORT SMITH-ZALDA GRAZN-PYRMD	OKM, SGF, RZC, EOS, TUL EIC, LIT, ELD, OKM, TXK
¥	PYRMD-HAKAT	ARG, LIT, FAM, ELD, SGF, RZC, MEM, TXK
	HAKAT-ESTEE	ARG, LIT, FAM, SGF, MEM
	ESTEE-POCKET CITY	ARG, CSX, FAM, PXV, ENL, MEM, STL, BWG, TTH, BNA
Q29	HARES-MEMPHIS	MEM, ARG, LIT, JAN, ELD, SQS
	MEMPHIS-SIDAE SIDAE-POCKET CITY	MEM, PXV, BNA, BWG, ARG, ENL PXV, TTH, BWG, ENL
030	SIDON-VULCAN	GLH, MEM, VUZ, JAN, JYU, MEI, MGM, SQS, RMG
Q31	DHART-JODOX	SQS, LIT, TXK
	JODOX-MARVELL	SQS, LIT, ELD, MEM, ARG
	MARVELL-TIIDE	ARG, BWG, PXV, FAM, LIT, MEM, ENL, TTH
Q32	TIIDE-POCKET CITY	BWG, PXV, ENL, TTH
Ų32	EL DORADO-GAGLE GAGLE-CRAMM	AEX, JAN, MEM, SQS, SWB, ELD, LIT, TXK JAN, SQS, MEM, ARG, VUZ, BNA, LIT
	CRAMM-NASHVILLE	BWG, MEM, VUZ, BNA, GQO
	NASHVILLE-SWAPP	BWG, IIU, PXV, VXV, BNA, GQO
Q33	DHART-LITTLE ROCK	AEX, ELD, LIT, TXK, SWB, ARG, MEM, SQS
024	LITTLE ROCK-PROWL	ELD, SGF, FAM, LIT, ARG, MEM, RZC, CSX, STL
Q34	TEXARKANA-MATIE MATIE-MEMPHIS	LIT, SWB, TXK, BYP, EIC, ELD, SQS LIT, ARG, MEM, ELD, SQS
	MEMPHIS-SWAPP	BWG, ARG, MEM, MKL, SQS,PXV, BNA, GQO, IIU, VXV
Q35	KIMBERLY-NEERO	LTJ, PDT, DSD, IMB, LKV, BOI, REO, BAM, SDO
	NEERO-WINEN	BQU, SDO, BAM, REO, BVL, ILC, DTA, ELY, CDC, MLF, BCE
	WINEN-CORKR	CDC, BCE, BLD, ILC, MLF, TBC, PGS, INW, DRK
036	CORKR-DRAKE RAZORBACK-TWITS	TBC, BCE, BLD, DRK, PGS, FLG, GCN, INW, TFD RZC, MEM, SGF, BUM, TUL, EOS, FAM, ARG, LIT
Q 50	TWITS-DEPEC	MEM, GQO, BNA, BWG, FAM, ARG, PXV, IIU
	DEPEC-NASHVILLE	GQO, BWG, BNA, PXV, IIU
	NASHVILLE-SWAPP	VXV, BWG, BNA, GQO, PXV, IIU
Q38	ROKIT-INCIN	DAS, LCH, SWB, IAH, LFK, HUB, AEX
	INCIN-LAREY LAREY-BESOM	JAN, MCB, SWB, AEX JAN, JYU, MEI, SQS, VUZ
040	ALEXANDRIA-DOOMS	AEX, SWB, LCH, JAN, HEZ, MCB
	DOOMS-WINAP	JAN, SQS, MEI, MCB
	WINAP-MISLE	MEI, VUZ, JYU
Q42	KIRKSVILLE-STRUK	CID, IOW, UIN, LMN, IRK, BDF, STL, DEC, ENL, CSX
	STRUK-DANVILLE	ENL, IOW, UIN, BDF, DEC, STL, CSX, SPI, TTH, BVT, JOT, VHP, OXI, ENL, OKK,
	DANVILLE-MUNCIE	OBK, GIJ, FWA, GSH, IRK GIJ, SPI, BDF, OBK, OKK, VHP, BVT, DEC, GSH, FWA, JOT, TTH, OXI, ROD, FLM
	MUNCIE-HIDON	FLM, VHP, GSH, TTH, GIJ, OKK, FWA, ROD, OXI, CRL, GSH, APE, DJB, DXO, HNN,
		AIR, HVQ, CXR, EWC
	HIDON-BUBAA	AIR, APE, HNN, CXR, HVQ, EWC, DJB
	BUBAA-PSYKO	AIR, APE, DJB, CXR, HNN, EWC, SLT, CSN, JHW, ETG, PSB
	PSYKO-BRNAN BRNAN-MAALS	PSB, JHW, EWC, AIR, ETG, CSN, EMI, SLT EMI, SLT, CSN, EWC, PSB, ETG, SAX, RBV, HNK, HUO, SIE
	MAALS-SUZIE	ETG, EMI, CSN, HUO, SIE, JFK, PSB, SLT, HNK
	SUZIE-EAST TEXAS	JFK, EMI, PSB, SLT, HNK, SIE, RBV, SAX, HUO, CYN
	EAST TEXAS-ELIOT	HUO, RBV, EMI, CYN, SAX, JFK, PSB, HNK
Q104	DEFUN-HEVVN	PIE, PZD, CRG, SZW, TAY, JYU, CEW, MGM, OTK, CRG
	HEVVN-PLYER PLYER-SWABE	PIE, ORL, OMN, SRQ, TAY, LAL, CRG, SZW, PZD PIE, ORL, OMN, SRQ, TAY
	SWABE-ST PETERSBURG	LAL, ORL, OMN, SRQ, PHK, PIE
	ST PETERSBURG-	PHK, PBI, SRQ, PIE, VRB, ORL, FLL, LAL, OMN
	CYPRESS	

Route	Segment	DME
Q106	SMELZ-BULZI	LAL, ORL, OMN, PHK, PIE, CRG, VRB, TAY, OTK, PZD, AMG, SZW
	BULZI-DRABK	AMG, PZD, TAY, CRG, SZW, MGM, OTK, JYU, CEW, SJI
	DRABK-GADAY	MGM, PZD, OTK, JYU, SZW, CEW, SJI
Q108	GADAY-CLAWZ	MGM, SJI, CEW, JYU, PZD, OTK, MCN, SZW, LGC, TAY, AMG
Q110	THNDR-JAYMC	SRQ, VRB, PHK, PIE, LAL, VKZ, ORL, PBI
	JAYMC-RVERO	VKZ, VRB, PHK, PIE, LAL, SRQ, ORL, OMN, PBI, DHP
	RVERO-KPASA	OMN, PIE, PBI, SRQ, ORL, LAL
	KPASA-BRUTS	SRQ, VRB, ORL, PHK, TAY, PIE, OMN, OTK, LAL, CRG, SZW, AMG
	BRUTS-GULFR	OMN, AMG, CRG, SZW, PIE, TAY, PZD, OTK
	GULFR-FEONA	TAY, MCN, PZD, CRG, OTK, SZW, AMG, MCN, ATL, MGM
Q112	DEFUN-HEVVN	PIE, OTK, CRG, OMN, LAL, SZW, SRQ, ORL, VRB
	HEVVN-INPIN	JYU, PZD, CEW, SZW, MGM, OTK, TAY, AMG, PIE, CRG
Q116	KPASA-BRUTS	SRQ, VRB, ORL, PHK, TAY, PIE, OMN, OTK, LAL, CRG, SZW, AMG
	BRUTS-GULFR	OMN, AMG, CRG, TAY, LAL, PZD, SZW, OTK
	GULFR-CEEYA	MCN, AMG, PZD, OTK, SZW, TAY
Q118	KPASA-BRUTS	SRQ, VRB, ORL, PHK, TAY, PIE, OMN, OTK, LAL, CRG, SZW, AMG
	BRUTS-LENIE	OMN, AMG, CRG, TAY, LAL, PZD, SZW, OTK, MCN
Q501	VIXIS-GOPHER	ECK, FNT, APN, SSM, GRR, MBL, SAW, BAE, MNM, DLL, AUW, ODI, STE, FGT, EAU,
		DLH, GEP, BRD, MCW, MSP, ASP, TVC, GRB, RWF
	GOPHER-SOBME	FGT, BRD, MCW, GEP, ABR, FAR, DLH, ODI, RWF, FSD
Q502	KENPA-GOPHER	SSM, FNT, ECK, APN, SAW, GRB, BAE, DLL, AUW, ODI, FGT, DLH, EAU, MCW,
		MSP, MNM, ASP, TVC, GEP, RWF, BRD
	GOPHER-SOBME	FGT, DLH, ODI, MCW, ABR, FAR, MSP, GEP, RWF, FSD, BRD
Q504	NOTAP-CESNA	SSM, ECK, APN, GLR, PLN, ISQ, MNM, DLL, RHI, DLH, GEP, FGT, ODI, ASP, TVC,
		SAW, GRB, BRD
	CESNA-HEMDI	ODI, GEP, DLH, FGT, RWF, FAR, AXN, FSD, ABR, DLL, BRD
Q505	OMAGA-RIMBE	SSM, TVC, ASP, SAW, GRB
	RIMBE-CESNA	SSM, RHI, DLL, DLH, GEP, FGT, TVC, SAW, GRB, BRD, ODI
	CESNA-HEMDI	GEP, DLH, FGT, RWF, FAR, AXN, FSD, ABR, BRD, ODI, GRB
*Denotes C	ritical DME Facility	

HIGH ALTITUDE REDESIGN (HAR) PHASE 1 RNAV ROUTING

RNAV Routing Pitch and Catch Points

The purpose of this section of the Special High Altitude Routes is to present user routing options for flight within the initial HAR Phase I expansion airspace. Users are able to fly user-preferred routes, referred to as non-restrictive routing (NRR), between specific fixes described by pitch (entry into) and catch (exit out of) fixes in the HAR airspace. Pitch points indicate an end of departure procedures, preferred IFR routings, or other established routing programs where a flight can begin a segment of NRR. The catch point indicates where a flight ends a segment of NRR and joins published arrival procedures, preferred IFR routing, or other established routing programs.

The HAR Phase I expansion airspace is defined as that airspace at and above FL 350 in fourteen of the western and southern Air Route Traffic Control Centers (ARTCCs). The airspace includes Minneapolis (ZMP), Chicago (ZAU), Kansas City (ZKC), Denver (ZDV), Salt Lake City (ZLC), Oakland (ZOA), Seattle Centers (ZSE), Los Angeles (ZLA), Albuquerque (ZAB), Fort Worth (ZFW), Memphis (ZME), and Houston (ZHU). Jacksonville (ZJX) and Miami (ZMA) are included for east-west routes only.

To develop a flight plan, select pitch and catch points based upon your desired route across the Phase I airspace. Filing requirements to pitch points, and from catch points, remain unchanged from current procedures. For the portion of the route between the pitch and catch points, non-restrictive routing is permitted.

Where pitch points for a specific airport are not identified, aircraft should file an appropriate departure procedure (DP), or any other user preferred routing prior to the NRR portion of their routing. Where catch points for a specific airport are not identified aircraft should file, after the NRR portion of their routing, an appropriate arrival procedure or other user preferred routing to their destination.

Additionally, information concerning the location and schedule of Special Use Airspace (SUA) and Air Traffic Control Assigned Airspace (ATCAA) can be found on the Web Site: http://sua.faa.gov/sua/Welcome.do. ATCAA refers to airspace in the high altitude structure supporting military and other special operations. Users are encouraged to file around these areas when they are scheduled to be active, thereby avoiding unplanned reroutes around them.

In conjunction with the HAR program RNAV routes have been established to provide for a systematic flow of air traffic in specific portions of the enroute flight environment. The designator for these RNAV routes begin with the letter Q, for example, Q-501. Where those routes aid in the efficient orderly management of air traffic they will be published as preferred IFR routes.

High Altitude Redesign (HAR) Phase One Expansion Airspace

HAR expansion airspace may pitch vertical pitch line, or at the fixes

Except as noted, flights entering at the airspace boundary, at the

west longitude to the ZHU southern boundary. 90 degrees west longitude, the 90 degrees south to the ZHU boundary. Then west to except between PMM and GSH, then boundary to the ZME/ZID boundary west longitude from the ZMP/ZAU following the ZME east boundary Vertical Pitch Line: 86 degrees No westbound traffic between PMM and GSH. ZNZ 787 ZDC ZNZ ZIMA ZOB E ZJX IN DEW ZID SSH SWT Sovido Boydo W 98 W 06 GEP CESNA ZME S. isted on the following page. ZKC ZHD ZFW ZMP VOZ ZAB ZLC ZLA ZSE ZOA

NW, 22 OCT 2009 to 17 DEC 2009

HAR Special High Altitude Pitch (entry) Points for Nonrestrictive Routing for Airports **Located Outside HAR Phase I Expansion Airspace**

Westbound traffic originating outside of HAR airspace entering ZMP, ZAU, ZKC and ZME can begin non-restrictive routing over any of the following pitch points (listed from north to south):

DLH, CESNA, GEP, BAE, MKG, GRR, PMM, GSH, CADIZ, FWA, VHP, FLM, IIU, PXV, SGF, RZC, BNA, SALMS, VUZ, BOYDD, MIF

Traffic originating outside of HAR airspace may also begin Nonrestrictive Routing upon crossing the pitch line depicted on the associated graphic.

HAR Special High Altitude Pitch Points for Airports Located Within (below) **HAR Phase I Expansion Airspace**

This section lists pitch points for airports within the HAR Phase I expansion airspace.

Albuquerque ABQ, GUP, HANOS or ZUN

Austin ABI, FUZ, JCT, MQP, NAVYS, SJT or TNV

Boca Raton, FL TBIRD KPASA 0118 LENIE

TBIRD KPASA 0116 CEEYA TBIRD KPASA 0110 FEONA

TBIRD SMELZ Q106 BULZI TBIRD SMELZ Q106 GADAY

GMN, MARKS

Santa Monica and Van Nuys DAG LAS

HEC EED PMD BLH

Chicago Terminal Area IOW, PLL275065, MZV or BAE

Dallas/Fort Worth Terminal Area ABI, LBB, GTH, CDS, MRMAC, IRW, TUL, MLC, TXK

ELD. SWB

Aircraft destined the Chicago terminal area Except MDW

EAKER MIDEE BDF BRADFORD-STAR

MLC J105 SGF BDF BRADFORD-STAR

Denver Terminal Area PUB, DVC, DBL, RLG, EKR, LAR, MBW, CYS, BFF, HANKI, NATTI, ASHBY, BELKE,

CABET, WEEDS, OR BINKE

Fort Lauderdale (or) Fort Lauderdale Executive

Rurhank includes

THNDR KPASA Q118 LENIE

THNDR KPASA Q116 CEEYA

THNDR KPASA Q110 FEONA

THNDR SMELZ Q106 GADAY

THNDR SMELZ Q106 BULZI

Houston Bush LIT, EMG, MLC, JCT

Aircraft destined Atlanta Terminal Area LCH Q24 PAYTN HONIE-RNAV STAR

Aircraft joining J37 to the northeast, BPT GUSTI Q22 CATLN

Aircraft joining J42 to the northeast, ELD Q32 J42

LIT, EMG, MLC, JCT, Houston Hobby

Aircraft joining J42 to the northeast, ELD Q32 J42

Jacksonville, FL

Kansas City Terminal Area TIFTO, CATTS or KENTN

GMN. RZS Los Angeles, includes Ontario or

DAG LAS or TRM EED

or TRM PKE

DOBNE, MOSBI, NICLE, TRALR or ZELOT Las Vegas

GMN SNS, EHF, LANDO Long Beach includes

Orange County

TRM PKE or

TRM EED

BNA, HAAWK, SALMS or SQS Memphis Miami Terminal Area WINCO KPASA Q118 LENIE

WINCO KPASA Q116 CEEYA

WINCO KPASA Q110 FEONA

WINCO SMELZ Q106 GADAY

WINCO SMELZ 0106 BULZI

Milwaukee GREAS

Minneapolis Terminal Area* ONL, ABR, FAR, OBH, OVR, FOD

New Orleans Terminal Area AEX, MEI, SQS, KAPLN Orlando Terminal Area WEBBS BRUTS Q118 LENIE

> or WEBBS GULFR Q116 CEEYA

WEBBS BULZI Q106 GADAY

WEBBS FEONA

or

WEBBS BULZI

Palm Beach, FL TBIRD KPASA Q118 LENIE

TBIRD KPASA Q116 CEEYA

TBIRD KPASA Q110 FEONA

TBIRD SMELZ Q106 BULZI TBIRD SMELZ Q106 GADAY

TRM JOTNU BLD Palm Springs

or

TRM EED TRM PKE

Phoenix CHILY, CIE, CULTS, RSK, DOVEE, GCN, MESSI, SJN, DRYHT or MOHAK

Portland, OR PDT, TIMEE Salt Lake City HVE, DTA, MLF, BCE, OAL, MTU, BVL, OCS, TWF, DBS, BPI

TCH J56 CHE TCH J173 EKR

Saint Louis VIH. MAP. MYERZ, MCM

HLV MCI

FUZ, SJT, MQP, ABI San Antonio Terminal Area

Aircraft North of LFK, LFK Aircraft South of HUB, ELA

Aircraft South of LFK and North of HUB LCH

San Diego TRM FFD

TRM PKE

TRM JOTNU BLD

San Francisco Bay Area GALLI, INSLO, HAROL JSICA Oakland GALLI, INSLO, HAROL JSICA

San Jose GALLI or INSLO

Seattle BLUIT

Southwest Florida Airports JOCKS KPASA Q118 LENIE

(RSW/FMY)

JOCKS KPASA 0116 CEEYA

JOCKS KPASA Q110 FEONA

JOCKS SMELZ Q106 GADAY

JOCKS SMELZ Q106 BULZI

Tampa Terminal Area FEONA, BULZI

> or BRUTS 0118 LENIE

GULFR Q116 CEEYA or BULZI Q106 GADAY

Catch Points for Airports Located Outside HAR Phase I Expansion Airspace

This section lists exit points for aircraft destined to specific destinations which are outside the HAR Phase I airspace.

Atlanta Terminal Area

Aircraft through ZME airspace from ZKC airspace east of FAM, Pless Q19 BNA

Aircraft through ZME airspace from ZKC airspace west of FAM, ARG Q26 DEVAC

MEM

Aircraft through ZME airspace from ZID airspace west of a line from VHP to

Aircraft through ZME airspace from ZID airspace east of a line from VHP to

BWG, BWG

Aircraft through ZME airspace from ZFW airspace, MEM

MEI HONIE (RNAV)-STAR

PATYN HONIE (RNAV)-STAR

^{*}MSP area departures with destinations east of 93 degrees west longitude via preferred IFR routing.

Baltimore–Washington* GIJ, GEP, FLM, IIU, BAE, VHP, WHETT, BNA or VUZ

Boston* GEP, CRL, ECK, IIU, BNA or VUZ

Buffalo* GEP, CRL

Hartford Bradley* GEP, CRL

Canton-Akron* GIJ, VHP, GEP

Charlotte BNA, VUZ

Cincinnati Terminal Area BNA, PXV

or

Aircraft north of SLC, JOT

or

Aircraft over or south of SLC, ENL

or

SLC or SFO departures, ENL, JOT

Cleveland Terminal Area* OBK

Detroit Terminal Area BAE MKG POLAR-STAR

or

VHP FWA MIZAR-STAR

Detroit Young VHP FWA

or

LAN SPRTN-STAR

Indianapolis Terminal Area BIB, SPI, JOT
Louisville ENL. MEM

Newark* GEP, VHP, FLM, IIU, BNA, VUZ

or

IOW GIJ J554 CRL J584 SLT FQM

New York Kennedy* GEP, VHP, FLM, IIU, BNA, VUZ

or

DBQ J94 PMM J70 LVZ LENDY-STAR

New York LaGuardia* GJJ, GEP, VHP, BAE, FLM, IIU, BNA, VUZ
Philadelphia Terminal Area* GJJ, GEP, VHP, BAE, WHETT, BNA, VUZ

Pittsburgh Terminal Area* VHP, GIJ, BAE, GEP
Pontiac LFD, LAN, VHP, FWA, GEP

Providence JHW, HEMDI, CESNA, GEP, GRB, TVC, ASP, VHP, IIU, BNA, VUZ

 Raleigh-Durham
 FLM, IIU, BNA, VUZ

 Toronto Terminal Area
 ECK, SVM, SSM, GEP

 Teterboro*
 GEP, VHP, CRL, BNA, VUZ

Washington Dulles/National* GIJ, GEP, FLM, IIU, BAE, VHP, WHETT, BNA, VUZ

White Plains* GEP, VHP, CRL, FLM, IIU, BNA, VUZ

Willow Run* LAN, LFD, VHP, FWA, GEP

*Eastbound aircraft over flying ZMP center airspace entering Toronto center airspace, file direct SSM or via J63, J522, Q505, Q504, Q502, Q501

or

Entering ZAU or ZOB airspace from north of DPR J16 MCW, GEP

or

Entering ZAU or ZOB airspace from or south of DPR J16 MCW, CRL.

248

HIGH ALTITUDE REDESIGN (HAR) PHASE 1 RNAV ROUTING

Catch Points for Airports Located Within (below) HAR Phase I Expansion Airspace

This section lists exit points for aircraft destined to airports which are below HAR Phase I airspace.

Albuquerque Terminal Area CURLY CURLY-STAR

or

ESPAN FRIHO-STAR

LAVAN LAVAN-STAR

FTI FRIHO-STAR

or

MIERA MIERA-STAR

Aircraft west of a north-south line at LFK, BLEWE Austin Terminal Area

Aircraft east of a north-south line at LFK,IDU

or

LLO

Boca Raton, FI CEW DEFUN Q112 INPIN SHDAY (RNAV)-STAR

Aircraft through ZHU remain south of ZME and ZTL airspace

DEFUN 0112 INPIN SHDAY (RNAV)-STAR

Aircraft through ZHU remain south of ZME and ZTL airspace

SZW INPIN SHDAY (RNAV)-STAR

Chicago Midway CVA MOTIF-STAR

PIA MOTIF-STAR

DBQ CVA MOTIF-STAR

LMN MOTIF-STAR

Chicago O'Hare Terminal Area GEP DLL MSN JVL JANESVILLE-STAR

TVC PULLMAN-STAR

FOD DBQ JVL JANESVILLE-STAR

MCW JANESVILLE-STAR

GCK IRK BRADFORD-STAR

Dallas/Fort Worth Terminal Area IRW, LOSZY, FSM, LIT, SQS, MLU, AEX, JUMBO, TQA, TURKI, HEATR

Aircraft through ZME airspace from north and west of PXV, RZC, Q23 FSM

Aircraft through ZME airspace from east of PXV, PXV Q25 MEEOW

Aircraft through ZME airspace from J6 down to, but not including J52, LIT, SQS

Aircraft through ZME airspace from J52 and south of J52, SQS

Denver Terminal Area OATHE DANDD-STAR

HGO QUAIL-STAR

LOPEC-STAR

ALS LARKS-STAR

HBU POWDR-STAR

EKR TOMSN-STAR

CHE TOMSN-STAR

BFF LANDR-STAR

LBF SAYGE-STAR

HCT SAYGE-STAR

RSK LARKS-STAR

LAA QUAIL-STAR

GCK J154 RYLIE DANDD-STAR

OCS J154 ALPOE RAMMS-STAR

YANKI J114 SNY LANDR-STAR

Aircraft filed BIL or east, MBW RAMMS-STAR

Ft Lauderdale or CEW DEFUN Q104 PIE SWAGS (RNAV)-STAR

Ft Lauderdale Executive Aircraft through ZHU airspace remain south ZME and ZTL

airspace

SZW HEVVN 0104 PIE SWAGS (RNAV)-STAR

Houston Bush CRP. CVE. LLO. LUKIY. SAT

Aircraft south and east of LLA, LLA

MISLE Q40 AEX

Aircraft north and east of SJI, SJI

Aircraft east of PXV. PXV 031 DHART SWB

Aircraft north and west of PXV, PROWL Q33 DHART SWB

Houston Hobby CRP, ELLVR, SAT, SWB

Aircraft south and east of GIRLY, GIRLY

Aircraft north and east of SJI, SJI

BESOM Q38 ROKIT ROKIT-STAR

Aircraft east of PXV, PXV Q29 HARES SWB

Aircraft north and west of PXV, PROWL Q33 DHART SWB

Jacksonville **GADAY ZOOSS TAY**

Aircraft through ZHU airspace remain south of ZME and ZTL

ZOOSS TAY

250 HIGH ALTITUDE REDESIGN (HAR) PHASE 1 RNAV ROUTING

John Wavne-Orange County HEC. PGS. BLD

Aircraft south of TBC from ZAB airspace, HIPPI

Kansas City Terminal Area LMN BRAYMER-STAR

PWE ROBINSON-STAR

EMP JHAWK-STAR

Las Vegas DILCO, LIDAT, IGM

Aircraft over PGA or north of PGA KSINO

Aircraft south of PGA PGS LYNSY

Los Angeles Terminal Area Aircraft North of TBC, HEC, PGS

Aircraft South of TBC from ZAB airspace, HIPPI,

MESSI

CEW DEFUN Q104 CYY DEEDS (RNAV)-STAR Miami Terminal Area

Aircraft through ZHU airspace remain south ZME and ZTL airspace

SZW HEVVN Q104 CYY DEEDS (RNAV)-STAR

Minneapolis Terminal Area Aircraft from north, west, south,

FAR GOPHER-STAR

or

RWF SKETR-STAR or ALO KASPR-STAR

BRD GOPHER-STAR

BAE EAU CLAIRE-STAR

or

FOD TWOLF-STAR

Memphis Terminal Area ARG, BWG, FSM, PXV, LIT, RZC, SQS, VUZ, BNA, GQO, ELD

Naples, FL CEW DEFUN 0104 PLYER PIKKR (RNAV)-STAR

Aircraft through ZHU AIRSPACE remain south of ZME and ZTL

airspace

SZW HEVVN 0104 PLYER PIKKR (RNAV)-STAR

Nashville CCT, GHM, GUITR, TINGS, VOLLS New Orleans Terminal Area BLUEZ, GPT, LCH, MCB, TBD, FATSO

Oakland II A

or

KATTS PAMMY

Aircraft over or south of a line ILC J16 DVC

REANA KATTS PAMMY

Aircraft from north of ILC, JOPER PAMMY

KATTS PAMMY

Aircraft over or south of ILC, REANA KATTS PAMMY

Orlando Terminal Area GADAY Q108 CLAWZ LEESE-STAR

Aircraft through ZHU airspace remain south of ZME/ZTL

airspace

OTK LEESE-STAR

Palm Beach, FL CEW DEFUN Q112 INPIN GULLO (RNAV)-STAR

Aircraft through ZHU airspace remain south of ZME and ZTL

airspace

or

SZW INPIN GULLO (RNAV)-STAR

Phoenix CORKR DRK

or

Aircraft from ZDV airspace,

GUP

or

Aircraft from ZAB airspace,

ZUN, MOHAK, SSO

Ω

VYLLA TUS

Phoenix Satellites FLG, SSO, MOHAK

or

VYLLA, TUS

Portland, OR Terminal Area ARNIT BONVL-STAR

or LARNO BONVL-STAR

or

MOXEE MOXEE-STAR

St. Louis Terminal Area SGF TRAKE-STAR

or

BUM TRAKE-STAR or ANX TRAKE-STAR

OI

LMN IRK RIVRS-STAR or RBS VANDALIA-STAR

Salt Lake City Terminal Area JNC J12 HELPR SPANE-STAR

10

EKR MTU SPANE-STAR or BCE DTA-TCH

or MLF DTA-TCH

or

BVL BONNEVILLE-STAR

or BYI BEARR-STAR

or

PIH BEARR-STAR

DBS BRIGHAM CITY-STAR

or

JAC BRIGHAM CITY-STAR or BPI BRIGHAM CITY-STAR

or

OCS BRIGHAM CITY-STAR

San Diego Terminal Area EED, LAX, GBN

Santa Ana HEC, PGS, BLD, HIPPI

San Antonio Terminal Area IDU, CSI, JCT, LLO, CRP, LRD

or

West of a north-south line at LFK, BLEWE

or

East of a north-south line at LFK, IDU

252

HIGH ALTITUDE REDESIGN (HAR) PHASE 1 RNAV ROUTING

San Francisco FMG GOLDEN GATE-STAR

MVA MODESTO-STAR ENI GOLDEN GATE-STAR

OAL MODESTO-STAR

South of a line ILC to DVC,

REANA KATTS OAL MODESTO-STAR

San Jose FMG HYP EL NIDO-STAR

OAL HYP EL NIDO-STAR

ENI GOLDEN GATE-STAR

South of a line ILC to DVC,

REANA KATTS KICHI CANDA EL NIDO-STAR

Seattle Terminal Area Aircraft From northeast, southeast, south,

TEMPL GLASR-STAR

SUNED CHINS-STAR

BTG OLMYPIA-STAR

Southwest Florida Airports CEW DEFUN Q104 SWABE JOSFF-STAR

RSW and FMY Aircraft through ZHU airspace remain south of ZME and ZTL

airspace

SZW HEVVN Q104 SWABE JOSFF-STAR

Tampa Terminal Area CEW DEFUN Q104 HEVVN DARBS-STAR

Aircraft through ZHU airspace remain south of ZME and ZTL

airspace

SZW DARBS-STAR

Tucson DRK PXR

or

MOHAK GBN

VFR WAYPOINTS VISUAL FLIGHT RULES (VFR) WAYPOINTS

VFR Waypoint names consist of five letters beginning with "VP". Stand-alone VFR Waypoints are portrayed on VFR Charts using the same four-point star symbol currently used for Instrument Flight Rules (IFR) Waypoints.

VFR Waypoints collocated with Visual Checkpoints (Visual Reporting Points) are portrayed with a Visual Check Point flag. The VFR Waypoint name is shown in parentheses adjacent to the Visual Check Point name.

VFR Waypoint names are not intended to be pronounceable and shall not be used in ATC communications.

CAUTION: GPS accuracy necessitates extra vigilance for other aircraft when navigating near any fix retrieved from a GPS database.

BALTIMORE-WASHINGTON TERMINAL AREA CHART/FLYWAY CHART

WAYPOINT IDENT	COLLOCATED VFR CHECKPOINT	LOCATION
VPAXI	COLLOCATED VFK CHECKFOINT	N38°34.57′/W076°20.38′
VPONX		N39°06.65′/W076°55.92′
VPOOP		N38°56.32′/W076°36.90′
VPOOP		N36 30.32 / W076 30.90
	BOSTON HELICOPTER CH	IART
VPBAY		N42°16.17′/W070°49.48′
VPBLT		N42°19.67′/W070°53.40′
VPCGS		N42°22.08′/W071°03.13′
VPEVS		N42°23.52′/W071°04.10′
VPFEN		N42°12.58′/W071°08.88′
VPFRE		N42°25.03′/W071°12.32′
VPGVL		N42°21.88′/W070°52.18′
VPHAM		N42°30.13′/W071°07.15′
VPPIK		N42°20.37′/W071°15.93′
VPQUA		N42°12.10′/W071°04.78′
VPQUB		N42°12.60′/W070°59.83′
VPSPF		N42°24.20′/W071°09.47′
VPTOB		N42°31.42′/W070°59.82′
VPWAN		N42°36.88′/W071°19.45′
	BOSTON TERMINAL AREA (CHART
VPCOH	Cohasset	N42°13.58′/W070°48.94′
VPCUT	Cuttyhunk Harbor	N41°25.50′/W070°55.03′
VPFRA	Framingham Shopping Center	N42°18.16′/W071°23.65′
VPHOL	Woods Hole	N41°31.06′/W070°40.60′
VPHUL	Hull	N42°18.20′/W070°55.30′
VPLPT	Nantucket Great Point	N41°23.41′/W070°02.78′
VPNED	Needham Towers	N42°18.51′/W071°14.64′
VPPEA	Peabody Shopping Center	N42°32.52′/W070°56.69′
VPROC	Rockingham Race Track	N42°46.29′/W071°13.57′
VPSCI	Scituate	N42°11.89′/W070°43.69′
VPTPT	Nantucket Third Point	N41°18.51′/W070°03.37′
VPTUC	Tuckernuck	N41°18.31′/W070°15.43′
VPWAK	Wakefield	N42°30.72′/W071°05.24′
VPWAN	Wang Towers	N42°36.88′/W071°19.45′
	CHARLOTTE SECTIONAL C	UADT
VPATO	GHARLOTTE SEGTIONAL G	N34°37.37′/W076°31.47′
VPAVA		N34°57.00′/W077°16.50′
VPBFE		N32°16.38′/W080°47.50′
VPBRA		N36°13.75′/W076°08.08′
VPGCE		N36°03.90′/W076°36.42′
VPGHI		N35°15.30′/W075°31.25′
VPGIO	 -	N35°32.50′/W076°37.33′
VPKJU		N35°26.58′/W076°10.22′
VPLMN		N34°55.43′/W077°46.42′
VPMAB		N34°42.20′/W077°03.50′
VPNPO	ISLE OF PALMS	N32°47.78′/W079°46.45′
VPOKY	ISEE OF FRENC	N35°06.53′/W075°59.17′
VPREP		N32°33.98′/W080°21.82′
VPRRS		N33°25.45′/W079°07.60′
VPUMO		N35°35.63′/W075°28.08′
VPWZO		N36°00.87′/W075°40.07′
VPZIE		N32°01.62′/W080°53.42′
		01.02 /000 002

CHICAGO SECTIONAL CHART

CHICAGU SECTIONAL CHART				
WAYPOINT IDENT	COLLOCATED VFR CHECKPOINT	LOCATION		
VPCOH		N31°49.35′/W081°51.07′		
DENVER TERMINAL AREA CHART/FLYWAY CHART				
Di	INVERTICIONAL AREA ONARI/TETRA			
VPBEN		N39°44.28′/W104°26.00′		
VPFTG	 	N39°44.35′/W104°32.75′		
VPNIC	NORTH INTERCHANGE	N39°58.90′/W104°59.27′		
HO	USTON TERMINAL AREA CHART/FLYW	AY CHART		
WAYPOINT IDENT	COLLOCATED VFR CHECKPOINT	LOCATION		
VPBWY		N29°46.25′/W095°09.24′		
VPDTN		N29°46.59′/W095°22.01′		
VPGLA		N30°08.32′/W095°06.62′		
VPGLB		N30°07.80′/W094°55.70′		
VPKTY		N29°47.05′/W095°44.92′		
VPPLN		N30°08.80′/W095°50.42′		
VPRSN		N29°30.00′/W095°41.00′		
VPSND		N29°23.13′/W095°28.86′		
VPSNT		N29°49.29′/W094°53.94′		
VPTNE		N29°47.48′/W095°03.34′		
VPTNW		N29°47.06′/W095°33.81′		
VPTRK		N29°24.06′/W095°10.44′		
	JACKSONVILLE SECTIONAL CHAR	T		
VPAFI		N31°49.35′/W081°51.07′		
VPAFY		N30°07.00′/W081°21.33′		
VPBEC		N29°46.25′/W081°15.10′		
VPCJA		N29°30.00′/W081°06.00′		
VPCKY		N28°46.50′/W082°34.00′		
VPCNY		N28°30.00′/W080°45.00′		
VPDAD	DADE CITY	N28°22.57′/W082°11.25′		
VPDAR		N31°22.38′/W081°24.13′		
VPDFI		N29°00.17′/W081°20.85′		
VPDUT		N27°37.70′/W082°09.10′		
VPEAR	CLEARWATER BEACH	N27°58.67′/W082°49.83′		
VPEGV		N29°39.97′/W081°24.87′		
VPFFU		N28°57.08′/W081°00.33′		
VPGPE	ST PETE BEACH	N27°43.50′/W082°44.67′		
VPHAA		N30°04.02′/W083°40.02′		
VPHUC		N28°19.87′/W082°43.77′		
VPIWA	MIDWAY	N31°48.33′/W081°25.85′		
VPJMY		N29°26.92′/W081°18.27′		
VPKER	LAKE PARKER	N28°04.00′/W081°56.00′		
VPLEV		N28°48.00′/W080°52.00′		
VPLJA VPMAI		N29°00.00′/W080°51.00′ N30°50.02′/W084°56.63′		
VPTLH		N30°32.70′/W083°52.22′		
VPXZY		N29°35.00′/W083°10.00′		
VPYIW		N30°42.28′/W081°27.25′		
VPZIE		N32°01.62′/W080°53.42′		
	KANSAS CITY SECTIONAL CHAR			
VPAGO	MANONO UITI DEUTIUNAL UNAK	N37°50.33′/W090°29.03′		
VPAGO VPBEK		N37°50.33′/W090°29.03′ N37°15.07′/W092°30.67′		
VPDEN		N37°46.75′/W092°19.20′		
VPENE		N37°44.75′/W091°55.78′		
VPESS		N36°59.48′/W091°00.88′		
VPFME		N37°41.00′/W092°38.33′		
VPGXY		N37°15.50′/W091°40.17′		
VPMBE		N37°11.08′/W090°27.92′		
VPMKE		N37°24.47′/W092°40.00′		
VPROV		N38°01.72′/W091°12.81′		
VPUTT		N37°52.05′/W092°01.20′		

VFR WAYPOINTS

	VIK WATI OINIS	
WAYPOINT IDENT	COLLOCATED VFR CHECKPOINT	LOCATION
VPWOC		N37°18.03′/W092°18.63′
VPWRO		N37°39.12′/W091°45.68′
VPXIZ		N37°26.60′/W092°05.42′
	KANSAS CITY TERMINAL ARE	EA CHART
VPATN	ATCHISON	N39°33.62′/W095°07.65′
VPBGS	BLUE SPRINGS	N39°01.82′/W094°16.32′
VPBSP	BONNER SPRINGS	N39°03.78′/W094°53.10′
VPCHB	CHOUTEAU BRIDGE	N39°08.77′/W094°32.03′
VPDS0	DE SOTO	N38°58.68′/W094°58.48′
VPESG	EXCELSIOR SPRINGS	N39°20.68′/W094°13.77′
VPGTB	GARRETSBURG	N39°40.92′/W094°41.45′
VPLAT	LATHROP WATER TANK	N39°32.87′/W094°20.00′
VPLEN	LENEXA	N38°57.77′/W094°43.68′
VPLVL	LONGVIEW LAKE	N38°54.63′/W094°28.28′
VPMCL	MC LOUTH	N39°11.65′/W095°12.50′
VPNHA	NASHUA	N39°17.83′/W094°34.80′
VPSCX	SPORTS COMPLEX	N39°03.00′/W094°29.02′
VPSKR VPSPK	SUGAR CREEK REFINERY SWOPE PARK	N39°07.00′/W094°27.02′ N39°00.47′/W094°31.93′
VPTSK	TWIN STACKS	N39°09.05′/W094°38.22′
VPWOF	WORLDS OF FUN	N39°10.42′/W094°29.12′
VI WOI	KLAMATH FALLS SECTIONAL	
VPORO	KLAMAIN FALLS SECTIONAL	N43°57.38′/W123°02.22′
VFORO		,
	LOS ANGELES HELICOPTER	R CHART
VPANA		N33°44.43′/W117°50.03′
VPART	MAGNOLIA	N33°51.45′/W117°58.92′
VPAUT	HWY 91 & 55	N33°50.63′/W117°49.57′
VPBOB		N33°59.60′/W117°21.45′
VPCAR		N33°49.90′/W118°17.23′
VPCNG	CONEJO GRADE US HWY 101	N34°12.54′/W118°59.61′
VPCOR VPCRX		N33°52.90′/W117°32.95′
VPCSU	CSU CHANNEL ISLANDS	N34°01.40′/W117°44.88′ N34°09.76′/W119°02.53′
VPDOW	CSU CHANNEL ISLANDS	N34 09.76 /W119 02.55 N33°56.47'/W118°05.80'
VPELA		N34°00.98′/W118°10.35′
VPETY		N33°38.70′/W117°44.12′
VPFCB		N34°02.03′/W118°01.63′
VPFPL	OXNARD FINANCIAL PLAZA	N34°13.71′/W119°10.39′
VPGOL		N34°09.33′/W118°17.37′
VPIMP		N33°55.85′/W118°16.85′
VPKAT		N33°48.23′/W117°54.22′
VPKEL		N34°03.92′/W117°48.40′
VPLAC		N34°03.75′/W118°14.93′
VPLLU		N34°03.85′/W117°17.82′
VPLQM	QUEEN MARY	N33°45.17′/W118°11.37′
VPLRT	SANTA ANITA RACE TRACK	N34°08.45′/W118°02.65′
VPLVT	VINCENT THOMAS BRIDGE	N33°44.97′/W118°16.32′
VPMDR	NEWHALL BACC	N33°59.27′/W118°23.97′
VPNEW	NEWHALL PASS	N34°20.18′/W118°30.72′
VPNUY VPPCH		N34°09.63′/W118°28.18′ N33°28.07′/W117°40.32′
VPPKC		N34°03.32′/W118°12.83′
VPPOR		N34 03.32 / W116 12.63 N34°00.10′/W117°50.12′
VPRRT		N33°59.37′/W118°16.83′
VPSEP		N34°05.80′/W118°28.63′
VPSFR	<u></u>	N34°17.45′/W118°28.07′
VPSTC	SATICOY BRIDGE	N34°16.62′/W119°08.34′
VPSTK		N34°13 97′/W118°24 60′

N34°13.97'/W118°24.60'

VPSTK

LOS ANGELES SECTIONAL CHART

WAYPOINT IDENT	COLLOCATED VFR CHECKPOINT	LOCATION
VPCNG	CONEJO GRADE US HWY 101	N34°12.54′/W118°59.61′
VPCSU	CSU CHANNEL ISLANDS	N34°09.76′/W119°02.53′
VPFPL	OXNARD FINANCIAL PLAZA	N34°13.71′/W119°10.39′
VPSTC	SATICOY BRIDGE	N34°16.62′/W119°08.34′
	LOC ANOTHER TERMINAL AREA CHART	TIVWAY OHADT

LOS ANGELES TERMINAL AREA CHART/FLYWAY CHART

VPCNG	CONEJO GRADE US HWY 101	N34°12.54′/W118°59.61′
VPCSU	CSU CHANNEL ISLANDS	N34°09.76′/W119°02.53′
VPGTY	GETTY CENTER	N34°04.84′/W118°28.66′
VPLBP	BANNING PASS	N33°56.05′/W116°59.63′
VPLCC	CHAFFEY COLLEGE	N34°08.87′/W117°34.33′
VPLCP	CAJON PASS	N34°18.07′/W117°27.68′
VPLDL	DISNEYLAND	N33°48.72′/W117°55.13′
VPLDP	DANA POINT	N33°27.62′/W117°42.87′
VPLDS	DODGER STADIUM	N34°04.42′/W118°14.42′
VPLFX	91/605 INTERCHANGE	N33°52.38′/W118°06.08′
VPLGP	GRIFFITH PARK OBSERVATORY	N34°07.10′/W118°18.02′
VPLHF	110/405 FWYS	N33°51.42′/W118°17.10′
VPLHP	HUNTINGTON PIER	N33°39.32′/W118°00.25′
VPLKH	KING HARBOR	N33°50.75′/W118°23.88′
VPLLC	L.A. COLISEUM	N34°00.83′/W118°17.27′
VPLLM	LAKE MATHEWS	N33°50.58′/W117°26.85′
VPLMM	MAGIC MOUNTAIN	N34°26.20′/W118°36.28′
VPLMS	MILE SQUARE PARK	N33°43.40′/W117°56.77′
VPLPD	PRADO DAM	N33°53.40′/W117°38.48′
VPLPP	PACIFIC PALISADES	N34°02.13'/W118°32.15'
VPLQM	QUEEN MARY	N33°45.17'/W118°11.37'
VPLRB	ROSE BOWL	N34°09.67'/W118°10.05'
VPLRT	SANTA ANITA RACE TRACK	N34°08.45'/W118°02.65'
VPLSA	SANTA ANA CANYON	N33°52.03′/W117°42.68′
VPLSB	SANTA FE FLOOD BASIN	N34°07.72′/W117°57.30′
VPLSC	STATE COLLEGE	N33°52.97′/W117°53.13′
VPLSF	SAN FERNANDO RESERVOIR	N34°17.87'/W118°29.00'
VPLSP	SIGNAL PEAK	N33°36.33'/W117°48.63'
VPLSR	HAWTHORNE & 405 FREEWAY	N33°53.07'/W118°21.13'
VPLSS	SANTA SUSANA PASS	N34°16.00′/W118°38.43′
VPLTW	TUJUNGA WASH & FOOTHILL	N34°16.40′/W118°20.30′
VPLVT	VINCENT THOMAS BRIDGE	N33°44.97'/W118°16.32'
VPLWT	WATER TANK	N34°10.82′/W118°46.27′
VPNEW	NEWHALL PASS	N34°20.18′/W118°30.72′
VPSTC	SATICOY BRIDGE	N34°16.62′/W119°08.34′

MIAMI SECTIONAL CHART

VPACH VPBOV VPCLE	HOLLYWOOD BEACH	N26°00.92′/W080°06.93′ N27°57.00′/W080°46.75′ N26°27.07′/W082°00.88′
VPCTE		N26°27.07 / W082 00.88 N26°09.28′/W081°20.70′
VPDAD	DADE CITY	N28°22.57′/W082°11.25′
VPDUT		N27°37.70′/W082°09.10′
VPDZE		N27°19.00′/W080°44.17′
VPEAR	CLEARWATER BEACH	N27°58.67′/W082°49.83′
VPEDY	ANDYTOWN TOLLGATE	N26°08.78′/W080°28.00′
VPFAH		N26°25.40′/W081°29.67′
VPGPE	ST PETE BEACH	N27°43.50′/W082°44.67′
VPHRO		N27°05.97′/W082°12.20′
VPHUC		N28°19.87′/W082°43.77′
VPIBR		N27°12.47′/W081°40.22′
VPKER	LAKE PARKER	N28°04.00′/W081°56.00′
VPKOE		N24°40.08′/W081°20.55′
VPLYY		N24°49.07′/W080°49.17′
VPMBO	GULFSTREAM PARK	N25°58.57′/W080°08.17′
VPOBA	PUMPING STATION	N26°28.30′/W080°26.75′
VPRBI		N25°50.67′/W080°55.18′
VPRNL	RANGER STATION	N25°22.92′/W080°36.58′
VPWMO		N27°03.00′/W080°35.00′

ı

MIAMI TERMINAL AREA CHART/FLYWAY CHART

I'	MIAMI ILKMINAL AKLA GHAKI/ILIWAI C	HANT
WAYPOINT IDENT	COLLOCATED VFR CHECKPOINT	LOCATION
VPACH	HOLLYWOOD BEACH	N26°00.92′/W080°06.93′
VPEDY	ANDYTOWN TOLLGATE	N26°08.78′/W080°28.00′
VPMBO	GULFSTREAM PARK	N25°58.57′W080°08.17′
VPOBA	PUMPING STATION	N26°28.30′/W080°26.75′
VPRBI		N25°50.67′/W080°55.18′
VPRNL	RANGER STATION	N25°22.92′/W080°36.58′
	NEW ORLEANS SECTIONAL CHART	
VPGPT		N30°25.95′/W089°05.62′
VPLIP	PHILLIPS INLET	
	PHILLIPS INLET	N30°16.23′/W085°59.25′
VPMAI		N30°50.02′/W084°56.63′
VPMOB		N30°23.00′/W088°31.72′
VPRAM		N30°18.95′/W089°35.88′
VPRER		N30°13.87′/W085°20.67′
VPRIV		N30°54.85'/W087°57.82'
VPSAW		N30°49.65′/W089°07.42′
VPTHR		N30°19.93′/W087°08.50′
	NEW YORK HELICOPTER CHART	
	NEW TORK HELIOOF TER OHART	
VPJAY		N40°59.00′/W073°07.00′
VPLYD		N40°57.37′/W073°29.59′
VPROK		N40°52.70′/W073°44.24′
Pł	IOENIX TERMINAL AREA CHART/FLYWAY	CHART
VDALL	ALLENVILLE	N00000 07/ 4W44000F 00/
VPALL		N33°20.97′/W112°35.20′
VPAQU	AQUEDUCT PUMPING STATION	N33°40.05′/W112°41.38′
VPARM	ARROWHEAD MALL	N33°38.52′/W112°13.48′
VPAWG	AHWATUKEE GOLF COURSE	N33°19.98′/W111°59.08′
VPAZM	ARIZONA MILLS	N33°23.43′/W111°57.88′
VPBAR	BARTLETT DAM	N33°49.10′/W111°37.92′
VPCCC	COUNTRY CLUB & CANAL	N33°30.73′/W111°50.37′
VPCNL	CANAL	N33°33.23′/W111°46.89°
VPFRB	FIREBIRD LAKE	N33°16.35′/W111°58.10′
VPFTN	FOUNTAIN HILLS	N33°36.12′/W111°42.72′
VPGLX	GILA CROSSING	N33°16.55′/W111°10.08′
VPGPP	GLENDALE POWER PLANT	N33°33.27′/W112°13.00′
VPMAR	MARICOPA	N33°03.42′/W112°02.88′
VPMHS	MESQUITE HIGH SCHOOL	N33°20.53′/W111°49.58′
VPNRV	NEW RIVER	N33°55.08′/W112°08.45′
VPNTT	NORTH TEST TRACK	N33°03.50′/W111°55.83′
VPPIR	PIR	N33°22.52′/W112°18.90′
VPQTR	QUINTERO GOLF COURSE	N33°49.53′/W112°23.58′
VPRVC	RIO VERDE COMMUNITY	N33°44.37′/W111°39.62′
VPSMC	SOUTH MOUNTAIN COLLEGE	N33°23.02′/W112°02.12′
VPSQP	SQUAW PEAK	N33°32.83′/W112°01.27′
VPSSS	SUPERSTITION SPRINGS MALL	N33°23.50′/W111°41.37′
VPSTN	SANTAN MOUNTAINS	N33°09.23′/W111°40.92′
VPSTT	SOUTH TEST TRACK	N32°56.25′/W111°59.67′
VPZZZ	SOUTH TEST TRACK	N33°20.18′/W111°26.53′
		•
21	LOUIS TERMINAL AREA CHART/FLYWAY	
VPAGN	TV ANTENNA	N38°32.08′/W090°22.42′
VPBPE		N38°23.80′/W090°20.38′
VPCJY	HOLIDAY SHORES	N38°55.00′/W089°56.00′
VPCOJ	WINFIELD DAM	N39°00.28′/W090°41.23′
VPDFA	JEFFERSON BARRACKS BRIDGE	N38°29.18′/W090°16.47′
VPEAZ	BUSCH STADIUM	N38°37.43′/W090°11.55′
VPEDZ	WATER TANKS	N38°45.30′/W090°34.87′
VPEGR		N38°35.80′/W090°19.32′
VPEGR VPEOX	GAS TANKS ST PETERS	
VPEUA	SIFEIERS	N38°47.17′/W090°39.25′

WAYPOINT IDENT	COLLOCATED VFR CHECKPOINT	LOCATION
VPFAI	HOWELL ISLAND	N38°40.00′/W090°43.00′
VPFFY		N38°55.37′/W090°17.30′
VPGPF		N38°35.60′/W090°26.92′
VPGVI		N38°32.30′/W090°27.80′
VPHRQ	CHAIN OF ROCKS BRIDGE	N38°45.88'/W090°10.42'
VPIBO	WATERLOO	N38°20.00′/W090°09.00′
VPJMU	HORSESHOE LAKE	N38°41.00′/W090°05.00′
VPKNY	PACIFIC	N38°29.00'/W090°44.00'
VPLES	ST CHARLES	N38°47.00′/W090°30.00′
VPLIW	SIX FLAGS	N38°30.67'/W090°40.47'
VPLXU	GATEWAY ARCH	N38°37.50′/W090°11.00′
VPNSY	WOOD RIVER REFINERIES	N38°50.00′/W090°05.00′
VPNZY	WENTZVILLE	N38°48.83'/W090°50.98'
VPRAZ	JERSEYVILLE	N39°07.00′/W090°20.00′
VPRMO	FOREST PARK	N38°38.00′/W090°17.00′
VPWKO	COLUMBIA	N38°27.00′/W090°12.00′
VPXXI	MILLSTADT	N38°27.50′/W090°05.68′
VPYID	MOSENTHEIN ISLAND	N38°43.00′/W090°12.25′

SALT LAKE CITY HELICOPTER CHART

VPAIR	SALTAIR	N40°44.85′/W112°11.22′
VPBEE	SOUTH INTERCHANGE	N40°38.18'/W111°54.23'
VPBRN	BARN	N40°54.28′/W112°10.15′
VPCAP	STATE CAPITOL	N40°46.67′/W111°53.25′
VPCHS		N40°42.28'/W112°05.92'
VPCOP	BINGHAM COPPER MINE	N40°31.38′/W112°09.00′
VPCWY	CAUSEWAY	N41°05.37′/W112°07.17′
VPCYN	PARLEYS CANYON	N40°42.67′/W111°48.10′
VPFPC	FREE PORT CENTER	N41°05.92′/W112°02.27′
VPFPK	FRANCIS PEAK	N41°01.98'/W111°50.30'
VPGFS	GARFIELD STACK	N40°43.28′/W112°11.88′
VPHVE	SPAGHETTI BOWL	N40°43.50′/W111°54.22′
VPJRT	JORDAN RIVER TEMPLE	N40°35.02′/W111°55.58′
VPKSL	KSL ANTENNA	N40°46.80′/W112°05.80′
VPLGN	LAGOON AMUSEMENT PARK	N40°59.08'/W111°53.57'
VPMDH	MCKAY DEE HOSPITAL	N41°11.50′/W111°57.08′
VPMMT	MICROWAVE TOWERS	N40°48.50′/W111°53.37′
VPMSH		N41°01.67'/W112°02.47'
VPNSL		N40°50.15'/W111°54.90'
VPNTP		N41°03.57′/W112°14.23′
VPOGE	GRAIN ELEVATOR	N41°13.13′/W112°00.45′
VPOPS	POWER STATION	N41°20.38′/W112°02.78′
VPPEN	STATE PRISON	N40°29.88'/W111°53.62'
VPPPT	PROMONTORY POINT	N41°12.28′/W112°25.73′
VPPTM	POINT OF THE MOUNTAIN	N40°27.42′/W111°54.83′
VPPVO	PROVO CANYON	N40°18.77′/W111°39.45′
VPRWY		N40°48.48'/W112°00.33'
VPSLC	I-15/I-80 INTERCHANGE	N40°45.83′/W111°54.85′
VPTIP	SOUTH TIP	N40°50.93′/W112°10.92′
VPWBR	WEBER CANYON	N41°08.17'/W111°54.83'
VPWBT		N40°38.00′/W112°03.33′

SALT LAKE CITY TERMINAL AREA CHART/FLYWAY CHART

VPAIR	SALTAIR	N40°44.85′/W112°11.22′
VPBEE	SOUTH INTERCHANGE	N40°38.18′/W111°54.23′
VPBRN	BARN	N40°54.28′/W112°10.15′
VPCAP	STATE CAPITOL	N40°46.67′/W111°53.25′
VPCHS		N40°42.28′/W112°05.92′
VPCOP	BINGHAM COPPER MINE	N40°31.38′/W112°09.00′
VPCVI	CENTERVILLE INTERCHANGE	N40°55.30′/W111°53.43′
VPCWY	CAUSEWAY	N41°05.37′/W112°07.17′
VPCYN	PARLEYS CANYON	N40°42.67′/W111°48.10′
VPFPC	FREE PORT CENTER	N41°05.92′/W112°02.27′
VPFPK	FRANCIS PEAK	N41°01.98′/W111°50.30′
VPGFS	GARFIELD STACK	N40°43.28′/W112°11.88′

WAYPOINT IDENT	COLLOCATED VFR CHECKPOINT	LOCATION
VPHVE	SPAGHETTI BOWL	N40°43.50′/W111°54.22′
VPJRT	JORDAN RIVER TEMPLE	N40°35.02′/W111°55.58′
VPKSL	KSL ANTENNA	N40°46.80′/W112°05.80′
VPLGN	LAGOON AMUSEMENT PARK	N40°59.08'/W111°53.57'
VPMDH	MCKAY DEE HOSPITAL	N41°11.50′/W111°57.08′
VPMMT	MICROWAVE TOWERS	N40°48.50′/W111°53.37′
VPMSH		N41°01.67'/W112°02.47'
VPNSL		N40°50.15′/W111°54.90′
VPNTP		N41°03.57′/W112°14.23′
VPOGE	GRAIN ELEVATOR	N41°13.13′/W112°00.45′
VPOPS	POWER STATION	N41°20.38′/W112°02.78′
VPPEN	STATE PRISON	N40°29.88'/W111°53.62'
VPPPT	PROMONTORY POINT	N41°12.28′/W112°25.73′
VPPTM	POINT OF THE MOUNTAIN	N40°27.42′/W111°54.83′
VPPVO	PROVO CANYON	N40°18.77′/W111°39.45′
VPRWY		N40°48.48′/W112°00.33′
VPSLC	I-15/I-80 INTERCHANGE	N40°45.83′/W111°54.85′
VPTIP	SOUTH TIP	N40°50.93'/W112°10.92'
VPUOU	U OF U EVENTS CENTER	N40°45.73′/W111°50.28′
VPWBR	WEBER CANYON	N41°08.17'/W111°54.83'
VPWBT		N40°38.00′/W112°03.33′
VPZ00	HOGLE ZOO	N40°45.00′/W111°48.95′

SAN DIEGO TERMINAL AREA CHART/FLYWAY CHART

VPLDP	DANA POINT	N33°27.62′/W117°42.87′
VPLSP	SIGNAL PEAK	N33°36.33′/W117°48.63′
VPOCN		N33°14.15′/W117°26.63′
VPSBC	BARONA CASINO	N32°56.25′/W116°52.60′
VPSBL		N33°05.18'/W117°18.55'
VPSBM	BLACK MOUNTAIN	N32°58.87'/W117°07.00'
VPSCF		N32°48.55′/W117°09.17′
VPSCM	COWLES MOUNTAIN	N32°48.72′/W117°01.97′
VPSCP	CRYSTAL PIER	N32°47.77′/W117°15.42′
VPSCR		N32°39.37′/W117°07.30′
VPSFB	IRON MOUNTAIN	N32°58.25′/W116°57.33′
VPSLJ	LAKE JENNINGS	N32°51.53′/W116°53.28′
VPSMB		N32°45.57′/W117°12.22′
VPSMP		N33°22.70′/W117°36.75′
VPSMS	MOUNT SOLEDAD	N32°50.40′/W117°15.10′
VPSMV		N32°45.75′/W117°09.80′
VPSMW	MOUNT WOODSON	N33°00.52′/W116°58.23′
VPSOP	OTAY MESA PRISON	N32°35.82′/W116°55.28′
VPSOT	LOWER OTAY LAKE	N32°37.73′/W116°55.38′
VPSPL	SOUTH POINT LOMA	N32°39.90′/W117°14.55′
VPSPP	POWER PLANT	N33°08.25′/W117°20.23′
VPSQS	QUALCOMM STADIUM	N32°46.98′/W117°07.23′
VPSRT	DEL MAR RACE TRACK	N32°58.58′/W117°15.95′
VPSSM	SAN MIGUEL MOUNTAIN	N32°41.78′/W116°56.18′
VPSSV	SAN VICENTE ISLAND	N32°55.53′/W116°55.00′
VPSTP	TORREY PINES GOLF COURSE	N32°54.17′/W117°14.68′
VPSVA		N33°11.48′/W117°16.38′

SAN FRANCISCO SECTIONAL CHART

VPKBG KINGSBURY GRADE N38°58.75′/W119°53.20′

SAN FRANCISCO TERMINAL AREA CHART/FLYWAY CHART

VPALT	ALTAMONT PASS	N37°44.35′/W121°35.42′
VPANT	ANTIOCH BRIDGE	N38°01.45′/W121°45.02′
VPBBR	BENICIA BRIDGE	N38°02.50′/W122°07.45′
VPCAL	CALAVERAS RESERVOIR	N37°28.16′/W121°48.93′
VPCBT	LAKE CHABOT	N37°43.68′/W122°06.94′
VPCOY	COYOTE HILLS	N37°32.50′/W122°05.06′
VPCQZ	CARQUINEZ BRIDGE	N38°03.66′/W122°13.52′
VPCRL		N37°11.00′/W121°41.06′
VPCRY	CRYSTAL SPRINGS CAUSEWAY	N37°30.56′/W122°21.10′

VPGCE

VPWZO

VFR WAYPOINTS

WAYPOINT IDENT	COLLOCATED VFR CHECKPOINT	LOCATION
VPCSH	CAL STATE UNIVERSITY	N37°39.52′/W122°03.52′
VPDAM	DEL VALLE DAM	N37°36.91′/W121°44.78′
VPDLR		N37°07.00′/W121°47.06′
VPDUB	DUBLIN	N37°42.06′/W121°55.36′
VPEMB	EMBASSY SUITES	N37°26.05′/W121°53.83′
VPGGF	GOLDEN GATE FIELDS	N37°53.07′/W122°18.71′
VPGIL	GILROY	N37°01.37′/W121°33.99′
VPHHH	HAMILTON	N38°03.58′/W122°30.66′
VPKGO	KGO	N37°31.58′/W122°06.10′
VPLEX	LEXINGTON RESERVOIR	N37°11.66′/W121°59.18′
VPMID	MID-SPAN SAN MATEO BRIDGE	N37°36.28′/W122°11.81′
VPMOR	MORMON TEMPLE	N37°48.46′/W122°11.95′
VPNUM	NUMMI PLANT	N37°29.56′/W121°56.58′
VPPAC		N37°38.00′/W122°32.07′
VPPRU	PRUNEYARD	N37°17.33′/W121°56.01′
VPSAR	SARATOGA	N37°15.26′/W122°02.33′
VPSLA	SLAC/LINEAR ACCELERATOR	N37°24.75′/W122°14.35′
VPSTB	STINSON BEACH	N37°54.45′/W122°40.41′
VPSUN	SUNOL GOLF COURSE	N37°34.85′/W121°53.23′
VPUTC	U.T.C.	N37°13.93′/W121°41.35′
VPWAL	WALNUT CREEK	N37°53.78′/W122°04.30′
VPWAM		N37°30.28′/W122°10.00′
VPWFR	CEMENT PLANT	N37°30.88′/W122°12.26′
	TAMPA/ORLANDO TERMINAL AREA CHAF	RT/FLYWAY CHART
VPBOV		N27°57.00′/W080°46.75′
VPCNY		N28°30.00′/W080°45.00′
VPDAD	DADE CITY	N28°22.57′/W082°11.25′
VPDFI		N29°00.17′/W081°20.85′
VPDUT		N27°37.70′/W082°09.10′
VPEAR	CLEARWATER BEACH	N27°58.67′/W082°49.83′
VPFFU		N28°57.08′/W081°00.33′
VPGPE	ST PETE BEACH	N27°43.50′/W082°44.67′
VPHUC		N28°19.87′/W082°43.77′
VPKER	LAKE PARKER	N28°04.00′/W081°56.00′
VPLEV		N28°48.00′/W080°52.00′
VPLJA		N29°00.00′/W080°51.00′
	WASHINGTON SECTIONAL C	HART
VPACE		N38°07.82′/W076°48.75′
VPAXI		N38°34.57′/W076°20.38′
VPBRA		N36°13.75′/W076°08.08′
VDCCE		N2C902 00/ /M07C92C 40/

N36°03.90′/W076°36.42′

N36°00.87'/W075°40.07'

VOR RECEIVER CHECK VOR RECEIVER CHECKPOINTS AND VOR TEST FACILITIES (VOT)

The use of VOR airborne and ground checkpoints is explained in Aeronautical Information Manual, Basic Flight Information and ATC Procedures.

NOTE: Under columns headed "Type of Checkpoint" & "Type of VOT Facility" G stands for ground. A/ stands for airborne followed by figures (2300) or (1000–3000) indicating the altitudes above mean sea level at which the check should be conducted. Facilities are listed in alphabetical order, in the state where the checkpoints or VOTs are located.

IDAHO

VOR RECEIVER CHECKPOINTS

Facility Name (Arpt Name)	Freq/Ident	Type Check Pt. Gnd. AB/ALT	Azimuth from Fac. Mag	Dist. from Fac. N.M.	Checkpoint Description
Boise	113.3/BOI	A/5000	090	6.2	Over dam outlet S end Lucky Peak Reservoir
Boise (Boise Air Terminal–Gowen Field)	113.3/BOI	G	275	1.0	On twy C adjacent to the intersection of Twy B at apch end Rwy 28L.
Coeur D'Alene	108.8/COE	A/4000	011	9.0	Over amusement park.
Idaho Falls (Idaho Falls Rgnl)	109.0/IDA	G	208		At intersection of Twys A and A3.
Nez Perce (Lewiston-Nez Perce County)	108.2/MQG	A/3000	247	6.2	Over tetrahedron on arpt.
Pocatello (Pocatello Rgni)	112.6/PIH	A/5800	034	8.7	Over radio antenna with white storage tanks at base.
Fld)	115.8/TWF	G	065	0.8	On runup area at apch end Rwy 25.

VOR TEST FACILITIES (VOT)

Facility Name		Type VOT	
(Airport Name)	Freq.	Facility	Remarks

Boise 116.7

MONTANA

RECEIVER CHECKPOINTS

		Type			
		Check Pt.	Azimuth from	Dist. from	
		Gnd.	Fac.	Fac.	
Facility Name (Arpt Name)	Freq/Ident	AB/ALT	Mag	N.M.	Checkpoint Description
Billings	114.5/BIL	A/5000	199	10.5	Over refinery at Laurel.
Bozeman (Gallatin Fld)	112.4/BZN	G	272	0.5	Twy at apch end Rwy 12.
	112.4/BZN	G	137	1.0	On runup as at apch end Rwy 30.
Coppertown (Bert Mooney)	111.6/CPN	A/6600	098	11.5	Over intersection of Rwys 11–29 and 15–33.
Dillon	113.0/DLN	A/7000	245	5.0	Over letter 'B' on bluff.
Great Falls (Great Falls Intl)	115.1/GTF	G	030	2.3	At intersection of Twys A and A3.
	115.1/GTF	G	030	2.9	On Twy A between A5 and A6.
Havre	111.8/HVR	A/4000	278	8.0	Over S end of dam.
Helena (Helena Rgnl)	117.7/HLN	G	238	0.7	On Twy E on South side of Rwy 27.
Kalispell (Glacier Park Intl)	108.4/FCA	A/4000	316	6.4	Over apch end Rwy 30.

		Type Check Pt.	Azimuth from	Dist.	
		Gnd.	Fac.	Fac.	
Facility Name (Arpt Name)	Freq/Ident	AB/ALT	Mag	N.M.	Checkpoint Description
Lewistown (Lewistown Muni)	112.0/LWT	A/5200	075	5.6	Over apch end Rwy 07.
Livingston	116.1/LVM	A/6500	237	5.5	Over northern most radio twr NE of city.
Miles City (Frank Wiley Field)	112.1/MLS	G	036	4.2	On twy leading to Rwy 30.
Missoula (Missoula Intl)	112.8/MSO	G	344	0.6	Terminal ramp east of Twy
					D

OREGON VOR RECEIVER CHECKPOINTS

		Type Check Pt. Gnd.	Azimuth from Fac.	Dist. from Fac.	
Facility Name (Arpt Name)	Freq/Ident	AB/ALT	Mag	N.M.	Checkpoint Description
Astoria (Astoria Regional)	114.0/AST	G	153	.5	East edge of ramp in front of large hangar.
Baker	115.3/BKE	A/6000	136	6.7	Over microwave tower on bluff.
Corvallis (Corvallis Muni)	115.4/CVO	G	049	0.5	On S edge of terminal ramp.
Eugene (Mahlon Sweet Field)	112.9/EUG	G	071	0.5	On ramp immediately W of tower.
Klamath Falls (Klamath Falls)	115.9/LMT	G	298	1.0	On ramp N of Twy E.
North Bend (North Bend Muni)	112.1/OTH	G	255	3.5	On circle at intersection twys to Rwys 13–31 and 04–22.
Pendleton (Eastern Oregon Rgnl At Pendleton)	114.7/PDT	G	073	3.9	On twy B.
Rogue Valley (Rogue Valley Intl)	113.6/0ED	A/3000	213	4.8	Over radio tower.
Roseburg (Roseburg Rgnl)	108.2/RBG	A/2500	337	3.0	Over S end of Rwy 16-34.
Wildhorse	113.8/ILR	A/6500	225	6.0	Over smoke stack.

VOR TEST FACILITIES (VOT)

	Type VOT	
Freq.	Facility	Remarks
11.0	G	
15.2	G	
17.2	G	Unusable on Twy A–6, hangar area W of Twy A–6 and Twy A NW of
1	L1.0 L5.2	Freq. Facility 11.0 G 15.2 G

WASHINGTON VOR RECEIVER CHECKPOINTS

Twy C.

		Type			
		Check	Azimuth	Dist.	
		Pt.	from	from	
		Gnd.	Fac.	Fac.	
Facility Name (Arpt Name)	Freq/Ident	AB/ALT	Mag	N.M.	Checkpoint Description
Ellensburg (Bowers Field)	117.9/ELN	A/2300	255	3.5	Over W end of Rwy 07-25.
Ephrata (Ephrata Muni)	112.6/EPH	A/2300	202	5.8	Over intersection of Rwys 02–20 and 11–29.
Hoquiam (Bowerman)	117.7/HQM	A/1100	062	8.4	Over centerline on apch end Rwy 06.
Whatcom (Bellingham Intl)	113.0/HUH	A/1700	162	5.4	Over Nooksack River/Interstate 5 Bridge.

Remarks

		Туре			
		Check	Azimuth	Dist.	
		Pt.	from	from	
		Gnd.	Fac.	Fac.	
Facility Name (Arpt Name)	Freq/Ident	AB/ALT	Mag	N.M.	Checkpoint Description
Moses Lake (Grant County Intl)	115.0/MWH	G	155	1.4	On runup area Rwy 32R.
	115.0/MWH	G	194	1.2	On runup area Rwy 04.
	115.0/MWH	G	313	1.0	On runup area Rwy 14L.
Olympia (Olympia Rgnl)	113.4/OLM	G	350	0.3	On E runup area Rwy 17.
Paine (Snohomish Co (Paine Fld))	110.6/PAE	G	173	8.0	Intersection of Rwy 11 and Twy H.
				1.1	On Twy A-7.
Pasco (Tri-Cities)	108.4/PSC	G	098		Twy Echo at Rwy 30 run-up area.
Seattle	116.8/SEA	A/2000	197	27.0	Over Nisqually River/Interstate 5 bridge.
Seattle	116.8/SEA	A/2500	308	19.5	Over NW end of bridge and Hwy 305.
Seattle (Crest Airpark)	116.8/SEA	A/2000	107	10.3	Over centerline on apch end Rwy 33.
Tatoosh (Sekiu)	112.2/TOU	A/2500	077	12.4	Over AER 08.
Walla Walla (Martin Field)	116.4/ALW	A/1500	225	5.6	Over largest hangar.
Walla Walla (Walla Walla Rgnl)	116.4/ALW	G	035	0.5	At the intersection of Twys A and C.
Wenatchee (Pangborn Mem)	111.0/EAT	G	105	0.6	On Twy at apch end of Rwy 30.
Yakima	116.0/YKM	A/3500	210	4.1	Over single tower on ridge line.

VOR TEST FACILITIES (VOT)

Facility Name (Airport Name)	Freq.	Type VOT Facility
Seattle (Boeing Field/King County Intl)	108.6	G
Seattle (Seattle Tacoma Intl)	117.5	G
Spokane (Felts Field)	114.0	G
Spokane Intl	109.6	G

WYOMING

VOR RECEIVER CHECKPOINTS

		Type			
		Check	Azimuth	Dist.	
		Pt.	from	from	
		Gnd.	Fac.	Fac.	
Facility Name (Arpt Name)	Freq/Ident	AB/ALT	Mag	N.M.	Checkpoint Description
Boysen Reservoir	117.8/BOY	A/6500	180	25	Over Riverton VOR.
Jackson (Jackson Hole)	115.4/JAC	G	174	0.5	On Twy A, approximately 1,000' S of AER 19.
Muddy Mountain (Casper/Natrona Co Intl)	116.2/DDY	A/6400	204	13.4	Over intersection Rwys 03–21, 08–26 and 12–30.
Newcastle (Mondell Fld)	108.2 ECS	A/5500	116	4.9	Over radio towers with strobe lights.
Rawlins (Rawlins Muni)	109.4/RWL	A/7500	093	5.5	Bridge over railroad track east of refinery.
Rock Springs (Rock Springs–Sweetwater	109.4/RWL	G	050	0.8	Runup area Rwy 22.
County)	116.0/0CS	G	270	2.3	Intersection twy to Rwy 09-27.
Sheridan (Sheridan County)	115.3/SHR	A/5000	129	5.0	Over centerline approach end Rwy 14.

The following tabulation lists all reported parachute jumping sites in the area of coverage of this directory. Unless otherwise indicated, all activities are conducted during daylight hours and under VFR conditions. The busiest periods of activity are normally on weekends and holidays, but jumps can be expected at anytime during the week at the locations listed. Jumps within restricted airspace are not listed.

All times are local and altitudes MSL unless otherwise specified.

Contact facility and frequency is listed at the end of the remarks, when available, in bold face type.

Refer to Federal Aviation Regulations Part 105 for required procedures relating to parachute jumping.

Organizations desiring listing of their jumping activities in this publication should contact the nearest FSS, tower or ARTCC.

Qualified parachute jumping sites will be depicted on the appropriate visual chart(s).

Note: (c) in this publication indicates that the parachute jump area is charted.

To qualify for charting, a jump area must meet the following criteria:

- (1) Been in operation for at least 1 year.
- (2) Operate year round (at least on weekends).
- (3) Log 4,000 or more jumps each year.

In addition, jump sites can be nominated by FAA Regions if special circumstances require charting.

LOCATION	DISTANCE AND RADIAL FROM NEAREST VOR/VORTAC	MAXIMUM ALTITUDE	REMARKS
	IDAHO		
Burley	13 NM; 035° Burley	15,000	Daily SR-SS.
(c) Caldwell Industrial Arpt		17,500	5 NM radius. ¹ /2 hour before SR-1 hour after SS.
(c) Star Skydiving Center	17 NM; 289° Boise	16,000	5NM radius. SR-2 hrs after SS daily.
	MONTANA		
Bozeman Gallatin Fld Arpt	1 NM; 038° Bozeman	15,000	2 NM radius. SR-SS daily.
(c) Butler Creek	19 NM; 296° Missoula	2,000 AGL	0.5 NM radius. Occasional use.
Dornblaser Fld	5.2 NM; 120° Missoula	12,500 AGL	0.5 NM radius. Occasional use.
(c) Grant Creek	1.5 NM; 053° Missoula	12,500 AGL	0.5 NM radius. Occasional use.
(c) Helena, Ft Harrison	6 NM; 265° Helena	12,000	1 NM radius. Wed-Sun SR-SS.
Kalispell	6 NM; 227° Kalispell	14,000	1 NM radius. 0900-SS daily.
(c) Kalispell, Carson Fld Arpt	28 NM; 238° Kalispell	14,000	2 NM radius. 0800-SS daily.
Kalispell, City Arpt	6 NM; 230° Kalispell	14,000 AGL	2 NM radius. 0800-SS daily.
(c) Laurel Muni Arpt	9 NM; 208° Billings	14,500	2 NM radius. Daily SR-SS.
Livingston, MIssion Fld	1 NM; 010° Livingston	14,500	2 NM radius. Daily SR-SS.
(c) Missoula Intl Arpt	1.4 NM; 315° Missoula	1,500 AGL	0.5 NM radius. May-Sep daily SR-SS, Oct-Apr occasional use.
Nine Mile R.S	17 NM; 289° Missoula	2,000 AGL	0.5 NM radius. Occasional use.
(c) Raser Ranch	2 NM; 357° Missoula	3,000 AGL	0.5 NM radius Apr-Oct occasional use.
Roundup Arpt	40 NM; 351° Billings	14,500	Weekends SR-SS.
(c) Six Mile	15 NM; 300° Missoula	2,000 AGL	0.5 NM radius. Occasional use.
(c) Stevensville Arpt	25 NM; 162° Missoula	14,000	1 NM radius. Wed and weekends SR-SS.
Stoney Creek	17 NM; 296° Missoula	2,000 AGL	0.5 NM radius. Occasional use.
Three Forks Arpt	18 NM; 275° Bozeman	14,500	2 NM radius. Daily SR-SS.
University Campus	5 NM; 108° Missoula	12,500 AGL	0.5 NM radius. Occasional use.
West Yellowstone, Yellowstone Arpt	60 NM; 034° DuBois	1,500 AGL	June-Sep.
	OREGON		
(c) Albany, Northwest Parachute Club	18 NM; 032° Corvallis	13,000	2 NM radius. SR-1 hr after SS Wed-Sun. Occasional hours Mon-Tue.
(c) Creswell, Hobby Fld	15 NM; 120° Eugene	15,000	5 NM radius. SR-SS daily.
(c) Estacada, Beaver Oaks Arpt	25 NM; 076° Newberg	13,000 AGL	1.5 NM radius. 0800-2300 Daily.
(c) Hermiston Muni Arpt	16 NM; 280° Pendleton	15,000	2 NM radius. SR-SS weekends. Occasional hours weekdays.
(c) Medford, Beagle Sky Ranch Arpt	5 NM; 350° Rogue Valley	14,000	Daily SR-2200.
(c) Mollala, Sky Dive Oregon Arpt	19 NM; 110° Newberg	14,500	5 NM radius. 0800–2200, Daily. Portland Intl Tower 118.1
(c) Redmond, Cline Falls Air Park Arpt	3 NM; 010° Deschutes	13,000	3 NM radius. 0800-2100.

PARACHUTE JUMPING AREAS

LOCATION	DISTANCE AND RADIAL FROM NEAREST VOR/VORTAC	MAXIMUM ALTITUDE	REMARKS
	WASHINGTON		
(c) Coupeville NOLF	5 NM; 110° Penn Cove	12,500 AGL	2 NM radius. Occasional use.
Fort Lewis, Abrams Drop Zone	7.5 NM; 200° McChord	10,000	1 NM radius. Occasional use.
Fort Lewis, Anzio Drop Zone	9 NM; 160° McChord	10,000	0.3 NM radius. Occasional use.
Fort Lewis, Dakto Drop Zone	7.5 NM; 175° McChord	10,000	0.3 NM radius. Occasional use.
Fort Lewis, Darby Drop Zone	8.5 NM; 097° Olympia	10,000	0.5 NM radius. Occasional use.
Fort Lewis, El Guettar Drop Zone	7.5 NM; 092° Olympia	10,000	0.3 NM radius. Occasional use.
Fort Lewis, Gray AAF Drop Zone	6 NM; 210° McChord	10,000	1 NM radius. Occasional use.
Fort Lewis, Marion Drop Zone	11 NM; 190° McChord	10,000	1 NM radius. Occasional use.
Fort Lewis, Merrill Drop Zone	9 NM; 092° Olympia	10,000	0.5 NM radius. Occasional use.
Fort Lewis, Mytkina Drop Zone	10 NM; 065° Olympia	10,000	1 NM radius. Occsional use.
Fort Lewis, Point Salinas Drop Zone	7.5 NM; 201° McChord	10,000	1 NM radius. Occasional use.
Fort Lewis, Pointe De Hoc Drop Zone	11.5 NM; 192° McChord	10,000	0.25 NM radius. Occasional use.
Fort lewis, Rogers Drop Zone	7 NM; 155° McChord	10,000	0.5 NM radius. Occasional use.
Fort Lewis, Solo Drop Zone	6.5 NM; 245° McChord	10,000	1 NM radius. Occasional use.
(c) Kapowsin Fld	13 NM; 110° McChord	16,000	2 NM radius. 0700-2300 daily.
Kennewick, Vista Field	5.1 NM; 217° Pasco	14,500	1 NM radius. SR-SS weekends, 1700-SS weekdays, Apr-Nov.
(c) Larson Drop Zone	17 NM; 217° Moses Lake	3,000	Continuous. Personnel and hvy equip. Grant Co Intl Tower 126.4
Monroe, Firstair Fld	14 NM; 091° Paine	12,500	0.5 mi radius. Daily SR-SS.
(c) Richland Arpt	8 NM; 270° Pasco	13,000	2 NM radius. Continuous.
(c) Ritzville, West Plains Skydiving			
Drop Zone	36.4 NM; 207° Spokane	15,000	2 NM radius. SR-SS weekends, 1700-SS weekdays. Heavy use Apr-Nov.
(c) Shelton, Sanderson Fld Arpt	19 NM; 309° Olympia	14,000	2 NM radius. Daily 0800-2300.
(c) Snohomish, Harvey Fld	7 NM; 078° Paine	15,000	2 NM radius. Continuous.
(c) Snohomish, Harvey Fld	8 NM; 075° Paine	15,000	1 NM radius. Continuous.
(c) Spokane, Hayford Drop Zone	12 NM; 340° Spokane	10,000	0.5 NM radius. Occasional use.
(c) Tacoma, McChord AFB	28 NM, 181° Seattle	15,000	Weekends and occasional nights.
(c) Tekoa, Willard Fld	31 NM; 110° Spokane	12,500	1 NM radius. Daily.
(c) Toledo, Ed Carlson Mem Fld–South			
Lewis Co	30 NM; 150° Olympia	12,500	5 NM radius. Continuous.

The purpose of this bulletin is to provide major changes in aeronautical information that have occurred since the last publication date of each Sectional Aeronautical, VFR Terminal Area, and Helicopter Route Charts listed. The general policy is to include only those changes to controlled airspace and special use airspace that present a hazardous condition or impose a restriction on the pilot, and major changes to airports and radio navigational facilities, thereby providing the VFR pilot with the essential data necessary to update and maintain chart currency. The data is grouped by type and then by effective date. When a new edition of the Aeronautical Chart is published, the corrective tabulation will be removed from this bulletin. Inasmuch as this Bulletin provides major changes only, pilots should consult the airport listing in this directory for all new information. Users of U.S. World Aeronautical Charts (WAC) and U.S. Gulf Coast VFR Aeronautical Charts should consult the appropriate Sectional and VFR Terminal Area Charts for revisions.

Military Training Routes (MTRs) are shown on Sectional Aeronautical Charts, VFR Terminal Area, and Helicopter Route Charts. Only the route centerline, direction of flight and the route designator are shown — route widths and altitudes are not shown. Since these routes are subject to change every 56 days and the charts are reissued generally every 6 months, routes with a change in the alignment of the charted route centerline will be listed in this Aeronautical Chart Bulletin below. You are advised to contact the nearest FSS for route dimensions and current status for those routes affecting your flight.

BILLINGS SECTIONAL 78th Edition. 27 Aug 2009

OBSTRUCTIONS 27 Aug 2009 No Major Changes. 22 Oct 2009 Add obst 2409'MSL (310'AGL)UC, 46°33'37"N, 101°12'48"W. Add obst 1981'MSL (295'AGL)UC, 46°23'06"N, 100°37'17"W. Add obst 2361'MSL (260'AGL)UC, 47°34'40"N, 100°36'13"W. Add obst 2237'MSL (260'AGL)UC, 47°24'38"N, 100°35'22"W. Add obst 2437'MSL (260'AGL)UC, 46°31'55"N, 101°33'11"W. **AIRPORTS 27 Aug 2009** No Major Changes. **22 Oct 2009** Delete MORGAN arpt, 49°00′00″N, 107°49′32″W. Delete DORBRINSKI arpt, 47°53′52″N, 101°51′17″W. Delete LOHSE arpt. 48°34′43″N. 103°27′59″W.

27 Aug 2009 No Major Changes. **22 Oct 2009** Delete PARSHALL NDB, 47°56′10″N, 102°08′14″W.

BELLE CREEK arpt abandoned, 45°07'30"N, 105°05'32"W,

AIRSPACE

27 Aug 2009 No Major Changes.
22 Oct 2009 Add PLENTYWOOD, MT Class E: That airspace extending upward from 700 feet above the surface within a 6.8-mile radius of Plentywood Sher-Wood Airport; and that airspace extending upward from 1,200 feet above the surface of the earth bounded by a line beginning at 49°00'00"N, 105°02′00″W; to 49°00′00″N, 104°02′00″W; to 48°32′35″N, 104°02′00″W; to 48°27′00″N, 104°11′12″W; to 48°40′00″N, 105°02′00″W; thence to the point of origin.

SPECIAL USE AIRSPACE

27 Aug 2009 - 22 Oct 2009 No Major Changes.

MILITARY TRAINING ROUTES

27 Aug 2009 - 22 Oct 2009 No Major Changes.

27 Aug 2009 - 22 Oct 2009 No Major Changes.

CF-16 WORLD AERONAUTICAL CHART 38th Edition, 15 Jan 2009

OBSTRUCTIONS

12 Mar 2009 - 22 Oct 2009 No Major Changes.

12 Mar 2009 - 22 Oct 2009 No Major Changes.

12 Mar 2009 Change ROME VORTAC freq from 122.5 to 112.5, 42°35′26″N, 117°52′05″W. 7 May 2009 - 22 Oct 2009 No Major Changes.

AIRSPACE

12 Mar 2009 - 22 Oct 2009 No Major Changes.

SPECIAL USE AIRSPACE

12 Mar 2009 - 22 Oct 2009 No Major Changes.

MILITARY TRAINING ROUTES

12 Mar 2009 - 22 Oct 2009 No Major Changes.

MISCELLANEOUS

12 Mar 2009 - 22 Oct 2009 No Major Changes.

CHEYENNE SECTIONAL 80th Edition, 30 Jul 2009

OBSTRUCTIONS

27 Aug 2009 Add windmill farm. 6365'UC is highest MSL, 43°04'40"N, 105°50'43"W.

27 Add obst 6988′MSL (407′AGL)UC, 41°0823″N, 104°59′52″W. **22 Oct 2009** Add obst 7523′MSL (263′AGL)UC, 41°3915″N, 106°04′16″W. Add obst 7508′MSL (391′AGL)UC, 41°4022″N, 105°59′52″W. Add obst 5157′MSL (258′AGL)UC, 42°4104″N, 103°55′53″W.

AIRPORTS

27 Aug 2009 - 22 Oct 2009 No Major Changes.

27 Aug 2009 Delete ANTELOPE NDB, 41°36'15"N, 109°00'06"W.

22 Oct 2009 No Major Changes.

AIRSPACE

27 Aug 2009 Add RUSHVILLE, NE Class E: That airspace extending upward from 700 feet above the surface within a 7.3-mile radius of Modisett airport. 22 Oct 2009 No Major Changes.

SPECIAL USE AIRSPACE

27 Aug 2009 - 22 Oct 2009 No Major Changes.

MILITARY TRAINING ROUTES

27 Aug 2009 - 22 Oct 2009 No Major Changes.

MISCELLANEOUS

27 Aug 2009 - 22 Oct 2009 No Major Changes.

GREAT FALLS SECTIONAL 77th Edition, 2 Jul 2009

OBSTRUCTIONS

2 Jul 2009 No Major Changes.

27 Aug 2009 Add obst 4190′MSL (300′AGL)UC, 48°32′20″N, 112°14′12″W.

Add windmill farm 4208'UC is highest MSL, 48°32'01"N, 112°08'37"W.

22 Oct 2009 No Major Changes.

AIRPORTS

2 Jul 2009 No Major Changes.

27 Aug 2009 Delete COTTONTAIL arpt, 46°07′56″N, 110°02′50″W.

Delete FRAMPTON arpt, 47°58'43"N, 115°46'05"W.

Change MISSOULA INTL ATCT freq from 387.1 to 377.175, 46°54′59″N, 114°05′26″W.

22 Oct 2009 No Major Changes.

NAVAIDs

2 Jul 2009 No Major Changes.

27 Aug 2009 Add LEENY NDB, freq 347, ident (LEN), class MHW, 47°44′34″N, 116°57′40″W. **22 Oct 2009** No Major Changes.

AIDCDACE

2 Jul 2009 -22 Oct 2009 No Major Changes.

SPECIAL USE AIRSPACE

2 Jul 2009 - 22 Oct 2009 No Major Changes.

MILITARY TRAINING ROUTES

2 Jul 2009 - 22 Oct 2009 No Major Changes.

MISCELLANEOUS

2 Jul 2009 - 22 Oct 2009 No Major Changes.

KLAMATH FALLS SECTIONAL 81st Edition, 24 Sep 2009

OBSTRUCTIONS

22 Oct 2009 No Major Changes.

AIRPORTS

22 Oct 2009 Delete RED & WHITE arpt, 43°07′09″N, 121°02′41″W. Delete UNITY arpt, 44°27′05″N, 118°11′12″W.

NAVAIDS

22 Oct 2009 No Major Changes.

AIRSPACE

22 Oct 2009 Add NORTH BEND, OR Class D: That airspace extending upward from the surface to and including 2500 feet MSL within a 4.2-mile radius of the Southwest Oregon Regional Airport. This Class D airspace area is effective during the specific dates and times established in advance by a Notice to Airmen. The effective date and time will thereafter be continuously published in the Airport/Facility Directory.

SPECIAL USE AIRSPACE

22 Oct 2009 No Major Changes.

MILITARY TRAINING ROUTES

22 Oct 2009 No Major Changes.

MISCELLANEOUS

22 Oct 2009 No Major Changes.

SALT LAKE CITY HELICOPTER ROUTE CHART 3rd Edition, 26 Oct 2006

OBSTRUCTIONS

23 Nov 2006 - 22 Oct 2009 No Major Changes.

23 Nov 2006 - 10 Apr 2008 No Major Changes.

5 Jun 2008 Delete PAYNE arpt, 41°05′54″N, 112°06′56″W. Delete WARD heli, 40°35′59″N, 111°48′03″W. **31 Jul 2008 – 20 Nov 2008** No Major Changes.

20 Nov 2008 Delete CHANNEL 4 heli, 40°43′57″N, 111°57′20″W.

15 Jan 2009 - 22 Oct 2009 No Major Changes.

23 Nov 2006 - 22 Oct 2009 No Major Changes.

23 Nov 2006 - 22 Oct 2009 No Major Changes.

SPECIAL USE AIRSPACE

23 Nov 2006 - 22 Oct 2009 No Major Changes.

MILITARY TRAINING ROUTES

23 Nov 2006 - 22 Oct 2009 No Major Changes.

MISCELLANEOUS

23 Nov 2006 - 22 Oct 2009 No Major Changes.

SALT LAKE CITY SECTIONAL 82nd Edition, 22 Oct 2009

OBSTRUCTIONS

22 Oct 2009 No Major Changes.

AIRPORTS

22 Oct 2009 No Major Changes.

NAVAIDs

22 Oct 2009 No Major Changes.

AIRSPACE

22 Oct 2009 No Major Changes.

SPECIAL USE AIRSPACE

22 Oct 2009 No Major Changes.

MILITARY TRAINING ROUTES

22 Oct 2009 No Major Changes.

MISCELLANEOUS

22 Oct 2009 No Major Changes.

SALT LAKE CITY TERMINAL AREA CHART 41st Edition, 22 Oct 2009

OBSTRUCTIONS

22 Oct 2009 No Major Changes.

AIRPORTS

22 Oct 2009 No Major Changes.

NAVAIDs

22 Oct 2009 No Major Changes.

AIRSPACE 22 Oct 2009 No Major Changes.

SPECIAL USE AIRSPACE

22 Oct 2009 No Major Changes.

MILITARY TRAINING ROUTES

22 Oct 2009 No Major Changes.

MISCELLANEOUS

22 Oct 2009 No Major Changes.

SEATTLE SECTIONAL 77th Edition, 4 Jun 2009

OBSTRUCTIONS

2 Jul 2009 Add obst 550'MSL (215'AGL), 49°02'34"N, 122°49'03"W. **27 Aug 2009** Add obst 2337'MSL (255'AGL)UC, 48°00'59"N, 122°55'39"W. Add windmill farm 2971'UC is highest MSL, 45°41'23"N, 120°53'05"W. **22 Oct 2009** Add obst 1310'MSL(226'AGL), 45°05'38"N, 123°57'21"W. Add obst 3755'MSL(250'AGL)UC, 45°35'08"N, 1183°55'01"W. Add obst 2156'MSL(316'AGL), 46°01'02"N, 122°46'44"W.

AIRPORTS

2 Jul 2009 Delete COLLINS arpt, 44°44′59″N,, 120°12′04″W.
Add RP 15R to HARVEY arpt, 47°54′18″N,, 122°06′10″W.
27 Aug 2009 Add CTAF 122.8 at APEX arpt, 47°39′24″N, 122°43′59″W.
Add CTAF 122.9 at PAGE arpt, 46°00′55″N, 118°22′14″W.
Add RP 35 to APEX arpt, 47°39′24″N, 122°43′59″W.
22 Oct 2009 Change RP 33 to RP 34 at RENTON MUNI arpt, 47°29′35″N, 122°12′57″W.
Change RP 8, 11 to RP 8, 12 at LEWISTON-NEZ PERCE CO arpt, 46°22′28″N, 117°00′55″W.
Delete UNITY arpt, 44°27′04″N, 118°11′12″W.

ΝΔΥΔΙΩς

2 Jul 2009 No Major Changes.

27 Aug 2009 Add LEENY NDB, freq 347, ident (LEN), class MHW, 47°44′34″N, 116°57′40″W. **22 Oct 2009** No Major Changes.

AIRSPACE

beginning.

2 Jul 2009 Add ABBOTSFORD, BC, CANADA Transition Area. The airspace above 1500' AGL within the area bounded by a line beginning at 49°00'08.80"N, 122°11'12.69"W thence counter-clockwise along the arc of a circle of 7 miles radius centered on 49°01'31.00"N, 122°21'38.00"W to 49°06'30.52"N, 122°14'10.65"W to 49°06'30.70"N, 122°18'12.85"W to 49°09'05.09"N, 122°17'43.73"W to 49°11'19.42"N, 121°57'23.50"W to 49°08'37.52"N, 121°57'23.50"W to 49°00'08.70"N, 122°09'41.40"W thence westerly along the Canada-United States boundary to 49°00'08.80"N, 122°11'12.69"W point of beginning.

Revise VANCOUVER, BC, CANADA Transition Area. The airspace above 1200' AGL within the area bounded by a line beginning at $48^\circ59'08.26''N$, $123^\circ52'21.39''W$ thence clockwise along the arc of a circle of 30 miles radius centered on $49^\circ11'42.00''N$, $123^\circ10'55.00''W$ to $49^\circ28'08.65''N$, $123^\circ49'14.20''W$ to $49^\circ11'42.00''N$, $123^\circ27'28.66''W$ thence counter-clockwise along the arc of a circle of 13 miles radius centered on $49^\circ11'42.00''N$, $123^\circ10'55.00''W$ to $49^\circ11'40.43''N$, $123^\circ30'44.17''W$ to $48^\circ50'20.23''N$, $123^\circ30'36.04''W$ thence clockwise along the arc of a circle of 25 miles radius centered on $49^\circ11'42.00''N$, $123^\circ30'36.04''W$ thence clockwise along the arc of a circle of 25 miles radius centered on $49^\circ11'42.00''N$, $123^\circ10'55.00''W$ to $49^\circ01'15.10''N$, $123^\circ45'27.84''W$ to $48^\circ59'08.26''N$, $123^\circ52'21.39''W$ point of beginning.

Add VICTORIA, BC, CANADA Transition Area. The airspace above 1200' AGL within the area bounded by a line beginning at 48°43'41.69"N, 123°08'48.26"W to 48°53'54.46"N, 123°07'53.50"W Canada-United States boundary to 48°49'52.40"N, 123°00'30.60"W Canada-United States boundary to 48°46'01.60"N, 123°00'30.60"W Canada-United States boundary to 48°43'41.69"N, 123°08'48.26"W point of beginning. Add VICTORIA HARBOUR, BC, CANADA Transition Area. The airspace above 700' AGL within the area bounded by a line beginning at 48°17'02.50"N, 123°14'54.40"W Canada-United States boundary to 48°20'53.13"N, 123°26'34.07"W thence clockwise along the arc of a circle of 5 miles radius centered on 48°25'22.00"N, 123°23'15.00"W to 48°22'19.13"N, 123°29'11.73"W to 48°26'24.52"N, 123°33'56.16"W to 48°27'33.05"N, 123°31'42.78"W to 48°32'14.86"N, 123°29'08.95"W thence counter-clockwise along the arc of a circle of 7 miles radius centered on 48°38'49.30"N, 123°25'32.80"W to 48°38'28.32"N, 123°15'00.24"W thence south along the Canada-United States

boundary to 48°17'02.50"N, 123°14'54.40"W point of beginning.

Revise VANCOUVER, BC, CANADA Terminal Control Area. Class D airspace above 1200' AGL to 2500' within the area bounded by a line beginning at 48°41'41.16"N, 123°15'54.65"W Canada-United States boundary thence counter-clockwise along the arc of a circle of 7 miles radius centered on 48°38'49.30"N, 123°25'32.80"W to 48°45'45.19"N, 123°24'08.00"W to 48°48'09.82"N, 123°23'38.13"W thence clockwise along the arc of a circle of 25 miles radius centered on 49°11'42.00"N, 123°10'55.00"W to 48°50'20.23"N, 123°30'36.04"W to 49°11'40.43"N,

123°30′44.17″W thence counter-clockwise along the arc of a circle of 13 miles radius centered on 49°11′42.00″N, 123°10′55.00″W to 49°00′07.50″N, 123°19′53.57″W to 49°00′07.50″N, 123°19′20.10″W thence south-east along the Canada-United States boundary to 48°53′54.46″N, 123°07′53.50″W Canada-United States boundary to 48°41′41.16″N, 123°15′54.65″W Canada-United States boundary to 48°41′41.16″N, 123°15′54.65″W Canada-United States boundary point of beginning.

Class D airspace above 1500' to 2500' within the area bounded by a line beginning at 49°00'07.51"N, 122°45'36.99"W Canada-United States boundary to 49°01'55.68"N, 122°45'36.99"W to 49°01'56.09"N, 122°33'17.10"W to 49°00'07.92"N, 122°33'17.10"W thence west along the Canada-United States boundary to 49°00'07.51"N, 122°45'36.99"W Canada-United States boundary point of beginning. Class C airspace above 1200' to 2500' within the area bounded by a line beginning at 49°07'14.40"N, 123°02'42.13"W thence counter-clockwise along the arc of a circle of 7 miles radius centered on 49°11'42.00"N, 123°10'55.00"W to 49°15'16.31"N, 123°01'44.14"W to 49°15'16.95"N, 122°53'19.25"W to 49°07'14.40"N, 123°02'42.13"W point of

CONTINUED ON NEXT PAGE

CONTINUED FROM PRECEDING PAGE

```
Class C airspace above 2500^{\circ} to 4500^{\circ} within the area bounded by a line beginning at 48^{\circ}17^{\circ}02.50^{\circ}N, 123^{\circ}14^{\prime}54.40^{\circ}W Canada-United States boundary to 48^{\circ}20^{\prime}53.13^{\circ}N, 123^{\circ}26^{\prime}34.07^{\circ}W thence clockwise along the arc of a circle of 5 miles radius centered on 48^{\circ}25^{\prime}22.00^{\circ}N, 123^{\circ}23^{\prime}15.00^{\circ}W to
48°22′19.13″N, 123°29′11.73″W to 48°26′24.52″N, 123°33′56.16″W to 48°27′33.05″N,
123°31'42.78"W to 48°32'14.86"N, 123°29'08.95"W thence clockwise along the arc of a circle of 7
miles radius centered on 48^\circ38'49.30''N, 123^\circ25'32.80''W to 48^\circ45'45.19''N, 123^\circ24'07.78''W to 48^\circ48'09.82''N, 123^\circ23'38.13''W thence clockwise along the arc of a circle of 25 miles radius centered
on 49°11′42.00″N, 123°10′55.00″W to 49°01′15.10″N, 123°45′27.84″W to 48°59′08.26″N,
123^\circ52'21.39''W thence clockwise along the arc of a circle of 30 miles radius centered on 49^\circ11'42.00''N, 123^\circ10'55.00''W to 49^\circ11'27.86''N, 123^\circ56'36.76''W to 49^\circ18'12.62''N, 124^\circ03'22.44''W thence clockwise along the arc of a circle of 35 miles radius centered on
49°11′42.00″N. 123°10′55.00″W to 49°30′52.39″N, 123°55′41.18″W to
49°18′51.32″N,123°27′28.66″W thence clockwise along the arc of a circle of 13 miles radius centered
on 49°11'42.00"N, 123°10'55.00"W to 49°23'53.71"N, 123°17'43.39"W to 49°20'08.72"N, 123°15'37.38"W to 49°20'04.85"N, 123°03'25.40"W to 49°18'50.01"N, 123°01'44.09"W to
49°15′16.31″N, 123°01′44.14″W to 49°15′17.00″N, 122°45′30.28″W thence clockwise along the arc of
a circle of 3 miles radius centered on 49°12′58.00″N, 122°42′36.00″W to 49°14′11.84″N,
122°38′25.62″W to 49°07′16.72″N, 122°33′41.11″W thence clockwise along the arc of a circle of 3
miles radius centered on 49°06′03.00″N, 122°37′51.00″W to 49°06′02.91″N, 122°33′17.10″W to
49°00'07.92"N, 122°33'17.10"W thence west along the Canada-United States boundary to
48°17'02.50"N, 123°14'54.40"W Canada-United States boundary point of beginning. Note: The
Vancouver TCA also contains that portion of airspace, south of the Canada-United States boundary, within
16 NM of the Vancouver VOR that is defined in U.S. publications.
Class C airspace above 4500' to 6500' within the area bounded by a line beginning at 48°17'02.50"N,
123°14′54.40″W Canada-United States boundary to 48°20′53.13″N, 123°26′34.07″W thence clockwise
along the arc of a circle of 5 miles radius centered on 48°25′22.00″N, 123°23′15.00″W to
48°22′19.13″N. 123°29′11.73″W to 48°26′24.52″N. 123°33′56.16″W to 48°27′33.05″N.
123°31'42.78"W to 48°32'14.86"N, 123°29'08.95"W thence clockwise along the arc of a circle of 7
miles radius centered on 48°38'49.30"N, 123°25'32.80"W to 48°45'45.19"N, 123°24'07.78"W to
48°48'09.82"N, 123°23'38.13"W thence clockwise along the arc of a circle of 25 miles radius centered on 49°11'42.00"N, 123°10'55.00"W to 49°01'15.10"N, 123°45'27.84"W to 48°57'01.19"N,
123°59′13.76″W thence clockwise along the arc of a circle of 35 miles radius centered on
49°11′42.00″N. 123°10′55.00″W to 49°30′52.39″N. 123°55′41.18″W to 49°18′51.32″N.
123°27′28.66″W thence clockwise along the arc of a circle of 13 miles radius centered on
49°11′42.00″N, 123°10′55.00″W to 49°23′53.71″N, 123°17′43.39″W to 49°20′08.72″N,
123°15′37.38″W to 49°20′04.85″N, 123°03′25.40″W to 49°18′50.00″N, 123°01′44.09″W to
49°18′50.00″N. 122°32′37.30″W to 49°09′05.09″N. 122°17′43.73″W to 49°06′30.70″N.
122°18′12.85″W to 49°06′30.52″N, 122°14′10.65″W thence clockwise along the arc of a circle of 7
miles radius centered on 49°01'31.00"N, 122°21'38.00"W to 49°00'08.80"N, 122°11'12.69"W thence
west along the Canada-United States boundary to 48°17′02.50″N, 123°14′54.40″W Canada-United
States boundary point of beginning.
Class C airspace above 700' AGL to 6500' within the area bounded by a line beginning at
48°32′53.59"N, 123°31′08.11"W to 48°38′02.02"N, 123°43′36.07"W thence clockwise along the arc of
a circle of 12 miles radius centered on 48°38'49.30"N, 123°25'32.80"W to 48°50'20.23"N,
123°30′36.04″W thence counter-clockwise along the arc of a circle of 25 miles radius centered on
49°11′42.00″N, 123°10′55.00″W to 48°48′09.82″N, 123°23′38.13″W to 48°45′45.19″N,
123^\circ24'07.78''\!W thence counter-clockwise along the arc of a circle of 7 miles radius centered on 48^\circ38'49.30''\!N,\,123^\circ25'32.80''\!W to 48^\circ32'53.59''\!N,\,123^\circ31'08.11''\!W point of beginning.
Class C airspace above 3000' to 6500' within the area bounded by a line beginning at 48°26'24.52"N,
123°33′56.16″W to 48°30′44.98″N, 123°38′59.14″W thence clockwise along the arc of a circle of 12
miles radius centered on 48°38'49.30"N, 123°25'32.80"W to 48°38'02.02"N, 123°43'36.07"W to
48^{\circ}32'53.59''N,\,123^{\circ}31'08.11''W thence counter-clockwise along the arc of a circle of 7 miles radius centered on 48^{\circ}38'49.30''N,\,123^{\circ}25'32.80''W to 48^{\circ}32'14.86''N,\,123^{\circ}29'08.95''W to 48^{\circ}27'33.05''N,\,123^{\circ}29'08.95''W to 48^{\circ}32'14.86''N,\,123^{\circ}29'08.95''W to 48^{\circ}27'33.05''N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123^{\circ}29'N,\,123
123°31'42.78"W to 48°26'24.52"N, 123°33'56.16"W point of beginning.
Class C airspace above 3500' to 6500' within the area bounded by a line beginning at 48°38'02.02"N,
123°43'36.07"W thence clockwise along the arc of a circle of 40 miles radius centered on 49°11'42.00"N, 123°10'55.00"W to 48°42'23.14"N, 123°52'10.08"W thence clockwise along the arc of a circle of 18 miles radius centered on 48°38'49.30"N, 123°25'32.80"W to 48°54'35.83"N,
123°38′35.92″W thence counter-clockwise along the arc of a circle of 25 miles radius centered on
49°11′42.00″N, 123°10′55.00″W to 48°50′20.Ž3″N, 123°30′36.04″W thence counter-clockwise along the arc of a circle of 12 miles radius centered on 48°38′49.30″N, 123°25′32.80″W to 48°38′02.02″N,
123°43'36.07"W point of beginning.
Class C airspace above 5500' to 6500' within the area bounded by a line beginning at 48°47'32.39"N.
123°49'18.43"W thence clockwise along the arc of a circle of 35 miles radius centered on
49^{\circ}11'42.00''N, 123^{\circ}10'55.00''W to 48^{\circ}57'01.19''N, 123^{\circ}59'13.76''W to 49^{\circ}01'15.10''N,
123°45′27.84″W thence counter-clockwise along the arc of a circle of 25 miles radius centered on
49°11′42.00″N, 123°10′55.00″W to 48°54′35.83″N, 123°38′35.92″W thence counter-clockwise along
the arc of a circle of 18 miles radius centered on 48°38'49.30"N, 123°25'32.80"W to 48°47'32.39"N,
```

123°49′18.43″W point of beginning. Class C airspace above 3200′ to 6500′ within the area bounded by a line beginning at 49°18′51.32″N, 123°27′28.66″W to 49°21′02.94″N, 123°32′35.37″W thence clockwise along the arc of a circle of 17 miles radius centered on 49°11′42.00″N, 123°10′55.00″W to 49°27′39.24″N, 123°19′50.04″W to 49°23′53.71″N, 123°17′43.39″W thence counter-clockwise along the arc of a circle of 13 miles radius centered on 49°11′42.00″N, 123°10′55.00″W to 49°18′51.32″N, 123°27′28.66″W point of beginning.

CONTINUED FROM PRECEDING PAGE

Class C airspace above 5000' to 6500' within the area bounded by a line beginning at $49^{\circ}21'02.94\text{"N}, 123^{\circ}32'35.37\text{"W}\ to <math display="inline">49^{\circ}24'19.57\text{"N}, 123^{\circ}40'15.43\text{"W}\ thence clockwise along the arc of a circle of 23 miles radius centered on <math display="inline">49^{\circ}11'42.00\text{"N}, 123^{\circ}10'55.00\text{"W}\ to <math display="inline">49^{\circ}33'16.91\text{"N}, 123^{\circ}23'00.30\text{"W}\ to <math display="inline">49^{\circ}27'39.24\text{"N}, 123^{\circ}19'50.04\text{"W}\ thence counter-clockwise along the arc of a circle of 17 miles radius centered on <math display="inline">49^{\circ}11'42.00\text{"N}, 123^{\circ}10'55.00\text{"W}\ to <math display="inline">49^{\circ}21'02.94\text{"N}, 123^{\circ}32'35.37\text{"W}\ point of beginning.}$ Class C airspace above 5500' to 6500' within the area bounded by a line beginning at $49^{\circ}00'08.80\text{"N}, 122^{\circ}11'12.69\text{"W}\ Canada-United States boundary thence counter-clockwise along the arc of a circle of 7 miles radius centered on <math display="inline">49^{\circ}01'31.00\text{"N}, 122^{\circ}21'38.00\text{"W}\ to <math display="inline">49^{\circ}06'30.52\text{"N}, 122^{\circ}14'10.65\text{"W}\ to }49^{\circ}11'29.75\text{"N}, 121^{\circ}47'06.54\text{"W}\ to }49^{\circ}00'02.61\text{"N}, 121^{\circ}58'45.95\text{"W}\ thence west along the Canada-United States boundary to }49^{\circ}00'08.80\text{"N}, 122^{\circ}11'12.69\text{"W}\ Canada-United States boundary point of beginning.}$

Class C airspace above 6500' to 8500' within the area bounded by a line beginning at 48°17'02.50"N, 123°14'54.40"W Canada-United States boundary to 48°20'53.13"N, 123°26'34.07"W thence clockwise along the arc of a circle of 5 miles radius centered on 48°25'22.00"N, 123°23'15.00"W to 48°20'19.13"N, 123°29'11.73"W to 48°30'44.98"N, 123°38'59.14"W thence clockwise along the arc of a circle of 12 miles radius centered on 48°38'49.30"N, 123°25'32.80"W to 48°38'02.02"N, 123°43'36.07"W thence clockwise along the arc of a circle of 40 miles radius centered on 49°11'42.00"N, 123°10'55.00"W to 48°42'23.14"N, 123°52'10.08"W thence clockwise along the arc of a circle of 18 miles radius centered on 48°38'49.30"N, 123°25'32.80"W to 48°47'32.39"N, 123°49'18.43"W thence clockwise along the arc of a circle of 35 miles radius centered on 49°11'42.00"N, 123°10'55.00"W to 49°38'57.73"N, 123°44'29.36"W to 49°37'01.00"N, 123°10'55.00"W to 49°38'57.73"N, 123°44'29.36"W to 49°37'01.00"N, 123°10'55.00"W to 49°38'57.73"N, 123°44'29.36"W to 49°37'04.94'26.65"W thence clockwise along the arc of a circle of 55 miles radius centered on 49°11'42.00"N, 123°10'55.00"W to 49°11'29.75"N, 121°47'06.54"W to 49°00'02.61"N, 121°58'45.95"W thence west along the Canada-United States boundary to 48°17'02.50"N, 123°14'54.40"W Canada-United States boundary point of beginning.

Class C airspace above 8500' to 9500' within the area bounded by a line beginning at 48°17'02.50"N, 123°14'54.40"W Canada-United States boundary to 48°20'53.10"N, 123°26'34.07"W thence clockwise along the arc of a circle of 5 miles radius centered on 48°25'22.00"N, 123°23'15.00"W to 48°22'19.13"N, 123°29'11.73"W to 48°30'44.98"N, 123°38'59.14"W thence clockwise along the arc of a circle of 12 miles radius centered on 48°38'49.30"N, 123°25'32.80"W to 48°38'02.02"N, 123°43'36.07"W thence clockwise along the arc of a circle of 40 miles radius centered on 49°11'42.00"N, 123°10'55.00"W to 48°42'23.14"N, 123°52'10.08"W thence clockwise along the arc of a circle of 18 miles radius centered on 48°38'49.30"N, 123°52'32.80"W to 48°47'32.39"N, 123°49'18.43"W thence clockwise along the arc of a circle of 35 miles radius centered on 49°11'42.00"N, 123°10'55.00"W to 49°21'58.65"N, 122°19'50.73"W to 49°25'47.09"N, 121°49'42.65"W thence clockwise along the arc of a circle of 55 miles radius centered on 49°11'42.00"N, 123°10'55.00"W to 49°11'29.75"N, 121°47'06.54"W to 49°00'02.61"N, 121°58'45.95"W thence west along the Canada-United States boundary to 48°17'02.50"N, 123°14'54.40"W Canada-United States boundary point of beginning.

Class C airspace above 9500' to 12,500' within the area bounded by a line beginning at 48°17'02.50"N, 123°14'54.40"W Canada-United States boundary to 48°0'05'34.07"W thence clockwise

Class C airspace above 9500' to 12,500' within the area bounded by a line beginning at 48°17'02.50"N, 123°14'54.40"W Canada-United States boundary to 48°20'53.13"N, 123°26'34.07"W thence clockwise along the arc of a circle of 5 miles radius centered on 48°25'22.00"N, 123°23'15.00"W to 48°22'19.13"N, 123°29'11.73"W to 48°30'44.98"N, 123°38'59.14"W thence clockwise along the arc of a circle of 45 miles radius centered on 49°11'42.00"N, 123°310'55.00"W to 49°19'04.26"N, 124°18'39.45"W to 49°25'16.60"N, 124°00'12.25"W thence clockwise along the arc of a circle of 35 miles radius centered on 49°11'42.00"N, 123°10'55.00"W to 49°28'56.32"N, 123°57'28.70"W to 49°36'49.14"N, 124°08'05.46"W thence clockwise along the arc of a circle of 45 miles radius centered on 49°11'42.00"N, 123°10'55.00"W to 49°23'54.25"N, 122°04'44.02"W to 49°25'48.80"N, 121°49'41.00"W thence clockwise along the arc of a circle of 55 miles radius centered on 49°11'42.00"N, 123°10'55.00"W to 49°23'54.25"N, 122°04'44.02"W to 49°25'48.80"N, 121°45'45.95"W thence west along the Canada-United States boundary to 48°17'02.50"N, 123°14'54.40"W Canada-United States boundary point of beginning. Revise ABBOTSFORD, BC, CANADA Class C Control Zone. The airspace to 4500' (4300' AAE) within the

Revise ABBOTSFORD, BC, CANADA Class C Control Zone. The airspace to 4500' (4300' AAE) within the area bounded by a line beginning at 49°00'07.92"N, 122°33'17.10"W to 49°01'56.09"N, 122°33'17.10"W to 49°01'56.09"N, 122°21'12.14"W thence clockwise along the arc of a circle of 5 miles radius centered on 49°01'31.00"N, 122°21'38.00"W to 49°06'30.75"N, 122°21'38.00"W to 49°06'30.52"N, 122°11'38.00"W to 49°06'30.52"N, 122°11'38.00"W to 49°00'07.91"12.69"W thence westerly along the Canada-United States boundary to 49°00'07.92"N, 122°33'17.10"W point of beginning. Note: The Abbotsford Control Zone also contains a portion south of the Canada-United States boundary that is defined in U.S. publications.

Revise BOUNDARY BAY, BC, CANADA Class C Control Zone. The airspace to 1000' (1000' AAE) within the area bounded by a line beginning at $49^\circ00'7.50''N$, $123^\circ05'05.00''W$ to $49^\circ05'50.73''N$, $123^\circ05'05.00''W$ thence counter-clockwise along the arc of a circle of 7 miles radius centered on $49^\circ11'42.00''N$, $123^\circ10'55.00''W$ to $49^\circ07'14.40''N$, $123^\circ02'42.13''W$ to $49^\circ07'14.68''N$, $122^\circ57'30.00''W$ to $49^\circ00'07.73''N$, $122^\circ57'30.00''W$ thence westerly along the Canada-United States boundary to $49^\circ00'07.50''N$, $123^\circ05'05.00''W$ point of beginning. The airspace above 1000' (1000' AAE) to 2500' (2500' AAE) within the area bounded by a line beginning at $49^\circ00'07.50''N$, $123^\circ05'05.00''W$ to $49^\circ05'50.73''N$, $123^\circ05'05.00''W$ thence counter-clockwise along the arc of a circle of 7 miles radius centered on $49^\circ11'42.00''N$, $123^\circ10'55.00''W$ to $49^\circ07'14.40''N$, $123^\circ02'42.13''W$ to $49^\circ07'14.71''N$, $122^\circ51'19.49''W$ to $49^\circ00'07.50''N$, $123^\circ05'05.00''W$ point of beginning.

CONTINUED ON NEXT PAGE

CONTINUED FROM PRECEDING PAGE

Revise VICTORIA, BC, CANADA Class C Control Zone. The airspace to 2500' (2400' AAE) within the area bounded by a line beginning at 48°38'28.32"N, 123°15'00.24"W Canada-United States boundary thence clockwise along the arc of a circle of 7 miles radius centered on 48°38'49.30"N, 123°25'32.80"W to 48°41'41.16"N, 123°15'54.65"W Canada-United States boundary to 48°38'28.32"N, 123°15'00.24"W Canada-United States boundary point of beginning. Add VANCOUVER OUTER CONTROL ZONE, BC, CANADA Class C Control Zone. The airspace above 800' (800' AAE) to 2500' within the area bounded by a line beginning at 49°00'07.50"N, 123°19'20.10"W Canada-United States boundary to 49°00′07.50"N, 123°19′53.57"W thence clockwise along the arc of a circle of 13 miles radius centered on 49°11'42.00"N, 123°10'55.00"W to 49°20'10.99"N, 123°25′56.81″W to 49°20′08.72″N. 123°15′37.38″W to 49°16′36.06″N. 123°13′38.60″W to 49°16′36.00″N, 123°18′33.00″W thence counter-clockwise along the arc of a circle of 7 miles radius centered on 49°11'42.00"N, 123°10'55.00"W to 49°05'50.73"N, 123°05'05.00"W to 49°00'07.50"N, 123°05′05.00″W to 49°00′07.50″N, 123°19′20.10″W Canada-United States boundary point of beginning. Revise VANCOUVER OUTER CONTROL ZONE, BC, CANADA Class D Control Zone. The airspace to 800' (800' AAE) within the area bounded by a line beginning at 49°00'07.50"N, 123°19'20.10"W Canada-United States boundary to 49°00'07.50"N, 123°19'53.57"W thence clockwise along the arc of a circle of 13 miles radius centered on 49°11′42.00″N, 123°10′55.00″W to 49°20′10.99″N, 123°25′56.81″W to 49°20′08.72″N, 123°15′37.38″W to 49°16′36.06″N, 123°13′38.60″W to 49°16'36.00"N, 123°18'33.00"W thence counter-clockwise along the arc of a circle of 7 miles radius centered on 49°11'42,00"N, 123°10'55,00"W to 49°05'50,73"N, 123°05'05,00"W to 49°00'07,50"N, 123°05′05.00″W to 49°00′07.50″N, 123°19′20.10″W Canada-United States boundary point of beginning. Revise NANAIMO, BC, CANADA Class E Control Zone. The airspace to 2500' (2400' AAE) within the area bounded by a line beginning at 49°02'25.14"N, 123°44'41.34"W thence clockwise along the arc of a circle of 5 miles radius centered on 49°03′08.00″N, 123°52′13.00″W to 49°07′25.23″N, 123°48′17.55″W to 49°02′25.14″N, 123°44′41.34″W point of beginning. Revise VANCOUVER, BC, CANADA Class D Transponder Airspace. The airspace above 1200' AGL to 2500' within the area bounded by a line beginning at 48°41′41.16″N. 123°15′54.65″W Canada-United States boundary thence counter-clockwise along the arc of a circle of 7 miles radius centered on 48°38′49.30″N, 123°25′32.80″W to 48°45′45.19″N, 123°24′08.00″W to 48°48′09.82″N, 123°23′38.13″W thence clockwise along the arc of a circle of 25 miles radius centered on 49°11′42.00″N, 123°10′55.00″W to 48°50′20.23″N, 123°30′36.04″W to 49°11′40.43″N, 123°30'44.17"W thence counter-clockwise along the arc of a circle of 13 miles radius centered on 49°11′42.00″N. 123°10′55.00″W to 49°00′07.50″N. 123°19′53.57″W to 49°00′07.50″N. 123°19′20.10″W thence south-east along the Canada-United States boundary to 48°53′54.46″N. 123°07′53.50″W Canada-United States boundary to 48°43′41.69″N, 123°08′48.26″W thence west along the Canada-United States boundary to 48°41'41.16"N, 123°15'54.65"W Canada-United States boundary point of beginning. Add ABBOTSFORD, BC, CANADA Class D Transponder Airspace. The airspace above 1500' to 2500' within the area bounded by a line beginning at $49^{\circ}00'07.51''N$, $122^{\circ}45'36.99''W$ Canada-United States boundary to $49^{\circ}01'55.68''N$, $122^{\circ}45'36.99''W$ to $49^{\circ}01'56.09''N$, $122^{\circ}33'17.10''W$ to $49^{\circ}00'07.92''N$, 122°33'17.10"W thence west along the Canada-United States boundary to 49°00'07.51"N, 122°45′36.99″W Canada-United States boundary point of beginning. Add VANCOUVER OUTER CONTROL ZONE, BC, CANADA Class D Transponder Airspace. The airspace to 800' (800' AAE) within the area bounded by a line beginning at 49°00'07.50"N, 123°19'20.10"W Canada-United States boundary to 49°00'07.50"N, 123°19'53.57"W thence clockwise along the arc of a circle of 13 miles radius centered on 49°11'42.00"N, 123°10'55.00"W to 49°20'10.99"N, 123°25′56.81″W to 49°20′08.72″N, 123°15′37.38″W to 49°16′36.06″N, 123°13′38.60″W to 49°16'36.00"N, 123°18'33.00"W thence counter-clockwise along the arc of a circle of 7 miles radius centered on 49°11'42.00"N, 123°10'55.00"W to 49°05'50.73"N, 123°05'05.00"W to 49°00'07.50"N, 123°05′05.00″W to 49°00′07.50″N, 123°19′20.10″W Canada-United States boundary point of beginning. Add ABBOTSFORD, BC, CANADA Class E Transponder Airspace. The airspace above 1500' AGL within the area bounded by a line beginning at 49°00′08.80″N, 122°11′12.69″W Canada-United States boundary thence counter-clockwise along the arc of a circle of 7 miles radius centered on 49°01′31.00″N, 122°21'38.00"W to 49°06'30.52"N, 122°14'10.65"W to 49°06'30.70"N, 122°18'12.85"W to 49°09′05.09″N, 122°17′43.73″W to 49°11′19.42″N, 121°57′23.50″W to 49°08′37.52″N, $121^{\circ}57'23.50''$ W to $49^{\circ}00'08.70''$ N, $122^{\circ}09'41.40''$ W thence westerly along the Canada-Únited States boundary to $49^{\circ}00'08.80''$ N, $122^{\circ}11'12.69''$ W Canada-United States boundary point of beginning. Add VANCOUVER, BC, CANADA Class E Transponder Airspace. The airspace above 1200' AGL within the area bounded by a line beginning at 48°59'08.26"N, 123°52'21.39"W thence clockwise along the arc of a circle of 30 miles radius centered on 49°11′42.00″N, 123°10′55.00″W to 49°28′08.65″N, 123°49′14.20″W to 49°18′51.32″N, 123°27′28.66″W thence counter-clockwise along the arc of a circle of 13 miles radius centered on 49°11'42.00"N, 123°10'55.00"W to 49°11'40.43"N, 123°30'44.17"W to $48^{\circ}50'20.23''N$, $123^{\circ}30'36.04''W$ thence clockwise along the arc of a circle of 25 miles radius centered on $49^{\circ}11'42.00''N$, $123^{\circ}10'55.00''W$ to $49^{\circ}01'15.10''N$, $123^{\circ}45'27.84''W$ to $48^{\circ}59'08.26''N$,

123°52′21.39″W point of beginning.
Add VICTORIA, BC, CANADA Class E Transponder Airspace. The airspace above 1200′ AGL within the area bounded by a line beginning at 48°43′41.69″N, 123°08′48.26″W to 48°53′54.46″N, 123°07′53.50″W Canada-United States boundary to 48°49′52.40″N, 123°00′30.60″W Canada-United States boundary to 48°46′01.60″N, 123°00′30.60″W Canada-United States boundary to 48°46′01.60″N, 123°00′30.60″W Canada-United States boundary to 48°43′41.69″N, 123°08′48.26″W point of beginning.

CONTINUED ON NEXT PAGE

AERONAUTICAL CHART BULLETIN

CONTINUED FROM PRECEDING PAGE

Add VICTORIA HARBOUR, BC, CANADA Class E Transponder Airspace. The airspace above 700' AGL within the area bounded by a line beginning at $48^{\circ}17^{\circ}02.50^{\circ}N$, $123^{\circ}14^{\circ}54.40^{\circ}W$ Canada-United States boundary to $48^{\circ}20^{\circ}53.13^{\circ}N$, $123^{\circ}26^{\circ}34.07^{\circ}W$ thence clockwise along the arc of a circle of 5 miles radius centered on $48^{\circ}25^{\circ}22.00^{\circ}N$, $123^{\circ}23^{\circ}15.00^{\circ}W$ to $48^{\circ}22^{\circ}19.13^{\circ}N$, $123^{\circ}29^{\circ}11.73^{\circ}W$ to $48^{\circ}26^{\circ}24.52^{\circ}N$, 123°33′56.16″W to 48°27′33.05″N, 123°31′42.78″W to 48°32′14.86″N, 123°29′08.95″W thence counter-clockwise along the arc of a circle of 7 miles radius centered on 48°38'49.30"N. 123°25'32.80"W to 48°38'28.32"N, 123°15'00.24"W thence south along the Canada-United States boundary to 48°17′02.50″N, 123°14′54.40″W Canada-United States boundary point of beginning.

27 Aug 2009 PORTLAND INSET: Add VANCOUVER, WA Class D: That airspace extending upward from the surface to but not including 1,100 feet MSL in an area bounded by a line beginning at the point where the 019° bearing from Pearson Field intersects the 5-mile arc from Portland International Airport extending southeast to a point 1 1/2 miles east of Pearson Field on the extended centerline of Runway 8/26, and thence south to the north shore of the Columbia River, thence west via the north shore of the Columbia River to the 5-mile arc from Portland International Airport and thence clockwise via the 5-mile arc to point of beginning. This Class D airspace area is effective during the specific dates and times established in advance by a Notice to Airmen. The effective date and time will thereafter be continuously published in the Airport/Facility Directory.

22 Oct 2009 No Major Changes.

SPECIAL USE AIRSPACE

2 Jul 2009 Revise CYA145(H) VICTORIA/SALTSPRING ISLAND, BC, CANADA, Designated Altitude will read: Surface to 4000'

27 Aug 2009 - 22 Oct 2009 No Major Changes.

MILITARY TRAINING ROUTES

2 Jul 2009 - 22 Aug 2009 No Major Changes.

MISCELLANEOUS

2 Jul 2009 - 22 Aug 2009 No Major Changes.

SEATTLE TERMINAL AREA CHART 72nd Edition, 4 Jun 2009

OBSTRUCTIONS

2 Jul 2009 No Major Changes.

27 Aug 2009 Add obst 2337 MSL (255 AGL)UC, 48°00′59″N, 122°55′39″W. **22 Oct 2009** No Major Changes.

AIRPORTS

2 Jul 2009 Add RP 15R to HARVEY arpt, 47°54'18"N, 122°06'10"W.

27 Aug 2009 Add CTAF 122.8 at APEX arpt, 47°39'24"N, 122°43'59"W. Add RP 35 to APEX arpt, 47°39'24"N, 122°43'59"W.

22 Oct 2009 Change RP 33 to RP 34 at RENTON MUNI arpt, 47°29'35"N, 122°12'57"W.

2 Jul 2009 - 22 Oct 2009 No Major Changes.

2 Jul 2009 - 22 Oct 2009 No Major Changes.

SPECIAL USE AIRSPACE

2 Jul 2009 - 22 Oct 2009 No Major Changes.

MILITARY TRAINING ROUTES

2 Jul 2009 - 22 Oct 2009 No Major Changes.

MISCELLANEOUS

2 Jul 2009 - 22 Oct 2009 No Major Changes.

CHART & PANEL

L-32G

L-32G

L-31D

H-1C

H-10G, 11B, L-31D

H-11E, L-32J

H-10G, L-30G

SUPPLEMENTAL COMMUNICATION REFERENCE

Contained within this tabulation, and listed alphabetically by airport name, are all private—use airports charted on the U.S. IFR Enroute Low and High Altitude charts in the United States, having terminal approach and departure control facilities. Additionally, listed by country, are all Canadian and Mexican airports that appear on the U.S. IFR Enroute charts with approach and departure control services. All frequencies transmit and receive unless otherwise noted. Radials defining sectors are outbound from the facility.

UNITED STATES

FACILITY NAME

Frankfort, IL (LL4Ø)	L-28H
Chicago App/Dep Con 133.1 285.6	
Glasgow Industrial, MT (Ø7MT)	H-1E, 2F, L-13D
Salt Lake Center App/Dep Con 126.85 305.2	
USAF Academy Bullseye Aux Airstrip, CO (CO9Ø)	L-10F
ASOS 118.325	
West Kentucky Airpark, KY (5KY3)	L-16I
Memphis Center App/Dep Con 133.65 292.15	
William P Gwinn, FL (Ø6FA)	H-8I, L-23C
Gwinn Tower 120.4 314.6 (Mon-Fri 1300-2100Z‡)	
Gnd Con 121.65 279.25	
CANADA	
CILITY NAME	CHART & PANEL
Abbotsford, BC (CYXX)	H-1B, L-12F
ATIS 119.8 (1500–0700Z‡)	
Victoria Trml App/Dep Con 132.7 (Avbl on ground) 290.8	
Tower 119.4 (Inner) 121.0 (Outer) 295.0 (1500–0700Z‡) Gnd Con 121.8	
MF 119.4 295.0 (0700–1500Z‡) (Shape irregular to 4500')	
Amos/Magny, QC (CYEY)	H-11B
Montreal Center App/Dep Con 125.9	
Atikokan Muni, ON (CYIB)	L-14I
MF 122.3 (5 NM to 4500' No ground station)	
Barrie-Orillia (Lake Simcoe Rgnl), ON (CNB9)	H-11B, L-31D
AWOS 122.55 (Pvt)	
Toronto Center App/Dep Con 124.025	
Bar River, ON (CPF2)	L-31C
Toronto Center App/Dep Con 132.65	
Bathurst, NB (CZBF)	L-32J
Moncton Center App/Dep Con 134.25	
Boundary Bay, BC (CZBB)	H-1B, L-1E
ATIS 125.5 (1500-0700Z‡)	
Vancouver App/Dep Con 132.3 363.8	
Tower 118.1 (Inner) 127.6 (Outer) (1500-0700Z‡) Gnd Con 124.3	
MF 118.1 (0700-1500Z‡ to 2000'. Vancouver Trml 125.2 above 2000'. Shape	
irregular to 2500'.)	
Brampton, ON (CNC3)	L-31D
Toronto Trml App/Dep Con 119.3 253.1	
Brandon Muni, MB (CYBR)	H-2H
Winnipeg Center App/Dep Con 132.25 285.4	
MF 122.1 (5 NM to 4000')	
Brantford, ON (CYFD)	L-31D
Toronto Trml App/Dep Con 128.27	

NW, 22 OC	Γ 2009 to 17	DEC 2009
-----------	--------------	-----------------

Brockville-Thousand Islands Rgnl Tackaberry, ON (CNL3)

Toronto Center App/Dep Con 119.3 253.1

Cleveland Center App/Dep Con 132.25

Vancouver Center App/Dep Con 134.2 227.3

Montreal Center App/Dep Con 132.35 MF 122.15 (5 NM to 3400')

Moncton Center App/Dep Con 135.65 384.8 MF 118.0 (5 NM to 3200')

Montreal Center App/Dep Con 134.675

Bromont, QC (CZBM)

Castlegar, BC (CYCG)

Charlottetown, PE (CYYG)

Chatham-Kent, ON (CNZ3)

Burlington Airpark, ON (CZBA)

MF 122.1 (5 NM to 6500')

Centralia/James T. Fld Muni, ON (CYCE)
Toronto Center App/Dep Con 135.30

ACILITY NAME	CHART & PANE
Collingwood, ON (CNY3) Toronto Center App/Dep Con 124.02	H-11B, L-31
Cornwall Rgnl, ON (CYCC)	L-32
Boston Center App/Dep Con 135.25 377.1	2 02
Cranbrook/Canadian Rockies Intl, BC (CYXC)	H-1
Vancouver Center App/Dep Con 133.6 MF 122.3 (5 NM to 6100')	
Debert, NS (CCQ3)	H-11E, L-32
Halifax Trml App/Dep Con 119.2	
Digby, NS (CYID)	L-32
Moncton Center App/Dep Con 123.9	
Downsview, ON (CYZD)	H-11B, L-31I
Toronto Center App Con 133.4	
Toronto Center Dep Con 133.4	
MF 126.2 (3 NM to 1900')	
Drummondville, QC (CSC3)	L-321
Montreal Center App/Dep Con 132.35	
Earlton (Timiskaming Rgnl), ON (CYXR)	H-11I
MF 122.0 (5 NM to 3800')	
AWOS 128.6	
Elliot Lake Muni, ON (CYEL)	L-31
Toronto Center App/Dep Con 135.4	
Fort Frances Muni, ON (CYAG)	L-14
Minneapolis Center App/Dep Con 120.9	
Fredericton Intl, NB (CYFC)	H-11E, L-32
ATIS 127.55	
Moncton Center App/Dep Con 124.3 135.5 270.8 Clnc Del 121.7 (Ltd hrs)	
MF 119.0 (5 NM to 3500')	
Goderich, ON (CYGD)	H-11B, L-31
Toronto Center App/Dep 135.3 266.3	
Greenwood, NS (CYZX)	H-11E, L-32
ATIS 128.85 244.3 (1100-0000Z‡)	
App/Dep Con 120.6 335.9 Tower 119.5 126.2 236.6 324.3	
Gnd Con 133.75 289.4 Clnc Del 128.05 283.9	
Grimsby Air Park, ON (CNZ8)	L-31
Toronto Trml App/Dep Con 128.27 268.75 Tower 125.0 308.475	11.445 1.00
Halifax/Shearwater, NS (CYAW)	H-11E, L-32
ATIS 129.175 (Ltd hrs)	
App/Dep Con 119.2 Tower 119.0 126.2 340.2 360.2 (Ltd hrs)	
Gnd Con 121.7 250.1	H 11E I 22
Halifax/Stanfield Intl, NS (CYHZ)	H-11E, L-32
ATIS 121.0 Magneton Contar Ann /Don Con 118 7 110 2 128 FE 125 2 225 2 263 8	
Moncton Center App/Dep Con 118.7 119.2 128.55 135.3 225.2 363.8 Tower 118.4 236.6 Gnd Con 121.9 275.8 Clnc Del 123.95	
Apron Advisory 122.125	
Hamilton, ON (CYHM)	H-10H, 11B, L-11
ATIS 128.1	H-10H, 11B, L-11
Toronto Trml App/Dep Con 128.27 268.75 Tower 119.7 125.0	
Gnd Con 121.6	
Kingston, ON (CYGK)	H-11C, L-31E, 32
Montreal Center App/Dep Con 135.05 398.4 (0400–1115Z‡)	11–110, 1–311, 32
MF 122.5 (1115–0400Z‡ 5 NM to 3300')	
Kitchener/Waterloo, ON (CYKF)	H-11B, L-31
ATIS 125.1 (1200–0400Z‡)	11-110, 1-01
Toronto Trml App/Dep Con 128.275	
Waterloo Tower 126.0 118.55 (1200–0400Z‡) Gnd Con 121.8	
MF 126.0 (0400–1200Z‡ 5 NM to 4000′)	
Lachute, QC (CSE4)	L-32
Montreal Center App Con 124.65 132.85 268.3	2 02
Montreal Center Dep Con 132.85 268.3	
La Tuque, QC (CYLQ)	H-11
Montreal Center App/Dep Con 134.5	11-11
Langley, BC (CYNJ)	L-1
ATIS 124.5 (1630–0230Z, DT 1530–0330Z)	L-1
Victoria Trml 132.7 290.8 Tower 119.0 (1630–0230Z, DT 1530–0330Z)	
Gnd Con 121.9 MF 119.0 (0230–1630Z, DT 0330–1530Z 3 NM to 1900')	

CILITY NAME Leamington, ON (CLM2)	CHART & PANI
Cleveland Center App/Dep Con 132.45	
ethbridge, AB (CYQL)	H-1
ATIS 124.4 (1300-0545Z‡)	
Edmonton Center App/Dep Con 132.75 265.2 MF 121.0 (5 NM to 6000')	
indsay, ON (CNF4)	L-31E, L-32
Toronto Center App/Dep 134.25	
iverpool/South Shore Rgnl, NS (CYAU)	L-32
Moncton Center App/Dep Con 123.9	
ondon, ON (CYXU)	H-10G, 11E
ATIS 127.8 (1120-0345Z‡)	L-30G, 31
Toronto Center App/Dep 135.3 135.625	
Tower 119.4 125.65 (1120-0345Z‡) Gnd Con 121.9	
MF 119.4 (0345–1120Z‡ 5 NM to 3000′)	
Manitowaning/Manitoulin East Muni, ON (CYEM)	L-31
Toronto Center App/Dep 135.4 260.9	
Maniwaki, QC (CYMW)	L-32
Montreal Center App/Dep Con 126.57	
lascouche, QC (CSK3)	L-32
MF 122.35 (5 NM to 2500'. No gnd station. Excluding the portion S of the	
N shore of Riviere des Milles-lles and 1 NM around Lac Agile Mascouche arpt.)	
Medicine Hat, AB (CYXH)	H-1
AWOS 124.875 (0345–1245Z‡)	
MF 122.2 (1245–0345Z‡ 5 NM to 5400')	
Midland/Huronia, ON (CYEE)	L-31
Toronto Center App/Dep 124.025	2 02
Miramichi, NB (CYCH)	H-11E. L-3:
Moncton Center App/Dep Con 123.7	111, 1 0.
Moncton/Greater Moncton Intl, NB (CYQM)	H-11E, L-3
ATIS 128.65	111, 2 0
App/Dep 124.4 Tower 120.8 236.6 Gnd Con 121.8 275.8	
Apron Advisory 122.075	
Mont-Laurier, QC (CSD4)	L-32
Montreal Center App/Dep Con 126.57	L 02
Montreal Intl (Mirabel), QC (CYMX)	H-11C, 12K, L-32
ATIS 125.7	11 110, 1211, 1 02
Montreal Center App Con 124.65 132.85 268.3	
Montreal Dep Con 132.85	
Montreal Dep Con 132.85 MF 119.1 (7 NM shape irregular to 2000') VFR Advisory 134.15	H_11C 12K I_33
Montreal Dep Con 132.85 MF 119.1 (7 NM shape irregular to 2000') VFR Advisory 134.15 Montreal/Pierre Elliott Trudeau Intl, QC (CYUL)	H-11C, 12K, L-32
Montreal Dep Con 132.85 MF 119.1 (7 NM shape irregular to 2000') VFR Advisory 134.15 Montreal/Pierre Elliott Trudeau Intl, QC (CYUL) ATIS 133.7	H-11C, 12K, L-32
Montreal Dep Con 132.85 MF 119.1 (7 NM shape irregular to 2000') VFR Advisory 134.15 Montreal/Pierre Elliott Trudeau Intl, QC (CYUL) ATIS 133.7 Montreal Trml App Con 118.9 124.65 126.9 132.85 268.3	H-11C, 12K, L-32
Montreal Dep Con 132.85 MF 119.1 (7 NM shape irregular to 2000') VFR Advisory 134.15 Montreal/Pierre Elliott Trudeau Intl, QC (CYUL) ATIS 133.7 Montreal Trml App Con 118.9 124.65 126.9 132.85 268.3 Tower 119.9 267.1 Gnd Con 121.9 275.8 Clnc Del 125.6 Apron 122.075	H-11C, 12K, L-32
Montreal Dep Con 132.85 MF 119.1 (7 NM shape irregular to 2000') VFR Advisory 134.15 Montreal/Pierre Elliott Trudeau Intl, QC (CYUL) ATIS 133.7 Montreal Trml App Con 118.9 124.65 126.9 132.85 268.3 Tower 119.9 267.1 Gnd Con 121.9 275.8 Clnc Del 125.6 Apron 122.075 Montreal Trml Dep Con 118.9 (SE–S–SW) 124.65 268.3 (W–NW–NE)	H-11C, 12K, L-32
Montreal Dep Con 132.85 MF 119.1 (7 NM shape irregular to 2000') VFR Advisory 134.15 Iontreal/Pierre Elliott Trudeau Intl, QC (CYUL) ATIS 133.7 Montreal Trml App Con 118.9 124.65 126.9 132.85 268.3 Tower 119.9 267.1 Gnd Con 121.9 275.8 Clnc Del 125.6 Apron 122.075 Montreal Trml Dep Con 118.9 (SE-S-SW) 124.65 268.3 (W-NW-NE) VFR Advisory 134.15	
Montreal Dep Con 132.85 MF 119.1 (7 NM shape irregular to 2000') VFR Advisory 134.15 Montreal/Pierre Elliott Trudeau Intl, QC (CYUL) ATIS 133.7 Montreal Trml App Con 118.9 124.65 126.9 132.85 268.3 Tower 119.9 267.1 Gnd Con 121.9 275.8 Clnc Del 125.6 Apron 122.075 Montreal Trml Dep Con 118.9 (SE-S-SW) 124.65 268.3 (W-NW-NE) VFR Advisory 134.15 Montreal/St-Hubert, QC (CYHU)	
Montreal Dep Con 132.85 MF 119.1 (7 NM shape irregular to 2000') VFR Advisory 134.15 Montreal/Pierre Elliott Trudeau Intl, QC (CYUL) ATIS 133.7 Montreal Trml App Con 118.9 124.65 126.9 132.85 268.3 Tower 119.9 267.1 Gnd Con 121.9 275.8 Clnc Del 125.6 Apron 122.075 Montreal Trml Dep Con 118.9 (SE-S-SW) 124.65 268.3 (W-NW-NE) VFR Advisory 134.15 Montreal/S-Hubert, QC (CYHU) ATIS 124.9 (Apr-Oct 1045-0500Z‡, Nov-Mar 1045-0400Z) AWOS 124.9	
Montreal Dep Con 132.85 MF 119.1 (7 NM shape irregular to 2000') VFR Advisory 134.15 Montreal/Pierre Elliott Trudeau Intl, QC (CYUL) ATIS 133.7 Montreal Trml App Con 118.9 124.65 126.9 132.85 268.3 Tower 119.9 267.1 Gnd Con 121.9 275.8 Clnc Del 125.6 Apron 122.075 Montreal Trml Dep Con 118.9 (SE-S-SW) 124.65 268.3 (W-NW-NE) VFR Advisory 134.15 Montreal/St-Hubert, QC (CYHU) ATIS 124.9 (Apr-Oct 1045-0500Z‡, Nov-Mar 1045-0400Z) AWOS 124.9 Montreal/Center App/Dep Con 125.15 268.3	
Montreal Dep Con 132.85 MF 119.1 (7 NM shape irregular to 2000') VFR Advisory 134.15 Montreal/Pierre Elliott Trudeau Intl, QC (CYUL) ATIS 133.7 Montreal Trml App Con 118.9 124.65 126.9 132.85 268.3 Tower 119.9 267.1 Gnd Con 121.9 275.8 Clnc Del 125.6 Apron 122.075 Montreal Trml Dep Con 118.9 (SE-S-SW) 124.65 268.3 (W-NW-NE) VFR Advisory 134.15 Montreal/St-Hubert, QC (CYHU) ATIS 124.9 (Apr-Oct 1045-0500Z‡, Nov-Mar 1045-0400Z) AWOS 124.9 Montreal Center App/Dep Con 125.15 268.3 St. Hubert Tower 118.4 (Apr-Oct 1045-0500Z‡, Nov-Mar 1045-0400Z)	
Montreal Dep Con 132.85 MF 119.1 (7 NM shape irregular to 2000') VFR Advisory 134.15 Montreal/Pierre Elliott Trudeau Intl, QC (CYUL) ATIS 133.7 Montreal Trml App Con 118.9 124.65 126.9 132.85 268.3 Tower 119.9 267.1 Gnd Con 121.9 275.8 Clnc Del 125.6 Apron 122.075 Montreal Trml Dep Con 118.9 (SE-S-SW) 124.65 268.3 (W-NW-NE) VFR Advisory 134.15 Montreal/St-Hubert, QC (CYHU) ATIS 124.9 (Apr-Oct 1045-0500Z‡, Nov-Mar 1045-0400Z) AWOS 124.9 Montreal Center App/Dep Con 125.15 268.3 St. Hubert Tower 118.4 (Apr-Oct 1045-0500Z‡, Nov-Mar 1045-0400Z) Gnd Con 126.4 MF 118.4 (Apr-Oct 0500-1045Z‡, Nov-Mar	
Montreal Dep Con 132.85 MF 119.1 (7 NM shape irregular to 2000') VFR Advisory 134.15 Montreal/Pierre Elliott Trudeau Intl, QC (CYUL) ATIS 133.7 Montreal Trml App Con 118.9 124.65 126.9 132.85 268.3 Tower 119.9 267.1 Gnd Con 121.9 275.8 Clnc Del 125.6 Apron 122.075 Montreal Trml Dep Con 118.9 (SE-S-SW) 124.65 268.3 (W-NW-NE) VFR Advisory 134.15 Montreal/St-Hubert, QC (CYHU) ATIS 124.9 (Apr-Oct 1045-0500Z‡, Nov-Mar 1045-0400Z) AWOS 124.9 Montreal Center App/Dep Con 125.15 268.3 St. Hubert Tower 118.4 (Apr-Oct 1045-0500Z‡, Nov-Mar 1045-0400Z) Gnd Con 126.4 MF 118.4 (Apr-Oct 0500-1045Z‡, Nov-Mar 0400-1045Z 5 NM shape irregular to 2500') VFR Advisory 134.15	H-11C, L-32
Montreal Dep Con 132.85 MF 119.1 (7 NM shape irregular to 2000') VFR Advisory 134.15 Montreal/Pierre Elliott Trudeau Intl, QC (CYUL) ATIS 133.7 Montreal Trml App Con 118.9 124.65 126.9 132.85 268.3 Tower 119.9 267.1 Gnd Con 121.9 275.8 Clnc Del 125.6 Apron 122.075 Montreal Trml Dep Con 118.9 (SE-S-SW) 124.65 268.3 (W-NW-NE) VFR Advisory 134.15 Montreal/St-Hubert, QC (CYHU) ATIS 124.9 (Apr-Oct 1045-0500Z‡, Nov-Mar 1045-0400Z) AWOS 124.9 Montreal Center App/Dep Con 125.15 268.3 St. Hubert Tower 118.4 (Apr-Oct 1045-0500Z‡, Nov-Mar 1045-0400Z) Gnd Con 126.4 MF 118.4 (Apr-Oct 0500-1045Z‡, Nov-Mar 0400-1045Z 5 NM shape irregular to 2500') VFR Advisory 134.15 Muskoka, ON (CYQA)	H-11C, L-32
Montreal Dep Con 132.85 MF 119.1 (7 NM shape irregular to 2000') VFR Advisory 134.15 Montreal/Pierre Elliott Trudeau Intl, QC (CYUL) ATIS 133.7 Montreal Trml App Con 118.9 124.65 126.9 132.85 268.3 Tower 119.9 267.1 Gnd Con 121.9 275.8 Clnc Del 125.6 Apron 122.075 Montreal Trml Dep Con 118.9 (SE-S-SW) 124.65 268.3 (W-NW-NE) VFR Advisory 134.15 Montreal/St-Hubert, QC (CYHU) ATIS 124.9 (Apr-Oct 1045-0500Z‡, Nov-Mar 1045-0400Z) AWOS 124.9 Montreal Center App/Dep Con 125.15 268.3 St. Hubert Tower 118.4 (Apr-Oct 1045-0500Z‡, Nov-Mar 1045-0400Z) Gnd Con 126.4 MF 118.4 (Apr-Oct 0500-1045Z‡, Nov-Mar 0400-1045Z 5 NM shape irregular to 2500') VFR Advisory 134.15 Muskoka, QN (CYQA) AWOS 124.575	H-11C, L-32
Montreal Dep Con 132.85 MF 119.1 (7 NM shape irregular to 2000') VFR Advisory 134.15 Montreal/Pierre Elliott Trudeau Intl, QC (CYUL) ATIS 133.7 Montreal Trml App Con 118.9 124.65 126.9 132.85 268.3 Tower 119.9 267.1 Gnd Con 121.9 275.8 Clnc Del 125.6 Apron 122.075 Montreal Trml Dep Con 118.9 (SE-S-SW) 124.65 268.3 (W-NW-NE) VFR Advisory 134.15 Montreal/St-Hubert, QC (CYHU) ATIS 124.9 (Apr-Oct 1045-0500Z‡, Nov-Mar 1045-0400Z) AWOS 124.9 Montreal Center App/Dep Con 125.15 268.3 St. Hubert Tower 118.4 (Apr-Oct 1045-0500Z‡, Nov-Mar 1045-0400Z) Gnd Con 126.4 MF 118.4 (Apr-Oct 0500-1045Z‡, Nov-Mar 0400-1045Z 5 NM shape irregular to 2500') VFR Advisory 134.15 Misskoka, DN (CYQA) AWOS 124.575 MF 122.3 (5 NM to 3900')	H-11C, L-32 H-11B, L-32
Montreal Dep Con 132.85 MF 119.1 (7 NM shape irregular to 2000') VFR Advisory 134.15 Montreal/Pierre Elliott Trudeau Intl, QC (CYUL) ATIS 133.7 Montreal Trml App Con 118.9 124.65 126.9 132.85 268.3 Tower 119.9 267.1 Gnd Con 121.9 275.8 Clnc Del 125.6 Apron 122.075 Montreal Trml Dep Con 118.9 (SE-S-SW) 124.65 268.3 (W-NW-NE) VFR Advisory 134.15 Montreal/St-Hubert, QC (CYHU) ATIS 124.9 (Apr-Oct 1045-05007‡, Nov-Mar 1045-0400Z) AWOS 124.9 Montreal Center App/Dep Con 125.15 268.3 St. Hubert Tower 118.4 (Apr-Oct 1045-05007‡, Nov-Mar 1045-0400Z) Gnd Con 126.4 MF 118.4 (Apr-Oct 0500-10452‡, Nov-Mar 0400-1045Z 5 NM shape irregular to 2500') VFR Advisory 134.15 Muskoka, QN (CYQA) AWOS 124.575 MF 122.3 (5 NM to 3900')	H-11C, L-32 H-11B, L-32
Montreal Dep Con 132.85 MF 119.1 (7 NM shape irregular to 2000') VFR Advisory 134.15 Montreal/Pierre Elliott Trudeau Intl, QC (CYUL) ATIS 133.7 Montreal Trml App Con 118.9 124.65 126.9 132.85 268.3 Tower 119.9 267.1 Gnd Con 121.9 275.8 Clnc Del 125.6 Apron 122.075 Montreal Trml Dep Con 118.9 (SE-S-SW) 124.65 268.3 (W-NW-NE) VFR Advisory 134.15 Montreal/St-Hubert, QC (CYHU) ATIS 124.9 (Apr-Oct 1045-0500Z‡, Nov-Mar 1045-0400Z) AWOS 124.9 Montreal Center App/Dep Con 125.15 268.3 St. Hubert Tower 118.4 (Apr-Oct 1045-0500Z‡, Nov-Mar 1045-0400Z) Gnd Con 126.4 MF 118.4 (Apr-Oct 0500-1045Z‡, Nov-Mar 040-1045Z 5 NM shape irregular to 2500') VFR Advisory 134.15 Muskoka, ON (CYQA) AWOS 124.575 MF 122.3 (5 NM to 3900') Janaimo, BC (CYCD) Victoria Trml App/Dep 120.8 133.95 252.3 MF 122.1 1330-0530Z‡ (5 NM to 2500')	H-11C, L-32 H-11B, L-32 H-1B, L-3
Montreal Dep Con 132.85 MF 119.1 (7 NM shape irregular to 2000') VFR Advisory 134.15 Montreal/Pierre Elliott Trudeau Intl, QC (CYUL) ATIS 133.7 Montreal Trml App Con 118.9 124.65 126.9 132.85 268.3 Tower 119.9 267.1 Gnd Con 121.9 275.8 Clnc Del 125.6 Apron 122.075 Montreal Trml Dep Con 118.9 (SE-S-SW) 124.65 268.3 (W-NW-NE) VFR Advisory 134.15 Montreal/St-Hubert, QC (CYHU) ATIS 124.9 (Apr-Oct 1045-0500Z‡, Nov-Mar 1045-0400Z) AWOS 124.9 Montreal Center App/Dep Con 125.15 268.3 St. Hubert Tower 118.4 (Apr-Oct 1045-0500Z‡, Nov-Mar 1045-0400Z) Gnd Con 126.4 MF 118.4 (Apr-Oct 0500-1045Z‡, Nov-Mar 040-1045Z 5 NM shape irregular to 2500') VFR Advisory 134.15 Muskoka, ON (CYQA) AWOS 124.575 MF 122.3 (5 NM to 3900') Maraimo, BC (CYCD) Victoria Trml App/Dep 120.8 133.95 252.3 MF 122.1 1330-0530Z‡ (5 NM to 2500') Notoria Trml App/Dep 120.8 133.95 252.3 MF 122.1 1330-0530Z‡ (5 NM to 2500')	H-11C, L-32 H-11B, L-32 H-1B, L-3
Montreal Dep Con 132.85 MF 119.1 (7 NM shape irregular to 2000') VFR Advisory 134.15 Montreal/Pierre Elliott Trudeau Intl, QC (CYUL) ATIS 133.7 Montreal Trml App Con 118.9 124.65 126.9 132.85 268.3 Tower 119.9 267.1 Gnd Con 121.9 275.8 Clnc Del 125.6 Apron 122.075 Montreal Trml Dep Con 118.9 (SE-S-SW) 124.65 268.3 (W-NW-NE) VFR Advisory 134.15 Montreal/St-Hubert, QC (CYHU) ATIS 124.9 (Apr-Oct 1045-0500Z‡, Nov-Mar 1045-0400Z) AWOS 124.9 Montreal Center App/Dep Con 125.15 268.3 St. Hubert Tower 118.4 (Apr-Oct 1045-0500Z‡, Nov-Mar 1045-0400Z) Gnd Con 126.4 MF 118.4 (Apr-Oct 0500-1045Z‡, Nov-Mar 0400-1045Z 5 NM shape irregular to 2500') VFR Advisory 134.15 Muskoka, QM (CYQA) AWOS 124.575 MF 122.3 (5 NM to 3900') Manaimo, BC (CYCD) Victoria Trml App/Dep 120.8 133.95 252.3 MF 122.1 1330-0530Z‡ (5 NM to 2500') North Bay, QM (CYYB) ATIS 124.9 (1130-0300Z‡)	H-11C, L-32 H-11B, L-32 H-1B, L-3
Montreal Dep Con 132.85 MF 119.1 (7 NM shape irregular to 2000') VFR Advisory 134.15 Montreal/Pierre Elliott Trudeau Intl, QC (CYUL) ATIS 133.7 Montreal Trml App Con 118.9 124.65 126.9 132.85 268.3 Tower 119.9 267.1 Gnd Con 121.9 275.8 Clnc Del 125.6 Apron 122.075 Montreal Trml Dep Con 118.9 (SE-S-SW) 124.65 268.3 (W-NW-NE) VFR Advisory 134.15 Montreal/St-Hubert, QC (CYHU) ATIS 124.9 (Apr-Oct 1045-0500Z‡, Nov-Mar 1045-0400Z) AWOS 124.9 Montreal Center App/Dep Con 125.15 268.3 St. Hubert Tower 118.4 (Apr-Oct 1045-0500Z‡, Nov-Mar 1045-0400Z) Gnd Con 126.4 MF 118.4 (Apr-Oct 0500-1045Z‡, Nov-Mar 0400-1045Z 5 NM shape irregular to 2500') VFR Advisory 134.15 Muskoka, QN (CYQA) AWOS 124.575 MF 122.3 (5 NM to 3900') Manaimo, BC (CYCD) Victoria Trml App/Dep 120.8 133.95 252.3 MF 122.1 1330-0530Z‡ (5 NM to 2500') Morth Bay, QN (CYYB) ATIS 124.9 (1130-0300Z‡) Toronto Center App/Dep 121.225 127.25	H-11C, L-32 H-11B, L-31 H-1B, L-3
Montreal Dep Con 132.85 MF 119.1 (7 NM shape irregular to 2000') VFR Advisory 134.15 Montreal/Pierre Elliott Trudeau Intl, QC (CYUL) ATIS 133.7 Montreal Trml App Con 118.9 124.65 126.9 132.85 268.3 Tower 119.9 267.1 Gnd Con 121.9 275.8 Clnc Del 125.6 Apron 122.075 Montreal Trml Dep Con 118.9 (SE-S-SW) 124.65 268.3 (W-NW-NE) VFR Advisory 134.15 Montreal/St-Hubert, QC (CYHU) ATIS 124.9 (Apr-Oct 1045-0500Z‡, Nov-Mar 1045-0400Z) AWOS 124.9 Montreal Center App/Dep Con 125.15 268.3 St. Hubert Tower 118.4 (Apr-Oct 1045-0500Z‡, Nov-Mar 1045-0400Z) Gnd Con 126.4 MF 118.4 (Apr-Oct 0500-1045Z‡, Nov-Mar 0400-1045Z 5 NM shape irregular to 2500') VFR Advisory 134.15 Muskoka, QN (CYQA) AWOS 124.575 MF 122.3 (5 NM to 3900') Janaimo, BC (CYCD) Victoria Trml App/Dep 120.8 133.95 252.3 MF 122.1 1330-0530Z‡ (5 NM to 2500') Jorth Bay, QN (CYYB) ATIS 124.9 (1130-0300Z‡) Toronto Center App/Dep 121.225 127.25 MF 118.3 (1130-0330Z‡ 7 NM to 5000')	H-11C, L-32 H-11B, L-31 H-11B, L-1
Montreal Dep Con 132.85 MF 119.1 (7 NM shape irregular to 2000') VFR Advisory 134.15 Montreal/Pierre Elliott Trudeau Intl, QC (CYUL) ATIS 133.7 Montreal Trml App Con 118.9 124.65 126.9 132.85 268.3 Tower 119.9 267.1 Gnd Con 121.9 275.8 Clnc Del 125.6 Apron 122.075 Montreal Trml Dep Con 118.9 (SE-S-SW) 124.65 268.3 (W-NW-NE) VFR Advisory 134.15 Montreal/St-Hubert, QC (CYHU) ATIS 124.9 (Apr-Oct 1045-0500Z‡, Nov-Mar 1045-0400Z) AWOS 124.9 Montreal Center App/Dep Con 125.15 268.3 St. Hubert Tower 118.4 (Apr-Oct 1045-0500Z‡, Nov-Mar 1045-0400Z) Gnd Con 126.4 MF 118.4 (Apr-Oct 0500-1045Z‡, Nov-Mar 0400-1045Z 5 NM shape irregular to 2500') VFR Advisory 134.15 Muskoka, QN (CYQA) AWOS 124.575 MF 122.3 (5 NM to 3900') Janaimo, BC (CYCD) Victoria Trml App/Dep 120.8 133.95 252.3 MF 122.1 1330-0530Z‡ (5 NM to 2500') Jorth Bay, QN (CYYB) ATIS 124.9 (1130-0300Z‡) Toronto Center App/Dep 121.225 127.25 MF 118.3 (1130-0330Z‡ 7 NM to 5000')	H-11C, L-32 H-11B, L-31 H-11B, L-1
Montreal Dep Con 132.85 MF 119.1 (7 NM shape irregular to 2000') VFR Advisory 134.15 Montreal/Pierre Elliott Trudeau Intl, QC (CYUL) ATIS 133.7 Montreal Trml App Con 118.9 124.65 126.9 132.85 268.3 Tower 119.9 267.1 Gnd Con 121.9 275.8 Clnc Del 125.6 Apron 122.075 Montreal Trml Dep Con 118.9 (SE-S-SW) 124.65 268.3 (W-NW-NE) VFR Advisory 134.15 Montreal/S-Hubert, QC (CYHU) ATIS 124.9 (Apr-Oct 1045-0500Z‡, Nov-Mar 1045-0400Z) AWOS 124.9 Montreal Center App/Dep Con 125.15 268.3 St. Hubert Tower 118.4 (Apr-Oct 1045-0500Z‡, Nov-Mar 1045-0400Z) Gnd Con 126.4 MF 118.4 (Apr-Oct 0500-1045Z‡, Nov-Mar 0400-1045Z 5 NM shape irregular to 2500') VFR Advisory 134.15 Muskoka, QN (CYQA) AWOS 124.575 MF 122.3 (5 NM to 3900') Manimo, BC (CYCD) Victoria Trml App/Dep 120.8 133.95 252.3 MF 122.1 1330-0530Z‡ (5 NM to 2500') Jorth Bay, QN (CYYB) ATIS 124.9 (1130-0300Z‡) Toronto Center App/Dep 121.225 127.25 MF 118.3 (1130-0330Z‡ 7 NM to 5000')	H-11C, L-32 H-11B, L-31 H-11B, L-1
Montreal Dep Con 132.85 MF 119.1 (7 NM shape irregular to 2000') VFR Advisory 134.15 Montreal/Pierre Elliott Trudeau Intl, QC (CYUL) ATIS 133.7 Montreal Trml App Con 118.9 124.65 126.9 132.85 268.3 Tower 119.9 267.1 Gnd Con 121.9 275.8 Clnc Del 125.6 Apron 122.075 Montreal Trml Dep Con 118.9 (SE-S-SW) 124.65 268.3 (W-NW-NE) VFR Advisory 134.15 Montreal/St-Hubert, QC (CYHU) ATIS 124.9 (Apr-Oct 1045-0500Z‡, Nov-Mar 1045-0400Z) AWOS 124.9 Montreal Center App/Dep Con 125.15 268.3 St. Hubert Tower 118.4 (Apr-Oct 1045-0500Z‡, Nov-Mar 1045-0400Z) Gnd Con 126.4 MF 118.4 (Apr-Oct 0500-1045Z‡, Nov-Mar 0400-1045Z 5 NM shape irregular to 2500') VFR Advisory 134.15 Muskoka, QN (CYQA) AWOS 124.575 MF 122.3 (5 NM to 3900') Vanaimo, BC (CYCD) Victoria Trml App/Dep 120.8 133.95 252.3 MF 122.1 1330-0530Z‡ (5 NM to 2500') Vorth Bay, QN (CYYB) ATIS 124.9 (1130-0300Z‡) Toronto Center App/Dep 121.225 127.25 MF 118.3 (1130-0330Z‡ 7 NM to 5000')	H-11C, L-32 H-11B, L-31 H-11B, L-31
Montreal Dep Con 132.85 MF 119.1 (7 NM shape irregular to 2000') VFR Advisory 134.15 Montreal/Pierre Elliott Trudeau Intl, QC (CYUL) ATIS 133.7 Montreal Trml App Con 118.9 124.65 126.9 132.85 268.3 Tower 119.9 267.1 Gnd Con 121.9 275.8 Clnc Del 125.6 Apron 122.075 Montreal Trml Dep Con 118.9 (SE-S-SW) 124.65 268.3 (W-NW-NE) VFR Advisory 134.15 Montreal/St-Hubert, QC (CYHU) ATIS 124.9 (Apr-Oct 1045-0500Z‡, Nov-Mar 1045-0400Z) AWOS 124.9 Montreal Center App/Dep Con 125.15 268.3 St. Hubert Tower 118.4 (Apr-Oct 1045-0500Z‡, Nov-Mar 1045-0400Z) Gnd Con 126.4 MF 118.4 (Apr-Oct 0500-1045Z‡, Nov-Mar 0400-1045Z 5 NM shape irregular to 2500') VFR Advisory 134.15 Muskoka, QN (CYQA) AWOS 124.575 MF 122.3 (5 NM to 3900') Maraimo, BC (CYCD) Victoria Trml App/Dep 120.8 133.95 252.3 MF 122.1 1330-0530Z‡ (5 NM to 2500') North Bay, QN (CYYB) ATIS 124.9 (1130-0300Z‡) Toronto Center App/Dep 121.225 127.25 MF 118.3 (1130-0330Z‡ 7 NM to 5000') Dishawa, QN (CYOO) ATIS 125.675 (1130-0330Z‡)	H-11C, 12K, L-32 H-11C, L-32 H-11B, L-31 H-11B, L-31 L-31

Ottawa/Carp, ON (CYRP)	CHART & PANEI L-31E, 32F
ATIS 121.15	L-31L, 321
Ottawa Trml App/Dep Con 128.175 252.5	
Ottawa/Gatineau, QC (CYND)	H-11C. L-320
Ottawa Trml App/Dep Con 127.7 128.175 252.5	,
MF 122.3 (5 NM shape irregular to 2500')	
VFR Advisory Ottawa Trml 127.7	
Ottawa/MacDonald-Cartier Intl, ON (CYOW)	L-110
ATIS 121.15	
Ottawa App Con 135.15 Tower 118.8 120.1 341.3	
Gnd Con 121.9 Clnc Del 119.4	
Ottawa Dep Con 128.175	
Owen Sound/Billy Bishop Rgnl, ON (CYOS)	L-310
Toronto Center App/Dep 132.575 290.6	
Pelee Island, ON (CYPT)	L-30F
Cleveland Center App/Dep Con 126.35 360.0	
Pembroke, ON (CYTA)	H-11C, L-31E, 32F
Montreal Center App/Dep Con 135.2	
Petawawa Advisory 126.4 250.1 (Mon-Fri 1300-2130Z‡, OT PPR)	
Penticton, BC (CYYF)	H-1E
Vancouver Center App/Dep Con 133.5 351.3 MF 118.5 (5 NM to 4100')	
Peterborough, ON (CYPQ)	H-11B, L-31E, 32I
AWOS 126.925	
Toronto Center App/Dep 134.25	
Pincher Creek, AB (CZPC)	H-10
Edmonton Center App/Dep Con 132.75 265.2	
Pitt Meadows, BC (CYPK)	L-11
ATIS 125.0 (1500-0700Z‡)	
Vancouver Center App Con 128.6 352.7 (Outer)	
Pitt Tower 126.3 (1500–0700Z‡) Gnd Con 123.8	
Vancouver Center Dep Con 132.3 363.8 (South)	
MF 126.3 (0700–1500Z‡) (3NM to 2500′)	
Quebec/Jean Lesage Intl, QC (CYQB)	H-11D, L-32H
ATIS 134.6	
AWOS 122.025 (Pvt)	
Montreal Center App/Dep Con 124.0 127.85 135.025 270.9 322.8	
(185.65 Quebec Twr VFR acft at or below 3000') Tower 118.65 236.6	
Gnd Con 121.9 250.0	
Riviere Du Loup, QC (CYRI)	H-110
AWOS 122.025 (Pvt)	
Montreal Center App/Dep Con 125.1 299.6	
Rouyn Noranda, QC (CYUY)	H-11E
Montreal Center App/Dep Con 125.9	
MF 122.2 (5 NM to 4000')	
Saint John, NB (CYSJ)	H-11E, L-32.
Moncton Center App/Dep Con 124.3 135.5 270.8 MF 118.5 (5 NM to 3400')	11.400.445.4.55
Sarnia (Chris Hadfield), ON (CYZR)	H-10G, 11B, L-30
Toronto Center 134.375	
Sault Ste Marie, ON (CYAM)	H-2K, L-31
ATIS 133.05 (1300-0100Z‡)	
Toronto Center App/Dep Con 132.65 344.5	
Tower 118.8 (1300–0100Z‡) Gnd Con 121.7	
MF 118.8 (0100–1300Z‡ 5 NM irregular shape to 3000')	
Sherbrooke, QC (CYAM)	H-11D, L-32H
AWOS 126.25	
Montreal Center App/Dep Con 132.55 MF 123.5 (Ltd hrs 5 NM to 3800')	
South Renfrew Muni, ON (CNP3)	L-31E, 32I
Montreal Center App/Dep 124.275	
Southport, MB (CYPG)	H-2H
ATIS 120.85 (Mon-Fri 1400-2300Z‡ except holidays)	
Tower 126.2 384.2 (Mon-Fri 1400-2300Z‡ except holidays)	

CILITY NAME Springwater Parria Airpark ON (CNA2)	CHART & PANEL
Springwater Barrie Airpark, ON (CNA3)	L-31D
Toronto Center App/Dep Con 124.025	
St. Catherines/Niagara District, ON (CYSN)	H-10H, 11B, L-31E
ATIS 128.525 (1215–0200Z‡)	
Toronto Trml App/Dep Con 133.4 253.1 MF 123.25 (1215–0200Z‡ 5 NM to 3300')	
it. Frederic, QC (CSZ4)	L-32H
Montreal Center App/Dep Con 135.025 270.9	L=3211
St. Georges, QC (CYSG)	H-32H, L-11D
Montreal Center App/Dep Con 132.35	11 0211, E 110
MF 122.15 (5 NM 3900' ASL)	
St. Jean, QC (CYJN)	L-32G
Montreal Center App/Dep Con 125.15 268.3	
Tower 118.2 (Apr–Oct 1230–0230Z‡ Nov–Mar 1300–0200Z‡)	
Gnd Con 121.7	
Sudbury, ON (CYSB)	H-31B, 10G, L-31D
ATIS 127.4	,,
Toronto Center App/Dep Con 135.5	
MF 125.5 (7 NM to 4000')	
Summerside, PE (CYSU)	H-11E, L-32J
AWOS 122.55 (Pvt)	,
Moncton Center App/Dep Con 124.4 384.8	
hunder Bay, ON (CYQT)	H-2J, L-14J
ATIS 128.8 (1100-0400Z‡)	
Winnipeg Center App/Dep Con 132.125 (0400–1100Z‡)	
Tower 118.1 (1100-0400Z‡) Gnd Con 121.9	
App/Dep 119.2 MF 118.1 (0400-1100Z‡ 5 NM to 4000')	
immins, ON (CYTS)	H-11B
ATIS 124.95 (1000-0500Z‡)	
Toronto Center App/Dep Con 128.3 226.3 MF 122.3 (5 NM to 4000')	
Foronto/Buttonville Muni, ON (CYKZ)	L-31E
ATIS 127.1 (1200-0400Z‡)	
Toronto Center App Con 133.4 Toronto Center Dep Con 133.4	
Tower 124.8 119.9 (1200-0400Z‡) Gnd Con 121.8	
MF 124.8 (0400–1200Z‡ No gnd station. 5 NM shape irregular to below 2500')	
Toronto/City Centre, ON (CYTZ)	L-31E
ATIS 133.6 (1130-0400Z‡)	
App Con 133.4 Dep Con 133.4	
Tower 118.2 119.2 226.5 (1130-0400Z‡) Gnd Con 121.7	
Foronto/Lester B Pearson Intl, ON (CYYZ)	H-11B, L-31D
ATIS 120.825	
App Con 124.475 125.4 132.8 Dep Con 127.575 128.8	
Tower 118.35 118.7 Gnd Con 118.0 119.1 121.65 121.9	
Cinc Del 121.3 (1200-0400Z‡) VFR Advisory 119.3 133.4	
renton, ON (CYTR)	H-11C, L-31E, 32F
ATIS 135.45 257.7	
App/Dep Con 128.4 324.3 Tower 128.7 236.6 Gnd Con 121.9 275.8	
Cinc Del 124.35 286.4	
Trenton/Mountain View, ON (CPZ3)	H-11C, L-31E, 32F
Trenton Mil Advisory 268.0	
Trois-Rivieres, QC (CYRQ)	H-11C, L-32H
Montreal Center App/Dep Con 128.225 229.2	
MF 123.0 (5 NM to 3200')	
/al-D'or, QC (CYVO)	H-11B
Montreal Center App/Dep Con 125.9 308.3	
MF 118.5 (1030–0325Z‡ 5 NM to 4000′)	
Vancouver Inti, BC (CYVR)	H-1B, L-1E
	,
ATIS 124.6 124.75	
App Con 128.6 128.17 352.7 (Outer) 133.1 134.225 352.7 (Inner)	

I

I

CILITY NAME	CHART & PANE
/ictoria Intl, BC (CYYJ)	H-1B, L-1
ATIS 118.8 (1400-0800Z‡)	
App Con 125.95 308.4 Dep Con 133.85 308.4	
Tower 119.1 (Outer) 119.7 (Inner) 239.6	
Gnd Con 121.9 361.4 (1400–0800Z‡ OT ctc Kamloops 119.7)	
Cinc Del 126.4 (1400-0800Z‡)	
/ictoriaville, QC (CSR3)	L-32
Montreal Center App Con 132.35 Naterville/Kings Co Muni, NS (CCW3)	L-32
Greenwood Trml App/Dep Con 120.6 335.9	L=32
Greenwood Tower 119.5 324.3	
Wiarton, ON (CYVV)	H-11B, L-31
Toronto Center App/Dep Con 132.575	11-110, 1-01
MF 122.2 (5 NM to 3700')	
Windsor, ON (CYQG)	H-10G, L-8
ATIS 134.5 (1130–0330Z‡)	11 100, 1
Detroit App/Dep Con 126.85 127.5 134.3 348.3 363.2	
Tower 124.7 (1130–0330Z‡) Gnd Con 121.7	
MF 124.7 (0330–1130Z‡ 6 NM irregular shape to below 3000')	
VFR Advisory Detroit App Con 134.3	
/armouth, NS (CYQI)	H-11E, L-3
Moncton Center App/Dep Con 123.9 368.5 MF 123.0 (5 NM to 3100')	11 111, 1 0
MEXICO	
CILITY NAME	CHART & PAN
Abraham Gonzalez Intl (MMCS)	H-4K, L-6
Juarez App Con 119.9 Juarez Tower 118.9	
Del Norte Intl (MMAN)	H-7B, L-20
ATIS 127.55 (1300-0300Z‡)	
Monterrey App 119.75 120.4 Tower 118.6	
Durango Intl (MMDO)	H-7
ATIS 132.1	
Tower 118.1 Durango Info 122.3	
General Abelardo L Rodriguez Intl (MMTJ)	H-4H, L-4
ATIS 127.9	
Tijuana App Con 119.5 120.3 Tijuana Tower 118.1 Clnc Del 122.35	
Tijuana Info 132.1	
General Lucio Blanco Intl (MMRX)	H-7B, L-20
delieral Lucio Dialico IIII (IVIIVIAA)	
Reynosa App Con 118.8 Reynosa Tower 118.8	
	H-7B, L-20
Reynosa App Con 118.8 Reynosa Tower 118.8	H-7B, L-20
Reynosa App Con 118.8 Reynosa Tower 118.8 General Mariano Escobedo Intl (MMMY)	H-7B, L-20
Reynosa App Con 118.8 Reynosa Tower 118.8 General Mariano Escobedo Intl (MMMY) ATIS 127.7	
Reynosa App Con 118.8 Reynosa Tower 118.8 General Mariano Escobedo Intl (MMMY) ATIS 127.7 Monterrey App Con 119.75 120.4 Monterrey Tower 118.1 Gnd Con 121.9	
Reynosa App Con 118.8 Reynosa Tower 118.8 General Mariano Escobedo Intl (MMMY) ATIS 127.7 Monterrey App Con 119.75 120.4 Monterrey Tower 118.1 Gnd Con 121.9 General R Fierro Villalobos Intl (MMCU)	
Reynosa App Con 118.8 Reynosa Tower 118.8 Seneral Mariano Escobedo Intl (MMMY) ATIS 127.7 Monterrey App Con 119.75 120.4 Monterrey Tower 118.1 Gnd Con 121.9 Seneral R Fierro Villalobos Intl (MMCU) ATIS 127.9	L-
Reynosa App Con 118.8 Reynosa Tower 118.8 Seneral Mariano Escobedo Intl (MMMY) ATIS 127.7 Monterrey App Con 119.75 120.4 Monterrey Tower 118.1 Gnd Con 121.9 Seneral R Fierro Villalobos Intl (MMCU) ATIS 127.9 Chihuahua App Con 121.0 Chihuahua Tower 118.4	L-
Reynosa App Con 118.8 Reynosa Tower 118.8 General Mariano Escobedo Intl (MMMY) ATIS 127.7 Monterrey App Con 119.75 120.4 Monterrey Tower 118.1 Gnd Con 121.9 General R Fierro Villalobos Intl (MMCU) ATIS 127.9 Chihuahua App Con 121.0 Chihuahua Tower 118.4 General Rodolfo Sanchez Taboada Intl (MMML)	L-
Reynosa App Con 118.8 Reynosa Tower 118.8 General Mariano Escobedo Intl (MMMY) ATIS 127.7 Monterrey App Con 119.75 120.4 Monterrey Tower 118.1 Gnd Con 121.9 General R Fierro Villalobos Intl (MMCU) ATIS 127.9 Chihuahua App Con 121.0 Chihuahua Tower 118.4 General Rodolfo Sanchez Taboada Intl (MMML) ATIS 127.6	L- H-4H, L-4J, 5
Reynosa App Con 118.8 Reynosa Tower 118.8 General Mariano Escobedo Intl (MMMY) ATIS 127.7 Monterrey App Con 119.75 120.4 Monterrey Tower 118.1 Gnd Con 121.9 General R Fierro Villalobos Intl (MMCU) ATIS 127.9 Chihuahua App Con 121.0 Chihuahua Tower 118.4 General R Rodolfo Sanchez Taboada Intl (MMML) ATIS 127.6 Mexicali App Con 118.2 Mexicali Tower 118.2 Mexicali Info 123.9 122.3	L- H-4H, L-4J, 5
Reynosa App Con 118.8 Reynosa Tower 118.8 General Mariano Escobedo Intl (MMMY) ATIS 127.7 Monterrey App Con 119.75 120.4 Monterrey Tower 118.1 Gnd Con 121.9 General R Fierro Villalobos Intl (MMCU) ATIS 127.9 Chihuahua App Con 121.0 Chihuahua Tower 118.4 General Rodolfo Sanchez Taboada Intl (MMML) ATIS 127.6 Mexicali App Con 118.2 Mexicali Tower 118.2 Mexicali Info 123.9 122.3 General Servando Canales (MMMA)	L– H–4H, L–4J, 5 H–7C, L–23
Reynosa App Con 118.8 Reynosa Tower 118.8 Seneral Mariano Escobedo Intl (MMMY) ATIS 127.7 Monterrey App Con 119.75 120.4 Monterrey Tower 118.1 Gnd Con 121.9 Seneral R Fierro Villalobos Intl (MMCU) ATIS 127.9 Chihuahua App Con 121.0 Chihuahua Tower 118.4 Seneral Rodolfo Sanchez Taboada Intl (MMML) ATIS 127.6 Mexicali App Con 118.2 Mexicali Tower 118.2 Mexicali Info 123.9 122.3 Seneral Servando Canales (MMMA) Matamoros App Con 118.0 Matamoros Tower 118.0	L-I H-4H, L-4J, 5 H-7C, L-21
Reynosa App Con 118.8 Reynosa Tower 118.8 Seneral Mariano Escobedo Intl (MMMY) ATIS 127.7 Monterrey App Con 119.75 120.4 Monterrey Tower 118.1 Gnd Con 121.9 Seneral R Fierro Villalobos Intl (MMCU) ATIS 127.9 Chihuahua App Con 121.0 Chihuahua Tower 118.4 Seneral Rodolfo Sanchez Taboada Intl (MMML) ATIS 127.6 Mexicali App Con 118.2 Mexicali Tower 118.2 Mexicali Info 123.9 122.3 Seneral Servando Canales (MMMA) Matamoros App Con 118.0 Matamoros Tower 118.0	H–4H, L–4J, E H–7C, L–21 H–7
Reynosa App Con 118.8 Reynosa Tower 118.8 Seneral Mariano Escobedo Intl (MMMY) ATIS 127.7 Monterrey App Con 119.75 120.4 Monterrey Tower 118.1 Gnd Con 121.9 Seneral R Fierro Villalobos Intl (MMCU) ATIS 127.9 Chihuahua App Con 121.0 Chihuahua Tower 118.4 Seneral Rodolfo Sanchez Taboada Intl (MMML) ATIS 127.6 Mexicali App Con 118.2 Mexicali Tower 118.2 Mexicali Info 123.9 122.3 Seneral Servando Canales (MMMA) Matamoros App Con 118.0 Matamoros Tower 118.0 Plan De Guadalupe Intl (MMIO) Saltillo App Con 127.4 Saltillo Tower 118.4	H–4H, L–4J, 5 H–7C, L–21 H–7
Reynosa App Con 118.8 Reynosa Tower 118.8 General Mariano Escobedo Intl (MMMY) ATIS 127.7 Monterrey App Con 119.75 120.4 Monterrey Tower 118.1 Gnd Con 121.9 General R Fierro Villalobos Intl (MMCU) ATIS 127.9 Chihuahua App Con 121.0 Chihuahua Tower 118.4 General Rodolfo Sanchez Taboada Intl (MMML) ATIS 127.6 Mexicali App Con 118.2 Mexicali Tower 118.2 Mexicali Info 123.9 122.3 General Servando Canales (MMMA) Matamoros App Con 118.0 Matamoros Tower 118.0 Plan De Guadalupe Intl (MMIC) Saltillo App Con 127.4 Saltillo Tower 118.4 Quetzalcoatl Intl (MMNL)	H-7B, L-20 L-4 H-4H, L-4J, 5 H-7C, L-21 H-7B, L-20 H-7B, L-20

In support of the Federal Aviation Administration's Runway Incursion Program, selected towered airport diagrams have been published in the Airport Diagram section of the A/FD. Diagrams will be listed alphabetically by associated city and airport name. Airport diagrams, depicting runway and taxiway configurations, will assist both VFR and IFR pilots in ground taxi operations. The airport diagrams in this publication are the same as those published in the U.S. Terminal Procedures Publications. For additional airport diagram legend information see the U.S. Terminal Procedures Publication.

NOTE: Some text data published under the individual airport in the front portion of the A/FD may be more current than the data published on the Airport Diagrams. The airport diagrams are updated only when significant changes occur.

GENERAL INFORMATION

PILOT CONTROLLED AIRPORT LIGHTING SYSTEMS

Available pilot controlled lighting (PCL) systems are indicated as follows:

- 1. Approach lighting systems that bear a system identification are symbolized using negative symbology, e.g., 🚳, 🔾, 🖸
- 2. Approach lighting systems that do not bear a system identification are indicated with a negative "0" beside the name. A star (*) indicates non-standard PCL, consult the individual airport in the front portion of the A/FD, e.g., 0*

To activate lights use frequency indicated in the communication section of the chart with a 0 or the appropriate lighting system identification e.g., UNICOM 122.8 0, 0, 0

KFY MIKF	

7 times within 5 seconds

5 times within 5 seconds
3 times within 5 seconds

Highest intensity available

Medium or lower intensity (Lower REIL or REIL-off) Lowest intensity available (Lower REIL or REIL-off)

FUNCTION

CHART CURRENCY INFORMATION

FAA procedure amendment number Amdt 11A 99365 Date of latest change Orig 00365

The Chart Date indentifies the Julian date the chart was added to the volume or last revised for any reason. The first two digits indicate the year, the last three digits indicate the day of the year (001 to 365/6) in which the latest addition or change was first published.

The Procedure Amendment Number precedes the Chart Date, and changes any time instrument information (e.g., DH, MDA, approach routing, etc.) changes. Procedure changes also cause the Chart Date to change.


MISCELLANEOUS

- ★ Indicates a non-continuously operating facility, see the individual airport in the front portion of the A/FD.
- # Indicates control tower temporarily closed UFN.

LEGEND

INSTRUMENT APPROACH PROCEDURES (CHARTS)

AIRPORT DIAGRAM



When Control Tower and Rotating Beacon are co-located, Beacon symbol will be used and further identified as TWR

Runway length depicted is the physical length of the runway (end-to-end, including displaced thresholds if any) but excluding areas designated as stopways.

A D symbol is shown to indicate runway declared distance information available, see appropriate A/FD, Alaska or Pacific Supplement for distance information. Helicopter Alighting Areas (H) [+] (H) (A) (+) Negative Symbols used to identify Copter Procedures

landing point...... 🕕 🕂 🖽

Runway Threshold elevation.....THRE 123 Runway TDZ elevation.....TDZE 123 — 0.3% DOWN

(shown when runway slope is greater than or equal to 0.3%)

NOTE:

Runway Slope measured to midpoint on runways 8000 feet or longer.

U.S. Navy Optical Landing System (OLS) "OLS" location is shown because of its height of approximately 7 feet and proximity to edge of runway may create an obstruction for some types of aircraft.

Approach light symbols are shown in the Flight Information Handbook.

Airport diagram scales are variable.

True/magnetic North orientation may vary from diagram to diagram


Coordinate values are shown in 1 or ½ minute increments. They are further broken down into 6 second ticks, within each 1 minute increments.

Positional accuracy within ±600 feet unless otherwise noted on the chart.

All new and revised airport diagrams are shown referenced to the World Geodetic System (WGS) (noted on appropriate diagram), and may not be compatible with local coordinates published in FLIP. (Foreign Only)

Runway Weight Bearing Capacity/or PCN Pavement Classification Number is shown as a codified expression. Refer to the appropriate Supplement/Directory for applicable codes e.g.,

RWY 14-32 S75, T185, ST175, TT325 PCN 80 F/D/X/U




Airport diagrams are specifically designed to assist in the movement of ground traffic at locations with complex runway/taxiway configurations and provide information for updating Computer Based Navigation Systems (I.E., INS, GPS) aboard aircraft. Airport diagrams are not intended to be used for approach and landing or departure operations. For revisions to Airport Diagrams: Consult FAA Order 7910.4.

.EGEND

AIRPORT DIAGRAMS HOT SPOTS


An "airport surface hot spot" is a location on an aerodrome movement area with a history or potential risk of collision or runway incursion, and where heightened attention by pilots/drivers is necessary. A "hot spot" is a runway safety related problem area on a airport that presents increased risk during surface operations. Typically it is a complex or confusing taxiway/taxiway or taxiway/runway intersection. The area of increased risk has either a history of or potential for runway incursions or surface incidents, due to a variety of causes, such as but not limited to: airport layout, traffic flow, airport marking, signage and lighting, situational awareness, and training. Hot spots are depicted on airport diagrams as open circles or polygons designated as "HOT¹", "HOT²", etc. and tabulated in the list below with a brief description of each hot spot. Hot spots will remain charted on airport diagrams until such time the increased risk has been reduced or eliminated.


CITY/AIRPORT	HOT SPOT	DESCRIPTION		
IDAHO				
IDAHO FALLS IDAHO FALLS RGNL (IDA)	HOT ¹	Pilots should use caution and look carefully for runway hold line when using Twy C. Rwy 17–35 does not have runway edge markings and can be mistaken for a twy.		
	HOT ²	Aircraft departing Rwy 20 often miss left turn on A-1 and taxi past A-1 entrance. Do not mistake Rwy 20 such hold line on Twy A for entrance to Rwy 20.		
	HOT ³	Do not cross hold line for Rwy 17 without authorization.		
LEWISTON LEWISTON-NEZ PERCE CO (LWS)	HOT ¹	Twy C and Twy G intersection close proximity to Rwy 12–30.		
	HOT ²	Twy G between Rwy 8–26 and Rwy 30 thld. Short distance between rwys.		
	MONTANA			
MISSOULA MISSOULA INTL (MSO)	HOT ¹	Intersection of Twy A and Twy F. Critical turn for eastbound ramp access.		
	OREGON			
PORTLAND PORTLAND INTL (PDX)	HOT ¹	Limited wing-tip clearance at taxiway convergence point. Pilots taxiing eastbound on taxiway B should hold at the taxiway holding position marking when directed by ATC.		
	WASHINGTON	I		
EVERETT SNOHOMISH COUNTY (PAINE FIELD) PAE	HOT ¹	Intersection of Twy D1, Twy A5, and Rwy 11–29, Rwy in close proximity to ramp areas.		
	HOT ²	Rwy 29 thld in close proximity to ramp areas.		
	HOT ³	Twy A between Twy A8 and Twy A9 not visible from ATCT.		
SEATTLE BOEING FIELD/KING	HOT ¹	Twy Z restricted access area.		
COUNTY INTL (BFI)	HOT ²	Rwy 13R–31L and Twy A9. Wrong rwy departure risk.		
SEATTLE SEATTLE-TACOMA INTL (SEA)	HOT ¹	Aircraft landing Rwy 34C and exiting Twy H who turn right on Twy J must clear the Rwy 34C hold bar completely, while using vigilance not to cross the hold bar for Rwy 34R (34C–34R hold bar separation distance 189 feet).		





AIRPORT DIAGRAM

BELLINGHAM, WASHINGTON BELLINGHAM INTL (BLI)













NW, 22 OCT 2009 to 17 DEC 2009


























AIRPORT DIAGRAMS 297 09183 IDAHO FALLS RGNL (IDA) AIRPORT DIAGRAM IDAHO FALLS, IDAHÓ AL-590 (FAA) ATIS 135.325 IDAHO FALLS TOWER * 118.5 257.8 GND CON 121.7 HOT³ JANUARY 2005 ANNUAL RATE OF CHANGE 0.1°W 4051 HOT 43°31′N [⊥] FIRE STATION TWR 4833 **PASSENGER** TERMINAL 4731 35 FIELD ELEV 4744 RWY 2-20 S140, D175, ST175, DT270 RWY 17-35


S43, D58 CAUTION: BE ALERT TO RUNWAY CROSSING CLEARANCES. ELEV READBACK OF ALL RUNWAY HOLDING INSTRUCTIONS IS REQUIRED. - 43°30′N — 112°05′W 112°04′W AIRPORT DIAGRAM IDAHO FALLS, IDAHO IDAHO FALLS RGNL (IDA)










KLAMATH FALLS, OREGON KLAMATH FALLS (LMT)












 $\begin{array}{c} \text{MEDFORD, OREGON} \\ \text{MEDFORD/ROGUE VALLEY INTL-MEDFORD } (MFR) \end{array}$







MOSES LAKE/GRANT COUNTY INTL (MWH)




MOUNTAIN HOME AFB (KMUO)







OLYMPIA, WASHINGTON OLYMPIA RGNL (OLM)











PENDLETON, OREGON PENDLETON (PDT) PENDLETON (PDT)














09239



AIRPORT DIAGRAM


RENTON, WASHINGTON RENTON MUNI (RNT)






NW, 22 OCT 2009 to 17 DEC 2009

09239




SEATTLE, WASHINGTON SEATTLE-TACOMA INTL (SEA)




NW, 22 OCT 2009 to 17 DEC 2009

08325


09015




SPOKANE INTL (GEG)




TACOMA, WASHINGTON TACOMA NARROWS (TIW)




NW, 22 OCT 2009 to 17 DEC 2009



walla walla, washington walla walla rgnl $(A\,L\,W)$





YAKIMA, WASHINGTON YAKIMA AIR TERMINAL/MCALLISTER FIELD (YKM)

08213

